

Interface to use Simplace from R

Gunther Krauss

May 08, 2023

1 Introduction

This package provides methods to interact with the modelling framework SIMPLACE ¹. Simplace is written in Java (and some parts in Scala) so one can access it from R via **rJava**. The purpose of this package is to simplify the interaction between R and Simplace, by providing functions to:

- initialize and configure Simplace
- load a simulation (solution and project)
- parameterize the simulation
- run whole simulation or run it stepwise
- get simulation output and convert it to formats suitable for R

2 Installing the Simplace Framework

For installing SIMPLACE, please consult the webpage www.simplace.net. A brief guide to install SIMPLACE:

- If you don't have installed Java, please install an appropriate version of the (JRE or JDK) from openjdk.java.net or adoptium.net (recommended).
- Get Simplace from www.simplace.net
- Install the **simplace** package in R:

```
install.packages('simplace',  
  repos=c('https://r-forge.r-project.org', 'https://cran.r-project.org'))
```

3 Basic Usage

The usage of SIMPLACE in R follows roughly this scheme:

- init SIMPLACE by providing the path to your simplace installation directory, your working directory and your outputs
- open a SIMPLACE project from a solution (and project) file
- create a list of simulation parameters you want to change
- create and run a Simulation
- get the result from the simulation
- convert the result to a R object (**data.frame**, **list** etc.)

4 Troubleshooting

- Package **rJava** should be installed automatically with **simplace**. If not, install it manually:
`install.packages('rJava')`

¹SCIENTIFIC IMPACT ASSESSMENT AND MODELLING PLATFORM FOR ADVANCED CROP AND ECOSYSTEM MANAGEMENT. See www.simplace.net for more information on Simplace

- Architecture of R and Java have to match. If you are using 64-bit Java, you have to use 64-bit R.
- If you want to use the development version instead of the console mode, make sure that the projects `simplace_core`, `simplace_modules` and optionally `simplace_run` are in a common directory and set the installation dir to this directory.

5 Example

5.1 Run the simulation

```
library(simplace)
SimplaceInstallationDir <- findFirstSimplaceInstallation()

Solution <- paste(SimplaceInstallationDir,
                  "simplace_run/simulation/gk/solution/complete/Complete.sol.xml", sep="")

simplace <- initSimplace(SimplaceInstallationDir)

openProject(simplace, Solution)

parameter <- list()
parameter$enddate <- "31-12-1992"

sid <- createSimulation(simplace, parameter)
runSimulations(simplace)

result <- getResult(simplace, "DIAGRAM_OUT", sid);

closeProject(simplace)
```

After specifying the directories and the solution, the framework is initialized and the project opened. The end date of the simulation is (re)set and the simulation is run. After the run the result is retrieved.

5.2 Get the result and plot it

```
resf <- resultToDataframe(result)

dates <- 300:730
weights <- resf[dates,
  c("TOP_LINE_Roots", "TOP_LINE_Leaves", "TOP_LINE_Stems", "TOP_LINE_StorageOrgans")]
matplot(dates, weights, type="l", xlab="Days", ylab="Weight [g/m2]", main="Simulated Biomass")
legend(300, 800, legend=c("Roots", "Leaves", "Stems", "Storage Organs"), lty=1:4, col=1:4)
```

The result is converted to a dataframe. Interesting variables are extracted and then plotted.

5.3 Get arrays and plot them as contour plot

```
resultlistexp <- resultToList(result, expand=TRUE)
water <- resultlistexp$BOTTOM_ARRAY_VolumetricWaterContent
wmat <- do.call(rbind, water)
wmatpart <- wmat[dates,]
layers <- dim(wmatpart)[2]
filled.contour(dates, -(layers:1), wmatpart[, layers:1],
               xlab="Day", ylab="Layer", main="Water content in soil",
               color.palette = function(n){rgb((n:1)/n, (n:1)/n, 1)})
```

As the result contains an array which holds the water content for 40 layers, it is transformed to a list and the array is expanded.

Contents

1	Introduction	1
2	Installing the Simplace Framework	1
3	Basic Usage	1
4	Troubleshooting	1
5	Example	2
5.1	Run the simulation	2
5.2	Get the result and plot it	3
5.3	Get arrays and plot them as contour plot	4