

Package ‘PPTcirc’

November 9, 2020

Type Package

Title Projected Polya Tree for Circular Data

Version 0.1.0

Author Karla Mayra Perez [aut, cre], Luis E. Nieto-Barajas [aut]

Maintainer Karla Mayra Perez <karla.mayra25@gmail.com>

Description Provides functionality for the prior and posterior projected Polya tree for the analysis of circular data (Nieto-Barajas and Nunez-Antonio (2019) <arXiv:1902.06020>).

License GPL-3

Encoding UTF-8

LazyData true

Depends R (>= 2.10)

RoxygenNote 7.1.1

Imports circular, stats, graphics, progress

URL <https://github.com/Karlampm/PPTcirc>

BugReports <https://github.com/Karlampm/PPTcirc/issues>

NeedsCompilation no

Repository CRAN

Date/Publication 2020-11-09 20:50:03 UTC

R topics documented:

| | |
|----------------------------|---|
| deer | 2 |
| dsimpostppt | 2 |
| dsimpriorppt | 4 |
| peccary | 5 |
| postppt.plot | 6 |
| postppt.summary | 7 |
| priorppt.plot | 7 |
| priorppt.summary | 8 |
| tapir | 9 |

| | |
|--------------|-----------|
| Index | 10 |
|--------------|-----------|

| | |
|------|---|
| deer | <i>Time of the day when a deer was observed</i> |
|------|---|

Description

Temporal activity information (time of the day in radians) when a camera detected the appearance of a deer at El Triunfo biosphere in Mexico in 2015 data provided by Eduardo Mendoza from *Universidad Michoacana de San Nicolas de Hidalgo*, Mexico.

Usage

```
data(deer)
```

Format

A vector of 115 observations (in radians).

References

Nieto-Barajas, L.E. & Nunez-Antonio, G. (2019). Projected Polya tree. <https://arxiv.org/pdf/1902.06020.pdf>

| | |
|-------------|--|
| dsimpostppt | <i>Posterior projected Polya Tree distribution</i> |
|-------------|--|

Description

Performs posterior inference for a given a circular dataset with the Projected Polya Tree via a MCMC algorithm.

Usage

```
dsimpostppt(datafile,units = c("radians", "degrees", "hours"),
mm = 4, mu = c(0, 0), sig = 1, aa = 1, delta = 1.1,
it = 500, bi = 50, ti = 2, kapa = 0.5, ha = 0, hm = 0,
c0 = 1, c1 = 2, iota = 6, mu0 = 0, taum = 1, control.circular = list())
```

Arguments

| | |
|----------|--|
| datafile | the data from which the estimate is to be computed. The object is circular or will be coerced to circular. |
| units | units of the support: "radians", "degrees" or "hours". |
| mm | number of finite levels of the Polya tree |
| mu | mean vector of the projected bivariate normal centering distribution. |
| sig | precision of the projected bivariate normal centering distribution. |

| | |
|------------------|--|
| aa | alpha. Standard deviation parameter of the projected Polya tree. |
| delta | controls of the speed at which the variances of the branching probabilities move down in the tree, $\rho(m)=m^{\delta}$. |
| it | number of iterations for MCMC. |
| bi | number of burn in iterations for MCMC. |
| ti | thinning parameter of the MCMC chain. |
| kapa | tunning parameter in the MH proposal distribution for the latent resultants R. |
| ha | logical. If TRUE alpha will be assigned $Ga(c0,c1)$ hyper-prior distribution. |
| hm | logical. If TRUE mu will be assigned $N(\mu0,\tau\mu)$ independent hyper-prior distributions for each coordinate. |
| c0, c1 | shape and rate hyper-parameters of the gamma prior distribution for alpha. These will be used only when ha=1. |
| iota | tunning parameter in the MH proposal distribution for alpha. |
| mu0, taum | mean and precision hyper-parameters of the independent normal prior distribution for each coordinate of mu. These will be used only when hm=1. |
| control.circular | the attribute used to coerced the resulting. object. See circular. |

Value

An object of class `postppt.circ` whose underlying structure is a list containing the following components:

| | |
|-------------------|--|
| x | points where the density is evaluated. |
| predictive | predictive density estimated with the projected Polya tree. |
| quantile2.5 | lower and upper 95% credible interval limits. |
| quantile97.5 | |
| stats | descriptive statistics: mean direction and concentration of each MCMC density. |
| cpo | conditional predictive ordinate statistic for the data. |
| LMPL | logarithm of the pseudo marginal likelihood statistic. |
| aa.sims | vector of simulated alphas when ha=1. |
| mu.sims | matrix of simulated bivariate means when hm=1. |
| acceptancerate | Acceptance rate of MH step for the latent resultants. |
| acceptancerate_aa | Acceptance rate of MH step for alpha. |
| data | original dataset. |

References

Nieto-Barajas, L.E. & Nunez-Antonio, G. (2019). Projected Polya tree. <https://arxiv.org/pdf/1902.06020.pdf>

See Also

[postppt.plot](#), [postppt.summary](#)

Examples

```

data(tapir)
#It is advised to increase the number of iterations for a better fitting
z1 <- dsimpostppt(tapir, units = "radians", it = 5, ti =1, bi=0, ha = 1, hm =1)
class(z1)
length(z1$acceptancerate)
z1$acceptancerate

postppt.summary(z1)
postppt.plot(z1, plot.type= "line" , ylim = c(0,0.8))

```

dsimpriorppt

Prior projected Polya tree distribution

Description

Simulates paths of prior projected Polya tree distributions centered around a projected normal distribution.

Usage

```

dsimpriorppt(nsim = 5, mm = 4, mu = c(0, 0),
sig = 1, ll = 100, aa = 1, delta = 1.1, units = "radians")

```

Arguments

| | |
|-------|---|
| nsim | integer indicating the number of simulations. |
| mm | integer indicating the number of finite levels of the Polya tree. |
| mu | mean vector of the projected bivariate normal distribution. |
| sig | standard deviation of the projected bivariate normal distribution. We advise to always use sig = 1. |
| ll | number of equally spaced points at which the projected distribution will be evaluated. |
| aa | alpha. Precision parameter of the Polya tree. |
| delta | controls of the speed at which the variances of the branching probabilities move down in the tree, $\rho(m)=m^{\delta}$. |
| units | units of the support: "radians", "degrees" or "hours". |

Value

An object with class `priorppt.circ` whose underlying structure is a list containing the following components:

| | |
|----------|---|
| x | points where the density is evaluated. |
| ppt.sims | simulated density paths of the prior projected Polya tree. |
| stats | descriptive statistics: mean direction and concentration of each simulated density. |

References

Nieto-Barajas, L.E. & Nunez-Antonio, G. (2019). Projected Polya tree. <https://arxiv.org/pdf/1902.06020.pdf>

See Also

[priorppt.plot](#), [priorppt.summary](#)

Examples

```
z <- dsimpriorppt(mu = c(5,5), nsim = 5, units = "radians")
priorppt.plot(z, plot.type = "line")
summary(z$stats)
```

peccary

Time of the day when a peccary was observed

Description

Temporal activity information (time of the day in radians) when a camera detected the appearance of a peccary at El Triunfo biosphere in Mexico in 2015 data provided by Eduardo Mendoza from *Universidad Michoacana de San Nicolas de Hidalgo*, Mexico.

Usage

```
data(peccary)
```

Format

A vector of 16 observations (in radians).

References

Nieto-Barajas, L.E. & Nunez-Antonio, G. (2019). Projected Polya tree. <https://arxiv.org/pdf/1902.06020.pdf>

 postppt.plot

Plot method for posterior projected Polya tree

Description

Plots posterior projected Polya tree estimates.

Usage

```
postppt.plot(postppt.circ,
  plot.type = c("circle", "line", "summary", "a.sim", "mu.sim", "cpos"),
  interval = TRUE, control.circular = list(),
  shrink = 1, tol = 0.04, ylim = NULL)
```

Arguments

| | |
|------------------|--|
| postppt.circ | object returned by the dsimpostppt function. |
| plot.type | type of plot to be drawn: "circle" for circular plot, "line" for linear plot, "summary" for boxplot of mean direction and concentration, "cpos" for cpos scatter plot "a.sim" for summary plots of simulated alphas and "mu.sim" for summary plots of simulated mu1 and mu2. |
| interval | logical. If TRUE 95% credible intervals will be shown in the circular and linear plots. |
| control.circular | attributes of circular object in order to draw the circle. See circular . |
| shrink | parameter that controls the size of the plotted circle. Default is 1. Larger values shrink the circle, while smaller values enlarge the circle. |
| tol | proportion of white space at the margins of plot. |
| ylim | range to be encompassed by "y" axis. |

See Also

[plot](#), [plot.density.circular](#)

Examples

```
z2 <- dsimpostppt(deer, units = "radians", it = 10, ti = 1, bi = 0, ha = 1)
postppt.plot(z2, plot.type = "line", shrink = 1.4, tol = 1.2, ylim = c(0, 0.6))
postppt.summary(z2)
postppt.plot(z2, plot.type = "cpos")
postppt.plot(z2, plot.type = "circle", shrink = 1.4, tol = 1.2)
```

| | |
|-----------------|---|
| postppt.summary | <i>Summary statistics for the post projected Polya tree</i> |
|-----------------|---|

Description

Extracts mean, quantiles 2.5% and 97.5% of the mean direction and concentration.

Usage

```
postppt.summary(postppt.circ)
```

Arguments

postppt.circ object returned by dsimpostppt function.

Value

table of descriptive statistics.

Examples

```
z1 <- dsimpostppt(tapir, units = "radians", it = 5, ti =1, bi=0)
postppt.summary(z1)
```

| | |
|---------------|---|
| priorppt.plot | <i>Plot method for prior projected Polya tree</i> |
|---------------|---|

Description

Plots density paths of simulated prior projected Polya tree, mean direction and concentration.

Usage

```
priorppt.plot(priorppt.circ, n.path="all",
plot.type = c("circle", "line", "summary"),control.circular = list(),
shrink=1, tol = 0.04,ylim)
```

Arguments

priorppt.circ object returned by dsimpriorppt function.

n.path "all" plots all the simulated paths or numeric atomic vector indicates the simulation path of the priorppt.circ object that will be plot.

plot.type type of plot to be drawn: "circle" for circular plot, "line" for linear plot and "summary" for boxplot of mean direction and concentration.

control.circular attributes of circular object in order to draw the circle. See [circular](#).

| | |
|--------|---|
| shrink | parameter that controls the size of the plotted circle. Default is 1. Larger values shrink the circle, while smaller values enlarge the circle. |
| tol | proportion of white space at the margins of plot. |
| ylim | range to be encompassed by "y" axis. |

Value

Circular plot of simulated paths when `plot.type = "circle"`. Linear plot of simulated paths for `plot.type = "line"`. Boxplot of mean direction and concentration for `plot.type = "summary"`

See Also

[plot](#), [plot.density.circular](#)

Examples

```
z <- dsimpriorppt(mu = c(0,1), nsim = 5, units = "degrees")
priorppt.plot(z, plot.type = "circle", shrink = 0.0071, tol = 3.9)
priorppt.plot(z, plot.type = "line", shrink = 0.0071, tol = 3.9)
priorppt.plot(z, plot.type = "summary", shrink = 0.0071, tol = 3.9)
```

priorppt.summary

Summary for the prior projected Polya tree simulations

Description

Mean, quantiles 2.5% and 97.5% of the mean direction and concentration.

Usage

```
priorppt.summary(priorppt.circ, units = "radians")
```

Arguments

`priorppt.circ` object returned by `dsimpriorppt` function.
`units` units of the support: "radians", "degrees" or "hours".

Value

Table of descriptive statistics for mean direction and concentration.

Examples

```
z <- dsimpriorppt(mu = c(-1,0), nsim = 5, units = "hours")
priorppt.summary(z)
```

tapir

Time of the day when a tapir was observed

Description

Temporal activity information (time of the day in radians) when a camera detected the appearance of a tapir at El Triunfo biosphere in Mexico in 2015 data provided by Eduardo Mendoza from *Universidad Michoacana de San Nicolas de Hidalgo, Mexico*.

Usage

```
data(tapir)
```

Format

A vector of 35 observations (in radians).

References

Nieto-Barajas, L.E. & Nunez-Antonio, G. (2019). Projected Polya tree. <https://arxiv.org/pdf/1902.06020.pdf>

Index

* datasets

deer, 2

peccary, 5

tapir, 9

circular, 6, 7

deer, 2

dsimpostppt, 2

dsimpriorppt, 4

peccary, 5

plot, 6, 8

plot.density.circular, 6, 8

postppt.plot, 3, 6

postppt.summary, 3, 7

priorppt.plot, 5, 7

priorppt.summary, 5, 8

tapir, 9