

Package ‘PRIMME’

April 13, 2017

Type Package

Title Eigenvalues and Singular Values and Vectors from Large Matrices

Version 2.1-0

Date 2017-04-11

Maintainer Eloy Romero <eloy@cs.wm.edu>

Description R interface to PRIMME, a C library for computing a few eigenvalues and their corresponding eigenvectors of a real symmetric or complex Hermitian matrix. It can also compute singular values and vectors of a square or rectangular matrix. It can find largest, smallest, or interior singular/eigenvalues and can use preconditioning to accelerate convergence.

URL <https://github.com/primme/primme>

BugReports <https://github.com/primme/primme/issues>

Imports Rcpp

LinkingTo Rcpp, Matrix

Suggests Matrix

SystemRequirements A POSIX system. Currently Linux and OS X are known to work. GNU make.

NeedsCompilation yes

License GPL-3

Encoding UTF-8

RoxygenNote 6.0.1

Author Eloy Romero [aut, cre],
Andreas Stathopoulos [aut],
College of William & Mary [cph]

Repository CRAN

Date/Publication 2017-04-13 21:32:02 UTC

R topics documented:

eigs_sym	2
svds	5

eigs_sym

*Find a few eigenvalues and vectors on large, sparse Hermitian matrix***Description**

Compute a few eigenpairs from a specified region (the largest, the smallest, the closest to a point) on a symmetric/Hermitian matrix using PRIMME [1]. Only the matrix-vector product of the matrix is required. The used method is usually faster than a direct method (such as [eigen](#)) if seeking a few eigenpairs and the matrix-vector product is cheap. For accelerating the convergence consider to use preconditioning and/or educated initial guesses.

Usage

```
eigs_sym(A, NEig = 1, which = "LA", targetShifts = NULL, tol = 1e-06,
        x0 = NULL, ortho = NULL, prec = NULL, isreal = NULL, ...)
```

Arguments

A	symmetric/Hermitian matrix or a function with signature $f(x)$ that returns $A \%*\% x$.
NEig	number of eigenvalues and vectors to seek.
which	which eigenvalues to find: "LA" the largest (rightmost) values; "SA" the smallest (leftmost) values; "LM" the farthest from targetShifts; "SM" the closest to targetShifts; "CLT" the closest but left to targetShifts; "CGT" the closest but greater than targetShifts; vector of numbers the closest values to these points.
targetShifts	return the closest eigenvalues to these points as indicated by target.
tol	the convergence tolerance: $\ Ax - x\lambda\ \leq tol\ A\ $.
x0	matrix whose columns are educated guesses of the eigenvectors to find.
ortho	find eigenvectors orthogonal to the space spanned by the columns of this matrix; useful to avoid finding some eigenvalues or to find new solutions.
prec	preconditioner used to accelerated the convergence; usually it is an approximation of the inverse of $A - \sigma I$ if finding the closest eigenvalues to σ . If it is a matrix it is used as $prec \%*\% x$; otherwise it is used as $prec(x)$.
isreal	whether $A \%*\% x$ always returns real number and not complex.
...	other PRIMME options (see details).

Details

Optional arguments to pass to PRIMME eigensolver (see further details at [2]):

method used by the solver, one of:

- "DYNAMIC" switches dynamically between DEFAULT_MIN_TIME and DEFAULT_MIN_MATVECS
- "DEFAULT_MIN_TIME" best method for light matrix-vector product
- "DEFAULT_MIN_MATVECS" best method for heavy matrix-vector product or preconditioner
- "Arnoldi" an Arnoldi not implemented efficiently
- "GD" classical block Generalized Davidson
- "GD_plusK" GD+k block GD with recurrence restarting
- "GD_Olsen_plusK" GD+k with approximate Olsen preconditioning
- "JD_Olsen_plusK" GD+k, exact Olsen (two preconditioner applications per step)
- "RQI" Rayleigh Quotient Iteration, also Inverse Iteration if targetShifts is provided
- "JDQR" original block, Jacobi Davidson
- "JDQMR" our block JDQMR method (similar to JDCG)
- "JDQMR_ETol" slight, but efficient JDQMR modification
- "STEEPEST_DESCENT" equivalent to GD(maxBlockSize,2*maxBlockSize)
- "LOBPCG_OrthoBasis" equivalent to GD(neig,3*neig)+neig
- "LOBPCG_OrthoBasis_Window" equivalent to GD(maxBlockSize,3*maxBlockSize)+maxBlockSize when neig>maxBlockSize

aNorm estimation of norm-2 of A, used in convergence test (if not provided, it is estimated as the largest eigenvalue in magnitude seen).

maxBlockSize maximum block size (like in subspace iteration or LOBPCG).

printLevel message level reporting, from 0 (no output) to 5 (show all).

locking 1, hard locking; 0, soft locking.

maxBasisSize maximum size of the search subspace.

minRestartSize minimum Ritz vectors to keep in restarting.

maxMatvecs maximum number of matrix vector multiplications.

maxit maximum number of outer iterations.

scheme the restart scheme (thick restart by default).

maxPrevRetain number of approximate eigenvectors retained from previous iteration, that are kept after restart.

robustShifts set to true to avoid stagnation.

maxInnerIterations maximum number of inner QMR iterations.

LeftQ use the locked vectors in the left projector.

LeftX use the approx. eigenvector in the left projector.

RightQ use the locked vectors in the right projector.

RightX use the approx. eigenvector in the right projector.

SkewQ use the preconditioned locked vectors in the right projector.

SkewX use the preconditioned approximate eigenvector in the right projector.

relTolBase a legacy from classical JDQR (recommend not use).

iseed an array of four numbers used as a random seed.

Value

list with the next elements

values the eigenvalues λ_i

vectors the eigenvectors x_i

rnorms the residual vector norms $\|Ax_i - \lambda_i x_i\|$.

stats\$numMatvecs number of matrix-vector products performed

stats\$numPreconds number of preconditioner applications performed

stats\$elapsedTime time expended by the eigensolver

stats\$timeMatvec time expended in the matrix-vector products

stats\$timePrecond time expended in applying the preconditioner

stats\$estimateMinEval estimation of the smallest eigenvalue of A

stats\$estimateMaxEval estimation of the largest eigenvalue of A

stats\$estimateANorm estimation of the norm of A

References

- [1] A. Stathopoulos and J. R. McCombs *PRIMME: PReconditioned Iterative MultiMethod Eigensolver: Methods and software description*, ACM Transaction on Mathematical Software Vol. 37, No. 2, (2010) 21:1-21:30.
- [2] <http://www.cs.wm.edu/~andreas/software/doc/primmec.html#parameters-guide>

See Also

[eigen](#) for computing all values; [svds](#) for computing a few singular values

Examples

```
A <- diag(1:10) # the eigenvalues of this matrix are 1:10 and the
                # eigenvectors are the columns of diag(10)
r <- eigs_sym(A, 3);
r$values # the three largest eigenvalues on diag(1:10)
r$vectors # the corresponding approximate eigenvectors
r$rnorms # the corresponding residual norms
r$stats$numMatvecs # total matrix-vector products spend

r <- eigs_sym(A, 3, 'SA') # compute the three smallest values

r <- eigs_sym(A, 3, 2.5) # compute the three closest values to 2.5

r <- eigs_sym(A, 3, 2.5, tol=1e-3); # compute the values with
r$rnorms # residual norm <= 1e-3*||A||

# Build a Jacobi preconditioner (too convenient for a diagonal matrix!)
# and see how reduce the number matrix-vector products
A <- diag(1:1000) # we use a larger matrix to amplify the difference
P <- diag(diag(A) - 2.5)
```

```
eigs_sym(A, 3, 2.5, tol=1e-3)$stats$numMatvecs
eigs_sym(A, 3, 2.5, tol=1e-3, prec=P)$stats$numMatvecs

# Passing A and the preconditioner as functions
Af <- function(x) (1:100) * x; # = diag(1:100) %**% x
Pf <- function(x) x / (1:100 - 2.5); # = solve(diag(1:100 - 2.5), x)
r <- eigs_sym(Af, 3, 2.5, tol=1e-3, prec=Pf, n=100)

# Passing initial guesses
A <- diag(1:1000) # we use a larger matrix to amplify the difference
x0 <- diag(1,1000,4) + matrix(rnorm(4000), 1000, 4)/100;
eigs_sym(A, 4, "SA", tol=1e-3)$stats$numMatvecs
eigs_sym(A, 4, "SA", tol=1e-3, x0=x0)$stats$numMatvecs

# Passing orthogonal constrain, in this case, already compute eigenvectors
r <- eigs_sym(A, 4, "SA", tol=1e-3); r$values
eigs_sym(A, 4, "SA", tol=1e-3, ortho=r$vectors)$values
```

svds

*Find a few singular values and vectors on large, sparse matrix***Description**

Compute a few singular triplets from a specified region (the largest, the smallest, the closest to a point) on a matrix using PRIMME [1]. Only the matrix-vector product of the matrix is required. The used method is usually faster than a direct method (such as [svd](#)) if seeking few singular values and the matrix-vector product is cheap. For accelerating the convergence consider to use preconditioning and/or educated initial guesses.

Usage

```
svds(A, NSvals, which = "L", tol = 1e-06, u0 = NULL, v0 = NULL,
     orthou = NULL, orthov = NULL, prec = NULL, isreal = NULL, ...)
```

Arguments

A	matrix or a function with signature <code>f(x, trans)</code> that returns <code>A %**% x</code> when <code>trans == "n"</code> and <code>t(Conj(A)) %**% x</code> when <code>trans == "c"</code> .
NSvals	number of singular triplets to seek.
which	which singular values to find: "l" the largest values; "s" the smallest values; vector of numbers the closest values to these points.
tol	a triplet (σ, u, v) is marked as converged when $\sqrt{\ Av - \sigma u\ ^2 + \ A^*u - \sigma v\ ^2} \leq tol \ A\ $ is smaller than $tol * \ A\ $, or close to the minimum tolerance that the selected method can achieve.

<code>u0</code>	matrix whose columns are educated guesses of the left singular vectors to find.								
<code>v0</code>	matrix whose columns are educated guesses of the right singular vectors to find.								
<code>orthou</code>	find left singular vectors orthogonal to the space spanned by the columns of this matrix; useful to avoid finding some triplets or to find new solutions.								
<code>orthov</code>	find right singular vectors orthogonal to the space spanned by the columns of this matrix.								
<code>prec</code>	preconditioner used to accelerated the convergence; it is a named list of matrices or functions such as <code>solve(prec[[mode]],x)</code> or <code>prec[[mode]](x)</code> return an approximation of $OP^{-1}x$, where <table style="margin-left: 40px; margin-top: 10px;"> <tr> <td><code>mode</code></td> <td>OP</td> </tr> <tr> <td><code>"AHA"</code></td> <td>A^*A</td> </tr> <tr> <td><code>"AAH"</code></td> <td>AA^*</td> </tr> <tr> <td><code>"aug"</code></td> <td>$[0A; A^*0]$</td> </tr> </table>	<code>mode</code>	OP	<code>"AHA"</code>	A^*A	<code>"AAH"</code>	AA^*	<code>"aug"</code>	$[0A; A^*0]$
<code>mode</code>	OP								
<code>"AHA"</code>	A^*A								
<code>"AAH"</code>	AA^*								
<code>"aug"</code>	$[0A; A^*0]$								
	The three values haven't to be set. It is recommended to set "AHA" for matrices with <code>nrow > ncol</code> ; "AAH" for matrices with <code>nrow < ncol</code> ; and additionally "aug" for <code>tol < 1e-8</code> .								
<code>isreal</code>	whether <code>A %% x</code> always returns real number and not complex.								
<code>...</code>	other PRIMME options (see details).								

Details

Optional arguments to pass to PRIMME eignesolver (see further details at [2]):

<code>aNorm</code>	estimation of norm-2 of A, used in convergence test (if not provided, it is estimated as the largest eigenvalue in magnitude seen)						
<code>maxBlockSize</code>	maximum block size (like in subspace iteration or LOBPCG)						
<code>printLevel</code>	message level reporting, from 0 (no output) to 5 (show all)						
<code>locking</code>	1, hard locking; 0, soft locking						
<code>maxBasisSize</code>	maximum size of the search subspace						
<code>minRestartSize</code>	minimum Ritz vectors to keep in restarting						
<code>maxMatvecs</code>	maximum number of matrix vector multiplications						
<code>iseed</code>	an array of four numbers used as a random seed						
<code>method</code>	which equivalent eigenproblem to solve <table style="margin-left: 20px; margin-top: 5px;"> <tr> <td><code>"primme_svds_normalequation"</code></td> <td>A^*A or AA^*</td> </tr> <tr> <td><code>"primme_svds_augmented"</code></td> <td>$[0A^*; A0]$</td> </tr> <tr> <td><code>"primme_svds_hybrid"</code></td> <td>first normal equations and then augmented (default)</td> </tr> </table>	<code>"primme_svds_normalequation"</code>	A^*A or AA^*	<code>"primme_svds_augmented"</code>	$[0A^*; A0]$	<code>"primme_svds_hybrid"</code>	first normal equations and then augmented (default)
<code>"primme_svds_normalequation"</code>	A^*A or AA^*						
<code>"primme_svds_augmented"</code>	$[0A^*; A0]$						
<code>"primme_svds_hybrid"</code>	first normal equations and then augmented (default)						
<code>locking</code>	1, hard locking; 0, soft locking						
<code>primmeStage1</code> , <code>primmeStage2</code>	list with options for the first and the second stage solver; see eigs_sym						

If method is "primme_svds_normalequation", the minimum tolerance that can be achieved is $\|A\|\epsilon/\sigma$, where ϵ is the machine precision. If method is "primme_svds_augmented" or "primme_svds_hybrid", the minimum tolerance is $\|A\|\epsilon$. However it may not return triplets with singular values smaller than $\|A\|\epsilon$.

Value

list with the next elements

d the singular values σ_i

u the left singular vectors u_i

v the right singular vectors v_i

rnorms the residual vector norms $\sqrt{\|Av - \sigma u\|^2 + \|A^*u - \sigma v\|^2}$

stats\$numMatvecs matrix-vector products performed

stats\$numPreconds number of preconditioner applications performed

stats\$elapsedTime time expended by the eigensolver

stats\$timeMatvec time expended in the matrix-vector products

stats\$timePrecond time expended in applying the preconditioner

stats\$estimateANorm estimation of the norm of A

References

[1] L. Wu, E. Romero and A. Stathopoulos, *PRIMME_SVDS: A High-Performance Preconditioned SVD Solver for Accurate Large-Scale Computations*, arXiv:1607.01404

[2] <http://www.cs.wm.edu/~andreas/software/doc/svds.html#parameters-guide>

See Also

[svd](#) for computing all singular triplets; [eigs_sym](#) for computing a few eigenvalues and vectors from a symmetric/Hermitian matrix.

Examples

```
A <- diag(1:5,10,5) # the singular values of this matrix are 1:10 and the
                    # left and right singular vectors are the columns of
                    # diag(1,100,10) and diag(10), respectively
r <- svds(A, 3);
r$d # the three largest singular values on A
r$u # the corresponding approximate left singular vectors
r$v # the corresponding approximate right singular vectors
r$rnorms # the corresponding residual norms
r$stats$numMatvecs # total matrix-vector products spend

r <- svds(A, 3, "S") # compute the three smallest values

r <- svds(A, 3, 2.5) # compute the three closest values to 2.5

A <- diag(1:500,500,100) # we use a larger matrix to amplify the difference
r <- svds(A, 3, 2.5, tol=1e-3); # compute the values with
r$rnorms # residual norm <= 1e-3*||A||

# Build the diagonal squared preconditioner
# and see how reduce the number matrix-vector products
P <- diag(colSums(A^2))
```

```
svds(A, 3, "S", tol=1e-3)$stats$numMatvecs
svds(A, 3, "S", tol=1e-3, prec=list(AHA=P))$stats$numMatvecs

# Passing A and the preconditioner as functions
Af <- function(x,mode) if (mode == "n") A%*%x else crossprod(A,x);
P = colSums(A^2);
PAHAf <- function(x) x / P;
r <- svds(Af, 3, "S", tol=1e-3, prec=list(AHA=PAHAf), m=500, n=100)

# Passing initial guesses
v0 <- diag(1,100,4) + matrix(rnorm(400), 100, 4)/100;
svds(A, 4, "S", tol=1e-3)$stats$numMatvecs
svds(A, 4, "S", tol=1e-3, v0=v0)$stats$numMatvecs

# Passing orthogonal constrain, in this case, already compute singular vectors
r <- svds(A, 4, "S", tol=1e-3); r$d
svds(A, 4, "S", tol=1e-3, orthov=r$v)$d
```


Index

eigen, [2](#), [4](#)
eigs_sym, [2](#), [6](#), [7](#)
svd, [5](#), [7](#)
svds, [4](#), [5](#)