

Package ‘usmap’

January 21, 2021

Version 0.5.2

Title US Maps Including Alaska and Hawaii

Description Obtain United States map data frames of varying region types (e.g. county, state). The map data frames include Alaska and Hawaii conveniently placed to the bottom left, as they appear in most maps of the US. Convenience functions for plotting choropleths and working with FIPS codes are also provided.

Depends R (>= 3.5.0)

License GPL-3 | file LICENSE

Encoding UTF-8

LazyData true

URL <https://usmap.dev>

BugReports <https://github.com/pdil/usmap/issues>

Imports utils

Suggests covr, ggplot2, ggrepel, knitr, maptools, proto, rgdal, rmarkdown, scales, sp, stringr, testthat

RoxygenNote 7.1.1

VignetteBuilder knitr

NeedsCompilation no

Author Paolo Di Lorenzo [aut, cre]

Maintainer Paolo Di Lorenzo <paolo@dilorenzo.pl>

Repository CRAN

Date/Publication 2021-01-21 16:20:03 UTC

R topics documented:

.east_north_central	2
.east_south_central	3
.midwest_region	3
.mid_atlantic	4

.mountain	4
.new_england	5
.northeast_region	5
.north_central_region	6
.pacific	6
.south_atlantic	7
.south_region	7
.west_north_central	8
.west_region	8
.west_south_central	9
citypop	9
countypop	10
countypov	10
earthquakes	11
fips	12
fips_info	13
map_with_data	14
plot_usmap	15
statepop	17
statepov	17
usmap	18
usmap_crs	19
usmap_transform	20
us_map	21

Index 22

.east_north_central *East North Central census division*

Description

US Census Bureau regional division containing Illinois, Indiana, Michigan, Ohio, and Wisconsin.

Usage

```
.east_north_central
```

Format

An object of class character of length 5.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .east_north_central, labels = TRUE)
```

.east_south_central *East South Central census division*

Description

US Census Bureau regional division containing Alabama, Kentucky, Mississippi, and Tennessee.

Usage

```
.east_south_central
```

Format

An object of class character of length 4.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .east_south_central, labels = TRUE)
```

.midwest_region *Midwest census region*

Description

US Census Bureau region containing the East North Central and West North Central divisions. This region was designated as "North Central Region" prior to June 1984.

Usage

```
.midwest_region
```

Format

An object of class character of length 12.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .midwest_region, labels = TRUE)
```

.mid_atlantic	<i>Mid-Atlantic census division</i>
---------------	-------------------------------------

Description

US Census Bureau regional division containing New Jersey, New York, and Pennsylvania.

Usage

```
.mid_atlantic
```

Format

An object of class character of length 3.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .mid_atlantic, labels = TRUE)
```

.mountain	<i>Mountain census division</i>
-----------	---------------------------------

Description

US Census Bureau regional division containing Arizona, Colorado, Idaho, Montana, Nevada, New Mexico, Utah, and Wyoming.

Usage

```
.mountain
```

Format

An object of class character of length 8.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .mountain, labels = TRUE)
```

.new_england *New England census division*

Description

US Census Bureau regional division containing Connecticut, Maine, Massachusetts, New Hampshire, Rhode Island, and Vermont.

Usage

```
.new_england
```

Format

An object of class character of length 6.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .new_england, labels = TRUE)
```

.northeast_region *Northeast census region*

Description

US Census Bureau region containing the New England and Mid-Atlantic divisions.

Usage

```
.northeast_region
```

Format

An object of class character of length 9.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .northeast_region, labels = TRUE)
```

`.north_central_region` *North-Central census region*

Description

Former US Census Bureau region containing the East North Central and West North Central divisions. This region has been designated as "Midwest" since June 1984.

Usage

```
.north_central_region
```

Format

An object of class character of length 12.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .north_central_region, labels = TRUE)
```

`.pacific` *Pacific census division*

Description

US Census Bureau regional division containing Alaska, California, Hawaii, Oregon, and Washington.

Usage

```
.pacific
```

Format

An object of class character of length 5.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .pacific, labels = TRUE)
```

.south_atlantic *South Atlantic census division*

Description

US Census Bureau regional division containing Delaware, Florida, Georgia, Maryland, North Carolina, South Carolina, Virginia, District of Columbia, and West Virginia.

Usage

```
.south_atlantic
```

Format

An object of class character of length 9.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .south_atlantic, labels = TRUE)
```

.south_region *South census region*

Description

US Census Bureau region containing the South Atlantic, East South Central, and West South Central divisions.

Usage

```
.south_region
```

Format

An object of class character of length 17.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .midwest_region, labels = TRUE)
```

.west_north_central *West North Central census division*

Description

US Census Bureau regional division containing Iowa, Kansas, Minnesota, Missouri, Nebraska, North Dakota, and South Dakota.

Usage

```
.west_north_central
```

Format

An object of class character of length 7.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .west_north_central, labels = TRUE)
```

.west_region *West census region*

Description

US Census Bureau region containing the Mountain and Pacific divisions.

Usage

```
.west_region
```

Format

An object of class character of length 13.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .midwest_region, labels = TRUE)
```

.west_south_central *West South Central census division*

Description

US Census Bureau regional division containing Arkansas, Louisiana, Oklahoma, and Texas.

Usage

```
.west_south_central
```

Format

An object of class character of length 4.

Details

See https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf

Examples

```
plot_usmap(include = .west_south_central, labels = TRUE)
```

citypop *Most populous city in each state (2010)*

Description

The most populous city in each US state, as of the 2010 US Census.

The data is formatted for transforming with `usmap_transform`. Once the longitude and latitude is transformed, it can be added to `plot_usmap` using ggplot2 layers.

Usage

```
data(citypop)
```

Format

A data frame with 51 rows and 5 variables.

Details

- lon The longitude of the most populous city.
- lat The latitude of the most populous city.
- state The name of the state containing the city.
- most_populous_city The name of the city.
- city_pop The population of the city.

References

- <https://www.census.gov/programs-surveys/decennial-census/decade.2010.html>

countypop	<i>Population estimates (2015), county level</i>
-----------	--

Description

US census population estimates by county for 2015.

The data is formatted for easy merging with output from [us_map](#).

Usage

```
data(countypop)
```

Format

A data frame with 3142 rows and 4 variables.

Details

- fips The 5-digit FIPS code corresponding to the county.
- abbr The 2-letter state abbreviation.
- county The full county name.
- pop_2015 The 2015 population estimate (in number of people) for the corresponding county.

References

- <https://www.census.gov/programs-surveys/popest.html>
- <https://www.ers.usda.gov/data-products/county-level-data-sets/>

countypov	<i>Poverty percentage estimates (2014), county level</i>
-----------	--

Description

US census poverty percentage estimates by county for 2014.

The data is formatted for easy merging with output from [us_map](#).

Usage

```
data(countypov)
```

Format

A data frame with 3142 rows and 4 variables.

Details

- `fips` The 5-digit FIPS code corresponding to the county.
- `abbr` The 2-letter state abbreviation.
- `county` The full county name.
- `pct_pov_2014` The 2014 poverty estimate (in percent of county population) for the corresponding county.

References

- <https://www.census.gov/topics/income-poverty/poverty.html>
- <https://www.ers.usda.gov/data-products/county-level-data-sets/>

earthquakes

Earthquakes (2019)

Description

US earthquakes with a magnitude of 2.5 or greater, occurring in the first half of 2019, from January 1st to June 30th, from USGS.

The data is formatted for transforming with `usmap_transform`. Once the longitude and latitude is transformed, it can be added to `plot_usmap` using `ggplot2` layers.

Usage

```
data(earthquakes)
```

Format

A data frame with 2254 rows and 3 variables.

Details

- `lon` The longitude of the earthquake's location.
- `lat` The latitude of the earthquake's location.
- `mag` The magnitude of the earthquake.

References

- <https://www.usgs.gov/natural-hazards/earthquake-hazards/earthquakes>
- <https://earthquake.usgs.gov/earthquakes/search/>

`fips`*Retrieve FIPS code for either a US state or county*

Description

Each US state and county has a unique FIPS (Federal Information Processing Standards) code. Use this function to obtain the FIPS code for a state or county.

Usage

```
fips(state, county = c())
```

Arguments

<code>state</code>	The state(s) for which to obtain a FIPS code(s). Can be entered as either a state abbreviation or full name (case-insensitive). 'state' can be entered as either a single state or a vector of states. If 'state' is a vector, 'county' must be omitted.
<code>county</code>	The county for which to obtain a FIPS code. Can be entered with or without "county" (case-insensitive).

Details

State and county FIPS (Federal Information Processing Standards) are two and five digit codes, respectively. They uniquely identify all states and counties within the United States. The first two digits of the five digit county codes correspond to the state that the county belongs to. FIPS codes also exist for US territories and minor outlying islands, though this package only provides information for the 50 US states (and their associated counties and census designated areas).

Value

The FIPS code(s) of given state or county.

If only states are entered, a vector of length equal to the number of states is returned. If any states are not found or are invalid, 'NA' is returned in their place.

If a state and county are entered, a single value with the FIPS code for the given county is returned. If the county is invalid for the given state, an error is thrown.

If both 'state' and 'county' are omitted, the entire list of available FIPS codes is returned, sorted by the state's abbreviation (e.g. Alaska (AK) comes before Alabama (AL)).

Note

A state must be included when searching for county, otherwise multiple results may be returned for duplicate county names.

Examples

```
fips()

fips("NJ")
fips("California")

fips(c("AK", "CA", "UT"))

fips("CA", county = "orange")
fips(state = "AL", county = "autauga")
fips(state = "Alabama", county = "Autauga County")
```

fips_info

*Retrieve states or counties using FIPS codes***Description**

Retrieve states or counties using FIPS codes

Usage

```
fips_info(fips)

## S3 method for class 'numeric'
fips_info(fips)

## S3 method for class 'character'
fips_info(fips)
```

Arguments

fips A one to five digit, either numeric or character, vector of FIPS codes for which to look up states or counties. States have a two digit FIPS code and counties have a five digit FIPS code (where the first 2 numbers pertain to the state).

Value

A data frame with the states or counties and the associated FIPS codes.

If ‘fips’ is omitted, the data frame containing all available states is returned.

Examples

```
fips_info(2)
fips_info("2")
fips_info(c("02", "03", "04"))

fips_info(2016)
fips_info(c("02016", "02017"))
```

map_with_data	<i>Join county or state level data to US map data</i>
---------------	---

Description

Join county or state level data to US map data

Usage

```
map_with_data(data, values = "values", include = c(), exclude = c(), na = NA)
```

Arguments

data	The data that should be joined to a US map. This parameter should be a data frame consisting of two columns, a fips code (2 characters for state, 5 characters for county) and the value that should be associated with that region. The columns of data <i>must</i> be fips or state and the value of the 'values' parameter. If both fips and state are provided, this function uses the fips.
values	The name of the column that contains the values to be associated with a given region. The default is "values".
include	The regions to include in the resulting map. If regions is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. If states are provided in the county map, only counties in the included states will be returned.
exclude	The regions to exclude in the resulting map. If regions is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. The regions listed in the include parameter are applied first and the exclude regions are then removed from the resulting map. Any excluded regions not present in the included regions will be ignored.
na	The value to be inserted for states or counties that don't have a value in data. This value must be of the same type as the value column of data.

Value

A data frame composed of the map data frame (from [us_map](#)) except an extra column containing the values in data is included.

The result can be plotted using `ggplot2`. See [us_map](#) or [plot_usmap](#) for more details.

Examples

```
state_data <- data.frame(fips = c("01", "02", "04"), values = c(1, 5, 8))
df <- map_with_data(state_data, na = 0)

state_data <- data.frame(state = c("AK", "CA", "Utah"), values = c(6, 9, 3))
```

```
df <- map_with_data(state_data, na = 0)
```

plot_usmap

Conveniently plot basic US map

Description

Conveniently plot basic US map

Usage

```
plot_usmap(
  regions = c("states", "state", "counties", "county"),
  include = c(),
  exclude = c(),
  data = data.frame(),
  values = "values",
  theme = theme_map(),
  labels = FALSE,
  label_color = "black",
  ...
)
```

Arguments

regions	The region breakdown for the map, can be one of ("states", "state", "counties", "county"). The default is "states".
include	The regions to include in the resulting map. If regions is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. If states are provided in the county map, only counties in the included states will be returned.
exclude	The regions to exclude in the resulting map. If regions is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. The regions listed in the include parameter are applied first and the exclude regions are then removed from the resulting map. Any excluded regions not present in the included regions will be ignored.
data	A data frame containing values to plot on the map. This parameter should be a data frame consisting of two columns, a fips code (2 characters for state, 5 characters for county) and the value that should be associated with that region. The columns of data <i>must</i> be fips or state and the value of the 'values' parameter.
values	The name of the column that contains the values to be associated with a given region. The default is "value".

theme	The theme that should be used for plotting the map. The default is theme_map from ggthemes .
labels	Whether or not to display labels on the map. Labels are not displayed by default. For now, labels only work for state maps. County labels may be added in the future.
label_color	The color of the labels to display. Corresponds to the color option in the aes mapping. The default is "black". Click here for more color options.
...	Other arguments to pass to ggplot2::aes(). These are often aesthetics, used to set an aesthetic to a fixed value, like color = "red" or size = 3. They affect the appearance of the polygons used to render the map (for example fill color, line color, line thickness, etc.). If any of color/colour, fill, or size are not specified they are set to their default values of color="black", fill="white", and size=0.4.

Value

A [ggplot](#) object that contains a basic US map with the described parameters. Since the result is a ggplot object, it can be extended with more geom layers, scales, labels, themes, etc.

See Also

[usmap](#), [theme](#)

Examples

```
plot_usmap()
plot_usmap(regions = "states")
plot_usmap(regions = "counties")
plot_usmap(regions = "state")
plot_usmap(regions = "county")

# Output is ggplot object so it can be extended
# with any number of ggplot layers
library(ggplot2)
plot_usmap(include = c("CA", "NV", "ID", "OR", "WA")) +
  labs(title = "Western States")

# Color maps with data
plot_usmap(data = statepop, values = "pop_2015")

# Include labels on map (e.g. state abbreviations)
plot_usmap(data = statepop, values = "pop_2015", labels = TRUE)
# Choose color for labels
plot_usmap(data = statepop, values = "pop_2015", labels = TRUE, label_color = "white")
```

statepop	<i>Population estimates (2015), state level</i>
----------	---

Description

US census population estimates by state for 2015.

The data is formatted for easy merging with output from [us_map](#).

Usage

```
data(statepop)
```

Format

A data frame with 51 rows and 4 variables.

Details

- `fips` The 2-digit FIPS code corresponding to the state.
- `abbr` The 2-letter state abbreviation.
- `full` The full state name.
- `pop_2015` The 2015 population estimate (in number of people) for the corresponding state.

References

- <https://www.census.gov/programs-surveys/popest.html>
- <https://www.ers.usda.gov/data-products/county-level-data-sets/>

statepov	<i>Poverty percentage estimates (2014), state level</i>
----------	---

Description

US census poverty percentage estimates by state for 2014.

The data is formatted for easy merging with output from [us_map](#).

Usage

```
data(statepov)
```

Format

A data frame with 51 rows and 4 variables.

Details

- `fips` The 2-digit FIPS code corresponding to the state.
- `abbr` The 2-letter state abbreviation.
- `full` The full state name.
- `pct_pov_2014` The 2014 poverty estimate (in percent of state population) for the corresponding state

References

- <https://www.census.gov/topics/income-poverty/poverty.html>
- <https://www.ers.usda.gov/data-products/county-level-data-sets/>

usmap

usmap: US maps including Alaska and Hawaii

Description

It is usually difficult or inconvenient to create US maps that include both Alaska and Hawaii in a convenient spot. All map data frames produced by this package use the Albers Equal Area projection.

Map data frames

Alaska and Hawaii have been manually moved to a new location so that their new coordinates place them to the bottom-left corner of the map. These maps can be accessed by using the `us_map` function.

The function provides the ability to retrieve maps with either state borders or county borders using the `regions` parameter for convenience.

States (or counties) can be included such that all other states (or counties) are excluded using the `include` parameter.

FIPS lookup tools

Several functions have been included to lookup the US state or county pertaining to a FIPS code.

Likewise a reverse lookup can be done where a FIPS code can be used to retrieve the associated state(s) or county(ies). This can be useful when preparing data to be merged with the map data frame.

Plot US map data

A convenience function `plot_usmap` has been included which takes similar parameters to `us_map` and returns a **ggplot2** object. Since the output is a `ggplot` object, other layers can be added such as scales, themes, and labels. Including data in the function call will color the map according to the values in the data, creating a choropleth.

Author(s)

Paolo Di Lorenzo

- Email: <paolo@dilorenzo.pl>
- Website: <https://dilorenzo.pl>
- Github: <https://github.com/pdil/>

References

Rudis, Bob. "Moving The Earth (well, Alaska & Hawaii) With R." Blog post. Rud.is., 16 Nov. 2014. Web. 10 Aug. 2015. <<https://rud.is/b/2014/11/16/moving-the-earth-well-alaska-hawaii-with-r/>>.

See Also

Helpful links:

- FIPS code information
https://en.wikipedia.org/wiki/FIPS_county_code https://en.wikipedia.org/wiki/FIPS_state_code
- US Census Shapefiles
<https://www.census.gov/geographies/mapping-files/time-series/geo/tiger-line-file.html>
- Map Features
https://en.wikipedia.org/wiki/Map_projection https://en.wikipedia.org/wiki/Albers_projection <https://en.wikipedia.org/wiki/Choropleth>

usmap_crs

usmap coordinate reference system

Description

This coordinate reference system (CRS) represents the canonical projection used by the usmap package. It can be used to transform shape files, spatial points, spatial data frames, etc. to the same coordinate representation that is used by the plot_usmap function.

Usage

usmap_crs()

usmap_transform	<i>Convert coordinate data frame to usmap projection</i>
-----------------	--

Description

Converting an external data frame of map coordinates will allow those points to line up with the regular usmap plot by applying the same Albers Equal Area projection to those points as well.

Usage

```
usmap_transform(data)

## S3 method for class 'data.frame'
usmap_transform(data)
```

Arguments

data A data frame containing coordinates in a two column format where the first column represents longitude and the second data frame represents latitude. The names of the data frame column do not matter, just that the order of the columns is kept intact.

Value

A data frame containing the transformed coordinates from the input data frame with the Albers Equal Area projection applied. The transformed columns will be appended to the data frame so that all original columns should remain intact.

Examples

```
data <- data.frame(
  lon = c(-74.01, -95.36, -118.24, -87.65, -134.42, -157.86),
  lat = c(40.71, 29.76, 34.05, 41.85, 58.30, 21.31),
  pop = c(8398748, 2325502, 3990456, 2705994, 32113, 347397)
)

# Transform data
transformed_data <- usmap_transform(data)

# Plot transformed data on map
library(ggplot2)

plot_usmap() + geom_point(
  data = transformed_data,
  aes(x = lon.1, y = lat.1, size = pop),
  color = "red", alpha = 0.5
)
```

`us_map`*Retrieve US map data*

Description

Retrieve US map data

Usage

```
us_map(  
  regions = c("states", "state", "counties", "county"),  
  include = c(),  
  exclude = c()  
)
```

Arguments

<code>regions</code>	The region breakdown for the map, can be one of ("states", "state", "counties", "county"). The default is "states".
<code>include</code>	The regions to include in the resulting map. If <code>regions</code> is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. If states are provided in the county map, only counties in the included states will be returned.
<code>exclude</code>	The regions to exclude in the resulting map. If <code>regions</code> is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. The regions listed in the <code>include</code> parameter are applied first and the <code>exclude</code> regions are then removed from the resulting map. Any excluded regions not present in the included regions will be ignored.

Value

A data frame of US map coordinates divided by the desired regions.

Examples

```
str(us_map())  
  
df <- us_map(regions = "counties")  
west_coast <- us_map(include = c("CA", "OR", "WA"))  
  
south_atl_excl_FL <- us_map(include = .south_atlantic, exclude = "FL")
```

Index

* datasets

- .east_north_central, 2
- .east_south_central, 3
- .mid_atlantic, 4
- .midwest_region, 3
- .mountain, 4
- .new_england, 5
- .north_central_region, 6
- .northeast_region, 5
- .pacific, 6
- .south_atlantic, 7
- .south_region, 7
- .west_north_central, 8
- .west_region, 8
- .west_south_central, 9

* data

- citypop, 9
- countypop, 10
- countypov, 10
- earthquakes, 11
- statepop, 17
- statepov, 17
- .east_north_central, 2
- .east_south_central, 3
- .mid_atlantic, 4
- .midwest_region, 3
- .mountain, 4
- .new_england, 5
- .north_central_region, 6
- .northeast_region, 5
- .pacific, 6
- .south_atlantic, 7
- .south_region, 7
- .west_north_central, 8
- .west_region, 8
- .west_south_central, 9

aes, 16

citypop, 9

countypop, 10

countypov, 10

earthquakes, 11

fips, 12

fips_info, 13

ggplot, 16

map_with_data, 14

plot_usmap, 9, 11, 14, 15, 18

statepop, 17

statepov, 17

theme, 16

us_map, 10, 14, 17, 18, 21

usmap, 16, 18

usmap-package (usmap), 18

usmap_crs, 19

usmap_transform, 9, 11, 20