

Package ‘altdoc’

June 8, 2023

Type Package

Title Use 'Docsify.js', 'Docute', or 'Mkdocs' to Generate a Package Documentation

Version 0.2.1

Description Most developers use 'pkgdown' to create a website for their packages. Other documentation generators exist, such as 'Docute', 'Docsify.js', or 'Mkdocs'. The aim of 'altdoc' is to provide helpers to create, populate, update, and preview websites made with these tools.

License MIT + file LICENSE

URL <https://github.com/etiennebacher/altdoc>

BugReports <https://github.com/etiennebacher/altdoc/issues>

Imports cli, desc, fs, here, htmltools, rmarkdown, rstudioapi, servr, tinkr, tools, usethis, utils, xml2, yaml

Suggests covr, spelling, testthat (>= 3.0.0), with

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.2.3.9000

Language en-US

NeedsCompilation no

Author Etienne Bacher [aut, cre, cph]

Maintainer Etienne Bacher <etienne.bacher@protonmail.com>

Repository CRAN

Date/Publication 2023-06-08 20:52:52 UTC

R topics documented:

preview	2
update_docs	2
use_docute	3

Index	5
--------------	----------

preview

Preview the documentation in a webpage or in viewer

Description

Preview the documentation in a webpage or in viewer

Usage

```
preview(path = ".")
```

Arguments

path Path. Default is the package root (detected with `here::here()`).

Value

No value returned. If RStudio is used, it shows a site preview in Viewer.

Examples

```
# Preview documentation
preview()
```

update_docs

Update documentation

Description

Update README, Changelog, License, Code of Conduct, and Reference sections (if they exist). Convert and add new or modified vignettes to the documentation. This will leave every other files unmodified.

Usage

```
update_docs(path = ".", custom_reference = NULL)
```

Arguments

path Path. Default is the package root (detected with `here::here()`).

custom_reference Path to the file that will be sourced to generate the "Reference" section.

Value

No value returned. Updates files in folder 'docs'.

Examples

```
if (interactive()) {
  # Update documentation
  update_docs()
}
```

 use_docute

Init Docute, Docsify, or Mkdocs

Description

Init Docute, Docsify, or Mkdocs

Usage

```
use_docute(path = ".", overwrite = FALSE, custom_reference = NULL)
```

```
use_docsify(path = ".", overwrite = FALSE, custom_reference = NULL)
```

```
use_mkdocs(
  theme = NULL,
  path = ".",
  overwrite = FALSE,
  custom_reference = NULL
)
```

Arguments

path	Path. Default is the package root (detected with <code>here::here()</code>).
overwrite	Overwrite the folder 'docs' if it already exists. If FALSE (default), there will be an interactive choice to make in the console to overwrite. If TRUE, the folder 'docs' is automatically overwritten.
custom_reference	Path to the file that will be sourced to generate the "Reference" section.
theme	Name of the theme to use. Default is basic theme. See Details section.

Details

If you are new to Mkdocs, the themes "readthedocs" and "material" are among the most popular and developed. You can also see a list of themes here: <https://github.com/mkdocs/mkdocs/wiki/MkDocs-Themes>.

Value

No value returned. Creates files in folder 'docs'. Other files and folders are not modified.

Examples

```
if (interactive()) {  
  # Create docute documentation  
  use_docute()  
  
  # Create docsify documentation  
  use_docsify()  
  
  # Create mkdocs documentation  
  use_mkdocs()  
}
```

Index

preview, [2](#)

update_docs, [2](#)

use_docsify (use_docute), [3](#)

use_docute, [3](#)

use_mkdocs (use_docute), [3](#)