

Package ‘cmvnorm’

May 20, 2019

Type Package

Title The Complex Multivariate Gaussian Distribution

Version 1.0-6

Depends emulator ($\geq 1.2-15$)

Suggests knitr

Imports elliptic

Maintainer Robin K. S. Hankin <hankin.robin@gmail.com>

Description Various utilities for the complex multivariate Gaussian distribution.

VignetteBuilder knitr

License GPL-2

URL <https://github.com/RobinHankin/cmvnorm.git>

BugReports <https://github.com/RobinHankin/cmvnorm/issues>

NeedsCompilation no

Author Robin K. S. Hankin [aut, cre] (<<https://orcid.org/0000-0001-5982-0415>>)

Repository CRAN

Date/Publication 2019-05-20 21:20:03 UTC

R topics documented:

cmvnorm-package	2
corr_complex	3
isHermitian	5
Mvcnorm	6
setreal	7
var	8

Index	10
--------------	-----------

cmvnorm-package

The Complex Multivariate Gaussian Distribution

Description

Various utilities for the complex multivariate Gaussian distribution.

Details

The DESCRIPTION file:

```
Package:      cmvnorm
Type:        Package
Title:       The Complex Multivariate Gaussian Distribution
Version:     1.0-6
Authors@R:   person(given=c("Robin", "K. S."), family="Hankin", role = c("aut","cre"), email="hankin.robin@gmail.co
Depends:     emulator (>= 1.2-15)
Suggests:   knitr
Imports:     elliptic
Maintainer:  Robin K. S. Hankin <hankin.robin@gmail.com>
Description: Various utilities for the complex multivariate Gaussian distribution.
VignetteBuilder: knitr
License:     GPL-2
URL:        https://github.com/RobinHankin/cmvnorm.git
BugReports: https://github.com/RobinHankin/cmvnorm/issues
Author:     Robin K. S. Hankin [aut, cre] (<https://orcid.org/0000-0001-5982-0415>)
```

Index of help topics:

```
Im<-          Manipulate real or imaginary components of an
              object
Mvnorm        Multivariate complex Gaussian density and
              random deviates
cmvnorm-package The Complex Multivariate Gaussian Distribution
corr_complex  Complex Gaussian processes
isHermitian   Is a Matrix Hermitian?
var           Variance and standard deviation of complex
              vectors
```

Generalizing the real multivariate Gaussian distribution to the complex case is not straightforward but one common approach is to replace the real symmetric variance matrix with a Hermitian positive-definite matrix. The **cmvnorm** package provides some functionality for the resulting density function.

Author(s)

NA

Maintainer: Robin K. S. Hankin <hankin.robin@gmail.com>

References

- N. R. Goodman 1963. “Statistical analysis based on a certain multivariate complex Gaussian distribution”. *The Annals of Mathematical Statistics*. 34(1): 152–177
- R. K. S. Hankin 2015. “The complex multivariate Gaussian distribution”. *R News*, volume 7, number 1.

Examples

```
S1 <- 4+diag(5)
S2 <- S1
S2[1,5] <- 4+1i
S2[5,1] <- 4-1i # Hermitian

rcmvnorm(10,sigma=S1)
rcmvnorm(10,mean=rep(1i,5),sigma=S2)

dcmvnorm(rep(1,5),sigma=S2)
```

corr_complex	<i>Complex Gaussian processes</i>
--------------	-----------------------------------

Description

Various utilities for investigating complex Gaussian processes

Usage

```
corr_complex(z1, z2 = NULL, distance.function = complex_CF, means =
NULL, scales = NULL, pos.def.matrix = NULL)
complex_CF(z1,z2, means, pos.def.matrix)
scales.likelihood.complex(pos.def.matrix, scales, means, zold, z,
give_log = TRUE, func = regressor.basis)
interpolant.quick.complex(x, d, zold, Ainv, scales = NULL, pos.def.matrix = NULL,
means=NULL, func = regressor.basis, give.Z = FALSE,
distance.function = corr_complex, ...)
```

Arguments

`z`, `z1`, `z2` Points in C^n
`distance.function` Function giving the (complex) covariance between two points in C^n

means, pos.def.matrix, scales

In function `complex_CF()`, the mean and covariance matrix of the distribution whose characteristic function is used as to give the covariance matrix; `scales` is used to specify the diagonal of `pos.def.matrix` if the off-diagonal elements are zero

zold, d, give_log, func, x, Ainv, give.Z,...

Direct analogues of the arguments in `interpolant()` and `scales.likelihood()` in the **emulator** package

Details

- Function `complex_CF()` returns a (slightly reparameterized) characteristic function of a complex Gaussian distribution. The covariance is given by

$$c(\mathbf{t}) = \exp(i\text{Re}(\mathbf{t}^* \mu) - \mathbf{t}^* B \mathbf{t})$$

where $\mathbf{t} = \mathbf{x} - \mathbf{x}'$ is interpreted as the distance between two observations, μ is the mean of the distribution (which is in general a complex vector), and B a positive-definite matrix.

- Function `corr_complex()` is the complex analogue of `corr.matrix()`. It returns a matrix with entry (i, j) equal to the covariance of the process at observation i and observation j , or $\text{cov}(\eta(\mathbf{x}_i), \eta(\mathbf{x}_j))$. The elements are calculated by `complex_CF()`.

This function includes only a single method, that of nested calls to `apply()`. I could not figure out how to generalize method 1 of `corr.matrix()` to the complex case.

- Function `scales.likelihood.complex()` is a complex version of `scales.likelihood()` which takes a positive definite matrix and a mean. The formula used is

$$(\sigma^2)^{-(n-q)} |A|^{-1} |H^* A^{-1} H|^{-1}$$

. Here and elsewhere, A^* means the complex conjugate of the transpose.

- Function `interpolant.quick.complex()` is a complex version of `interpolant.quick()`.

$$\mathbf{h}(\mathbf{x})^* \hat{\beta} + \mathbf{t}(\mathbf{x})^* A^{-1} (\mathbf{y} - H \hat{\beta})$$

This is the complex version of Oakley's equation 2.30 or Hankin's equation 5.

More details are given in the package vignette.

Author(s)

Robin K. S. Hankin

References

- Hankin, R. K. S. 2005. "Introducing BACCO, an R bundle for Bayesian Analysis of Computer Code Output", *Journal of Statistical Software*, 14(15)
- J. Oakley 1999. *Bayesian uncertainty analysis for complex computer codes*, PhD thesis, University of Sheffield.

Examples

```

complex_CF(c(1,1i),c(1,-1i),means=c(1i,1i),pos.def.matrix=diag(2))

V <- latin.hypercube(7,2,complex=TRUE)

cm <- c(1,1+1i)           # "complex mean"
cs <- matrix(c(2,1i,-1i,1),2,2) # "complex scales"
tb <- c(1,1i,1-1i)       # "true beta"

A <- corr_complex(V,means=cm,pos.def.matrix=cs)
Ainv <- solve(A)
z <- drop(rcmvnorm(n=1,mean=regressor.multi(V) %*% tb, sigma=A))

betahat.fun(V,Ainv,z)    # should be close to 'tb'

#scales.likelihood.complex(cs,cm,V,z) # log-likelihood evaluated true parameters

interpolant.quick.complex(x=0.1i+V[1:3,],d=z,zold=V,Ainv=Ainv,pos.def.matrix=cs,means=cm)

```

isHermitian

Is a Matrix Hermitian?

Description

Returns TRUE if a matrix is Hermitian or Hermitian positive-definite

Usage

```

isHermitian(x, tol = 100 * .Machine$double.eps)
ishpd(x,tol= 100 * .Machine$double.eps)
zapim(x,tol= 100 * .Machine$double.eps)

```

Arguments

x	A square matrix
tol	Tolerance for numerical scruff

Details

Functions isHermitian() and ishpd() return a Boolean. Function zapim() zaps small imaginary parts of components vector, returning real if all elements are so zapped.

Author(s)

Robin K. S. Hankin

Examples

```
v <- 2^(1:30)
zapim(v+1i*exp(-v))
```

```
ishpd(matrix(c(1,0.1i,-0.1i,1),2,2)) # should be TRUE
isHermitian(matrix(c(1,3i,-3i,1),2,2)) # should be TRUE
```

Mvnorm

Multivariate complex Gaussian density and random deviates

Description

Density function and a random number generator for the multivariate complex Gaussian distribution.

Usage

```
rcnorm(n)
dcmvnorm(z, mean, sigma, log = FALSE)
rcmvnorm(n, mean = rep(0, nrow(sigma)), sigma = diag(length(mean)),
  method = c("svd", "eigen", "chol"),
  tol = 100 * .Machine$double.eps)
```

Arguments

z	Complex vector or matrix of quantiles. If a matrix, each row is taken to be a quantile
n	Number of observations
mean	Mean vector
sigma	Covariance matrix, Hermitian positive-definite
tol	numerical tolerance term for verifying positive definiteness
log	In dcmvnorm(), Boolean with default TRUE meaning to return the Gaussian density function, and FALSE meaning to return the logarithm
method	Matrix decomposition used to determine the positive-definite matrix square root of sigma, possible methods are eigenvalue decomposition ("eigen", default), and singular value decomposition ("svd")

Details

Function `dcmvnorm()` is the density function of the complex multivariate normal (Gaussian) distribution:

$$p(\mathbf{z}) = \frac{\exp(-\mathbf{z}^* \Gamma \mathbf{z})}{|\pi \Gamma|}$$

Function `rcnorm()` is a low-level function designed to generate observations drawn from a standard complex Gaussian. Function `rcmvnorm()` is a user-friendly wrapper for this.

Author(s)

Robin K. S. Hankin

References

N. R. Goodman 1963. "Statistical analysis based on a certain multivariate complex Gaussian distribution". *The Annals of Mathematical Statistics*. 34(1): 152–177

Examples

```
S <- emulator::cprod(rcmvnorm(3,mean=c(1,1i),sigma=diag(2)))

rcmvnorm(10,sigma=S)
rcmvnorm(10,mean=c(0,1+10i),sigma=S)

# Now try and estimate the mean (viz 1,1i) and variance (S) from a
# random sample:

n <- 101
z <- rcmvnorm(n,mean=c(0,1+10i),sigma=S)
xbar <- colMeans(z)
Sbar <- cprod(sweep(z,2,xbar))/n
```

 setreal

Manipulate real or imaginary components of an object

Description

Manipulate real or imaginary components of an object

Usage

```
Im(x) <- value  
Re(x) <- value
```

Arguments

x	Complex-valued object
value	Real-valued object

Author(s)

Robin K. S. Hankin

Examples

```
A <- matrix(c(1,0.1i,-0.1i,1),2,2)  
Im(A) <- Im(A)*3  
Re(A) <- matrix(c(5,2,2,5),2,2)
```

var

Variance and standard deviation of complex vectors

Description

Complex generalizations of `stats::sd()` and `stats::var()`

Usage

```
var(x, y=NULL, na.rm=FALSE, use)  
sd(x, na.rm=FALSE)
```

Arguments

x, y	Complex vector or matrix
na.rm	Boolean with default FALSE meaning to leave NA values present and TRUE meaning to remove them
use	Ignored

Details

Intended to be broadly compatible with `stats::sd()` and `stats::var()`.

If given real values, `var()` and `sd()` return the variance and standard deviation as per ordinary real analysis. If given complex values, returns the complex generalization in which Hermitian transposes are used.

If `z` is a complex matrix, `var(z)` returns the variance of the rows.

These functions use $n - 1$ on the denominator purely for consistency with `stats::var()` (for the record, I disagree with the rationale for $n - 1$).

Author(s)

Robin K. S. Hankin

Examples

```
sd(rcnorm(10)) # imaginary component suppressed by zapim()
var(rcmvnorm(1e5, mean=c(0,0)))
```

Index

- *Topic **complex**
 - isHermitian, 5
 - Mvnorm, 6
 - setreal, 7
- *Topic **distribution**
 - Mvnorm, 6
- *Topic **math**
 - setreal, 7
- *Topic **multivariate**
 - Mvnorm, 6
- *Topic **package**
 - cmvnorm-package, 2

cmvnorm (cmvnorm-package), 2
cmvnorm-package, 2
complex_CF (corr_complex), 3
corr_complex, 3

dcmvnorm (Mvnorm), 6

Im<- (setreal), 7
interpolant.quick.complex
 (corr_complex), 3
isHermitian, 5
ishpd (isHermitian), 5

Mvnorm, 6

rcmvnorm (Mvnorm), 6
rcnorm (Mvnorm), 6
Re<- (setreal), 7

scales.likelihood.complex
 (corr_complex), 3
sd (var), 8
setreal, 7

var, 8

zapim (isHermitian), 5