

Package ‘generalCorr’

November 10, 2021

Type Package

Title Generalized Correlations, Causal Paths and Portfolio Selection

Version 1.2.0

Date 2021-11-09

Author Prof. H. D. Vinod, Fordham University, NY.

Maintainer H. D. Vinod <vinod@fordham.edu>

Encoding UTF-8

Depends R (>= 3.0.0), np (>= 0.60), xtable (>= 1.8), meboot (>= 1.4),
psych, lattice

Suggests R.rsp

VignetteBuilder R.rsp

Description Since causal paths from data are important for all sciences, the package provides many sophisticated functions. `causeSummBlk()` gives easy-to-interpret causal paths. Let Z denote control variables and compare two flipped kernel regressions: $X=f(Y, Z)+e_1$ and $Y=g(X, Z)+e_2$. Our criterion Cr_1 says that if $|e_1 * Y| > |e_2 * X|$ then variation in X is more “exogenous or independent” than in Y and causal path is X to Y . Criterion Cr_2 requires $|e_2| < |e_1|$. These inequalities between many absolute values are quantified by four orders of stochastic dominance. Our third criterion Cr_3 for the causal path X to Y requires new generalized partial correlations to satisfy $|r^*(x|y, z)| < |r^*(y|x, z)|$. The function `parcorVec()` reports generalized partials between the first variable and all others. The package provides several R functions including `get0outliers()` for outlier detection, `bigfp()` for numerical integration by the trapezoidal rule, `stochdom2()` for stochastic dominance, `pillar3D()` for 3D charts, `canonRho()` for generalized canonical correlations, `depMeas()` measures nonlinear dependence, and `causeSummary(mtx)` reports summary of causal paths among matrix columns is easiest to use. Portfolio selection: `decileVote()`, `momentVote()`, `dif4mtx()`, `exactSdMtx()` can rank several stocks. Several functions whose names begin with 'boot' provide bootstrap statistical inference including a new `bootGcRsqr()` test for “Granger-causality” allowing nonlinear relations. See five vignettes of the package for theory and usage tips. See Vinod (2019) \doi{10.1080/03610918.2015.1122048}.

License GPL (>= 2)

LazyData true

RoxygenNote 7.1.2

NeedsCompilation no

Repository CRAN

Date/Publication 2021-11-10 05:20:02 UTC

R topics documented:

absBstdres	5
absBstdresC	6
absBstdrhserC	7
abs_res	8
abs_stdapd	9
abs_stdapdC	10
abs_stdres	11
abs_stdresC	12
abs_stdrhserC	14
abs_stdrhser	15
allPairs	16
badCol	17
bigfp	18
bootDom12	19
bootGcLC	20
bootGcRsq	21
bootPairs	23
bootPairs0	24
bootQuantile	26
bootSign	27
bootSignPcent	29
bootSummary	30
canonRho	31
causeAllPair	33
causeSummary	35
causeSummary0	37
causeSummBlk	40
causeSumNoP	42
cofactor	44
comp_portfo2	45
da	46
da2Lag	47
decileVote	47
depMeas	48
dif4	49
dif4mtx	50
diff.e0	51
dig	51

e0	51
EuroCrime	52
exactSdMtx	52
GcRsqX12	53
GcRsqX12c	54
GcRsqYX	56
GcRsqYXc	57
generalCorrInfo	59
get0outliers	60
getSeq	61
gmc0	62
gmc1	62
gmcmtx0	63
gmcmtxBlk	64
gmcmtxZ	66
gmcxy_np	67
goodCol	68
heurist	68
i	69
ibad	69
ii	69
j	70
kern	70
kern2	71
kern2ctrl	73
kern_ctrl	74
mag	76
mag_ctrl	77
min.e0	78
minor	78
momentVote	79
mtx	80
mtx0	81
mtx2	81
n	81
nall	82
nam.badCol	82
nam.goodCol	82
nam.mtx0	82
napair	83
naTriplet	83
NLhat	84
out1	85
p1	85
Panel2Lag	86
PanelLag	87
parcorBijk	88
parcorBMany	89

parcorHijk	90
parcorMany	91
parcorMtx	93
parcorSilent	94
parcorVec	96
parcorVecH	98
parcor_ijk	99
parcor_ijkOLD	100
parcor_linear	101
parcor_ridg	102
pcause	104
pillar3D	105
prelec2	106
probSign	107
rhs.lag2	109
rhs1	109
ridgek	109
rij	109
rijMrji	110
rji	110
rrij	110
rrji	110
rstar	111
sales2Lag	112
salesLag	112
seed	112
sgn.e0	113
silentMtx	113
silentMtx0	115
silentPairs	117
silentPairs0	119
siPairsBlk	121
some0Pairs	124
someCPairs	126
someCPairs2	128
someMagPairs	130
somePairs	132
somePairs2	134
sort.abse0	135
sort.e0	135
sort_matrix	136
stdres	136
stdz_xy	137
stochdom2	138
sudoCoefParcor	139
sudoCoefParcorH	141
summaryRank	143
symmze	143

absBstdres *Block version of abs-stdres Absolute values of residuals of kernel regressions of standardized x on standardized y, no control variables.*

Description

1) Standardize the data to force mean zero and variance unity, 2) kernel regress x on y, with the option 'residuals = TRUE' and finally 3) compute the absolute values of residuals.

Usage

```
absBstdres(x, y, blksiz = 10)
```

Arguments

x	vector of data on the dependent variable
y	data on the regressors which can be a matrix
blksiz	block size, default=10, if chosen blksiz >n, where n=rows in matrix then blksiz=n. That is, no blocking is done

Details

The first argument is assumed to be the dependent variable. If `abs_stdres(x,y)` is used, you are regressing x on y (not the usual y on x). The regressors can be a matrix with 2 or more columns. The missing values are suitably ignored by the standardization.

Value

Absolute values of kernel regression residuals are returned after standardizing the data on both sides so that the magnitudes of residuals are comparable between regression of x on y on the one hand and regression of y on x on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

Examples

```
## Not run:
set.seed(330)
x=sample(20:50)
y=sample(20:50)
abs_stdres(x,y)

## End(Not run)
```

absBstdresC

Block version of Absolute values of residuals of kernel regressions of standardized x on standardized y and control variables.

Description

1) standardize the data to force mean zero and variance unity, 2) kernel regress x on y and a matrix of control variables, with the option 'residuals = TRUE' and finally 3) compute the absolute values of residuals.

Usage

```
absBstdresC(x, y, ctrl, blksize = 10)
```

Arguments

x	vector of data on the dependent variable
y	data on the regressors which can be a matrix
ctrl	Data matrix on the control variable(s) beyond causal path issues
blksize	block size, default=10, if chosen blksize >n, where n=rows in matrix then blksize=n. That is, no blocking is done

Details

The first argument is assumed to be the dependent variable. If `abs_stdres(x,y)` is used, you are regressing x on y (not the usual y on x). The regressors can be a matrix with two or more columns. The missing values are suitably ignored by the standardization.

Value

Absolute values of kernel regression residuals are returned after standardizing the data on both sides so that the magnitudes of residuals are comparable between regression of x on y on the one hand and regression of y on x on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D.'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [gffn86](#)

See Also

See [abs_stdres](#).

Examples

```
## Not run:
set.seed(330)
x=sample(20:50)
y=sample(20:50)
z=sample(21:51)
absBstdresC(x,y,ctrl=z)

## End(Not run)
```

absBstdrhserC	<i>Block version abs_stdrhser Absolute residuals kernel regressions of standardized x on y and control variables, CrI has abs(Resid*RHS).</i>
---------------	---

Description

1) standardize the data to force mean zero and variance unity, 2) kernel regress x on y and a matrix of control variables, with the option 'residuals = TRUE' and finally 3) compute the absolute values of residuals.

Usage

```
absBstdrhserC(x, y, ctrl, ycolumn = 1, blksiz = 10)
```

Arguments

x	vector of data on the dependent variable
y	data on the regressors which can be a matrix
ctrl	Data matrix on the control variable(s) beyond causal path issues
ycolumn	if y has more than one column, the column number used when multiplying residuals times this column of y, default=1 or first column of y matrix is used
blksiz	block size, default=10, if chosen blksiz >n, where n=rows in matrix then blksiz=n. That is, no blocking is done

Details

The first argument is assumed to be the dependent variable. If `absBstdrhserC(x,y)` is used, you are regressing x on y (not the usual y on x). The regressors can be a matrix with 2 or more columns. The missing values are suitably ignored by the standardization.

Value

Absolute values of kernel regression residuals are returned after standardizing the data on both sides so that the magnitudes of residuals are comparable between regression of x on y on the one hand and regression of y on x on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

See Also

See [abs_stdres](#).

Examples

```
## Not run:
set.seed(330)
x=sample(20:50)
y=sample(20:50)
z=sample(21:51)
absBstdrhserC(x,y,ctrl=z)

## End(Not run)
```

abs_res

Absolute residuals of kernel regression of x on y .

Description

This internal function calls the kern function to implement kernel regression with the option `residuals=TRUE` and returns absolute residuals.

Usage

```
abs_res(x, y)
```


Arguments

x vector of data on the dependent variable
y vector of data on the regressor

Details

The first argument is assumed to be the dependent variable. If `abs_res(x,y)` is used, you are regressing x on y (not the usual y on x)

Value

absolute values of kernel regression residuals are returned.

Note

This function is intended for internal use.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
## Not run:
set.seed(330)
x=sample(20:50)
y=sample(20:50)
abs_res(x,y)

## End(Not run)
```

abs_stdapd	<i>Absolute values of gradients (apd's) of kernel regressions of x on y when both x and y are standardized.</i>
------------	---

Description

1) standardize the data to force mean zero and variance unity, 2) kernel regress x on y, with the option 'gradients = TRUE' and finally 3) compute the absolute values of gradients

Usage

```
abs_stdapd(x, y)
```

Arguments

x vector of data on the dependent variable
y data on the regressors which can be a matrix

Details

The first argument is assumed to be the dependent variable. If `abs_stdapd(x, y)` is used, you are regressing x on y (not the usual y on x). The regressors can be a matrix with 2 or more columns. The missing values are suitably ignored by the standardization.

Value

Absolute values of kernel regression gradients are returned after standardizing the data on both sides so that the magnitudes of amorphous partial derivatives (apd's) are comparable between regression of x on y on the one hand and regression of y on x on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
## Not run:
set.seed(330)
x=sample(20:50)
y=sample(20:50)
abs_stdapd(x,y)

## End(Not run)
```

abs_stdapdC

Absolute values of gradients (apd's) of kernel regressions of x on y when both x and y are standardized and control variables are present.

Description

1) standardize the data to force mean zero and variance unity, 2) kernel regress x on y and a matrix of control variables, with the option 'gradients = TRUE' and finally 3) compute the absolute values of gradients

Usage

```
abs_stdapdC(x, y, ctrl)
```

Arguments

<code>x</code>	vector of data on the dependent variable
<code>y</code>	data on the regressors which can be a matrix
<code>ctrl</code>	Data matrix on the control variable(s) beyond causal path issues

Details

The first argument is assumed to be the dependent variable. If `abs_stdapdC(x, y)` is used, you are regressing x on y (not the usual y on x). The regressors can be a matrix with 2 or more columns. The missing values are suitably ignored by the standardization.

Value

Absolute values of kernel regression gradients are returned after standardizing the data on both sides so that the magnitudes of amorphous partial derivatives (apd's) are comparable between regression of x on y on the one hand and regression of y on x on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

See Also

See [abs_stdapd](#).

Examples

```
## Not run:
set.seed(330)
x=sample(20:50)
y=sample(20:50)
z=sample(20:50)
abs_stdapdC(x,y,ctrl=z)

## End(Not run)
```

abs_stdres	<i>Absolute values of residuals of kernel regressions of x on y when both x and y are standardized.</i>
------------	---

Description

1) Standardize the data to force mean zero and variance unity, 2) kernel regress x on y , with the option 'residuals = TRUE' and finally 3) compute the absolute values of residuals.

Usage

```
abs_stdres(x, y)
```

Arguments

x	vector of data on the dependent variable
y	data on the regressors which can be a matrix

Details

The first argument is assumed to be the dependent variable. If `abs_stdres(x,y)` is used, you are regressing x on y (not the usual y on x). The regressors can be a matrix with 2 or more columns. The missing values are suitably ignored by the standardization.

Value

Absolute values of kernel regression residuals are returned after standardizing the data on both sides so that the magnitudes of residuals are comparable between regression of x on y on the one hand and regression of y on x on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. ‘Generalized Correlation and Kernel Causality with Applications in Development Economics’ in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

Examples

```
## Not run:
set.seed(330)
x=sample(20:50)
y=sample(20:50)
abs_stdres(x,y)

## End(Not run)
```

abs_stdresC

Absolute values of residuals of kernel regressions of x on y when both x and y are standardized and control variables are present (C for control presence).

Description

1) standardize the data to force mean zero and variance unity, 2) kernel regress x on y and a matrix of control variables, with the option ‘residuals = TRUE’ and finally 3) compute the absolute values of residuals.

Usage

```
abs_stdresC(x, y, ctrl)
```

Arguments

x	vector of data on the dependent variable
y	data on the regressors which can be a matrix
ctrl	Data matrix on the control variable(s) beyond causal path issues

Details

The first argument is assumed to be the dependent variable. If `abs_stdres(x,y)` is used, you are regressing x on y (not the usual y on x). The regressors can be a matrix with two or more columns. The missing values are suitably ignored by the standardization.

Value

Absolute values of kernel regression residuals are returned after standardizing the data on both sides so that the magnitudes of residuals are comparable between regression of x on y on the one hand and regression of y on x on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D.'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

See [abs_stdres](#).

Examples

```
## Not run:  
set.seed(330)  
x=sample(20:50)  
y=sample(20:50)  
z=sample(21:51)  
abs_stdresC(x,y,ctrl=z)  
  
## End(Not run)
```

abs_stdrhserC *Absolute residuals kernel regressions of standardized x on y and control variables, Cr1 has abs(RHS*y) not gradients.*

Description

1) standardize the data to force mean zero and variance unity, 2) kernel regress x on y and a matrix of control variables, with the option 'residuals = TRUE' and finally 3) compute the absolute values of residuals.

Usage

```
abs_stdrhserC(x, y, ctrl, ycolumn = 1)
```

Arguments

x	vector of data on the dependent variable
y	data on the regressors which can be a matrix
ctrl	Data matrix on the control variable(s) beyond causal path issues
ycolumn	if y has more than one column, the column number used when multiplying residuals times this column of y, default=1 or first column of y matrix is used

Details

The first argument is assumed to be the dependent variable. If `abs_stdrhserC(x,y)` is used, you are regressing x on y (not the usual y on x). The regressors can be a matrix with 2 or more columns. The missing values are suitably ignored by the standardization.

Value

Absolute values of kernel regression residuals are returned after standardizing the data on both sides so that the magnitudes of residuals are comparable between regression of x on y on the one hand and regression of y on x on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

See [abs_stdres](#).

Examples

```
## Not run:  
set.seed(330)  
x=sample(20:50)  
y=sample(20:50)  
z=sample(21:51)  
abs_stdrhserC(x,y,ctrl=z)  
  
## End(Not run)
```

abs_stdrhser	<i>Absolute values of Hausman-Wu null in kernel regressions of x on y when both x and y are standardized.</i>
--------------	---

Description

1) standardize the data to force mean zero and variance unity, 2) kernel regress x on y, with the option 'gradients = TRUE' and finally 3) compute the absolute values of Hausman-Wu null hypothesis for testing exogeneity, or $E(\text{RHS.regressor} \cdot \text{error}) = 0$ where error is approximated by kernel regression residuals

Usage

```
abs_stdrhser(x, y)
```

Arguments

x	vector of data on the dependent variable
y	data on the regressors which can be a matrix

Details

The first argument is assumed to be the dependent variable. If `abs_stdrhser(x,y)` is used, you are regressing x on y (not the usual y on x). The regressors can be a matrix with 2 or more columns. The missing values are suitably ignored by the standardization.

Value

Absolute values of kernel regression $\text{RHS} \cdot \text{residuals}$ are returned after standardizing the data on both sides so that the magnitudes of Hausman-Wu null values are comparable between regression of x on y on the one hand and flipped regression of y on x on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
## Not run:
set.seed(330)
x=sample(20:50)
y=sample(20:50)
abs_stdhrserr(x,y)

## End(Not run)
```

allPairs

Report causal identification for all pairs of variables in a matrix (deprecated function). It is better to choose a target variable and pair it with all others, instead of considering all possible targets.

Description

This studies all possible (perhaps too many) causal directions in a matrix. It is deprecated because it uses older criterion 1 by calling `abs_stdapd` I recommend using `causeSummary` or its block version `cuseSummBlk`. This uses `abs_stdres`, `comp_portfo2`, etc. and returns a matrix with 7 columns having detailed output. Criterion 1 has been revised as described in Vinod (2019) and is known to work better.

Usage

```
allPairs(mtx, dig = 6, verbo = FALSE, typ = 1, rnam = FALSE)
```

Arguments

<code>mtx</code>	Input matrix with variable names
<code>dig</code>	Digits of accuracy in reporting (=6, default)
<code>verbo</code>	Logical variable, set to 'TRUE' if printing is desired
<code>typ</code>	Causal direction criterion number (<code>typ=1</code> is default) Criterion 1 (Cr1) compares kernel regression absolute values of gradients. Criterion 2 (Cr2) compares kernel regression absolute values of residuals. Criterion 3 (Cr3) compares kernel regression based $r^*(x y)$ with $r^*(y x)$.
<code>rnam</code>	Logical variable, default <code>rnam=FALSE</code> means the user does not want the row names to be (somewhat too cleverly) assigned by the function.

Value

A 7-column matrix called 'outcause' with names of variables X and Y in the first two columns and the name of the 'causal' variable in 3rd col. Remaining four columns report numerical computations of SD1 to SD4, $r^*(x|y)$, $r^*(y|x)$. Pearson r and p-values for its traditional significance testing.

Note

The cause reported in the third column is identified from the sign of the first SD1 only, ignoring SD2, SD3 and SD4 under both Cr1 and Cr2. It is a good idea to loop a call to this function with `typ=1:3`. One can print the resulting 'outcause' matrix with the `xtable(outcause)` for the Latex output. A similar deprecated function included in this package, called `some0Pairs`, incorporates all SD1 to SD4 and all three criteria Cr1 rto Cr3 to report a 'sum' of indexes representing the signed number whose sign can more comprehensively help determine the causal direction(s). Since the Cr1 here is revised in later work, this is deprecated.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D.'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

See Also

See Also `somePairs`, `some0Pairs` `causeSummary`

Examples

```
data(mtcars)
options(np.messages=FALSE)
for(j in 1:3){
a1=allPairs(mtcars[,1:3], typ=j)
print(a1)}
```

badCol

internal badCol

Description

intended for internal use

Usage

```
data(badCol)
```

Format

The format is: int 4

bigfp

Compute the numerical integration by the trapezoidal rule.

Description

See page 220 of Vinod (2008) “Hands-on Intermediate Econometrics Using R,” for the trapezoidal integration formula needed for stochastic dominance. The book explains pre-multiplication by two large sparse matrices denoted by I_F, I_f . Here we accomplish the same computation without actually creating the large sparse matrices. For example, the I_f is replaced by cumsum in this code (unlike the R code in my textbook).

Usage

bigfp(d, p)

Arguments

d A vector of consecutive interval lengths, upon combining both data vectors
 p Vector of probabilities of the type 1/2T, 2/2T, 3/2T, etc. to 1.

Value

Returns a result after pre-multiplication by I_F, I_f matrices, without actually creating the large sparse matrices. This is an internal function.

Note

This is an internal function, called by the function stochdom2, for comparison of two portfolios in terms of stochastic dominance (SD) of orders 1 to 4. Typical usage is: sd1b=bigfp(d=dj,p=rhs) sd2b=bigfp(d=dj,p=sd1b) sd3b=bigfp(d=dj,p=sd2b) sd4b=bigfp(d=dj,p=sd3b). This produces numerical evaluation vectors for the four orders, SD1 to SD4.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D., 'Hands-On Intermediate Econometrics Using R' (2008) World Scientific Publishers: Hackensack, NJ. <https://www.worldscientific.com/worldscibooks/10.1142/6895>

bootDom12	<i>bootstrap confidence intervals for exact stochastic dominance SD1 to SD4.</i>
-----------	--

Description

This calls the meboot package to create J=999 replications of portfolio return matrices and compute 95% confidence intervals on x1, x2 and their difference (x2-x1). If the interval on (x2-x1) contains zero the choice between the two can reverse due to sampling variation

Usage

```
bootDom12(x1, x2, confLevel = 95, reps = 999)
```

Arguments

x1	a vector of n portfolio returns
x2	a vector of n portfolio returns
confLevel	confidence level confLevel=95 is default
reps	number of bootstrap resamples, default is reps=999

Value

a matrix with six columns. First two Low1 and Upp1 are confidence interval limits for x1. Next two columns have analogous limits for x2. The last but first columns entitled Lowx2mx1 means lower confidence limit for (x2-x1), where m=minus. The last column entitled Uppx2mx1 means upper confidence limit for (x2-x1).

For strong stochastic dominance of x2 over x1 dominance beyond sampling variability, zero should not be inside the confidence interval in the last two columns.

@note

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

See Also

see [exactSdMtx](#)

bootGcLC

*Compute vector of n999 nonlinear Granger causality paths***Description**

Maximum entropy bootstrap (meboot) package is used for statistical inference. The bootstrap output can be analyzed to estimate an approximate confidence interval on sample-based direction of the causal path. The LC in the function name stands for local constant. Kernel regression np package options `regtype="lc"` for local constant, and `bwmethod="cv.ls"` for least squares-based bandwidth selection are fixed.

Usage

```
bootGcLC(x1, x2, px2 = 4, px1 = 4, pwanted = 4, ctrl = 0, n999 = 9)
```

Arguments

x1	The data vector x1
x2	The data vector x2
px2	number of lags of x2 in the data, default px2=4
px1	number of lags of x1 in the data default px1=4
pwanted	number of lags of both x2 and x1 wanted for Granger causal analysis, default =4
ctrl	data matrix having control variable(s) if any
n999	Number of bootstrap replications (default=9)

Value

out is n999 X 3 matrix for 3 outputs of GcauseX12 resampled

Note

This computation is computer intensive and generally very slow. It may be better to use this function at a later stage in the investigation, after a preliminary causal determination is already made. The 3 outputs of GauseX12 are two Rsquares and the difference between after subtracting the second from the first. Col. 1 has (RsquX1onX2) Col.2 has (RsquX2onX1), and Col.3 has $dif=(RsquX1onX2 - RsquX2onX1)$. Note that R-squares are always positive. If $dif>0$, $RsquX1onX2>RsquX2onX1$, implying that x2 on RHS performs better that is, $x2 \rightarrow x1$ is the path, or x2 Granger-causes x1. If $dif<0$, $x1 \rightarrow x2$ holds. If dif is too close to zero, we may have bidirectional causality $x1 \leftrightarrow x2$. The proportion of resamples (out of n999) having $dif<0$ suggests level of confidence in the conclusion $x1 \rightarrow x2$. The proportion of resamples (out of n999) having $dif>0$ suggests level of confidence in the conclusion $x2 \rightarrow x1$.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Zheng, S., Shi, N.-Z., and Zhang, Z. (2012). Generalized measures of correlation for asymmetry, nonlinearity, and beyond. Journal of the American Statistical Association, vol. 107, pp. 1239-1252.

Vinod, H. D. and Lopez-de-Lacalle, J. (2009). 'Maximum entropy bootstrap for time series: The meboot R package.' Journal of Statistical Software, Vol. 29(5), pp. 1-19.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See Also [GcRsqX12c](#).

Examples

```
## Not run:
library(Ecdat);options(np.messages=FALSE);attach(data.frame(MoneyUS))
bootGcLC(y,m,n999=9)

## End(Not run)
## Not run:
library(lmtest); data(ChickEgg);attach(data.frame(ChickEgg))
b2=bootGcLC(x1=chicken,x2=egg,pwanted=3,px1=3,px2=3,n999=99)

## End(Not run)
```

bootGcRsq

Compute vector of n999 nonlinear Granger causality paths

Description

Maximum entropy bootstrap (meboot) package is used for statistical inference The bootstrap output can be analyzed to estimate an approximate confidence interval on sample-based direction of the causal path. Kernel regression np package options regtype="ll" for local linear, and bwmethod="cv.aic" for AIC-based bandwidth selection are fixed.

Usage

```
bootGcRsq(x1, x2, px2 = 4, px1 = 4, pwanted = 4, ctrl = 0, n999 = 9)
```

Arguments

x1	The data vector x1
x2	The data vector x2
px2	number of lags of x2 in the data, default px2=4
px1	number of lags of x1 in the data default px1=4
pwanted	number of lags of both x2 and x1 wanted for Granger causal analysis, default =4
ctrl	data matrix having control variable(s) if any
n999	Number of bootstrap replications (default=9)

Value

out is n999 X 3 matrix for 3 outputs of GcauseX12 resampled

Note

This computation is computer intensive and generally very slow. It may be better to use this function it at a later stage in the investigation, after a preliminary causal determination is already made. The 3 outputs of GauseX12 are two Rsquares and the difference between them after subtracting the second from the first. Col. 1 has (RsqX1onX2), Col.2 has (RsqX2onX1), and Col.3 has dif=(RsqX1onX2 -RsqX2onX1) Note that R-squares are always positive. If dif>0, RsqX1onX2>RsqX2onX1, implying that x2 on RHS performs better that is, x2 → x1 is the causal path. If dif<0, x1 → x2 holds. If dif is too close to zero, we may have bidirectional causality x1 ↔ x2. The proportion of resamples (out of n999) having dif<0 suggests level of confidence in the conclusion x1 → x2. The proportion of resamples (out of n999) having dif>0 suggests level of confidence in the conclusion x2 → x1.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

- Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>
- Zheng, S., Shi, N.-Z., and Zhang, Z. (2012). Generalized measures of correlation for asymmetry, nonlinearity, and beyond. Journal of the American Statistical Association, vol. 107, pp. 1239-1252.
- Vinod, H. D. and Lopez-de-Lacalle, J. (2009). 'Maximum entropy bootstrap for time series: The meboot R package.' Journal of Statistical Software, Vol. 29(5), pp. 1-19.
- Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See Also [GcRsqX12](#).

Examples

```
## Not run:
library(Ecdat);options(np.messages=FALSE);attach(data.frame(MoneyUS))
bootGcRsq(y,m,n999=9)

## End(Not run)
## Not run:
library(lmtest); data(ChickEgg);attach(data.frame(ChickEgg))
options(np.messages=FALSE)
b2=bootGcLC(x1=chicken,x2=egg,pwanted=3,px1=3,px2=3,n999=99)
Fn=function(x)quantile(x,prob=c(0.025, 0.975))#confInt
apply(b1,2,Fn)#reports 95 percent confidence interval

## End(Not run)
```

bootPairs	<i>Compute matrix of n999 rows and p-1 columns of bootstrap 'sum' (strength from Cr1 to Cr3).</i>
-----------	---

Description

Maximum entropy bootstrap (meboot) package is used for statistical inference using the sum of three signs sg1 to sg3 from the three criteria Cr1 to Cr3 to assess preponderance of evidence in favor of a sign. (+1, 0, -1). The bootstrap output can be analyzed to assess approximate preponderance of a particular sign which determines the causal direction.

Usage

```
bootPairs(mtx, ctrl = 0, n999 = 9)
```

Arguments

mtx	data matrix with two or more columns
ctrl	data matrix having control variable(s) if any
n999	Number of bootstrap replications (default=9)

Value

out When `mtx` has `p` columns, `out` of `bootPairs(mtx)` is a matrix of `n999` rows and `p-1` columns each containing resampled 'sum' values summarizing the weighted sums associated with all three criteria from the function `silentPairs(mtx)` applied to each bootstrap sample separately.

Note

This computation is computer intensive and generally very slow. It may be better to use it at a later stage in the investigation when a preliminary causal determination is already made. A positive sign for `j`-th weighted sum reported in the column 'sum' means that the first variable listed in the argument matrix `mtx` is the 'kernel cause' of the variable in the `(j+1)`-th column of `mtx`.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Zheng, S., Shi, N.-Z., and Zhang, Z. (2012). Generalized measures of correlation for asymmetry, nonlinearity, and beyond. Journal of the American Statistical Association, vol. 107, pp. 1239-1252.

Vinod, H. D. and Lopez-de-Lacalle, J. (2009). 'Maximum entropy bootstrap for time series: The meboot R package.' Journal of Statistical Software, Vol. 29(5), pp. 1-19.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See Also [silentPairs](#).

Examples

```
## Not run:
options(np.messages = FALSE)
set.seed(34);x=sample(1:10);y=sample(2:11)
bb=bootPairs(cbind(x,y),n999=29)
apply(bb,2,summary) #gives summary stats for n999 bootstrap sum computations

bb=bootPairs(airquality,n999=999);options(np.messages=FALSE)
apply(bb,2,summary) #gives summary stats for n999 bootstrap sum computations

data('EuroCrime')
attach(EuroCrime)
bootPairs(cbind(crim,off),n999=29)#First col. crim causes officer deployment,
#hence positives signs are most sensible for such call to bootPairs
#note that n999=29 is too small for real problems, chosen for quickness here.

## End(Not run)
```

bootPairs0

Compute matrix of n999 rows and p-1 columns of bootstrap 'sum' index (strength from older criterion Cr1, with newer Cr2 and Cr3).

Description

Maximum entropy bootstrap (meboot) package is used for statistical inference using the sum of three signs sg1 to sg3 from the three criteria Cr1 to Cr3 to assess preponderance of evidence in favor of a sign. (+1, 0, -1). The bootstrap output can be analyzed to assess approximate preponderance of a particular sign which determines the causal direction.

Usage

```
bootPairs0(mtx, ctrl = 0, n999 = 9)
```

Arguments

mtx	data matrix with two or more columns
ctrl	data matrix having control variable(s) if any
n999	Number of bootstrap replications (default=9)

Value

When `mtx` has `p` columns, `bootPairs(mtx)` is a matrix of `n999` rows and `p-1` columns each containing resampled 'sum' values summarizing the weighted sums associated with all three criteria from the function `silentPairs(mtx)` applied to each bootstrap sample separately.

Note

This computation is computer intensive and generally very slow. It may be better to use it at a later stage in the investigation when a preliminary causal determination is already made. A positive sign for `j`-th weighted sum reported in the column 'sum' means that the first variable listed in the argument matrix `mtx` is the 'kernel cause' of the variable in the `(j+1)`-th column of `mtx`.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

- Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>
- Zheng, S., Shi, N.-Z., and Zhang, Z. (2012). Generalized measures of correlation for asymmetry, nonlinearity, and beyond. *Journal of the American Statistical Association*, vol. 107, pp. 1239-1252.
- Vinod, H. D. and Lopez-de-Lacalle, J. (2009). 'Maximum entropy bootstrap for time series: The meboot R package.' *Journal of Statistical Software*, Vol. 29(5), pp. 1-19.
- Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See Also [silentPairs0](#), [bootPairs](#) has the version with later version of Cr1.

Examples

```
## Not run:
options(np.messages = FALSE)
set.seed(34);x=sample(1:10);y=sample(2:11)
bb=bootPairs0(cbind(x,y),n999=29)
```

```

apply(bb,2,summary) #gives summary stats for n999 bootstrap sum computations

bb=bootPairs0(airquality,n999=999);options(np.messages=FALSE)
apply(bb,2,summary) #gives summary stats for n999 bootstrap sum computations

data('EuroCrime')
attach(EuroCrime)
bootPairs0(cbind(crim,off),n999=29)#First col. crim causes officer deployment,
#hence positives signs are most sensible for such call to bootPairs
#note that n999=29 is too small for real problems, chosen for quickness here.

## End(Not run)

```

bootQuantile	<i>Compute confidence intervals [quantile(s)] of indexes from bootPairs output</i>
--------------	--

Description

Begin with the output of bootPairs function, a (n999 by p-1) matrix when there are p columns of data, bootQuantile produces a (k by p-1) mtx of quantile(s) of bootstrap output assuming that there are k quantiles needed.

Usage

```
bootQuantile(out, probs = c(0.025, 0.975), per100 = TRUE)
```

Arguments

out	output from bootPairs with p-1 columns and n999 rows
probs	quantile evaluation probabilities. The default is k=2, probs=c(.025,0.975) for a 95 percent confidence interval. Note that there are k=2 quantiles desired for each column with this specification
per100	logical (default per100=TRUE) to change the range of 'sum' to [-100, 100] values which are easier to interpret

Value

CI k quantiles evaluated at probs as a matrix with k rows and quantile of pairwise p-1 indexes representing p-1 column pairs (fixing the first column in each pair) This function summarizes the output of of bootPairs(mtx) (a n999 by p-1 matrix) each containing resampled 'sum' values summarizing the weighted sums associated with all three criteria from the function silentPairs(mtx) applied to each bootstrap sample separately. #'

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. and Lopez-de-Lacalle, J. (2009). 'Maximum entropy bootstrap for time series: The meboot R package.' Journal of Statistical Software, Vol. 29(5), pp. 1-19.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See Also [silentPairs](#).

Examples

```
## Not run:
options(np.messages = FALSE)
set.seed(34);x=sample(1:10);y=sample(2:11)
bb=bootPairs(cbind(x,y),n999=29)
bootQuantile(bb) #gives summary stats for n999 bootstrap sum computations

bb=bootPairs(airquality,n999=999);options(np.messages=FALSE)
bootQuantile(bb,tau=0.476)#signs for n999 bootstrap sum computations

data('EuroCrime')
attach(EuroCrime)
bb=bootPairs(cbind(crim,off),n999=29) #col.1= crim causes off
#hence positive signs are more intuitively meaningful.
#note that n999=29 is too small for real problems, chosen for quickness here.
bootQuantile(bb)# quantile matrix for n999 bootstrap sum computations

## End(Not run)
```

bootSign

Probability of unambiguously correct (+ or -) sign from bootPairs output

Description

If there are p columns of data, bootSign produces a $p-1$ by 1 vector of probabilities of correct signs assuming that the mean of $n999$ values has the correct sign and assuming that m of the 'sum' index values inside the range $[-\tau, \tau]$ are neither positive nor negative but indeterminate or ambiguous (being too close to zero). That is, the denominator of $P(+1)$ or $P(-1)$ is $(n999-m)$ if m signs are too close to zero. Thus it measures the bootstrap success rate in identifying the correct sign, when the sign of the average of $n999$ bootstraps is assumed to be correct.

Usage

```
bootSign(out, tau = 0.476)
```

Arguments

out	output from bootPairs with p-1 columns and n999 rows
tau	threshold to determine what value is too close to zero, default tau=0.476 is equivalent to 15 percent threshold for the unanimity index ui

Value

sgn When `mtx` has `p` columns, `sgn` reports pairwise `p-1` signs representing (fixing the first column in each pair) the average sign after averaging the output of `bootPairs(mtx)` (a `n999` by `p-1` matrix) each containing resampled 'sum' values summarizing the weighted sums associated with all three criteria from the function `silentPairs(mtx)` applied to each bootstrap sample separately. #'

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. and Lopez-de-Lacalle, J. (2009). 'Maximum entropy bootstrap for time series: The meboot R package.' Journal of Statistical Software, Vol. 29(5), pp. 1-19.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See Also [silentPairs](#), [bootQuantile](#), [bootSignPcent](#).

Examples

```
## Not run:
options(np.messages = FALSE)
set.seed(34);x=sample(1:10);y=sample(2:11)
bb=bootPairs(cbind(x,y),n999=29)
bootSign(bb,tau=0.476) #gives success rate in n999 bootstrap sum computations

bb=bootPairs(airquality,n999=999);options(np.messages=FALSE)
bootSign(bb,tau=0.476)#signs for n999 bootstrap sum computations

data('EuroCrime');options(np.messages=FALSE)
attach(EuroCrime)
bb=bootPairs(cbind(crim,off),n999=29) #col.1= crim causes off
#hence positive signs are more intuitively meaningful.
```

```
#note that n999=29 is too small for real problems, chosen for quickness here.
bootSign(bb,tau=0.476)#gives success rate in n999 bootstrap sum computations

## End(Not run)
```

bootSignPcent	<i>Probability of unambiguously correct (+ or -) sign from bootPairs output transformed to percentages.</i>
---------------	---

Description

If there are p columns of data, `bootSignPcent` produces a $p-1$ by 1 vector of probabilities of correct signs assuming that the mean of $n999$ values has the correct sign and assuming that m of the 'ui' index values inside the range $[-\tau, \tau]$ are neither positive nor negative but indeterminate or ambiguous (being too close to zero). That is, the denominator of $P(+1)$ or $P(-1)$ is $(n999-m)$ if m signs are too close to zero. Thus it measures the bootstrap success rate in identifying the correct sign, when the sign of the average of $n999$ bootstraps is assumed to be correct.

Usage

```
bootSignPcent(out, tau = 5)
```

Arguments

out	output from <code>bootPairs</code> with $p-1$ columns and $n999$ rows
tau	threshold to determine what value is too close to zero, default $\tau=5$ is 5 percent threshold for the unanimity index <code>ui</code>

Value

`sgn` When `mtx` has p columns, `sgn` reports pairwise $p-1$ signs representing (fixing the first column in each pair) the average sign after averaging the output of `bootPairs(mtx)` (a $n999$ by $p-1$ matrix) each containing resampled 'sum' values summarizing the weighted sums associated with all three criteria from the function `silentPairs(mtx)` applied to each bootstrap sample separately. #'

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

- Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in *Communications in Statistics -Simulation and Computation*, 2015, <https://doi.org/gffn86>
- Vinod, H. D. and Lopez-de-Lacalle, J. (2009). 'Maximum entropy bootstrap for time series: The meboot R package.' *Journal of Statistical Software*, Vol. 29(5), pp. 1-19.
- Vinod, H. D. *Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy* (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See Also [silentPairs](#), [bootQuantile](#), [bootSign](#).

Examples

```
## Not run:
options(np.messages = FALSE)
set.seed(34);x=sample(1:10);y=sample(2:11)
bb=bootPairs(cbind(x,y),n999=29)
bootSignPcent(bb,tau=5) #gives success rate in n999 bootstrap sum computations

bb=bootPairs(airquality,n999=999);options(np.messages=FALSE)
bootSignPcent(bb,tau=5)#success rate for signs from n999 bootstraps

data('EuroCrime');options(np.messages=FALSE)
attach(EuroCrime)
bb=bootPairs(cbind(crim,off),n999=29) #col.1= crim causes off
#hence positive signs are more intuitively meaningful.
#note that n999=29 is too small for real problems, chosen for quickness here.
bootSignPcent(bb,tau=5)#successful signs from n999 bootstraps

## End(Not run)
```

bootSummary

Compute usual summary stats of 'sum' indexes from bootPairs output

Description

Begin with the output of bootPairs function, a (n999 by p-1) matrix when there are p columns of data, bootSummary produces a (6 by p-1) mtx of summary of bootstrap output (Min, 1st Qu,Median, Mean, 3rd Qi.,Max)

Usage

```
bootSummary(out, per100 = TRUE)
```

Arguments

out	output from bootPairs with p-1 columns and n999 rows in input here
per100	logical (default per100=TRUE) to change the range of 'sum' to [-100, 100] values which are easier to interpret

Value

summ summary output from the (n999 by p-1) matrix output of bootPairs(mtx) each containing resampled 'sum' values summarizing the weighted sums associated with all three criteria from the function silentPairs(mtx) applied to each bootstrap sample separately.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. ‘Generalized Correlation and Kernel Causality with Applications in Development Economics’ in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. and Lopez-de-Lacalle, J. (2009). ‘Maximum entropy bootstrap for time series: The meboot R package.’ Journal of Statistical Software, Vol. 29(5), pp. 1-19.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See Also [silentPairs](#).

Examples

```
## Not run:
options(np.messages = FALSE)
set.seed(34);x=sample(1:10);y=sample(2:11)
bb=bootPairs(cbind(x,y),n999=29)
bootSummary(bb) #gives summary stats for n999 bootstrap sum computations

bb=bootPairs(airquality,n999=999);options(np.messages=FALSE)
bootSummary(bb)#signs for n999 bootstrap sum computations

data('EuroCrime')
attach(EuroCrime)
bb=bootPairs(cbind(crim,off),n999=29) #col.1= crim causes off
#hence positive signs are more intuitively meaningful.
#note that n999=29 is too small for real problems, chosen for quickness here.
bootSummary(bb)#signs for n999 bootstrap sum computations

## End(Not run)
```

canonRho

Generalized canonical correlation, estimating alpha, beta, rho.

Description

This function uses data on two sets of column vectors. LHS set [x1, x2 .. xr] has r=nLHS number of columns with coefficients alpha and the larger RHS set [xr+1, xr+2, .. xp] has nRHS=(p-r) columns and RHS coefficients beta. Must arrange the sets so that the larger set is on RHS with coefficients beta estimated first from an eigenvector of the problem $A^* \beta = \rho^2 \beta$ where A^* is a partitioning of generalized matrix of (non-symmetric) correlation coefficients.

Usage

```
canonRho(mtx, nLHS = 2, sgn = 1, verbo = FALSE, ridg = c(0, 0))
```

Arguments

mtx	Input matrix of generalized correlation coefficients R^*
nLHS	number of columns in the LHS set, default=2
sgn	preferred sign of coefficients default=1 for positive, use sgn= -1 if prior knowledge suggests that negative signs of coefficients are more realistic
verbo	logical, verbo=FALSE default means do not print results
ridg	two regularization constants added before computing matrix inverses of S11 and S22, respectively, with default=c(0,0). Some suggest ridg=c(0.01,0.01) for stable results

Value

A	eigenvalue computing matrix for Generalized canonical correlations
rho	Generalized canonical correlation coefficient
bet	RHS coefficient vector
alp	LHS coefficient vector

Note

This function calls [kern](#),

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

- Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in 'Handbook of Statistics: Computational Statistics with R', Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.
- Vinod, H. D. 'Canonical ridge and econometrics of joint production,' Journal of Econometrics, vol. 4, 147-166.
- Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

See Also

See [gmcmtx0](#).

Examples

```
## Not run:
set.seed(99)
mtx2=matrix(sample(1:25),nrow=5)
g1=gmcmtx0(mtx2)
canonRho(g1, verbo=TRUE)

## End(Not run)##'
```

causeAllPair	<i>All Pair Version Kernel (block) causality summary paths from three criteria</i>
--------------	--

Description

Allowing input matrix of control variables, this function produces a 5 column matrix summarizing the results where the estimated signs of stochastic dominance order values, (+1, 0, -1), are weighted by $wt=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2 and added to the Cr3 estimate as: (+1, 0, -1). The final range for the unanimity of sign index is [-100, 100].

Usage

```
causeAllPair(
  mtx,
  nam = colnames(mtx),
  blksiz = 10,
  ctrl = 0,
  dig = 6,
  wt = c(1.2, 1.1, 1.05, 1),
  sumwt = 4
)
```

Arguments

mtx	The data matrix with many columns, We consider causal paths among all possible pairs of mtx columns.
nam	vector of column names for mtx. Default: colnames(mtx)
blksiz	block size, default=10, if chosen blksiz >n, where n=rows in matrix then blksiz=n. That is, no blocking is done
ctrl	data matrix for designated control variable(s) outside causal paths
dig	Number of digits for reporting (default dig=6).
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The reason for slightly declining weights on the signs from SD1 to SD4 stochastic dominance orders is simply their slightly increasing sampling unreliability due to higher order trapezoidal approximations of integrals of densities involved in definitions of SD1 to SD4. The summary results for all three criteria are reported in one matrix called out:

Value

If there are p columns in the input matrix, x_1, x_2, \dots, x_p , say, there are $\text{choose}(p,2)$ or $[p*(p-1)/2]$ possible pairs and as many causal paths. This function returns a matrix of $p*(p-1)/2$ rows and 5 columns entitled: "cause", "response", "strength", "corr." and "p-value", respectively with self-explanatory titles. The first two columns have names of variables x_1 or $x_{(1+j)}$, depending on which is the cause. The 'strength' column has absolute value of summary index in range $[0,100]$ providing summary of causal results based on preponderance of evidence from criteria Cr1 to Cr3 from four orders of stochastic dominance, etc. The fourth column 'corr.' reports the Pearson correlation coefficient while the fifth column has the p-value for testing the null of zero Pearson coeff. This function merely calls `causeSumNoP` repeatedly to include all pairs. The background function `siPairsBlk` allows for control variables. The output of this function can be sent to 'xtable' for a nice Latex table.

Note

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers. Since Cr1 to Cr3 near unanimously suggest 'crim' as the cause of 'off', strength index 100 suggests unanimity. `attach(EuroCrime); causeSummary(cbind(crim,off))`

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See [bootPairs](#), [causeSummBlk](#)

See [someCPairs](#)

[siPairsBlk](#), [causeSummary](#)

Examples

```
## Not run:
mtx=data.frame(mtcars[,1:3]) #make sure columns of mtx have names
ctrl=data.frame(mtcars[,4:5])
  causeAllPair(mtx=mtx,ctrl=ctrl)

## End(Not run)

options(np.messages=FALSE)
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
causeAllPair(mtx=cbind(x2,y2), ctrl=cbind(z,w2))
```

causeSummary	<i>Kernel causality summary of evidence for causal paths from three criteria</i>
--------------	--

Description

While allowing the researcher to keep some variables as controls, or outside the scope of causal path determination (e.g., age or latitude) this function produces detailed causal path information in a 5 column matrix identifying the names of variables, causal path directions, path strengths re-scaled to be in the range $[-100, 100]$, (table reports absolute values of the strength) plus Pearson correlation and its p-value.

Usage

```
causeSummary(
  mtx,
  nam = colnames(mtx),
  ctrl = 0,
  dig = 6,
  wt = c(1.2, 1.1, 1.05, 1),
  sumwt = 4
)
```

Arguments

mtx	The data matrix with many columns, y the first column is fixed and then paired with all columns, one by one, and still called x for the purpose of flipping.
-----	--

nam	vector of column names for mtX. Default: colnames(mtx)
ctrl	data matrix for designated control variable(s) outside causal paths
dig	Number of digits for reporting (default dig=6).
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The algorithm determines causal path directions from the sign of the strength index and strength index values by comparing three aspects of flipped kernel regressions: [x1 on (x2, x3, .. xp)] and its flipped version [x2 on (x1, x3, .. xp)] We compare (i) formal exogeneity test criterion, (ii) absolute residuals, and (iii) R-squares of the flipped regressions implying three criteria Cr1, to Cr3. The criteria are quantified by sophisticated methods using four orders of stochastic dominance, SD1 to SD4. We assume slightly declining weights on causal path signs because known reliability ranking. SD1 is better than SD2, better than SD3, better than SD4. The user can optionally change our weights.

Value

If there are p columns in the input matrix, x1, x2, ..., xp, say, and if we keep x1 as a common member of all causal direction pairs (x1, x(1+j)) for (j=1, 2, ..., p-1) which can be flipped. That is, either x1 is the cause or x(1+j) is the cause in a chosen pair. The control variables are not flipped. The printed output of this function reports the results for p-1 pairs indicating which variable (by name) causes which another variable (also by name). It also prints a signed summary strength index in the range [-100,100]. A positive sign of the strength index means x1 kernel causes x(1+j), whereas negative strength index means x(1+j) kernel causes x1. The function also prints Pearson correlation and its p-value. In short, function returns a matrix of p-1 rows and 5 columns entitled: "cause", "response", "strength", "corr." and "p-value", respectively with self-explanatory titles. The first two columns have names of variables x1 or x(1+j), depending on which is the cause. The 'strength' column reports the absolute value of summary index, now in the range [0,100] providing summary of causal results based on preponderance of evidence from Cr1 to Cr3 from four orders of stochastic dominance, etc. The order of input columns matters. The fourth column 'corr.' reports the Pearson correlation coefficient while the fifth column has the p-value for testing the null of zero Pearson coeff. This function calls silentPairs allowing for control variables. The output of this function can be sent to 'xtable' for a nice Latex table.

Note

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers. Since Cr1 to Cr3 near unanimously suggest 'crim' as the cause of 'off', strength index 100 suggests unanimity. `attach(EuroCrime); causeSummary(cbind(crim,off))`

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [gffn86](#)

Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See [bootPairs](#), [causeSummary0](#) has an older version of this function.

See [someCPairs](#)

[silentPairs](#)

Examples

```
## Not run:
mtx=as.matrix(mtcars[,1:3])
ctrl=as.matrix(mtcars[,4:5])
causeSummary(mtx,ctrl,nam=colnames(mtx))

## End(Not run)

options(np.messages=FALSE)
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
causeSummary(mtx=cbind(x2,y2), ctrl=cbind(z,w2))
```

causeSummary0

Older Kernel causality summary of evidence for causal paths from three criteria

Description

Allowing input matrix of control variables, this function produces a 5 column matrix summarizing the results where the estimated signs of stochastic dominance order values, (+1, 0, -1), are weighted by $w_t=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2 and added to the Cr3 estimate as: (+1, 0, -1). The final range for the unanimity of sign index is [-100, 100].

Usage

```
causeSummary0(
  mtx,
  nam = colnames(mtx),
  ctrl = 0,
  dig = 6,
  wt = c(1.2, 1.1, 1.05, 1),
  sumwt = 4
)
```

Arguments

mtx	The data matrix with many columns, y the first column is fixed and then paired with all columns, one by one, and still called x for the purpose of flipping.
nam	vector of column names for <code>mtx</code> . Default: <code>colnames(mtx)</code>
ctrl	data matrix for designated control variable(s) outside causal paths
dig	Number of digits for reporting (default <code>dig=6</code>).
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The reason for slightly declining weights on the signs from SD1 to SD4 is simply that the local mean comparisons implicit in SD1 are known to be more reliable than local variance implicit in SD2, local skewness implicit in SD3 and local kurtosis implicit in SD4. The reason for slightly declining sampling unreliability of higher moments is simply that SD4 involves fourth power of the deviations from the mean and SD3 involves 3rd power, etc. The summary results for all three criteria are reported in one matrix called `out`:

Value

If there are p columns in the input matrix, x_1, x_2, \dots, x_p , say, and if we keep x_1 as a common member of all causal direction pairs $(x_1, x_{(1+j)})$ for $(j=1, 2, \dots, p-1)$ which can be flipped. That is, either x_1 is the cause or $x_{(1+j)}$ is the cause in a chosen pair. The control variables are not flipped. The printed output of this function reports the results for $p-1$ pairs indicating which variable (by name) causes which other variable (also by name). It also prints strength or signed summary strength index in range $[-100,100]$. A positive sign of the strength index means x_1 kernel causes $x_{(1+j)}$, whereas negative strength index means $x_{(1+j)}$ kernel causes x_1 . The function also prints Pearson correlation and its p -value. This function also returns a matrix of $p-1$ rows and 5 columns entitled: "cause", "response", "strength", "corr." and "p-value", respectively with self-explanatory titles. The first two columns have names of variables x_1 or $x_{(1+j)}$, depending on which is the cause. The 'strength' column has absolute value of summary index in range $[0,100]$ providing summary of causal results based on preponderance of evidence from Cr_1 to Cr_3 from four orders of stochastic dominance, etc. The order of input columns matters. The fourth column 'corr.' reports the Pearson correlation coefficient while the fifth column has the p -value for testing the null of zero Pearson coeff. This function calls `silentPairs0` (the older version) allowing for control variables. The output of this function can be sent to 'xtable' for a nice Latex table.

Note

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers. Since Cr1 to Cr3 near unanimously suggest 'crim' as the cause of 'off', strength index 100 suggests unanimity. `attach(EuroCrime); causeSummary0(cbind(crim,off))`. Both versions give identical result for this example. Old version of Cr1 using gradients was also motivated by the same Hausman-Wu test statistic.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See [bootPairs](#)

See [someCPairs](#)

[silentPairs](#)

Examples

```
## Not run:
mtx=as.matrix(mtcars[,1:3])
ctrl=as.matrix(mtcars[,4:5])
  causeSummary0(mtx,ctrl,nam=colnames(mtx))

## End(Not run)

options(np.messages=FALSE)
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
causeSummary0(mtx=cbind(x2,y2), ctrl=cbind(z,w2))
```

causeSummBlk	<i>Block Version Kernel causality summary causal paths from three criteria</i>
--------------	--

Description

A block version of `causeSummary()`. While allowing the researcher to keep some variables as controls, or outside the scope of causal path determination (e.g., age or latitude) this function produces detailed causal path information in a 5 column matrix identifying the names of variables, causal path directions, path strengths re-scaled to be in the range $[-100, 100]$, (table reports absolute values of the strength) plus Pearson correlation and its p-value.

Usage

```
causeSummBlk(
  mtx,
  nam = colnames(mtx),
  blksize = 10,
  ctrl = 0,
  dig = 6,
  wt = c(1.2, 1.1, 1.05, 1),
  sumwt = 4
)
```

Arguments

<code>mtx</code>	The data matrix with many columns, y the first column is a fixed target and then it is paired with all other columns, one by one, and still called x for the purpose of flipping.
<code>nam</code>	vector of column names for <code>mtx</code> . Default: <code>colnames(mtx)</code>
<code>blksize</code>	block size, default=10, if chosen <code>blksize > n</code> , where <code>n=rows</code> in matrix then <code>blksize=n</code> . That is, no blocking is done
<code>ctrl</code>	data matrix for designated control variable(s) outside causal paths
<code>dig</code>	Number of digits for reporting (default <code>dig=6</code>).
<code>wt</code>	Allows user to choose a vector of four alternative weights for SD1 to SD4.
<code>sumwt</code>	Sum of weights can be changed here =4(default).

Details

The algorithm determines causal path directions from the sign of the strength index and strength index values by comparing three aspects of flipped kernel regressions: $[x1 \text{ on } (x2, x3, \dots xp)]$ and its flipped version $[x2 \text{ on } (x1, x3, \dots xp)]$ We compare (i) formal exogeneity test criterion, (ii) absolute residuals, and (iii) R-squares of the flipped regressions implying three criteria Cr1, to Cr3. The criteria are quantified by sophisticated methods using four orders of stochastic dominance, SD1 to SD4. We assume slightly declining weights on causal path signs because known reliability ranking. SD1 is better than SD2, better than SD3, better than SD4. The user can optionally change our weights.

Value

If there are p columns in the input matrix, x_1, x_2, \dots, x_p , say, and if we keep x_1 as a common member of all causal-direction-pairs $(x_1, x_{(1+j)})$ for $(j=1, 2, \dots, p-1)$ which can be flipped. That is, either x_1 is the cause or $x_{(1+j)}$ is the cause in a chosen pair. The control variables are not flipped. The printed output of this function reports the results for $p-1$ pairs indicating which variable (by name) causes which other variable (also by name). It also prints strength or signed summary strength index in range $[-100,100]$. A positive sign of the strength index means x_1 kernel causes $x_{(1+j)}$, whereas negative strength index means $x_{(1+j)}$ kernel causes x_1 . The function also prints Pearson correlation and its p -value. This function also returns a matrix of $p-1$ rows and 5 columns entitled: "cause", "response", "strength", "corr." and "p-value", respectively with self-explanatory titles. The first two columns have names of variables x_1 or $x_{(1+j)}$, depending on which is the cause. The 'strength' column has absolute value of summary index in range $[0,100]$ providing summary of causal results based on preponderance of evidence from Cr1 to Cr3 from four orders of stochastic dominance, etc. The order of input columns matters. The fourth column 'corr.' reports the Pearson correlation coefficient while the fifth column has the p -value for testing the null of zero Pearson coeff. This function calls `siPairsBlk` allowing for control variables. The output of this function can be sent to 'xtable' for a nice Latex table.

Note

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers. Since Cr1 to Cr3 near unanimously suggest 'crim' as the cause of 'off', strength index 100 suggests unanimity. `attach(EuroCrime); causeSummary(cbind(crim,off))`

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [gffn86](#)

Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See [bootPairs](#), [causeSummary](#) has an older version of this function.

See [someCPairs](#)

[siPairsBlk](#), [causeSummary](#)

Examples

```
## Not run:
mtx=as.matrix(mtcars[,1:3])
ctrl=as.matrix(mtcars[,4:5])
  causeSummBlk(mtx,ctrl,nam=colnames(mtx))

## End(Not run)

options(np.messages=FALSE)
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
causeSummBlk(mtx=cbind(x2,y2), ctrl=cbind(z,w2))
```

causeSumNoP	<i>No print (NoP) version of causeSummBlk summary causal paths from three criteria</i>
-------------	--

Description

Allowing input matrix of control variables, this function produces a 5 column matrix summarizing the results where the estimated signs of stochastic dominance order values, (+1, 0, -1), are weighted by $wt=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2 and added to the Cr3 estimate as: (+1, 0, -1). The final range for the unanimity of sign index is [-100, 100].

Usage

```
causeSumNoP(
  mtx,
  nam = colnames(mtx),
  blksiz = 10,
  ctrl = 0,
  dig = 6,
  wt = c(1.2, 1.1, 1.05, 1),
  sumwt = 4
)
```

Arguments

mtx	The data matrix with many columns, y the first column is a fixed target and then it is paired with all other columns, one by one, and still called x for the purpose of flipping.
nam	vector of column names for mtx. Default: colnames(mtx)
blksiz	block size, default=10, if chosen blksiz >n, where n=rows in matrix then blk-siz=n. That is, no blocking is done
ctrl	data matrix for designated control variable(s) outside causal paths
dig	Number of digits for reporting (default dig=6).
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The reason for slightly declining weights on the signs from SD1 to SD4 is simply that the higher order stochastic dominance numbers are less reliable. The summary results for all three criteria are reported in one matrix called out but not printed:

Value

If there are p columns in the input matrix, x1, x2, ..., xp, say, and if we keep x1 as a common member of all causal-direction-pairs (x1, x(1+j)) for (j=1, 2, ..., p-1) which can be flipped. That is, either x1 is the cause or x(1+j) is the cause in a chosen pair. The control variables are not flipped. The printed output of this function reports the results for p-1 pairs indicating which variable (by name) causes which other variable (also by name). It also prints strength or signed summary strength index in range [-100,100]. A positive sign of the strength index means x1 kernel causes x(1+j), whereas negative strength index means x(1+j) kernel causes x1. The function also prints Pearson correlation and its p-value. This function also returns a matrix of p-1 rows and 5 columns entitled: "cause", "response", "strength", "corr." and "p-value", respectively with self-explanatory titles. The first two columns have names of variables x1 or x(1+j), depending on which is the cause. The 'strength' column has absolute value of summary index in range [0,100] providing summary of causal results based on preponderance of evidence from Cr1 to Cr3 from four orders of stochastic dominance, etc. The order of input columns matters. The fourth column 'corr.' reports the Pearson correlation coefficient while the fifth column has the p-value for testing the null of zero Pearson coeff. This function calls siPairsBlk allowing for control variables. The output of this function can be sent to 'xtable' for a nice Latex table.

Note

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers. Since Cr1 to Cr3 near unanimously suggest 'crim' as the cause of 'off', strength index 100 suggests unanimity. `attach(EuroCrime); causeSummary(cbind(crim,off))`

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [gffn86](#)

Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See [bootPairs](#), [causeSummary0](#) has an older version of this function.

See [causeAllPair](#)

[siPairsBlk](#), [causeSummary](#)

Examples

```
## Not run:
mtx=data.frame(mtcars[,1:3])
ctrl=data.frame(mtcars[,4:5])
  causeSumNoP(mtx=mtx,ctrl=ctrl)

## End(Not run)

options(np.messages=FALSE)
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
causeSumNoP(mtx=cbind(x2,y2), ctrl=cbind(z,w2))
```

cofactor

Compute cofactor of a matrix based on row r and column c.

Description

Compute cofactor of a matrix based on row r and column c.

Usage

```
cofactor(x, r, c)
```

Arguments

x matrix whose cofactor is desired to be computed
 r row number
 c column number

Value

cofactor of x, w.r.t. row r and column c.

Note

needs the function ‘minor’ in memory. attaches sign $(-1)^{(r+c)}$ to the minor.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

See Also

minor(x, r, c)

Examples

```
## The function is currently defined as
function (x, r, c)
{
  out = minor(x, r, c) * ((-1)^(r + c))
  return(out)
}
```

comp_portfo2	<i>Compares two vectors (portfolios) using stochastic dominance of orders 1 to 4.</i>
--------------	---

Description

Given two vectors of portfolio returns this function calls the internal function wtdpapb to report the simple means of four sophisticated measures of stochastic dominance. as explained in Vinod (2008).

Usage

```
comp_portfo2(xa, xb)
```

Arguments

xa Data on returns for portfolio A in the form of a T by 1 vector
 xb Data on returns for portfolio B in the form of a T by 1 vector

Value

Returns four numbers which are averages of four sophisticated measures of stochastic dominance measurements called SD1 to SD4.

Note

It is possible to modify this function to report the median or standard deviation or any other descriptive statistic by changing the line in the code `'oumean = apply(outb, 2, mean)'` toward the end of this function. A trimmed mean may be of interest when outliers are suspected.

`require(np)`

Make sure that functions `wtdpab`, `bigfp`, `stochdom2` are in the memory. and `options(np.messages=FALSE)`

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D.", "Hands-On Intermediate Econometrics Using R" (2008) World Scientific Publishers: Hackensack, NJ. (Chapter 4) <https://www.worldscientific.com/worldscibooks/10.1142/6895>

See Also

[stochdom2](#)

Examples

```
set.seed(30)
xa=sample(20:30)#generally lower returns
xb=sample(32:40)# higher returns in xb
gp = comp_portfo2(xa, xb)#all Av(sdi) positive means xb dominates
##positive SD1 to SD4 means xb dominates xa as it should
```

da

internal da

Description

intended for internal use only

Usage

da

da2Lag	<i>internal da2Lag</i>
--------	------------------------

Description

intended for internal use

Usage

data(da2Lag)

Format

The format is: int 4

decileVote	<i>Function compares nine deciles of a matrix to reference minimum (eg p stock returns)</i>
------------	---

Description

The first step computes a minimum reference return and nine deciles. The input x must be a matrix having p columns (col.names recommended). and n rows as in the data. If data are missing for some columns, insert NA's. Thus x has p column of data matrix ready for comparison and ranking. For example, x has a matrix of stock returns. The output matrix produced by this function also has p columns for each column (i.e. for each stock being compared). The output matrix has nineteen rows. Top nine rows have the magnitudes of deciles. rows 10 to 18 have respective ranks of the decile magnitudes. The output final row reports a weighted sum of ranks. Ranking always gives the smallest number 1 to the most desirable outcome. The 19th line of the output matrix has weighted sum of ranks and we suggest higher portfolio weight be given to the column having smallest value (in the 19th line) or choosing in the order of numbers in the last (20th) line of out matrix.

Usage

decileVote(mtx, howManySd = 0.1)

Arguments

mtx	(n X p) matrix of data. For example, returns on p stocks n months
howManySd	used to define fixmin= imaginary lowest return defined by going howManySd=default=0.1 maximum standard deviations of all stockss below the minimum return for all stocks in the data

Value

out is a matrix with p columns (same as in the input matrix x) and twenty rows. Top nine rows have deciel quantities, next nine are their ranks. The 19-th row of out has weighted sum of ranks. All compared to the minimum rank portfolio manager can give largest weight to the column with smallest bottom line. The bottom line (20-th) labelled choice of output matrix suggests portfolio manager give the highest weight to the investment option in the column having number 1 and the lowest weight (=0?) to the column having number p as the choice number. Another output of the function is fixmin calculated in this function.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
x1=c(1,4,7,2,6)
x2=c(3,4,8,4,7)
decileVote(cbind(x1,x2))
```

depMeas

depMeas Signed measure of nonlinear nonparametric dependence between two vectors.

Description

An infant may depend on the mother for survival, but not vice versa. Dependence relations need not be symmetric, yet correlation coefficients are symmetric. One way to measure the extent of dependence is to find the max of the absolute values of the two asymmetric correlations using Vinod (2015) definition of generalized (asymmetric) correlation coefficients. It requires a kernel regression of x on y obtained by using the ‘np’ package and its flipped version. We use a block version of ‘gmcmtx0’ called ‘gmcmtxBlk’ to admit several bandwidths.

Usage

```
depMeas(x, y, blksiz = length(x))
```

Arguments

x	Vector of data on the first variable
y	Vector of data on the second variable
blksiz	block size, default blksiz =n, where n=rows in the matrix or no blocking is done

Value

A measure of dependence having the same sign as Pearson correlation. Its magnitude equals the larger of the two generalized correlation coefficients

Note

This function needs the `gmcmtxBlk` function, which in turn needs the `np` package.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

Vinod, H. D. (2021) 'Generalized, Partial and Canonical Correlation Coefficients' Computational Economics, 59(1), 1–28.

See Also

See Also [gmcmtx0](#) and [gmcmtxBlk](#)

Examples

```
library(generalCorr)
options(np.messages = FALSE)
x=1:20;y=sin(x)
depMeas(x,y,blksiz=20)
```

dif4

order 4 differencing of a time series vector

Description

This is for momentum traders who focus on growth, acceleration, its growth and further acceleration. The `diff` function of R seems to do recycling of available numbers, not wanted for our purposes.

Usage

```
dif4(x)
```

Arguments

`x` (n X 1) vector of time series (market returns) with n items each

Value

ou2 matrix having five columns, first for x, the next four columns have diff(x), diff-squared(x), diff-cubed(x) and diff-fourth(x)

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
x=c(2,8,3,5,1,8,19,22,23)
dif4(x)
```

dif4mtx

order 4 differencing of a matrix of time series

Description

This is for momentum traders who focus on growth, acceleration, its growth and further acceleration. The diff function of R seems to do recycling of available numbers, not wanted for our purposes.

Usage

```
dif4mtx(mtx)
```

Arguments

mtx (n X p) matrix of p time series (market returns) with n items each

Value

out matrix having 12 rows, (data, D1 to D4 and ranks of D1 to D4 The column names of out are those of input matrix mtx.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
x=c(2,8,3,5,1,8,19,22,23)
y=c(3,11,2,6,7,9,20,25,21)
dif4mtx(cbind(x,y))
```

diff.e0	<i>Internal diff.e0</i>
---------	-------------------------

Description

Internal diff.e0

Usage

data(diff.e0)

dig	<i>Internal dig</i>
-----	---------------------

Description

Intended for internal use

Usage

data(dig)

Format

The format digs: int 78

e0	<i>internal e0</i>
----	--------------------

Description

intended for internal use only

Usage

e0

EuroCrime	<i>European Crime Data</i>
-----------	----------------------------

Description

This data set refers to crime in European countries during 2008. The sources are World Bank and Eurostat. The crime statistics refers to homicides. It avoids possible reporting bias from the presence of police officers, because homicide reporting in most countries is standardized. Typical usage is: `data(EuroCrime);attach(EuroCrime)`. The secondary source 'quandl.com' was used for collecting these data.

Details

The variables included in the dataset are:

- Country Name of the European country
- `crim` Per capita crime rate
- `off` Per capita deployment of police officers

exactSdMtx	<i>Exact stochastic dominance computation from areas above ECDFs compared to common reference minimum (refmin) for order SD1 to SD4</i>
------------	---

Description

This function inputs 'mtx' (n X p) matrix data (e.g. monthly returns on p stocks) Its output has four matrices SD1 to SD4 each with dimension (n X p).

Usage

```
exactSdMtx(mtx, howManySd = 0.1)
```

Arguments

<code>mtx</code>	(n X p) matrix of data. For example, returns on p stocks n months
<code>howManySd</code>	used to define (x.ref)= lowest return number by going default=0.1 howManySd =number of maximum standard deviations in the data below the all-row all-column minimum return in the data

Value

four matrices SD1 to SD4 for four order of stochastic dominance over a common x.ref. The "out" matrix is another output having 4 rows for SD1 to SD4 and p columns (p=No. of columns in data matrix `mtx`).

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
x1=c(2,5,6,9,13,18,21)
x2=c(3,6,9,12,14,19,27)
st1=exactSdMtx(cbind(x1,x2))
```

GcRsqX12

Granger nonlinear causality R^2 for $x1=f(x1,x2)$, R^2 for flipped $x1$ and $x2$ and the difference between the two R^2 values

Description

Calls GcRsqYX for R square from kernel regression (local linear version) $R^2[x1=f(x1,x2)]$ choosing GcRsqYX($y=x1$, $x=x2$). It predicts $x1$ from both $x1$ and $x2$ using all information till time ($t-1$). It also calls GcRsqYX again after flipping $x1$ and $x2$. It returns RsqX1onX2, RsqX2onX1 and the difference $dif=(RsqX1onX2-RsqX2onX1)$ If ($dif>0$) the regression $x1=f(x1,x2)$ is better than the flipped version implying that $x1$ is more predictable or $x2$ Granger causes $x1$, $x2 \rightarrow x1$, rather than vice versa. The kernel regressions use $regtype="ll"$ for local linear, $bwmethod="cv.aic"$ for AIC-based bandwidth selection.

Usage

```
GcRsqX12(x1, x2, px1 = 4, px2 = 4, pwanted = 4, ctrl = 0)
```

Arguments

x1	The data vector x1
x2	The data vector x2
px1	number of lags of x1 in the data default px1=4
px2	number of lags of x2 in the data, default px2=4
pwanted	number of lags of both x2 and x1 wanted for Granger causal analysis, default =4
ctrl	data matrix for designated control variable(s) outside causal paths default=0 means no control variables are present

Value

This function returns 3 numbers: RsqX1onX2, RsqX2onX1 and dif
returns a list of 3 numbers. RsqX1onX2=(Rsquare of kernel regression of X1 on X1 and X2), RsqX2onX1=(Rsquare of kernel regression of x2 on X2 and X1), and the difference between the two Rquares (first minus second) called dif

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

Zheng, S., Shi, N.-Z., Zhang, Z., 2012. Generalized measures of correlation for asymmetry, non-linearity, and beyond. Journal of the American Statistical Association 107, 1239-1252. -at-note internal routine

See Also

[bootGcRsq](#), [causeSummary](#), [GcRsqYX](#).

Examples

```
## Not run:
library(Ecdat);options(np.messages=FALSE);attach(data.frame(MoneyUS))
GcRsqX12(y,m)

## End(Not run)
```

GcRsqX12c

Granger nonlinear causality R^2 for $x1=f(x1,x2)$ minus R^2 for flipped 1 and 2

Description

Calls GcRsqYXc for R square from kernel regression (local constant version) $R^2[x1=f(x1,x2)]$ choosing GcRsqYXc(y=x1, x=x2). It predicts x1 from both x1 and x2 using all information till time (t-1). It also calls GcRsqYXc again after flipping x1 and x2. It returns RsqX1onX2, RsqX2onX1 and the difference dif=(RsqX1onX2-RsqX2onX1) If (dif>0) the regression $x1=f(x1,x2)$ is better than the flipped version implying that x1 is more predictable or x2 Granger causes x1 $x2 \rightarrow x1$, rather than vice versa. The kernel regressions use regtype="lc" for local constant, bwmethod="cv.ls" for least squares-based bandwidth selection.

Usage

```
GcRsqrX12c(x1, x2, px1 = 4, px2 = 4, pwanted = 4, ctrl = 0)
```

Arguments

x1	The data vector x1
x2	The data vector x2
px1	number of lags of x1 in the data default px1=4
px2	number of lags of x2 in the data, default px2=4
pwanted	number of lags of both x2 and x1 wanted for Granger causal analysis, default =4
ctrl	data matrix for designated control variable(s) outside causal paths default=0 means no control variables are present

Value

This function returns 3 numbers: RsqX1onX2, RsqX2onX1 and dif

returns a list of 3 numbers. RsqX1onX2=(Rsquare of kernel regression of X1 on X1 and X2), RsqX2onX1= (Rsquare of kernel regression of x2 on X2 and X1), and the difference between the two Rquares called dif

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

Zheng, S., Shi, N.-Z., Zhang, Z., 2012. Generalized measures of correlation for asymmetry, non-linearity, and beyond. Journal of the American Statistical Association 107, 1239-1252. -at-note internal routine

See Also

[causeSummary](#)

[GcRsqrYXc](#)

Examples

```
## Not run:
library(Ecdat);options(np.messages=FALSE);attach(data.frame(MoneyUS))
GcRsqX12c(y,m)

## End(Not run)
```

GcRsqYX

Nonlinear Granger causality between two time series workhorse function.

Description

Function input is y =LHS=First time series and x =RHS=Second time series. Kernel regression np package options `regtype="ll"` for local linear, and `bwmethod="cv.aic"` for AIC-based bandwidth selection are fixed. Denote $Rsq=Rsquare=R^2$ in nonlinear kernel regression. `GcRsqYX(.)` computes the following two R^2 values. `out[1]=Rsqqyx = R^2` when we regress y on own lags of y and x . `out[2]=Rsqqy = R^2` when we regress y on own lags of y alone.

Usage

```
GcRsqYX(y, x, px = 4, py = 4, pwanted = 4, ctrl = 0)
```

Arguments

<code>y</code>	The data vector y for the Left side or dependent or first variable
<code>x</code>	The data vector x for the right side or explanatory or second variable
<code>px</code>	number of lags of x in the data
<code>py</code>	number of lags of y in the data. <code>px=4</code> for quarterly data
<code>pwanted</code>	number of lags of both x and y wanted for Granger causal analysis
<code>ctrl</code>	data matrix for designated control variable(s) outside causal paths default=0 means no control variables are present

Value

This function returns a set of 2 numbers measuring nonlinear Granger-causality for time series. `out[1]=Rsqqyx`, `out[2]=Rsqqy`.

Note

If data are annual or if no quarterly-type structure is present, use this function with `pwanted=px=py`. For example, the egg or chicken data from `lmtest` package.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

Zheng, S., Shi, N.-Z., Zhang, Z., 2012. Generalized measures of correlation for asymmetry, nonlinearity, and beyond. Journal of the American Statistical Association 107, 1239-1252.

See Also

[GcRsqX12](#), [kern2](#), [kern2ctrl](#).

Examples

```
## Not run:
library(Ecdat);options(np.messages=FALSE);attach(data.frame(MoneyUS))
GcRsqYX(y,m)

## End(Not run)
```

GcRsqYXc

Nonlinear Granger causality between two time series workhorse function.(local constant version)

Description

Function input is y=LHS=First time series and x=RHS=Second time series. Kernel regression np package options regtype="lc" for local constant, and bwmethod="cv.ls" for least squares-based bandwidth selection are fixed. Denote Rsq=Rsquare=R² in nonlinear kernel regression. GcRsqYXc(.) computes the following two R² values. out[1]=Rsqqyx = R² when we regress y on own lags of y and x. out[2]=Rsqqy = R² when we regress y on own lags of y alone.

Usage

```
GcRsqYXc(y, x, px = 4, py = 4, pwanted = 4, ctrl = 0)
```

Arguments

y	The data vector y for the Left side or dependent or first variable
x	The data vector x for the right side or explanatory or second variable
px	number of lags of x in the data
py	number of lags of y in the data. px=4 for quarterly data
pwanted	number of lags of both x and y wanted for Granger causal analysis
ctrl	data matrix for designated control variable(s) outside causal paths default=0 means no control variables are present

Value

This function returns a set of 2 numbers measuring nonlinear Granger-causality for time series. out[1]=Rsqyx, out[2]=Rsqyy.

Note

If data are annual or if no quarterly-type structure is present, use this function with pwanted=px=py. For example, the egg or chicken data from lmtest package, Thurman W.N. and Fisher M.E. (1988)

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

Zheng, S., Shi, N.-Z., Zhang, Z., 2012. Generalized measures of correlation for asymmetry, nonlinearity, and beyond. Journal of the American Statistical Association 107, 1239-1252.

See Also

[GcRsqX12c](#)

[kern_ctrl](#)

Examples

```
## Not run:
library(Ecdat);options(np.messages=FALSE);attach(data.frame(MoneyUS))
GcRsqYXc(y,m)

## End(Not run)
```

generalCorrInfo

generalCorr package description:

Description

This package provides convenient software tools for causal path determinations using Vinod (2014, 2015, 2018, 2021) and is explained in many vignettes of the package. `causeSummary(mtx)` and similar `causeSummBlk` for its blocked version report pair-wise causal path directions and the absolute causal strength [0, 100]. We fit a kernel regression of X_1 on (X_2, X_3, \dots, X_k) and another flipped regression of X_2 on (X_1, x_3, \dots, X_k) . We compare the two fits using three sophisticated criteria called Cr1 to Cr3. We rescale the weighted sum of the quantified three criteria to the [-100, 100] range. The sign of the weighted sum gives the direction of the causal path, and the magnitude of the weighted sum gives the strength of the causal path. A matrix of non-symmetric generalized correlations $r^*(x|y)$ is reported by the functions `rstar()` and `gmcmtx0()`. `sudoCoefParcor()` computes pseudo kernel regression coefficients based on generalized partial correlation coefficients (GPCC) `depMeas()` a measure of nonlinear nonparametric dependence between two vectors. `parcorVec()` has generalized partial correlation coefficients, Vinod (2021) `parcorVecH()` has a hybrid version of the above (using HGPCC). The usual partial correlations $r(x,y|z)$ for regression of y on (x, z) measure the effect of y on x after removing the effect of z , where z can have several variables. Vinod (2021) suggests new generalized partial correlation coefficients (GPCC) using kernel regressions, $r^*(x,y|z)$.

Details

The criterion Cr1 uses observable values of standard exogeneity test criterion, namely, (kernel regression residual) times (regressor values) Cr2 computes absolute values kernel regression residuals. The quantification of Cr1 and Cr2 further uses four orders of stochastic dominance measures. Cr3 compares the R-square of the two fits. The package provides additional tools for matrix algebra, such as `cofactor()`, for outlier detection `get0outlier()`, for numerical integration by the trapezoidal rule, stochastic dominance `stochdom2()` and `comp_portfo2()`, etc. The package has a function `pcause()` for bootstrap-based statistical inference and another one for a heuristic t-test called `heurist()`. Pairwise deletion of missing data is done in `napair()`, while triplet-wise deletion is in `naTriplet()` intended for use when control variable(s) are also present. If one has panel data, functions `PanelLag()` and `Panel2Lag()` are relevant. `pillar3D` provides 3-dimensional plots of data which look more like surfaces, than usual plots with vertical pins.

Recent 2020 additions include `canonRho()` for generalized canonical correlations, and many functions for Granger causality between lagged time series including `GcRsqX12()`, `bootGcRsq()` and `GcRsqYXc()`.

Recent 2021 additions include several functions for portfolio choice. `sudocoefParcor()` for pseudo regression coefficients for kernel regressions. `decileVote()`, `momentVote()`, `exactSdMtx()` for exact computation of stochastic dominance from ECDF areas. `dif4mtx()` computes growth, change in growth etc. up-to order 4 differencing of time series.

Note

Five vignettes provided with this package at CRAN describe the theory and usage of the package with examples. Read them using the command: `vignette("generalCorr-vignette")` to read the first vignette. vignettes 2 to 5 can be read by including the vignette number. For example, `vignette("generalCorr-vignette5")` to read the fifth vignette.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [gffn86](#)

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in 'Handbook of Statistics: Computational Statistics with R', Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

Zheng, S., Shi, N.-Z., and Zhang, Z. (2012). 'Generalized measures of correlation for asymmetry, nonlinearity, and beyond,' Journal of the American Statistical Association, vol. 107, pp. 1239-1252.

Vinod, H. D. (2021) 'Generalized, Partial and Canonical Correlation Coefficients' Computational Economics, 59(1), 1-28.

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.

<code>get0outliers</code>	<i>Function to compute outliers and their count using Tukey method using 1.5 times interquartile range (IQR) to define boundaries.</i>
---------------------------	--

Description

Function to compute outliers and their count using Tukey method using 1.5 times interquartile range (IQR) to define boundaries.

Usage

```
get0outliers(x, verbo = TRUE, mult = 1.5)
```

Arguments

x	vector of data.
verbo	set to TRUE(default) assuming printed details are desired.
mult	=1.5(default), the number of times IQR is used in defining outlier boundaries.

Value

below	which items are lower than the lower limit
above	which items are larger than the upper limit
low.lim	the lower boundary for outlier detection
up.lim	the upper boundary for outlier detection
nUP	count of number of data points above upper boundary
nLO	count of number of data points below lower boundary

Note

The function removes the missing data before checking for outliers.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
set.seed(101);x=sample(1:100)[1:15];x[16]=150;x[17]=NA
get0outliers(x)#correctly identifies outlier=150
```

getSeq	<i>Two sequences: starting+ending values from n and blocksize (internal use)</i>
--------	--

Description

This is an auxiliary function for gmcmtxBlk. It gives sequences of starting and ending values

Usage

```
getSeq(n, blksiz)
```

Arguments

n	length of the range
blksiz	blocksize

Value

two vectors sqLO and sqUP

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

See Also

[gmcmtxBlk](#)

Examples

```
getSeq(n=99, blksiz=10)
```

gmc0

internal gmc0

Description

intended for internal use only

Usage

```
gmc0
```

gmc1

internal gmc1

Description

intended for internal use only

Usage

```
gmc1
```

gmcmtx0	<i>Matrix R* of generalized correlation coefficients captures nonlinearities.</i>
---------	---

Description

This function checks for missing data for each pair individually. It then uses the kern function to kernel regress x on y, and conversely y on x. It needs the library 'np' which reports R-squares of each regression. This function reports their square roots after assigning them the observed sign of the Pearson correlation coefficient. Its advantages are: (i) It is asymmetric yielding causal direction information, by relaxing the assumption of linearity implicit in usual correlation coefficients. (ii) The r^* correlation coefficients are generally larger upon admitting arbitrary nonlinearities. (iii) $\max(|R^*_{ij}|, |R^*_{ji}|)$ measures (nonlinear) dependence. For example, let $x=1:20$ and $y=\sin(x)$. This y has a perfect (100 percent) nonlinear dependence on x and yet Pearson correlation coefficient $r(xy)$ -0.0948372 is near zero and usual confidence interval (-0.516, 0.363) includes zero, implying that it is not different from zero. This shows a miserable failure of traditional $r(x,y)$ to measure dependence when nonlinearities are present.

Usage

```
gmcmtx0(mym, nam = colnames(mym))
```

Arguments

mym	A matrix of data on variables in columns
nam	Column names of the variables in the data matrix

Value

A non-symmetric R^* matrix of generalized correlation coefficients

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

- Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>
- Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in 'Handbook of Statistics: Computational Statistics with R', Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.
- Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.
- Zheng, S., Shi, N.-Z., and Zhang, Z. (2012). 'Generalized measures of correlation for asymmetry, nonlinearity, and beyond,' Journal of the American Statistical Association, vol. 107, pp. 1239-1252.

See Also

See Also as [gmcmtxBlk](#) for a more general version using blocking.

Examples

```
gmcmtx0(mtcars[,1:3])

## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('v1', 'v2', 'v3')
gmcmtx0(x)
## End(Not run)
```

gmcmtxBlk	<i>Matrix R^* of generalized correlation coefficients captures nonlinearities using blocks.</i>
-----------	--

Description

The algorithm uses two auxiliary functions, getSeq and NLhat. The latter uses the kern function to kernel regress x on y , and conversely y on x . It needs the package ‘np,’ which reports residuals and allows one to compute fitted values (\hat{x} , \hat{y}). Unlike `gmcmtx0`, this function considers blocks of `blksiz=10` (default) pairs of data points separately with distinct bandwidths for each block, usually creating superior local fits.

Usage

```
gmcmtxBlk(mym, nam = colnames(mym), blksiz = 10)
```

Arguments

mym	A matrix of data on selected variables arranged in columns
nam	Column names of the variables in the data matrix
blksiz	block size, default=10, if chosen <code>blksiz > n</code> , where <code>n=rows</code> in matrix then <code>blksiz=n</code> . That is, no blocking is done

Details

This function does pairwise checks of missing data for all pairs. Assume that there are n rows in the input matrix ‘mym’ with some missing rows. If the columns of mym are denoted (X_1, X_2, \dots, X_p) , we are considering all pairs (X_i, X_j) , treated as (x, y) , with ‘nv’ number of valid (non-missing) rows. Note that each x and y is an $(nv \text{ by } 1)$ vector. This function further splits these (x, y) vectors into as many subgroups or blocks as are needed for the nv paired valid data points for the chosen block length (`blksiz`)

Next, the algorithm strings together various blocks of fitted value vectors (\hat{x} , \hat{y}) also of dimension n_v by 1. Now for each pair of $X_i X_j$ (column X_j = cause, row X_i =response, treated as x and y), the algorithm computes R^{*ij} the simple Pearson correlation coefficient between (x , \hat{x}) and as R^{*ji} the correlation coeff. between (y , \hat{y}). Next, it assigns $|R^{*ij}|$ and $|R^{*ji}|$ the observed sign of the Pearson correlation coefficient between x and y .

Its advantages discussed in Vinod (2015, 2019) are: (i) It is asymmetric yielding causal direction information, by relaxing the assumption of linearity implicit in usual correlation coefficients. (ii) The R^* correlation coefficients are generally larger upon admitting arbitrary nonlinearities. (iii) $\max(|R^{*ij}|, |R^{*ji}|)$ measures (nonlinear) dependence. For example, let $x=1:20$ and $y=\sin(x)$. This y has a perfect (100 percent) nonlinear dependence on x and yet Pearson correlation coefficient $r(x, y) = -0.0948372$ is near zero, and its 95% confidence interval $(-0.516, 0.363)$ includes zero, implying that the population $r(x, y)$ is not significantly different from zero. This example highlights a serious failure of the traditional $r(x, y)$ in measuring dependence between x and y when nonlinearities are present. `gmcmtx0` without blocking does work if $x=1:n$, and $y=f(x)=\sin(x)$ is used with $n < 20$. But for larger n , the fixed bandwidth used by the kern function becomes a problem. The block version has additional bandwidths for each block, and hence it correctly quantifies the presence of high dependence even when $x=1:n$, and $y=f(x)$ are defined for large n and complicated nonlinear functional forms for $f(x)$.

Value

A non-symmetric R^* matrix of generalized correlation coefficients

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

- Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>
- Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in 'Handbook of Statistics: Computational Statistics with R', Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.
- Vinod, H. D. 'New exogeneity tests and causal paths,' Chapter 2 in 'Handbook of Statistics: Conceptual Econometrics Using R', Vol.32, co-editors: H. D. Vinod and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2019, pp. 33-64.
- Zheng, S., Shi, N.-Z., and Zhang, Z. (2012). 'Generalized measures of correlation for asymmetry, nonlinearity, and beyond,' Journal of the American Statistical Association, vol. 107, pp. 1239-1252.

Examples

```
## Not run:
x=1:20; y=sin(x)
gmcmtxBlk(cbind(x,y),blksiz=10)
## End(Not run)
```

`gmcmtxZ`*compute the matrix R^* of generalized correlation coefficients.*

Description

This function checks for missing data separately for each pair using kern function to kernel regress x on y, and conversely y on x. It needs the library ‘np’ which reports R-squares of each regression. This function reports their square roots with the sign of the Pearson correlation coefficients. Its appeal is that it is asymmetric yielding causal direction information. It avoids the assumption of linearity implicit in the usual correlation coefficients.

Usage

```
gmcmtxZ(mym, nam = colnames(mym))
```

Arguments

<code>mym</code>	A matrix of data on variables in columns
<code>nam</code>	Column names of the variables in the data matrix

Value

A non-symmetric R^* matrix of generalized correlation coefficients

Note

This allows the user to change `gmcmtx0` and further experiment with my code.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. ‘Generalized Correlation and Kernel Causality with Applications in Development Economics’ in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Examples

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('V1', 'v2', 'V3')
gmcmtxZ(x)

## End(Not run)
```

gmcxy_np	<i>Function to compute generalized correlation coefficients $r^*(x y)$ and $r^*(y x)$ from two vectors (not matrices)</i>
----------	---

Description

This function uses the 'np' package and assumes that there are no missing data.

Usage

```
gmcxy_np(x, y)
```

Arguments

x	vector of x data
y	vector of y data

Value

corxy	$r^*(x y)$ from regressing x on y, where y is the kernel cause.
coryx	$r^*(y x)$ from regressing y on x, where x is the cause.

Note

This is provided if the user want to avoid calling kern.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R,' Chapter 4 in 'Handbook of Statistics: Computational Statistics with R,' Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

Examples

```
## Not run:  
set.seed(34);x=sample(1:10);y=sample(2:11)  
gmcxy_np(x,y)  
## End(Not run)
```

goodCol	<i>internal goodCol</i>
---------	-------------------------

Description

intended for internal use only

Usage

goodCol

heurist	<i>Heuristic t test of the difference between two generalized correlations.</i>
---------	---

Description

Function to run a heuristic t test of the difference between two generalized correlations.

Usage

heurist(rxy, ryx, n)

Arguments

rxy	generalized correlation $r^*(x y)$ where y is the kernel cause.
ryx	generalized correlation $r^*(y x)$ where x is the kernel cause.
n	Sample size needed to determine the degrees of freedom for the t test.

Value

Prints the t statistics and p-values.

Note

This function requires Revele's R package called 'psych' in memory. This test is known to be conservative (i.e., often fails to reject the null hypothesis of zero difference between the two generalized correlation coefficients.)

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```

set.seed(34);x=sample(1:10);y=sample(2:11)
g1=gmcxy_np(x,y)
n=length(x)
h1=heurist(g1$corxy,g1$coryx,n)
print(h1)
print(h1$t) #t statistic
print(h1$p) #p-value

```

i	<i>internal i</i>
---	-------------------

Description

intended for internal use

Usage

data(i)

Format

The format is: int 78

ibad	<i>internal object</i>
------	------------------------

Description

intended for internal use

ii	<i>internal ii</i>
----	--------------------

Description

intended for internal use

j	<i>internal j</i>
---	-------------------

Description

intended for internal use

Usage

data(j)

Format

The format is: int 4

kern	<i>Kernel regression with options for residuals and gradients.</i>
------	--

Description

Function to run kernel regression with options for residuals and gradients assuming no missing data.

Usage

```
kern(dep.y, reg.x, tol = 0.1, ftol = 0.1, gradients = FALSE, residuals = FALSE)
```

Arguments

dep.y	Data on the dependent (response) variable
reg.x	Data on the regressor (stimulus) variables
tol	Tolerance on the position of located minima of the cross-validation function (default =0.1)
ftol	Fractional tolerance on the value of cross validation function evaluated at local minima (default =0.1)
gradients	Make this TRUE if gradients computations are desired
residuals	Make this TRUE if residuals are desired

Value

Creates a model object 'mod' containing the entire kernel regression output. Type names(mod) to reveal the variety of outputs produced by 'npreg' of the 'np' package. The user can access all of them at will by using the dollar notation of R.

Note

This is a work horse for causal identification.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D.'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

See [kern_ctrl](#).

Examples

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:50],ncol=2)
require(np); options(np.messages=FALSE)
k1=kern(x[,1],x[,2])
print(k1$R2) #prints the R square of the kernel regression

## End(Not run)
```

kern2	<i>Kernel regression version 2 with optional residuals and gradients with regtype="ll" for local linear, bwmethod="cv.aic" for AIC-based bandwidth selection.</i>
-------	---

Description

Kernel regression version 2 with optional residuals and gradients with regtype="ll" for local linear, bwmethod="cv.aic" for AIC-based bandwidth selection.

Usage

```
kern2(
  dep.y,
  reg.x,
  tol = 0.1,
  ftol = 0.1,
  gradients = FALSE,
  residuals = FALSE
)
```

Arguments

dep.y	Data on the dependent (response) variable
reg.x	Data on the regressor (stimulus) variables
tol	Tolerance on the position of located minima of the cross-validation function (default =0.1)
ftol	Fractional tolerance on the value of cross validation function evaluated at local minima (default =0.1)
gradients	Make this TRUE if gradients computations are desired
residuals	Make this TRUE if residuals are desired

Value

Creates a model object 'mod' containing the entire kernel regression output. Type names(mod) to reveal the variety of outputs produced by 'npreg' of the 'np' package. The user can access all of them at will by using the dollar notation of R.

Note

This is version 2 ("II", "cv.aic") of a work horse for causal identification.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D.'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

See [kern_ctrl](#).

Examples

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:50],ncol=2)
require(np); options(np.messages=FALSE)
k1=kern(x[,1],x[,2])
print(k1$R2) #prints the R square of the kernel regression

## End(Not run)
```

kern2ctrl	<i>Kernel regression with control variables and optional residuals and gradients. version 2 regtype="ll" for local linear, bwmethod="cv.aic" for AIC-based bandwidth selection. It admits control variables.</i>
-----------	--

Description

Kernel regression with control variables and optional residuals and gradients. version 2 regtype="ll" for local linear, bwmethod="cv.aic" for AIC-based bandwidth selection. It admits control variables.

Usage

```
kern2ctrl(
  dep.y,
  reg.x,
  ctrl,
  tol = 0.1,
  ftol = 0.1,
  gradients = FALSE,
  residuals = FALSE
)
```

Arguments

dep.y	Data on the dependent (response) variable
reg.x	Data on the regressor (stimulus) variable
ctrl	Data matrix on the control variable(s) kept outside the causal paths. A constant vector is not allowed as a control variable.
tol	Tolerance on the position of located minima of the cross-validation function (default=0.1)
ftol	Fractional tolerance on the value of cross validation function evaluated at local minima (default=0.1)
gradients	Set to TRUE if gradients computations are desired
residuals	Set to TRUE if residuals are desired

Value

Creates a model object 'mod' containing the entire kernel regression output. If this function is called as `mod=kern_ctrl(x,y,ctrl=z)`, the researcher can simply type names(mod) to reveal the large variety of outputs produced by 'npreg' of the 'np' package. The user can access all of them at will using the dollar notation of R.

Note

This is version 2 ("ll","cv.aic") of a work horse for causal identification.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

See [kern](#).

Examples

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:50],ncol=5)
require(np)
k1=kern_ctrl(x[,1],x[,2],ctrl=x[,4:5])
print(k1$R2) #prints the R square of the kernel regression

## End(Not run)
```

kern_ctrl	<i>Kernel regression with control variables and optional residuals and gradients.</i>
-----------	---

Description

Allowing matrix input of control variables, this function runs kernel regression with options for residuals and gradients.

Usage

```
kern_ctrl(
  dep.y,
  reg.x,
  ctrl,
  tol = 0.1,
  ftol = 0.1,
  gradients = FALSE,
  residuals = FALSE
)
```

Arguments

dep.y	Data on the dependent (response) variable
reg.x	Data on the regressor (stimulus) variable
ctrl	Data matrix on the control variable(s) kept outside the causal paths. A constant vector is not allowed as a control variable.
tol	Tolerance on the position of located minima of the cross-validation function (default=0.1)
ftol	Fractional tolerance on the value of cross validation function evaluated at local minima (default=0.1)
gradients	Set to TRUE if gradients computations are desired
residuals	Set to TRUE if residuals are desired

Value

Creates a model object 'mod' containing the entire kernel regression output. If this function is called as `mod=kern_ctrl(x,y,ctrl=z)`, the researcher can simply type `names(mod)` to reveal the large variety of outputs produced by 'npreg' of the 'np' package. The user can access all of them at will using the dollar notation of R.

Note

This is a work horse for causal identification.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

See [kern](#).

Examples

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:50],ncol=5)
require(np)
k1=kern_ctrl(x[,1],x[,2],ctrl=x[,4:5])
print(k1$R2) #prints the R square of the kernel regression

## End(Not run)
```

mag	<i>Approximate overall magnitudes of kernel regression partials dx/dy and dy/dx.</i>
-----	--

Description

Uses Vinod (2015) and runs kernel regression of x on y, and also of y on x by using the ‘np’ package. The function goes on to compute a summary magnitude of the overall approximate partial derivative dx/dy (and dy/dx), after adjusting for units by using an appropriate ratio of standard deviations. Of course, the real partial derivatives of nonlinear functions are generally distinct for each observation.

Usage

```
mag(x, y)
```

Arguments

x	Vector of data on the dependent variable
y	Vector of data on the regressor

Value

vector of two magnitudes of kernel regression partials dx/dy and dy/dx.

Note

This function is intended for use only after the direction of causal path is already determined by various functions in this package (e.g. `somePairs`). For example, if the researcher knows that x causes y, then only dy/dx denoted by `dydx` is relevant. The other output of the function `dxdy` is to be ignored. Similarly, only ‘`dxdy`’ is relevant if y is known to be the cause of x.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. ‘Generalized Correlation and Kernel Causality with Applications in Development Economics’ in *Communications in Statistics -Simulation and Computation*, 2015, doi: [gffn86](#)

Vinod, H. D. ‘Matrix Algebra Topics in Statistics and Economics Using R’, Chapter 4 in *Handbook of Statistics: Computational Statistics with R*, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

See Also

See [mag_ctrl](#).

Examples

```
set.seed(123);x=sample(1:10);y=1+2*x+rnorm(10)
mag(x,y)#dxdy approx=.5 and dydx approx=2 will be nice.
```

mag_ctrl	<i>After removing control variables, magnitude of effect of x on y, and of y on x.</i>
----------	--

Description

Uses Vinod (2015) and runs kernel regressions: $x \sim y + \text{ctrl}$ and $x \sim \text{ctrl}$ to evaluate the ‘incremental change’ in R-squares. Let $(\text{rxy};\text{ctrl})$ denote the square root of that ‘incremental change’ after its sign is made the same as that of the Pearson correlation coefficient from $\text{cor}(x, y)$. One can interpret $(\text{rxy};\text{ctrl})$ as a generalized partial correlation coefficient when x is regressed on y after removing the effect of control variable(s) in ctrl . It is more general than the usual partial correlation coefficient, since this one allows for nonlinear relations among variables. Next, the function computes ‘dxdy’ obtained by multiplying $(\text{rxy};\text{ctrl})$ by the ratio of standard deviations, $\text{sd}(x)/\text{sd}(y)$. Now our ‘dxdy’ approximates the magnitude of the partial derivative (dx/dy) in a causal model where y is the cause and x is the effect. The function also reports entirely analogous ‘dydx’ obtained by interchanging x and y .

Usage

```
mag_ctrl(x, y, ctrl)
```

Arguments

<code>x</code>	Vector of data on the dependent variable.
<code>y</code>	Vector of data on the regressor.
<code>ctrl</code>	data matrix for designated control variable(s) outside causal paths. A constant vector is not allowed as a control variable.

Value

vector of two magnitudes ‘dxdy’ (effect when x is regressed on y) and ‘dydx’ for reverse regression. Both regressions remove the effect of control variable(s).

Note

This function is intended for use only after the causal path direction is already determined by various functions in this package (e.g. `someCPairs`). That is, after the researcher knows whether x causes y or vice versa. The output of this function is a vector of two numbers: $(\text{dxdy}, \text{dydx})$, in that order, representing the magnitude of effect of one variable on the other. We expect the researcher to use only ‘dxdy’ if y is the known cause, or ‘dydx’ if x is the cause. These approximate overall measures may not be well-defined in some applications, because the real partial derivatives of nonlinear functions are generally distinct for each evaluation point.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [gffn86](#)

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C. R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

See Also

See [mag](#)

Examples

```
set.seed(123);x=sample(1:10); z=runif(10); y=1+2*x+3*z+rnorm(10)
options(np.messages=FALSE)
mag_ctrl(x,y,z)#dx/dy=0.47 is approximately 0.5, but dy/dx=1.41 is not approx=2,
```

min.e0

internal min.e0

Description

intended for internal use only

Usage

min.e0

minor

Function to do compute the minor of a matrix defined by row r and column c.

Description

Function to do compute the minor of a matrix defined by row r and column c.

Usage

minor(x, r, c)

Arguments

x	The input matrix
r	The row number
c	The column number

Value

The appropriate 'minor' matrix defined from the input matrix.

Note

This function is needed by the cofactor function.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
## Not run:
x=matrix(1:20,ncol=4)
minor(x,1,2)
## End(Not run)
```

momentVote

Function compares Pearson Stats and Sharpe Ratio for a matrix of stock returns

Description

The first step computes mean, std.dev, skewness, kurtosis (kurt),and the Sharpe Ratio (mean/sd) representing risk-adjusted return where sd measures the risk. The input x must be a matrix having p columns (col.names recommended). and n rows as in the data. If data are missing for some columns, insert NA's. Thus x has p column of data matrix ready for comparison and ranking. For example, x has a matrix of stock returns. The output matrix produced by this function has p columns for each data column (i.e. for each stock being compared). The output matrix has twelve rows. Top five rows have the magnitudes of mean, sd, skew, kurt, Sharpe ratios. Output matrix rows 6 to 10 have respective ranks of moment stats. The output 11-th row reports a weighted sum of ranks with following weights mean=1,sd=-1,skew=0.5,kurt=-0.5,Sharpe Ratio=1. User has the option to change the weights. They measure relative importance.

Usage

```
momentVote(mtx, weight = c(1, -1, 0.5, -0.5, 1))
```

Arguments

mtx	n by p matrix of data, For example, p stock returns, mtx columns should have names
weight	vector of reliability weights. default: mean=1, sd=1, skew=0.5,kurt=0.5,sharpe=1

Details

Since skewness and kurtosis are measured relatively less reliably (have greater sampling variation due to higher powers) their weight is 0.5. Our ranking gives the smallest number 1 to the most desirable outcome. The 11-th line of the output matrix has weighted sum of ranks and we suggest higher portfolio weight be given to the column having smallest value (in the bottom line). The 12-th row of output matrix has choice, where input weights give the number 1 is for the top choice column of data and all other choice numbers. A second column of the output matrix has the chosen weights.

Value

a matrix with same number of columns as in the input matrix x and eleven rows. Top five rows have moment quantities, next five are their ranks the eleventh row has weighted sum of ranks with the input weights (see default) and the 12-th row has choice numbers (choice=1 is best)

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
x1=c(1,4,7,2,6)
x2=c(3,4,8,4,7)
momentVote(cbind(x1,x2))
```

 mtx

internal mtx

Description

intended for internal use only

Usage

```
mtx
```

mtx0

internal mtx0

Description

intended for internal use only

Usage

mtx0

mtx2

internal mtx2

Description

intended for internal use only

Usage

mtx2

n

internal n

Description

intended for internal use

Usage

n

Format

The format is: int 78

na11	<i>internal na11</i>
------	----------------------

Description

intended for internal use only

Usage

na11

nam.badCol	<i>internal nam.badCol</i>
------------	----------------------------

Description

intended for internal use only

Usage

nam.badCol

nam.goodCol	<i>internal nam.goodCol</i>
-------------	-----------------------------

Description

intended for internal use only

Usage

nam.goodCol

nam.mtx0	<i>internal nam.mtx0</i>
----------	--------------------------

Description

intended for internal use only

Usage

nam.mtx0

napair	<i>Function to do pairwise deletion of missing rows.</i>
--------	--

Description

The aim in pair-wise deletions is to retain the largest number of available data pairs with all non-missing data.

Usage

```
napair(x, y)
```

Arguments

x	Vector of x data
y	Vector of y data

Value

newx	A new vector x after removing pairwise missing data
newy	A new vector y after removing pairwise missing data

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
## Not run:  
x=sample(1:10);y=sample(1:10);x[2]=NA; y[3]=NA  
napair(x,y)  
## End(Not run)
```

naTriplet	<i>Function to do matched deletion of missing rows from x, y and control variable(s).</i>
-----------	---

Description

The aim in three-way deletions is to retain only the largest number of available data triplets with all non-missing data.

Usage

```
naTriplet(x, y, ctrl)
```

Arguments

x	Vector of x data
y	Vector of y data
ctrl	Data matrix on the control variable(s) kept beyond causal path determinations

Value

newx	A new vector x after removing triplet-wise missing data
newy	A new vector or matrix y after removing triplet-wise missing data
newctrl	A new vector or matrix ctrl after removing triplet-wise missing data

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

See Also

See [napair](#).

Examples

```
## Not run:
x=sample(1:10);y=sample(1:10);x[2]=NA; y[3]=NA
w=sample(2:11)
naTriplet(x,y,w)
## End(Not run)
```

NLhat

Compute fitted values from kernel regression of x on y and y on x

Description

This is an auxiliary function for ‘gmcmtxBlk.’ It uses two numerical vectors (x, y) of same length to create two vectors (xhat, yhat) of fitted values using nonlinear kernel regressions. It uses package ‘np’ called by kern function to kernel regress x on y, and conversely y on x. It uses the option ‘residuals=TRUE’ of ‘kern’

Usage

```
NLhat(x, y)
```

Arguments

x	A column vector of x data
y	A column vector of y data

Value

two vectors named xhat and yhat for fitted values

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

See Also

See Also as [gmcmtxB1k](#).

Examples

```
## Not run:  
set.seed(34);x=sample(1:15);y=sample(1:15)  
NLhat(x,y)  
## End(Not run)
```

out1

internal out1

Description

intended for internal use only

Usage

out1

p1

internal p1

Description

intended for internal use only

Usage

p1

Panel2Lag	<i>Function to compute a vector of 2 lagged values of a variable from panel data.</i>
-----------	---

Description

The panel data have a set of time series for each entity (e.g. country) arranged such that all time series data for one entity is together. The data for the second entity should be below the entire data for first entity. When a variable is lagged twice, special care is needed to insert NA's for the first two time points (e.g. weeks) for each entity (country).

Usage

```
Panel2Lag(ID, xj)
```

Arguments

ID	Location of the column having time identities (e.g. the week number)
xj	Data on variable to be lagged linked to ID

Value

Vector containing 2 lagged values of xj.

Note

This function is provided for convenient user modifications.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

See Also

A more general function [PanelLag](#) has examples.

PanelLag	<i>Function for computing a vector of one-lagged values of xj, a variable from panel data.</i>
----------	--

Description

Panel data have a set of time series for each entity (e.g. country) arranged such that all time series data for one entity is together, and the data for the second entity should be below the entire data for first entity and so on for entities. In such a data setup, When a variable is lagged once, special care is needed to insert an NA for the first time point in the data (e.g. week) for each entity.

Usage

```
PanelLag(ID, xj, lag = 1)
```

Arguments

ID	Location of the column having time identities (e.g. week number).
xj	Data vector of variable to be lagged and is linked with the ID.
lag	Number of lags desired (lag=1 is the default).

Value

Vector containing one-lagged values of variable xj.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
## Not run:
indiv=gl(6,12,labels=LETTERS[1:6])
#creates A,A,A 12 times B B B also 12 times etc.
set.seed(99);cost=sample(30:90, 72, replace=TRUE)
revenu=sample(50:110, 72, replace=TRUE); month=rep(1:12,6)
df=data.frame(indiv,month,cost,revenu);head(df);tail(df)
L2cost=PanelLag(ID=month,xj=df[, 'cost'], lag=2)
head(L2cost)
tail(L2cost)

gmcmtx0(cbind(revenu,cost,L2cost))

gmcxy_np(revenu,cost)

## End(Not run)
```

parcorBijk	<i>Block version of generalized partial correlation coefficients between X_i and X_j, after removing the effect of x_k, via nonparametric regression residuals.</i>
------------	--

Description

This function uses data on two column vectors, x_i , x_j and a third x_k which can be a vector or a matrix, usually of the remaining variables in the model, including control variables, if any. It first removes missing data from all input variables. Then, it computes residuals of kernel regression (x_i on x_k) and (x_j on x_k). This is a block version of `parcor_ijk`.

Usage

```
parcorBijk(xi, xj, xk, blksize = 10)
```

Arguments

x_i	Input vector of data for variable x_i
x_j	Input vector of data for variable x_j
x_k	Input data for variables in x_k , usually control variables
blksize	block size, default=10, if chosen blksize > n, where n=rows in matrix then blksize=n. That is, no blocking is done

Value

ou_{ij}	Generalized partial correlation X_i with X_j (=cause) after removing x_k
ou_{ji}	Generalized partial correlation X_j with X_i (=cause) after removing x_k

allowing for control variables.

Note

This function calls [kern](#),

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

See Also

See [parcor_ijk](#).

Examples

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
options(np.messages=FALSE)
parcorBijk(x[,1], x[,2], x[,3], blksi=10)

## End(Not run)##'
```

parcorBMany	<i>Block version reports many generalized partial correlation coefficients allowing control variables.</i>
-------------	--

Description

This function calls a block version `parcorBijk` of the function which uses original data to compute generalized partial correlations between X_{idep} and X_j where j can be any one of the remaining variables in the input matrix `mtx`. Partial correlations remove the effect of variables X_k other than X_i and X_j . Calculation further allows for the presence of control variable(s) (if any) to remain always outside the input matrix and whose effect is also removed in computing partial correlations.

Usage

```
parcorBMany(mtx, ctrl = 0, dig = 4, idep = 1, blksiz = 10, verbo = FALSE)
```

Arguments

<code>mtx</code>	Input data matrix with at least 3 columns.
<code>ctrl</code>	Input vector or matrix of data for control variable(s), default is <code>ctrl=0</code> when control variables are absent
<code>dig</code>	The number of digits for reporting (=4, default)
<code>idep</code>	The column number of the dependent variable (=1, default)
<code>blksiz</code>	block size, default=10, if chosen <code>blksiz > n</code> , where <code>n=rows</code> in matrix then <code>blksiz=n</code> . That is, no blocking is done
<code>verbo</code>	Make this TRUE for detailed printing of computational steps

Value

A five column 'out' matrix containing partials. The first column has the name of the `idep` variable. The second column has the name of the j variable, while the third column has partial correlation coefficients $r^*(i,j | k)$. The last column reports the absolute difference between two partial correlations.

Note

This function reports all partial correlation coefficients, while avoiding ridge type adjustment.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlations and Instantaneous Causality for Data Pairs Benchmark,' (March 8, 2015) <https://www.ssrn.com/abstract=2574891>

Vinod, H. D. (2021) 'Generalized, Partial and Canonical Correlation Coefficients' Computational Economics, 59(1), 1–28.

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

See Also

See Also [parcor_ijk](#), [parcorMany](#).

Examples

```
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is partly indep and partly affected by z
y=1+2*x+3*z+rnorm(10)# y depends on x and z not vice versa
mtx=cbind(x,y,z)
parcorBMany(mtx, blksiz=10)
```

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('V1', 'v2', 'V3')
parcorBMany(x, idep=1)
```

```
## End(Not run)
```

parcorHijk

Generalized partial correlation coefficients between X_i and X_j , after removing the effect of X_k , via OLS regression residuals.

Description

This function uses data on two column vectors, x_i , x_j , and a third x_k , which can be a vector or a matrix, usually of the remaining variables in the model, including control variables, if any. It first removes missing data from all input variables. Then, it computes residuals of OLS regression (x_i on x_k) and (x_j on x_k). This hybrid version uses both OLS and then generalized correlation among OLS residuals.

Usage

```
parcorHijk(xi, xj, xk)
```

Arguments

xi	Input vector of data for variable xi
xj	Input vector of data for variable xj
xk	Input data for variables in xk, usually control variables

Value

ouij	Generalized partial correlation X_i with X_j (=cause) after removing x_k
ouji	Generalized partial correlation X_j with X_i (=cause) after removing x_k allowing for control variables.

Note

This function calls [kern](#),

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

See Also

See [parcor_ijk](#).

Examples

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
options(np.messages=FALSE)
parcorHijk(x[,1], x[,2], x[,3])

## End(Not run)##'
```

parcorMany	<i>Report many generalized partial correlation coefficients allowing control variables.</i>
------------	---

Description

This function calls `parcor_ijk` function which uses original data to compute generalized partial correlations between $X_{i_{dep}}$ and X_j where j can be any one of the remaining variables in the input matrix `mtx`. Partial correlations remove the effect of variables x_k other than X_i and X_j . Calculation further allows for the presence of control variable(s) (if any) to remain always outside the input matrix and whose effect is also removed in computing partial correlations.

Usage

```
parcorMany(mtx, ctrl = 0, dig = 4, idep = 1, verbo = FALSE)
```

Arguments

mtx	Input data matrix with at least 3 columns.
ctrl	Input vector or matrix of data for control variable(s), default is ctrl=0 when control variables are absent
dig	The number of digits for reporting (=4, default)
idep	The column number of the first variable (=1, default)
verbo	Make this TRUE for detailed printing of computational steps

Value

A five column 'out' matrix containing partials. The first column has the name of the idep variable. The second column has the name of the j variable, while the third column has partial correlation coefficients $r^{*(i,j|k)}$. The last column reports the absolute difference between two partial correlations.

Note

This function reports all partial correlation coefficients, while avoiding ridge type adjustment.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlations and Instantaneous Causality for Data Pairs Benchmark,' (March 8, 2015) <https://www.ssrn.com/abstract=2574891>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

See Also

See Also [parcor_ijk](#).

Examples

```
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is partly indep and partly affected by z
y=1+2*x+3*z+rnorm(10)# y depends on x and z not vice versa
mtx=cbind(x,y,z)
parcorMany(mtx)
```

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('V1', 'v2', 'V3')
parcorMany(x, idep=1)

## End(Not run)
```

parcorMtx	<i>Matrix of generalized partial correlation coefficients, always leaving out control variables, if any.</i>
-----------	--

Description

This function calls `parcor_ijk` function which uses original data to compute generalized partial correlations between X_i and X_j where j can be any one of the remaining variables in the input matrix `mtx`. Partial correlations remove the effect of variables x_k other than X_i and X_j . Calculation further allows for the presence of control variable(s) (if any) to remain always outside the input matrix and whose effect is also removed in computing partial correlations.

Usage

```
parcorMtx(mtx, ctrl = 0, dig = 4, verbo = FALSE)
```

Arguments

<code>mtx</code>	Input data matrix with p columns. p is at least 3 columns.
<code>ctrl</code>	Input vector or matrix of data for control variable(s), default is <code>ctrl=0</code> when control variables are absent
<code>dig</code>	The number of digits for reporting (=4, default)
<code>verbo</code>	Make this TRUE for detailed printing of computational steps

Value

A p by p 'out' matrix containing partials $r^*(i,j | k)$. and $r^*(j,i | k)$.

Note

We want to get all partial correlation coefficient pairs removing other column effects. Vinod (2018) shows why one needs more than one criterion to decide the causal paths or exogeneity.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlations and Instantaneous Causality for Data Pairs Benchmark,' (March 8, 2015) <https://www.ssrn.com/abstract=2574891>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

Vinod, H. D. 'New Exogeneity Tests and Causal Paths,' (June 30, 2018). Available at SSRN: <https://www.ssrn.com/abstract=3206096>

See Also

See Also [parcor_ijk](#).

Examples

```
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is partly indep and partly affected by z
y=1+2*x+3*z+rnorm(10)# y depends on x and z not vice versa
mtx=cbind(x,y,z)
parcorMtx(mtx)
```

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('V1', 'v2', 'V3')
parcorMtx(x)
```

```
## End(Not run)
```

parcorSilent

Silently compute generalized (ridge-adjusted) partial correlation coefficients from matrix R.*

Description

This function calls `parcor_ijkOLD` function which uses a generalized correlation matrix R^* as input to compute generalized partial correlations between X_i and X_j where j can be any one of the remaining variables. Computation removes the effect of all other variables in the matrix. It further adjusts the resulting partial correlation coefficients to be in the appropriate $[-1,1]$ range by using an additive constant in the fashion of ridge regression.

Usage

```
parcorSilent(gmc0, dig = 4, idep = 1, verbo = FALSE, incr = 3)
```

Arguments

gmc0	This must be a p by p matrix R^* of generalized correlation coefficients.
dig	The number of digits for reporting (=4, default)
idep	The column number of the first variable (=1, default)
verbo	Make this TRUE for detailed printing of computational steps
incr	incremental constant for iteratively adjusting 'ridgek' where ridgek is the constant times the identity matrix used to make sure that the gmc0 matrix is positive definite. If not, this function iteratively increases the incr till relevant partial correlations are within the [-1,1] interval.

Value

A five column 'out' matrix containing partials. The first column has the name of the idep variable. The second column has the name of the j variable, while the third column has $r^*(i,j | k)$. The 4-th column has $r^*(j,i | k)$ (denoted partji), and the 5-th column has $r_{ij}Mr_{ji}$, that is the difference in absolute values ($abs(partij) - abs(partji)$).

Note

The ridgek constant created by the function during the first round may not be large enough to make sure that that other pairs of $r^*(i,j | k)$ are within the [-1,1] interval. The user may have to choose a suitably larger input incr to get all relevant partial correlation coefficients in the correct [-1,1] interval.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlations and Instantaneous Causality for Data Pairs Benchmark,' (March 8, 2015) <https://www.ssrn.com/abstract=2574891>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

Vinod, H. D. "A Survey of Ridge Regression and Related Techniques for Improvements over Ordinary Least Squares," Review of Economics and Statistics, Vol. 60, February 1978, pp. 121-131.

See Also

See Also [parcor_ijk](#) for a better version using original data as input.

Examples

```
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is partly indep and partly affected by z
y=1+2*x+3*z+rnorm(10)# y depends on x and z not vice versa
```

```

mtx=cbind(x,y,z)
g1=gmcmtx0(mtx)
parcor_ijkOLD(g1,1,2) # ouji> ouij implies i=x is the cause of j=y
parcor_ridg(g1,idep=1)
parcorSilent(g1,idep=1)

## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('V1', 'v2', 'V3')
gm1=gmcmtx0(x)
parcorSilent(gm1, idep=1)

## End(Not run)

```

parcorVec	<i>Vector of generalized partial correlation coefficients (GPCC), always leaving out control variables, if any.</i>
-----------	---

Description

This function calls `parcor_ijk` function which uses original data to compute generalized partial correlations between X_i , the dependent variable, and X_j which is the current regressor of interest. Note that j can be any one of the remaining variables in the input matrix `mtx`. Partial correlations remove the effect of variables X_k other than X_i and X_j . Calculation merges control variable(s) (if any) into X_k . Let the remainder effect from kernel regressions of X_i on X_k equal the residuals $u^*(i,k)$. Analogously define $u^*(j,k)$. (asterisk for kernel regressions) Now partial correlation is generalized correlation between $u^*(i,k)$ and $u^*(j,k)$. Calculation merges control variable(s) (if any) into X_k .

Usage

```
parcorVec(mtx, ctrl = 0, verbo = FALSE, idep = 1)
```

Arguments

<code>mtx</code>	Input data matrix with p ($>$ or $=$ 3) columns
<code>ctrl</code>	Input vector or matrix of data for control variable(s), default is <code>ctrl=0</code> when control variables are absent
<code>verbo</code>	Make this TRUE for detailed printing of computational steps
<code>idep</code>	The column number of the dependent variable ($=1$, default)

Value

A p by 1 'out' vector containing partials $r^*(i,j | k)$.

Note

Generalized Partial Correlation Coefficients (GPCC) allow comparison of the relative contribution of each X_j to the explanation of X_i , because GPCC are scale-free pure numbers

We want to get all partial correlation coefficient pairs removing other column effects. Vinod (2018) shows why one needs more than one criterion to decide the causal paths or exogeneity.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlations and Instantaneous Causality for Data Pairs Benchmark,' (March 8, 2015) <https://www.ssrn.com/abstract=2574891>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

Vinod, H. D. 'New Exogeneity Tests and Causal Paths,' (June 30, 2018). Available at SSRN: <https://www.ssrn.com/abstract=3206096>

Vinod, H. D. (2021) 'Generalized, Partial and Canonical Correlation Coefficients' Computational Economics, 59(1), 1–28.

See Also

See Also [parcor_ijk](#).

See Also a hybrid version [parcorVech](#).

Examples

```
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is partly indep and partly affected by z
y=1+2*x+3*z+rnorm(10)# y depends on x and z not vice versa
mtx=cbind(x,y,z)
parcorVec(mtx)
```

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('v1', 'v2', 'v3')#some names needed
parcorVec(x)
```

```
## End(Not run)
```

parcorVecH	<i>Vector of hybrid generalized partial correlation coefficients, hybrid version of parcorVec subtracting only linear effects but using generalized correlation between OLS residuals</i>
------------	---

Description

This function calls `parcor_ijk` function which uses original data to compute generalized partial correlations between X_i , the dependent variable, and X_j which is the current regressor of interest. Note that j can be any one of the remaining variables in the input matrix `mtx`. Partial correlations remove the effect of variables X_k other than X_i and X_j . Calculation merges control variable(s) (if any) into X_k . Let the remainder effect from OLS regressions of X_i on X_k equal the residuals $u(i,k)$. Analogously define $u(j,k)$. It is a hybrid of OLS and generalized. Finally, partial correlation is generalized (kernel) correlation between $u(i,k)$ and $u(j,k)$.

Usage

```
parcorVecH(mtx, ctrl = 0, dig = 4, verbo = FALSE, idep = 1)
```

Arguments

<code>mtx</code>	Input data matrix with p ($>$ or $=$ 3) columns, first column must have the dependent variable
<code>ctrl</code>	Input vector or matrix of data for control variable(s), default is <code>ctrl=0</code> when control variables are absent
<code>dig</code>	The number of digits for reporting ($=$ 4, default)
<code>verbo</code>	Make this TRUE for detailed printing of computational steps
<code>idep</code>	The column number of the dependent variable ($=$ 1, default)

Value

A p by 1 'out' vector containing hybrid partials $r^*(i,j | k)$.

Note

Hybrid Generalized Partial Correlation Coefficients (HGPPCC) allow comparison of the relative contribution of each X_j to the explanation of X_i , because HGPPCC are scale-free pure numbers.

We want to get all partial correlation coefficient pairs removing other column effects. Vinod (2018) shows why one needs more than one criterion to decide the causal paths or exogeneity.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlations and Instantaneous Causality for Data Pairs Benchmark,' (March 8, 2015) <https://www.ssrn.com/abstract=2574891>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

Vinod, H. D. 'New Exogeneity Tests and Causal Paths,' (June 30, 2018). Available at SSRN: <https://www.ssrn.com/abstract=3206096>

Vinod, H. D. (2021) 'Generalized, Partial and Canonical Correlation Coefficients' Computational Economics, 59(1), 1–28.

See Also

See Also [parcor_ijk](#).

See Also [parcorVec](#).

Examples

```
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is partly indep and partly affected by z
y=1+2*x+3*z+rnorm(10)# y depends on x and z not vice versa
mtx=cbind(x,y,z)
parcorVecH(mtx)
```

```
## Not run:
set.seed(34);mtx=matrix(sample(1:600)[1:80],ncol=4)
colnames(mtx)=c('V1', 'v2', 'V3', 'V4')
parcorVecH(mtx,verbo=TRUE, idep=2)
```

```
## End(Not run)
```

parcor_ijk

Generalized partial correlation coefficients between X_i and X_j , after removing the effect of x_k , via nonparametric regression residuals.

Description

This function uses data on two column vectors, x_i , x_j and a third x_k which can be a vector or a matrix, usually of the remaining variables in the model, including control variables, if any. It first removes missing data from all input variables. Then, it computes residuals of kernel regression (x_i on x_k) and (x_j on x_k). This version avoids ridge type adjustment present in an older version.

Usage

```
parcor_ijk(xi, xj, xk)
```

Arguments

<code>xi</code>	Input vector of data for variable xi
<code>xj</code>	Input vector of data for variable xj
<code>xk</code>	Input data for variables in xk, usually control variables

Value

<code>ouij</code>	Generalized partial correlation X_i with X_j (=cause) after removing <code>xk</code>
<code>ouji</code>	Generalized partial correlation X_j with X_i (=cause) after removing <code>xk</code> allowing for control variables.

Note

This function calls [kern](#),

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

See Also

See [parcor_linear](#).

Examples

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
options(np.messages=FALSE)
parcor_ijk(x[,1], x[,2], x[,3])

## End(Not run)##'
```

parcor_ijkOLD

Generalized partial correlation coefficient between X_i and X_j after removing the effect of all others. (older version, deprecated)

Description

This function uses a generalized correlation matrix R^* as input to compute generalized partial correlations between X_i and X_j where j can be any one of the remaining variables. Computation removes the effect of all other variables in the matrix. The user is encouraged to remove all known irrelevant rows and columns from the R^* matrix before submitting it to this function.

Usage

```
parcor_ijkOLD(x, i, j)
```

Arguments

x	Input a p by p matrix R* of generalized correlation coefficients.
i	A column number identifying the first variable.
j	A column number identifying the second variable.

Value

ouij	Partial correlation X_i with X_j (=cause) after removing all other X's
ouji	Partial correlation X_j with X_i (=cause) after removing all other X's
myk	A list of column numbers whose effect has been removed

Note

This function calls `minor`, and `cofactor` and is called by `parcor_ridge`.

Examples

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('V1', 'v2', 'V3')
gm1=gmcmtx0(x)
parcor_ijkOLD(gm1, 2,3)

## End(Not run)##'
```

parcor_linear	<i>Partial correlation coefficient between X_i and X_j after removing the linear effect of all others.</i>
---------------	--

Description

This function uses a symmetric correlation matrix R as input to compute usual partial correlations between X_i and X_j where j can be any one of the remaining variables. Computation removes the effect of all other variables in the matrix. The user is encouraged to remove all known irrelevant rows and columns from the R matrix before submitting it to this function.

Usage

```
parcor_linear(x, i, j)
```

Arguments

x	Input a p by p matrix R of symmetric correlation coefficients.
i	A column number identifying the first variable.
j	A column number identifying the second variable.

Value

ouij	Partial correlation X_i with X_j after removing all other X 's
ouji	Partial correlation X_j with X_i after removing all other X 's
myk	A list of column numbers whose effect has been removed

Note

This function calls [minor](#), and [cofactor](#)

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

See Also

See [parcor_ijk](#) for generalized partial correlation coefficients useful for causal path determinations.

Examples

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('V1', 'v2', 'V3')
c1=cor(x)
parcor_linear(c1, 2,3)

## End(Not run)
```

parcor_ridg	<i>Compute generalized (ridge-adjusted) partial correlation coefficients from matrix R^*. (deprecated)</i>
-------------	---

Description

This function calls `parcor_ijkOLD` function which uses a generalized correlation matrix R^* as input to compute generalized partial correlations between X_i and X_j where j can be any one of the remaining variables. Computation removes the effect of all other variables in the matrix. It further adjusts the resulting partial correlation coefficients to be in the appropriate $[-1,1]$ range by using an additive constant in the fashion of ridge regression.

Usage

```
parcor_ridg(gmc0, dig = 4, idep = 1, verbo = FALSE, incr = 3)
```

Arguments

gmc0	This must be a p by p matrix R^* of generalized correlation coefficients.
dig	The number of digits for reporting (=4, default)
idep	The column number of the first variable (=1, default)
verbo	Make this TRUE for detailed printing of computational steps
incr	incremental constant for iteratively adjusting 'ridgek' where ridgek is the constant times the identity matrix used to make sure that the gmc0 matrix is positive definite. If not iteratively increases the incr till all partial correlations are within the [-1,1] interval.

Value

A five column 'out' matrix containing partials. The first column has the name of the idep variable. The second column has the name of the j variable, while the third column has $r^*(i,j | k)$. The 4-th column has $r^*(j,i | k)$ (denoted partji), and the 5-th column has $rijMrji$, that is the difference in absolute values ($abs(partij) - abs(partji)$).

Note

The ridgek constant created by the function during the first round may not be large enough to make sure that that other pairs of $r^*(i,j | k)$ are within the [-1,1] interval. The user may have to choose a suitably larger input incr to get all relevant partial correlation coefficients in the correct [-1,1] interval.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlations and Instantaneous Causality for Data Pairs Benchmark,' (March 8, 2015) <https://www.ssrn.com/abstract=2574891>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

Vinod, H. D. "A Survey of Ridge Regression and Related Techniques for Improvements over Ordinary Least Squares," Review of Economics and Statistics, Vol. 60, February 1978, pp. 121-131.

See Also

See Also [parcor_ijkOLD](#).

Examples

```
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is partly indep and partly affected by z
y=1+2*x+3*z+rnorm(10)# y depends on x and z not vice versa
```

```

mtx=cbind(x,y,z)
g1=gmcmtx0(mtx)
parcor_ijkOLD(g1,1,2) # ouji> ouij implies i=x is the cause of j=y
parcor_ridg(g1,idep=1)

## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('V1', 'v2', 'V3')
gm1=gmcmtx0(x)
parcor_ridg(gm1, idep=1)

## End(Not run)

```

pcause

Compute the bootstrap probability of correct causal direction.

Description

Maximum entropy bootstrap ('meboot') package is used for statistical inference regarding δ which equals GMC(X|Y)-GMC(Y|X) defined by Zheng et al (2012). The bootstrap provides an approximation to chances of correct determination of the causal direction.

Usage

```
pcause(x, y, n999 = 999)
```

Arguments

x	Vector of x data
y	Vector of y data
n999	Number of bootstrap replications (default=999)

Value

P(cause) the bootstrap proportion of correct causal determinations.

Note

'pcause' is computer intensive and generally slow. It is better to use it at a later stage in the investigation when a preliminary causal determination is already made. Its use may slow the exploratory phase. In my experience, if P(cause) is less than 0.55, there is a cause for concern.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

Zheng, S., Shi, N.-Z., and Zhang, Z. (2012). Generalized measures of correlation for asymmetry, nonlinearity, and beyond. Journal of the American Statistical Association, vol. 107, pp. 1239-1252.

Vinod, H. D. and Lopez-de-Lacalle, J. (2009). 'Maximum entropy bootstrap for time series: The meboot R package.' Journal of Statistical Software, Vol. 29(5), pp. 1-19.

Examples

```
## Not run:
set.seed(34);x=sample(1:10);y=sample(2:11)
pcause(x,y,n999=29)

data('EuroCrime')
attach(EuroCrime)
pcause(crim,off,n999=29)

## End(Not run)
```

pillar3D

Create a 3D pillar chart to display (x, y, z) data coordinate surface.

Description

Give data on x, y, z coordinate values of a 3D surface, this function plots them after making pillars near each z value by adding and subtracting small amounts dz. Instead of pins of the height z this creates pillars which better resemble a surface. It uses the wireframe() function of 'lattice' package to do the plotting.

Usage

```
pillar3D(
  z = c(657, 936, 1111, 1201),
  x = c(280, 542, 722, 1168),
  y = c(162, 214, 186, 246),
  drape = TRUE,
  xlab = "y",
  ylab = "x",
  zlab = "z",
  mymain = "Pillar Chart"
)
```

Arguments

z	z-coordinate values
x	x-coordinate values
y	y-coordinate values
drape	logical value, default drape=TRUE to give color to heights
xlab	default "x" label on the x axis
ylab	default "y" label on the y axis
zlab	default "z" label on the z axis
mymain	default "Pillar Chart" main label on the plot

Details

For additional plotting features type ‘pillar3D()’ on the R console to get my code and adjust wireframe() function defaults.

Value

A 3D plot

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
## Not run:
pillar3D()
## End(Not run)
```

```
prelec2
```

Intermediate weighting function giving Non-Expected Utility theory weights.

Description

Computes cumulative probabilities and difference between consecutive cumulative probabilities described in Vinod (2008) textbook. This is a simpler version of the version in the book without mapping to non-expected utility theory weights as explained in Vinod (2008).

Usage

```
prelec2(n)
```

Arguments

n A (usually small) integer.

Value

x sequence 1:n
 p probabilities $p = x[i]/n$
 pdif consecutive differences $p[i] - p[i - 1]$

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Hands-On Intermediate Econometrics Using R' (2008) World Scientific Publishers: Hackensack, NJ. <https://www.worldscientific.com/worldscibooks/10.1142/6895>

Examples

```
## Not run: prelec2(10)
```

probSign	<i>Compute probability of positive or negative sign from bootPairs output</i>
----------	---

Description

If there are p columns of data, probSign produces a $p-1$ by 1 vector of probabilities of correct signs assuming that the mean of $n999$ values has the correct sign and assuming that m of the 'sum' index values inside the range $[-\tau, \tau]$ are neither positive nor negative but indeterminate or ambiguous (being too close to zero). That is, the denominator of $P(+1)$ or $P(-1)$ is $(n999-m)$ if m signs are too close to zero.

Usage

```
probSign(out, tau = 0.476)
```

Arguments

out output from bootPairs with $p-1$ columns and $n999$ rows
 tau threshold to determine what value is too close to zero, default $\tau=0.476$ is equivalent to 15 percent threshold for the unanimity index u_i

Value

sgn When `mtx` has `p` columns, `sgn` reports pairwise `p-1` signs representing (fixing the first column in each pair) the average sign after averaging the output of `bootPairs(mtx)` (a `n999` by `p-1` matrix) each containing resampled 'sum' values summarizing the weighted sums associated with all three criteria from the function `silentPairs(mtx)` applied to each bootstrap sample separately. #'

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in *Communications in Statistics -Simulation and Computation*, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

Vinod, H. D. and Lopez-de-Lacalle, J. (2009). 'Maximum entropy bootstrap for time series: The `meboot` R package.' *Journal of Statistical Software*, Vol. 29(5), pp. 1-19.

Vinod, H. D. Causal Paths and Exogeneity Tests in `Generalcorr` Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See Also [silentPairs](#).

Examples

```
## Not run:
options(np.messages = FALSE)
set.seed(34);x=sample(1:10);y=sample(2:11)
bb=bootPairs(cbind(x,y),n999=29)
probSign(bb,tau=0.476) #gives summary stats for n999 bootstrap sum computations

bb=bootPairs(airquality,n999=999);options(np.messages=FALSE)
probSign(bb,tau=0.476)#signs for n999 bootstrap sum computations

data('EuroCrime')
attach(EuroCrime)
bb=bootPairs(cbind(crim,off),n999=29) #col.1= crim causes off
#hence positive signs are more intuitively meaningful.
#note that n999=29 is too small for real problems, chosen for quickness here.
probSign(bb,tau=0.476)#signs for n999 bootstrap sum computations

## End(Not run)
```

rhs.lag2	<i>internal rhs.lag2</i>
----------	--------------------------

Description

intended for internal use only

Usage

rhs.lag2

rhs1	<i>internal rhs1</i>
------	----------------------

Description

intended for internal use only

Usage

rhs1

ridgek	<i>internal ridgek</i>
--------	------------------------

Description

intended for internal use only

Usage

ridgek

rij	<i>internal rij</i>
-----	---------------------

Description

intended for internal use only

Usage

rij

rijMrji	<i>internal rijMrji</i>
---------	-------------------------

Description

intended for internal use only

Usage

rijMrji

rji	<i>internal rji</i>
-----	---------------------

Description

intended for internal use only

Usage

rji

rrij	<i>internal rrij</i>
------	----------------------

Description

intended for internal use only

Usage

rrij

rrji	<i>internal rrji</i>
------	----------------------

Description

intended for internal use only

Usage

rrji

rstar *Function to compute generalized correlation coefficients $r^*(x,y)$.*

Description

Uses Vinod (2015) definition of generalized (asymmetric) correlation coefficients. It requires kernel regression of x on y obtained by using the 'np' package. It also reports usual Pearson correlation coefficient r and p-value for testing the null hypothesis that (population r)=0.

Usage

```
rstar(x, y)
```

Arguments

x	Vector of data on the dependent variable
y	Vector of data on the regressor

Value

Four objects created by this function are:

corxy	$r^*_{x y}$ or regressing x on y
coryx	$r^*_{y x}$ or regressing y on x
pearson.r	Pearson's product moment correlation coefficient
pv	The p-value for testing the Pearson r

Note

This function needs the kern function which in turn needs the np package.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, <https://doi.org/gffn86>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

See Also

See Also [gmcmtx0](#) and [gmcmtxBlk](#).

Examples

```
x=sample(1:30);y=sample(1:30); rstar(x,y)
```

sales2Lag	<i>internal sales2Lag</i>
-----------	---------------------------

Description

intended for internal use only

Usage

sales2Lag

salesLag	<i>internal salesLag</i>
----------	--------------------------

Description

intended for internal use only

Usage

salesLag

seed	<i>internal seed</i>
------	----------------------

Description

intended for internal use only

Usage

seed

sgn.e0	<i>internal sgn.e0</i>
--------	------------------------

Description

intended for internal use only

Usage

sgn.e0

silentMtx	<i>No-print kernel-causality unanimity score matrix with optional control variables</i>
-----------	---

Description

Allowing input matrix of control variables and missing data, this function produces a p by p matrix summarizing the results, where the estimated signs of stochastic dominance order values (+1, 0, -1) are weighted by $wt=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2 and added to the Cr3 estimate as: (+1, 0, -1). Final weighted index is always in the range [-3.175, 3.175]. It is converted to the more intuitive range [-100, 100].

Usage

silentMtx(mtx, ctrl = 0, dig = 6, wt = c(1.2, 1.1, 1.05, 1), sumwt = 4)

Arguments

mtx	The data matrix with p columns. Denote x1 as the first column which is fixed and then paired with all other columns, say: x2, x3, ..., xp, one by one for the purpose of flipping with x1. p must be 2 or more
ctrl	data matrix for designated control variable(s) outside causal paths
dig	Number of digits for reporting (default dig=6).
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The reason for slightly declining weights on the signs from SD1 to SD4 is simply that the local mean comparisons implicit in SD1 are known to be more reliable than local variance implicit in SD2, local skewness implicit in SD3 and local kurtosis implicit in SD4. Why are higher moment estimates less reliable? The higher power of the deviations from the mean needed in their computations lead to greater sampling variability. The summary results for all three criteria are reported in a vector of numbers internally called crall:

Value

With p columns in `mtx` argument to this function, `x1` can be paired with a total of $p-1$ columns (`x2`, `x3`, ..., `xp`). Note we never flip any of the control variables with `x1`. This function produces $i=1,2,\dots,p-1$ numbers representing the summary sign, or 'sum' from the signs `sg1` to `sg3` associated with the three criteria: `Cr1`, `Cr2` and `Cr3`. Note that `sg1` and `sg2` themselves are weighted signs using weighted sum of signs from four orders of stochastic dominance. In general, a positive sign in the i -th location of the 'sum' output of this function means that `x1` is the kernel cause while the variable in $(i+1)$ -th column of `mtx` is the 'effect' or 'response' or 'endogenous.' The magnitude represents the strength (unanimity) of the evidence for a particular sign. Conversely a negative sign in the i -th location of the 'sum' output of this function means that that the first variable listed as the input to this function is the 'effect,' while the variable in $(i+1)$ -th column of `mtx` is the exogenous kernel cause. This function is a summary of `someCPairs` allowing for control variables.

Note

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers. The command `attach(EuroCrime); silentPairs(cbind(crim,off))` returns only one number: 3.175, implying a high unanimity strength. The index 3.175 is the highest. The positive sign of the index suggests that 'crim' variable in the first column of the matrix input to this function kernel causes 'off' in the second column of the matrix argument `mtx` to this function.

Interpretation of the output matrix produced by this function is as follows. A negative index means the variable named in the column kernel-causes the variable named in the row. A positive index means the row name variable kernel-causes the column name variable. The `abs(index)` measures unanimity by three criteria, `Cr1` to `Cr3` representing the strength of evidence for the identified causal path.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

H. D. Vinod 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in *Communications in Statistics -Simulation and Computation*, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

Vinod, H. D. Causal Paths and Exogeneity Tests in `Generalcorr` Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See `silentPairs`.

See `someCPairs`, `some0Pairs`

Examples

```

## Not run:
options(np.messages=FALSE)
colnames(mtcars[2:ncol(mtcars)])
silentMtx(mtcars[,1:3],ctrl=mtcars[,4:5]) # mpg paired with others

## End(Not run)

options(np.messages=FALSE)
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
silentMtx(mtx=cbind(x2,y2), ctrl=cbind(z,w2))

```

silentMtx0	<i>Older kernel-causality unanimity score matrix with optional control variables</i>
------------	--

Description

Allowing input matrix of control variables and missing data, this function produces a p by p matrix summarizing the results, where the estimated signs of stochastic dominance order values (+1, 0, -1) are weighted by $wt=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2 and added to the Cr3 estimate as: (+1, 0, -1). Final weighted index is always in the range [-3.175, 3.175]. It is converted to the more intuitive range [-100, 100].

Usage

```
silentMtx0(mtx, ctrl = 0, dig = 6, wt = c(1.2, 1.1, 1.05, 1), sumwt = 4)
```

Arguments

mtx	The data matrix with p columns. Denote x_1 as the first column which is fixed and then paired with all other columns, say: x_2, x_3, \dots, x_p , one by one for the purpose of flipping with x_1 . p must be 2 or more
ctrl	data matrix for designated control variable(s) outside causal paths
dig	Number of digits for reporting (default dig=6).
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The reason for slightly declining weights on the signs from SD1 to SD4 is simply that the local mean comparisons implicit in SD1 are known to be more reliable than local variance implicit in SD2, local skewness implicit in SD3 and local kurtosis implicit in SD4. Why are higher moment estimates less reliable? The higher power of the deviations from the mean needed in their computations lead to greater sampling variability. The summary results for all three criteria are reported in a vector of numbers internally called `crall`:

Value

With p columns in `mtx` argument to this function, x_1 can be paired with a total of $p-1$ columns (x_2, x_3, \dots, x_p). Note we never flip any of the control variables with x_1 . This function produces $i=1,2,\dots,p-1$ numbers representing the summary sign, or ‘sum’ from the signs `sg1` to `sg3` associated with the three criteria: `Cr1`, `Cr2` and `Cr3`. Note that `sg1` and `sg2` themselves are weighted signs using weighted sum of signs from four orders of stochastic dominance. In general, a positive sign in the i -th location of the ‘sum’ output of this function means that x_1 is the kernel cause while the variable in $(i+1)$ -th column of `mtx` is the ‘effect’ or ‘response’ or ‘endogenous.’ The magnitude represents the strength (unanimity) of the evidence for a particular sign. Conversely a negative sign in the i -th location of the ‘sum’ output of this function means that that the first variable listed as the input to this function is the ‘effect,’ while the variable in $(i+1)$ -th column of `mtx` is the exogenous kernel cause. This function allows for control variables.

Note

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers. The command `attach(EuroCrime); silentPairs(cbind(crim,off))` returns only one number: 3.175, implying a high unanimity strength. The index 3.175 is the highest. The positive sign of the index suggests that ‘`crim`’ variable in the first column of the matrix input to this function kernel causes ‘`off`’ in the second column of the matrix argument `mtx` to this function.

Interpretation of the output matrix produced by this function is as follows. A negative index means the variable named in the column kernel-causes the variable named in the row. A positive index means the row name variable kernel-causes the column name variable. The `abs(index)` measures unanimity by three criteria, `Cr1` to `Cr3` representing the strength of evidence for the identified causal path.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

H. D. Vinod ‘Generalized Correlation and Kernel Causality with Applications in Development Economics’ in *Communications in Statistics -Simulation and Computation*, 2015, doi: [gffn86](https://doi.org/10.1080/00936999.2015.1053866)

Vinod, H. D. Causal Paths and Exogeneity Tests in *Generalcorr* Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See [silentPairs0](#) using older Cr1 criterion based on kernel regression local gradients.

See [someCPairs](#), [some0Pairs](#)

Examples

```
## Not run:
options(np.messages=FALSE)
colnames(mtcars[2:ncol(mtcars)])
silentMtx0(mtcars[,1:3],ctrl=mtcars[,4:5]) # mpg paired with others

## End(Not run)

## Not run:
options(np.messages=FALSE)
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
silentMtx0(mtx=cbind(x2,y2), ctrl=cbind(z,w2))

## End(Not run)
```

silentPairs

*No-print kernel causality scores with control variables Hausman-Wu
Criterion 1*

Description

Allowing input matrix of control variables and missing data, this function produces a 3 column matrix summarizing the results where the estimated signs of stochastic dominance order values (+1, 0, -1) are weighted by $wt=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2 and added to the Cr3 estimate as: (+1, 0, -1), always in the range [-3.175, 3.175].

Usage

```
silentPairs(mtx, ctrl = 0, dig = 6, wt = c(1.2, 1.1, 1.05, 1), sumwt = 4)
```

Arguments

mtx	The data matrix with p columns. Denote x1 as the first column which is fixed and then paired with all other columns, say: x2, x3, ..., xp, one by one for the purpose of flipping with x1. p must be 2 or more
ctrl	data matrix for designated control variable(s) outside causal paths default ctrl=0 which means that there are no control variables used.
dig	Number of digits for reporting (default dig=6).
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The reason for slightly declining weights on the signs from SD1 to SD4 is simply that the local mean comparisons implicit in SD1 are known to be more reliable than local variance implicit in SD2, local skewness implicit in SD3 and local kurtosis implicit in SD4. The source of slightly declining sampling unreliability of higher moments is the higher power of the deviations from the mean needed in their computations. The summary results for all three criteria are reported in a vector of numbers internally called `crall`:

Value

With p columns in `mtx` argument to this function, x1 can be paired with a total of p-1 columns (x2, x3, ..., xp). Note we never flip any of the control variables with x1. This function produces i=1,2,...,p-1 numbers representing the summary sign, or 'sum' from the signs sg1 to sg3 associated with the three criteria: Cr1, Cr2 and Cr3. Note that sg1 and sg2 themselves are weighted signs using weighted sum of signs from four orders of stochastic dominance. In general, a positive sign in the i-th location of the 'sum' output of this function means that x1 is the kernel cause while the variable in (i+1)-th column of `mtx` is the 'effect' or 'response' or 'endogenous.' The magnitude represents the strength (unanimity) of the evidence for a particular sign. Conversely a negative sign in the i-th location of the 'sum' output of this function means that that the first variable listed as the input to this function is the 'effect,' while the variable in (i+1)-th column of `mtx` is the exogenous kernel cause.

Note

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers. The command `attach(EuroCrime); silentPairs(cbind(crim,off))` returns only one number: 3.175, implying the highest unanimity strength index, with the positive sign suggesting 'crim' in the first column kernel causes 'off' in the second column of the argument `mtx` to this function.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

H. D. Vinod 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See [bootPairs](#), [silentMtx](#)

See [someCPairs](#), [some0Pairs](#)

Examples

```
## Not run:
options(np.messages=FALSE)
colnames(mtcars[2:ncol(mtcars)])
silentPairs(mtcars[,1:3],ctrl=mtcars[,4:5]) # mpg paired with others

## End(Not run)

options(np.messages=FALSE)
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
silentPairs(mtx=cbind(x2,y2), ctrl=cbind(z,w2))
```

silentPairs0

Older version, kernel causality weighted sum allowing control variables

Description

Allowing input matrix of control variables and missing data, this function produces a 3 column matrix summarizing the results where the estimated signs of stochastic dominance order values (+1, 0, -1) are weighted by $wt=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2 and added to the Cr3 estimate as: (+1, 0, -1), always in the range [-3.175, 3.175].

Usage

```
silentPairs0(mtx, ctrl = 0, dig = 6, wt = c(1.2, 1.1, 1.05, 1), sumwt = 4)
```

Arguments

<code>mtx</code>	The data matrix with p columns. Denote x_1 as the first column which is fixed and then paired with all other columns, say: x_2, x_3, \dots, x_p , one by one for the purpose of flipping with x_1 . p must be 2 or more
<code>ctrl</code>	data matrix for designated control variable(s) outside causal paths default <code>ctrl=0</code> which means that there are no control variables used.
<code>dig</code>	Number of digits for reporting (default <code>dig=6</code>).
<code>wt</code>	Allows user to choose a vector of four alternative weights for SD1 to SD4.
<code>sumwt</code>	Sum of weights can be changed here <code>=4</code> (default).

Details

This uses an older version of the first criterion `Cr1` based on absolute values of local gradients of kernel regressions, not absolute Hausman-Wu statistic (RHS variable times kernel residuals). It calls `abs_stdapd` and `abs_stdapdC`. The reason for slightly declining weights on the signs from SD1 to SD4 is simply that the local mean comparisons implicit in SD1 are known to be more reliable than local variance implicit in SD2, local skewness implicit in SD3 and local kurtosis implicit in SD4. The source of slightly declining sampling unreliability of higher moments is the higher power of the deviations from the mean needed in their computations. The summary results for all three criteria are reported in a vector of numbers internally called `crall`:

Value

With p columns in `mtx` argument to this function, x_1 can be paired with a total of $p-1$ columns (x_2, x_3, \dots, x_p). Note we never flip any of the control variables with x_1 . This function produces $i=1,2,\dots,p-1$ numbers representing the summary sign, or 'sum' from the signs `sg1` to `sg3` associated with the three criteria: `Cr1`, `Cr2` and `Cr3`. Note that `sg1` and `sg2` themselves are weighted signs using weighted sum of signs from four orders of stochastic dominance. In general, a positive sign in the i -th location of the 'sum' output of this function means that x_1 is the kernel cause while the variable in $(i+1)$ -th column of `mtx` is the 'effect' or 'response' or 'endogenous.' The magnitude represents the strength (unanimity) of the evidence for a particular sign. Conversely a negative sign in the i -th location of the 'sum' output of this function means that that the first variable listed as the input to this function is the 'effect,' while the variable in $(i+1)$ -th column of `mtx` is the exogenous kernel cause. This function is a summary of `someCPairs` allowing for control variables.

Note

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers. The command `attach(EuroCrime); silentPairs(cbind(crim,off))` returns only one number: 3.175, implying the highest unanimity strength index, with the positive sign suggesting 'crim' in the first column kernel causes 'off' in the second column of the argument `mtx` to this function.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

H. D. Vinod 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See [bootPairs](#), [silentMtx](#)

See [someCPairs](#), [some0Pairs](#)

See [silentPairs](#) for newer version using more direct Hausman-Wu exogeneity test statistic.

Examples

```
## Not run:
options(np.messages=FALSE)
colnames(mtcars[2:ncol(mtcars)])
silentPairs0(mtcars[,1:3],ctrl=mtcars[,4:5]) # mpg paired with others

## End(Not run)

options(np.messages=FALSE)
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
silentPairs0(mtx=cbind(x2,y2), ctrl=cbind(z,w2))
```

 siPairsBlk

Block Version of silentPairs for causality scores with control variables

Description

Allowing input matrix of control variables and missing data, this function produces a 3 column matrix summarizing the results where the estimated signs of stochastic dominance order values (+1, 0, -1) are weighted by $w_t=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2 and added to the Cr3 estimate as: (+1, 0, -1), always in the range [-3.175, 3.175].

Usage

```

siPairsBlk(
  mtx,
  ctrl = 0,
  dig = 6,
  blksiz = 10,
  wt = c(1.2, 1.1, 1.05, 1),
  sumwt = 4
)

```

Arguments

mtx	The data matrix with p columns. Denote x1 as the first column which is fixed and then paired with all other columns, say: x2, x3, ..., xp, one by one for the purpose of flipping with x1. p must be 2 or more
ctrl	data matrix for designated control variable(s) outside causal paths default ctrl=0 which means that there are no control variables used.
dig	Number of digits for reporting (default dig=6).
blksiz	block size, default=10, if chosen blksiz >n, where n=rows in matrix then blk-siz=n. That is, no blocking is done
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The reason for slightly declining weights on the signs from SD1 to SD4 is simply that the local mean comparisons implicit in SD1 are known to be more reliable than local variance implicit in SD2, local skewness implicit in SD3 and local kurtosis implicit in SD4. The source of slightly declining sampling unreliability of higher moments is the higher power of the deviations from the mean needed in their computations. The summary results for all three criteria are reported in a vector of numbers internally called `crall`:

Value

With p columns in `mtx` argument to this function, x1 can be paired with a total of p-1 columns (x2, x3, ..., xp). Note we never flip any of the control variables with x1. This function produces i=1,2,...,p-1 numbers representing the summary sign, or 'sum' from the signs sg1 to sg3 associated with the three criteria: Cr1, Cr2 and Cr3. Note that sg1 and sg2 themselves are weighted signs using weighted sum of signs from four orders of stochastic dominance. In general, a positive sign in the i-th location of the 'sum' output of this function means that x1 is the kernel cause while the variable in (i+1)-th column of `mtx` is the 'effect' or 'response' or 'endogenous.' The magnitude represents the strength (unanimity) of the evidence for a particular sign. Conversely a negative sign in the i-th location of the 'sum' output of this function means that that the first variable listed as the input to this function is the 'effect,' while the variable in (i+1)-th column of `mtx` is the exogenous kernel cause.

Note

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers. The command `attach(EuroCrime); silentPairs(cbind(crim,off))` returns only one number: 3.175, implying the highest unanimity strength index, with the positive sign suggesting 'crim' in the first column kernel causes 'off' in the second column of the argument `mtx` to this function.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

H. D. Vinod 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

Vinod, H. D. Causal Paths and Exogeneity Tests in Generalcorr Package for Air Pollution and Monetary Policy (June 6, 2017). Available at SSRN: <https://www.ssrn.com/abstract=2982128>

See Also

See [bootPairs](#), [silentMtx](#)

See [someCPairs](#), [some0Pairs](#)

Examples

```
## Not run:
options(np.messages=FALSE)
colnames(mtcars[2:ncol(mtcars)])
siPairsBlk(mtcars[,1:3],ctrl=mtcars[,4:5]) # mpg paired with others

## End(Not run)

options(np.messages=FALSE)
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
siPairsBlk(mtx=cbind(x2,y2), ctrl=cbind(z,w2))
```

some0Pairs	<i>Function reporting detailed kernel causality results in a 7-column matrix (uses deprecated criterion 1, no longer recommended but may be useful for second and third criterion typ=2,3)</i>
------------	--

Description

The seven columns produced by this function summarize the results where the signs of stochastic dominance order values (+1 or -1) are weighted by $wt=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2. The weighting is obviously not needed for the third criterion Cr3.

Usage

```
some0Pairs(
  mtx,
  dig = 6,
  verbo = TRUE,
  rnam = FALSE,
  wt = c(1.2, 1.1, 1.05, 1),
  sumwt = 4
)
```

Arguments

mtx	The data matrix in the first column is paired with all others.
dig	Number of digits for reporting (default dig=6).
verbo	Make verbo= TRUE for printing detailed steps.
rnam	Make rnam= TRUE if cleverly created row-names are desired.
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The reason for slightly declining weights on the signs from SD1 to SD4 is simply that the local mean comparisons implicit in SD1 are known to be more reliable than local variance implicit in SD2, local skewness implicit in SD3 and local kurtosis implicit in SD4. The source of slightly declining sampling unreliability of higher moments is the higher power of the deviations from the mean needed in their computations. The summary results for all three criteria are reported in one matrix called outVote:

typ=1 reports ('Y', 'X', 'Cause', 'SD1apd', 'SD2apd', 'SD3apd', 'SD4apd') naming variables identifying 'cause' and measures of stochastic dominance using absolute values of kernel regression gradients (or amorphous partial derivatives, apd-s) being minimized by the kernel regression algorithm while comparing the kernel regression of X on Y with that of Y on X.

typ=2 reports ('Y', 'X', 'Cause', 'SD1res', 'SD2res', 'SD3res', 'SD4res') and measures of stochastic dominance using absolute values of kernel regression residuals comparing regression of X on Y with that of Y on X.

typ=3 reports ('Y', 'X', 'Cause', 'r*xly', 'r*y|x', 'r', 'p-val') containing generalized correlation coefficients r*, 'r' refers to. Pearson correlation coefficient p-val is the p-value for testing the significance of 'r'

Value

Prints three matrices detailing results for Cr1, Cr2 and Cr3. It also returns a grand summary matrix called 'outVote' which summarizes all three criteria. In general, a positive sign for weighted sum reported in the column 'sum' means that the first variable listed as the input to this function is the 'kernel cause.' For example, crime 'kernel causes' police officer deployment (not vice versa) is indicated by the positive sign of 'sum' (=3.175) reported for that example included in this package.

Note

The output matrix last column for 'mtcars' example has the sum of the scores by the three criteria combined. If 'sum' is positive, then variable X (mpg) is more likely to have been engineered to kernel cause the response variable Y, rather than vice versa.

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

See Also [somePairs](#)

Examples

```
## Not run:
some0Pairs(mtcars) # first variable is mpg and effect on mpg is of interest

## End(Not run)

## Not run:
data(EuroCrime)
attach(EuroCrime)
some0Pairs(cbind(crim,off))
```

```
## End(Not run)
```

someCPairs	<i>Kernel causality computations admitting control variables reporting a 7-column matrix (has older Cr1)</i>
------------	--

Description

Allowing input matrix of control variables, produce 7 column matrix summarizing the results where the signs of stochastic dominance order values (+1 or -1) are weighted by $wt=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2. The weighting is obviously not needed for the third criterion Cr3.

Usage

```
someCPairs(
  mtx,
  ctrl,
  dig = 6,
  verbo = TRUE,
  rnam = FALSE,
  wt = c(1.2, 1.1, 1.05, 1),
  sumwt = 4
)
```

Arguments

mtx	The data matrix with many columns where the first column is fixed and then paired with all other columns, one by one.
ctrl	data matrix for designated control variable(s) outside causal paths
dig	Number of digits for reporting (default dig=6).
verbo	Make verbo= TRUE for printing detailed steps.
rnam	Make rnam= TRUE if cleverly created rownames are desired.
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The reason for slightly declining weights on the signs from SD1 to SD4 is simply that the local mean comparisons implicit in SD1 are known to be more reliable than local variance implicit in SD2, local skewness implicit in SD3 and local kurtosis implicit in SD4. The source of slightly declining sampling unreliability of higher moments is the higher power of the deviations from the

mean needed in their computations. The summary results for all three criteria are reported in one matrix called `outVote`:

`typ=1` reports ('Y', 'X', 'Cause', 'SD1apdC', 'SD2apdC', 'SD3apdC', 'SD4apdC') naming variables identifying 'cause' and measures of stochastic dominance using absolute values of kernel regression gradients (or amorphous partial derivatives, apd-s) being minimized by the kernel regression algorithm while comparing the kernel regression of X on Y with that of Y on X. The letter C in the titles reminds presence of control variable(s).

`typ=2` reports ('Y', 'X', 'Cause', 'SD1resC', 'SD2resC', 'SD3resC', 'SD4resC') and measures of stochastic dominance using absolute values of kernel regression residuals comparing regression of X on Y with that of Y on X.

`typ=3` reports ('Y', 'X', 'Cause', 'r*xlyC', 'r*ylyxC', 'r', 'p-val') containing generalized correlation coefficients r^* , 'r' refers to. Pearson correlation coefficient p-val is the p-value for testing the significance of 'r'. The letter C in the titles reminds the presence of control variable(s).

Value

Prints three matrices detailing results for Cr1, Cr2 and Cr3. It also returns a grand summary matrix called 'outVote' which summarizes all three criteria. In general, a positive sign for weighted sum reported in the column 'sum' means that the first variable listed as the input to this function is the 'kernel cause.' This function is an extension of `some0Pairs` to allow for control variables. For example, crime 'kernel causes' police officer deployment (not vice versa) is indicated by the positive sign of 'sum' (=3.175) reported for that example included in this package.

Note

The output matrix last column for 'mtcars' example has the sum of the scores by the three criteria combined. If 'sum' is positive, then variable X (mpg) is more likely to have been engineered to kernel cause the response variable Y, rather than vice versa.

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in *Communications in Statistics -Simulation and Computation*, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

See Also [somePairs](#), [some0Pairs](#)

Examples

```
## Not run:
someCPairs(mtcars[,1:3],ctrl=mtcars[4:5]) # first variable is mpg and effect on mpg is of interest

## End(Not run)

## Not run:
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
someCPairs(cbind(x2,y2), cbind(z,w2)) #yields x2 as correct cause

## End(Not run)
```

someCPairs2

Kernel causality computations admitting control variables reporting a 7-column matrix, version 2.

Description

Second version of someCPairs also allows input matrix of control variables, produce 7 column matrix summarizing the results where the signs of stochastic dominance order values (+1 or -1) are weighted by $wt=c(1.2, 1.1, 1.05, 1)$ to compute an overall result for all orders of stochastic dominance by a weighted sum for the criteria Cr1 and Cr2. The weighting is obviously not needed for the third criterion Cr3.

Usage

```
someCPairs2(
  mtx,
  ctrl,
  dig = 6,
  verbo = TRUE,
  rnam = FALSE,
  wt = c(1.2, 1.1, 1.05, 1),
  sumwt = 4
)
```


Arguments

mtx	The data matrix with many columns where the first column is fixed and then paired with all other columns, one by one.
ctrl	data matrix for designated control variable(s) outside causal paths
dig	Number of digits for reporting (default dig=6).
verbo	Make verbo= TRUE for printing detailed steps.
rnam	Make rnam= TRUE if cleverly created rownames are desired.
wt	Allows user to choose a vector of four alternative weights for SD1 to SD4.
sumwt	Sum of weights can be changed here =4(default).

Details

The reason for slightly declining weights on the signs from SD1 to SD4 is simply that the local mean comparisons implicit in SD1 are known to be more reliable than local variance implicit in SD2, local skewness implicit in SD3 and local kurtosis implicit in SD4. The source of slightly declining sampling unreliability of higher moments is the higher power of the deviations from the mean needed in their computations. The summary results for all three criteria are reported in one matrix called outVote:

(typ=1) reports ('Y', 'X', 'Cause', 'SD1.rhserr', 'SD2.rhserr', 'SD3.rhserr', 'SD4.rhserr') naming variables identifying the 'cause' and measures of stochastic dominance using absolute values of kernel regression $\text{abs}(\text{RHS first regressor} * \text{residual})$ values comparing flipped regressions X on Y versus Y on X. The letter C in the titles reminds presence of control variable(s).

typ=2 reports ('Y', 'X', 'Cause', 'SD1resC', 'SD2resC', 'SD3resC', 'SD4resC') and measures of stochastic dominance using absolute values of kernel regression residuals comparing regression of X on Y with that of Y on X.

typ=3 reports ('Y', 'X', 'Cause', 'r*x|yC', 'r*y|xC', 'r', 'p-val') containing generalized correlation coefficients r^* , 'r' refers to. Pearson correlation coefficient p-val is the p-value for testing the significance of 'r'. The letter C in the titles reminds the presence of control variable(s).

Value

Prints three matrices detailing results for Cr1, Cr2 and Cr3. It also returns a grand summary matrix called 'outVote' which summarizes all three criteria. In general, a positive sign for weighted sum reported in the column 'sum' means that the first variable listed as the input to this function is the 'kernel cause.' This function is an extension of some@Pairs to allow for control variables. For example, crime 'kernel causes' police officer deployment (not vice versa) is indicated by the positive sign of 'sum' (=3.175) reported for that example included in this package.

Note

The output matrix last column for 'mtcars' example has the sum of the scores by the three criteria combined. If 'sum' is positive, then variable X (mpg) is more likely to have been engineered to kernel cause the response variable Y, rather than vice versa.

The European Crime data has all three criteria correctly suggesting that high crime rate kernel causes the deployment of a large number of police officers.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

See Also [somePairs](#), [some0Pairs](#)

Examples

```
## Not run:
someCPairs2(mtcars[,1:3],ctrl=mtcars[4:5]) # first variable is mpg and effect on mpg is of interest

## End(Not run)

## Not run:
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is somewhat indep and affected by z
y=1+2*x+3*z+rnorm(10)
w=runif(10)
x2=x;x2[4]=NA;y2=y;y2[8]=NA;w2=w;w2[4]=NA
someCPairs2(cbind(x2,y2), cbind(z,w2)) #yields x2 as correct cause

## End(Not run)
```

someMagPairs

Summary magnitudes after removing control variables in several pairs where dependent variable is fixed.

Description

This builds on the function `mag_ctrl`, where the input matrix `mtx` has `p` columns. The first column is present in each of the $(p-1)$ pairs. Its output is a matrix with four columns containing the names of variables and approximate overall estimates of the magnitudes of partial derivatives (dy/dx) and (dx/dy) for a distinct (x,y) pair in a row. The estimated overall derivatives are not always well-defined, because the real partial derivatives of nonlinear functions are generally distinct for each observation point.

Usage

```
someMagPairs(mtx, ctrl, dig = 6, verbo = TRUE)
```

Arguments

mtx	The data matrix with many columns where the first column is fixed and then paired with all other columns, one by one.
ctrl	data matrix for designated control variable(s) outside causal paths. A constant vector is not allowed as a control variable.
dig	Number of digits for reporting (default dig=6).
verbo	Make verbo= TRUE for printing detailed steps.

Details

The function `mag_ctrl` has kernel regressions: $x \sim y + \text{ctrl}$ and $x \sim \text{ctrl}$ to evaluate the ‘incremental change’ in R-squares. Let $(r_{xy}; \text{ctrl})$ denote the square root of that ‘incremental change’ after its sign is made the same as that of the Pearson correlation coefficient from `cor(x, y)`. One can interpret $(r_{xy}; \text{ctrl})$ as a generalized partial correlation coefficient when x is regressed on y after removing the effect of control variable(s) in `ctrl`. It is more general than the usual partial correlation coefficient, since this one allows for nonlinear relations among variables. Next, the function computes ‘`dxdy`’ obtained by multiplying $(r_{xy}; \text{ctrl})$ by the ratio of standard deviations, $\text{sd}(x)/\text{sd}(y)$. Now our ‘`dxdy`’ approximates the magnitude of the partial derivative (dx/dy) in a causal model where y is the cause and x is the effect. The function also reports entirely analogous ‘`dydx`’ obtained by interchanging x and y .

`someMegPairs` function runs the function `mag_ctrl` on several column pairs in a matrix input `mtx` where the first column is held fixed and all others are changed one by one, reporting two partial derivatives for each row.

Value

Table containing names of X_i and X_j and two magnitudes: $(dX_{id}X_j, dX_{jd}X_i)$. $dX_{id}X_j$ is the magnitude of the effect on X_i when X_i is regressed on X_j (i.e., when X_j is the cause). The analogous $dX_{jd}X_i$ is the magnitude when X_j is regressed on X_i .

Note

This function is intended for use only after the causal path direction is already determined by various functions in this package (e.g. `someCPairs`). That is, after the researcher knows whether X_i causes X_j or vice versa. The output of this function is a matrix of 4 columns, where first columns list the names of X_i and X_j and the next two numbers in each row are $dX_{id}X_j$, $dX_{jd}X_i$, respectively, representing the magnitude of effect of one variable on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C. R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

See Also

See [mag_ctrl](#), [someCPairs](#)

Examples

```
set.seed(34);x=sample(1:10);y=1+2*x+rnorm(10);z=sample(2:11)
w=runif(10)
ss=someMagPairs(cbind(y,x,z),ctrl=w)
```

somePairs	<i>Function reporting kernel causality results as a 7-column matrix.(deprecated)</i>
-----------	--

Description

This function lets the user choose one of three criteria to determine causal direction by setting `typ` as 1, 2 or 3. This function reports results for only one criterion at a time unlike the function `some0Pairs` which summarizes the resulting causal directions for all criteria with suitable weights. If some variables are 'control' variables, use `someCPairs`, `C=control`.

Usage

```
somePairs(mtx, dig = 6, verbo = FALSE, typ = 1, rnam = FALSE)
```

Arguments

<code>mtx</code>	The data matrix in the first column is paired with all others.
<code>dig</code>	Number of digits for reporting (default <code>dig=6</code>).
<code>verbo</code>	Make <code>verbo= TRUE</code> for printing detailed steps.
<code>typ</code>	Must be 1 (default), 2 or 3 for the three criteria.
<code>rnam</code>	Make <code>rnam= TRUE</code> if cleverly created rownames are desired.

Details

(typ=1) reports ('Y', 'X', 'Cause', 'SD1apd', 'SD2apd', 'SD3apd', 'SD4apd') naming variables identifying 'cause' and measures of stochastic dominance using absolute values of kernel regression gradients comparing regression of X on Y with that of Y on X.

(typ=2) reports ('Y', 'X', 'Cause', 'SD1res', 'SD2res', 'SD3res', 'SD4res') and measures of stochastic dominance using absolute values of kernel regression residuals comparing regression of X on Y with that of Y on X.

(typ=3) reports ('Y', 'X', 'Cause', 'r*X|Y', 'r*Y|X', 'r', 'p-val') containing generalized correlation coefficients r*, 'r' refers to the Pearson correlation coefficient and p-val column has the p-values for testing the significance of Pearson's 'r'.

Value

A matrix containing causal identification results for one criterion. The first column of the input `mtx` having `p` columns is paired with `(p-1)` other columns. The output matrix headings are self-explanatory and distinct for each criterion `Cr1` to `Cr3`.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

H. D. Vinod 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

The related function `some0Pairs` may be more useful, since it reports on all three criteria (by choosing `typ=1,2,3`) and further summarizes their results by weighting to help choose causal paths.

Examples

```
## Not run:
data(mtcars)
somePairs(mtcars)

## End(Not run)
```

somePairs2	<i>Function reporting kernel causality results as a 7-column matrix, version 2.</i>
------------	---

Description

This function is an alternative implementation of `somePairs` which also lets the user choose one of three criteria to determine causal direction by setting `typ` as 1, 2 or 3. This function reports results for only one criterion at a time unlike the function `somePairs` which summarizes the resulting causal directions for all criteria with suitable weights. If some variables are ‘control’ variables, use `someCPairs`, where notation C=control.

Usage

```
somePairs2(mtx, dig = 6, verbo = FALSE, typ = 1, rnam = FALSE)
```

Arguments

<code>mtx</code>	The data matrix in the first column is paired with all others.
<code>dig</code>	Number of digits for reporting (default <code>dig=6</code>).
<code>verbo</code>	Make <code>verbo= TRUE</code> for printing detailed steps.
<code>typ</code>	Must be 1 (default), 2 or 3 for the three criteria.
<code>rnam</code>	Make <code>rnam= TRUE</code> if cleverly created rownames are desired.

Details

(`typ=1`) reports (‘Y’, ‘X’, ‘Cause’, ‘SD1.rhserr’, ‘SD2.rhserr’, ‘SD3.rhserr’, ‘SD4.rhserr’) naming variables identifying the ‘cause,’ using Hausman-Wu criterion. It measures of stochastic dominance using absolute values of kernel regression $\text{abs}(\text{RHS first regressor} \times \text{residual})$, comparing flipped regressions X on Y versus Y on X.

(`typ=2`) reports (‘Y’, ‘X’, ‘Cause’, ‘SD1res’, ‘SD2res’, ‘SD3res’, ‘SD4res’) and measures of stochastic dominance using absolute values of kernel regression residuals comparing regression of X on Y with that of Y on X.

(`typ=3`) reports (‘Y’, ‘X’, ‘Cause’, ‘r*XIY’, ‘r*YIX’, ‘r’, ‘p-val’) containing generalized correlation coefficients `r*`, ‘r’ refers to the Pearson correlation coefficient and `p-val` column has the p-values for testing the significance of Pearson’s ‘r’.

Value

A matrix containing causal identification results for one criterion. The first column of the input `mtx` having `p` columns is paired with (`p-1`) other columns The output matrix headings are self-explanatory and distinct for each criterion `Cr1` to `Cr3`.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

H. D. Vinod 'Generalized Correlation and Kernel Causality with Applications in Development Economics' in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

See Also

The related function `some0Pairs` may be more useful, since it reports on all three criteria (by choosing `typ=1,2,3`) and further summarizes their results by weighting to help choose causal paths.

Alternative and revised function `somePairs2` implements the Cr1 (first criterion) with a direct estimate of the Hausman-Wu statistic for testing exogeneity.

Examples

```
## Not run:
data(mtcars)
somePairs2(mtcars)

## End(Not run)
```

sort.abse0

internal sort.abse0

Description

intended for internal use only

Usage

```
sort.abse0
```

sort.e0

internal sort.e0

Description

intended for internal use only

Usage

```
sort.e0
```

sort_matrix	<i>Sort all columns of matrix x with respect to the j-th column.</i>
-------------	--

Description

This function can use the sort.list function in R. The reason for using it is that one wants the sort to carry along all columns.

Usage

```
sort_matrix(x, j)
```

Arguments

x	An input matrix with several columns
j	The column number with reference to which one wants to sort

Value

A sorted matrix

Examples

```
set.seed(30)
x=matrix(sample(1:50),ncol=5)
y=sort_matrix(x,3);y
```

stdres	<i>Residuals of kernel regressions of x on y when both x and y are standardized.</i>
--------	--

Description

1) Standardize the data to force mean zero and variance unity, 2) kernel regress x on y, with the option 'residuals = TRUE' and finally 3) compute the residuals.

Usage

```
stdres(x, y)
```

Arguments

x	vector of data on the dependent variable
y	data on the regressors which can be a matrix

Details

The first argument is assumed to be the dependent variable. If `stdres(x,y)` is used, you are regressing x on y (not the usual y on x). The regressors can be a matrix with 2 or more columns. The missing values are suitably ignored by the standardization.

Value

kernel regression residuals are returned after standardizing the data on both sides so that the magnitudes of residuals are comparable between regression of x on y on the one hand and regression of y on x on the other.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D. ‘Generalized Correlation and Kernel Causality with Applications in Development Economics’ in Communications in Statistics -Simulation and Computation, 2015, doi: [10.1080/03610918.2015.1122048](https://doi.org/10.1080/03610918.2015.1122048)

Examples

```
## Not run:  
set.seed(330)  
x=sample(20:50)  
y=sample(20:50)  
stdres(x,y)  
  
## End(Not run)
```

`stdz_xy`*Standardize x and y vectors to achieve zero mean and unit variance.*

Description

Standardize x and y vectors to achieve zero mean and unit variance.

Usage

```
stdz_xy(x, y)
```

Arguments

<code>x</code>	Vector of data which can have NA's
<code>y</code>	Vector of data which can have NA's

Value

stdx	standardized values of x
stdy	standardized values of y

Note

This works even if there are missing x or y values.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

Examples

```
## Not run:
set.seed(30)
x=sample(20:30)
y=sample(21:31)
stdz_xy(x,y)
## End(Not run)
```

stochdom2

Compute vectors measuring stochastic dominance of four orders.

Description

Stochastic dominance originated as a sophisticated comparison of two distributions of stock market returns. The dominating distribution is superior in terms of local mean, variance, skewness and kurtosis respectively, representing dominance orders 1 to 4, without simply computing the four moment summary measures for the entire data. Vinod (2008, sec. 4.3) explains the details. This function uses the output of 'wtdpab'.

Usage

```
stochdom2(dj, wpa, wpb)
```

Arguments

dj	Vector of (unequal) distances of consecutive intervals defined on common support of two probability distributions being compared
wpa	Vector of the first set of (weighted) probabilities
wpb	Vector of the second set of (weighted) probabilities

Value

sd1b	Vector measuring stochastic dominance of order 1, SD1
sd2b	Vector measuring stochastic dominance of order 2, SD2
sd3b	Vector measuring stochastic dominance of order 3, SD3
sd4b	Vector measuring stochastic dominance of order 4, SD4

Note

The input to this function is the output of the function wtdpapb.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D., 'Hands-On Intermediate Econometrics Using R' (2008) World Scientific Publishers: Hackensack, NJ. <https://www.worldscientific.com/worldscibooks/10.1142/6895>

Vinod, H. D. 'Ranking Mutual Funds Using Unconventional Utility Theory and Stochastic Dominance,' Journal of Empirical Finance Vol. 11(3) 2004, pp. 353-377.

See Also

See Also [wtdpapb](#)

Examples

```
## Not run:
set.seed(234);x=sample(1:30);y=sample(5:34)
w1=wtdpapb(x,y) #y should dominate x with mostly positive SDs
stochdom2(w1$dj, w1$wpa, w1$wpb)
## End(Not run)
```

sudoCoefParcor

Pseudo regression coefficients from generalized partial correlation coefficients, (GPCC).

Description

This function gets GPCCs by calling parcorVec function. Pseudo regression coefficient of a kernel regression is obtained by $GPCC * (sd \text{ dep.var}) / (sd \text{ regressor})$, that is multiplying the GPCC by the standard deviation (sd) of the dependent variable and dividing by the sd of the regressor.

Usage

```
sudoCoefParcor(mtx, ctrl = 0, verbo = FALSE, idep = 1)
```

Arguments

mtx	Input data matrix with p (> or = 3) columns,
ctrl	Input vector or matrix of data for control variable(s), default is ctrl=0 when control variables are absent
verbo	Make this TRUE for detailed printing of computational steps
idep	The column number of the dependent variable (=1, default)

Value

A p by 1 'out' vector pseudo partial derivatives

Note

Generalized Partial Correlation Coefficients (GPCC) allow comparison of the relative contribution of each X_j to the explanation of X_i , because GPCC are scale-free pseudo regr coeff are $GPCC * (sd \text{ dep. var}) / (sd \text{ regressor})$

We want to get all partial correlation coefficient pairs removing other column effects. Vinod (2018) shows why one needs more than one criterion to decide the causal paths or exogeneity.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlations and Instantaneous Causality for Data Pairs Benchmark,' (March 8, 2015) <https://www.ssrn.com/abstract=2574891>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

Vinod, H. D. 'New Exogeneity Tests and Causal Paths,' (June 30, 2018). Available at SSRN: <https://www.ssrn.com/abstract=3206096>

Vinod, H. D. (2021) 'Generalized, Partial and Canonical Correlation Coefficients' Computational Economics, 59(1), 1–28.

See Also

See Also [parcor_ijk](#).

See Also a hybrid version [parcorVech](#).

Examples

```

set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is partly indep and partly affected by z
y=1+2*x+3*z+rnorm(10)# y depends on x and z not vice versa
mtx=cbind(x,y,z)
sudoCoefParcor(mtx, idep=2)

## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('V1', 'v2', 'V3')#some names needed
sudoCoefParcor(x)

## End(Not run)

```

sudoCoefParcorH	<i>Pseudo regression coefficients from hybrid generalized partial correlation coefficients (HGPPCC).</i>
-----------------	--

Description

This function gets HGPPCCs by calling parcorVecH function. Pseudo regression coefficient of a kernel regression is obtained by $HGPPCC * (sd \text{ dep.var}) / (sd \text{ regressor})$, that is multiplying the HGPPCC by the standard deviation (sd) of the dependent variable and dividing by the sd of the regressor.

Usage

```
sudoCoefParcorH(mtx, ctrl = 0, verbo = FALSE, idep = 1)
```

Arguments

mtx	Input data matrix with p (> or = 3) columns,
ctrl	Input vector or matrix of data for control variable(s), default is ctrl=0 when control variables are absent
verbo	Make this TRUE for detailed printing of computational steps
idep	The column number of the dependent variable (=1, default)

Value

A p by 1 'out' vector pseudo partial derivatives

Note

Hybrid Generalized Partial Correlation Coefficients (HGPPCC) allow comparison of the relative contribution of each X_j to the explanation of X_i , because GPCC are scale-free. Hybrid refers to use of OLS residuals. Now pseudo hybrid regr coeff are $HGPPCC*(sd\ dep.var)/(sd\ regressor)$

We want to get all partial correlation coefficient pairs removing other column effects. Vinod (2018) shows why one needs more than one criterion to decide the causal paths or exogeneity.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

References

Vinod, H. D. 'Generalized Correlations and Instantaneous Causality for Data Pairs Benchmark,' (March 8, 2015) <https://www.ssrn.com/abstract=2574891>

Vinod, H. D. 'Matrix Algebra Topics in Statistics and Economics Using R', Chapter 4 in Handbook of Statistics: Computational Statistics with R, Vol.32, co-editors: M. B. Rao and C.R. Rao. New York: North Holland, Elsevier Science Publishers, 2014, pp. 143-176.

Vinod, H. D. 'New Exogeneity Tests and Causal Paths,' (June 30, 2018). Available at SSRN: <https://www.ssrn.com/abstract=3206096>

Vinod, H. D. (2021) 'Generalized, Partial and Canonical Correlation Coefficients' Computational Economics, 59(1), 1–28.

See Also

See Also [parcor_ijk](#).

See Also a hybrid version [parcorVech](#).

Examples

```
set.seed(234)
z=runif(10,2,11)# z is independently created
x=sample(1:10)+z/10 #x is partly indep and partly affected by z
y=1+2*x+3*z+rnorm(10)# y depends on x and z not vice versa
mtx=cbind(x,y,z)
sudoCoefParcor(mtx, idep=2)
```

```
## Not run:
set.seed(34);x=matrix(sample(1:600)[1:99],ncol=3)
colnames(x)=c('V1', 'v2', 'V3')#some names needed
sudoCoefParcorH(x)
```

```
## End(Not run)
```

summaryRank	<i>Compute ranks of rows of matrix and summarize them into a choice suggestion.</i>
-------------	---

Description

This function allows getting out the choice (of column stock) from four rows of numbers quantifying the four orders of exact stochastic dominance comparisons. If the choice row has 1 then that column is to be chosen with the largest (portfolio) weight. If the original matrix row names exist, same are repeated for the extra rows representing the ranks. The row name for sum of ranks is sumRanks and the ranking of the sumRanks providing the choice is named choice along the bottom row of the output matrix called "out."

Usage

```
summaryRank(mtx)
```

Arguments

mtx	matrix to be ranked by row and summarized
-----	---

Value

a matrix appending 4 more rows of ranks and a couple of rows summarizing ranks and also choice priority number for each stock (asset)

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

symmze	<i>Replace asymmetric matrix by max of abs values of [ij] or [ji] elements useful in symmetrizing gmcmtx0 general correlation matrix</i>
--------	--

Description

Replace asymmetric matrix by max of abs values of [ij] or [ji] elements useful in symmetrizing gmcmtx0 general correlation matrix

Usage

```
symmze(mtx)
```

Arguments

mtx	non-symmetric matrix
-----	----------------------

Value

mtx2 replace [i,j] and [j,i] by the max of absolute values with common sign

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY.

Examples

```
## Not run:
example
mtx=matrix(1:16,nrow=4)
symmze(mtx)

## End(Not run)##'
```

wtdpapb

Creates input for the stochastic dominance function stochdom2

Description

Stochastic dominance is a sophisticated comparison of two distributions of stock market returns. The dominating distribution is superior in terms of mean, variance, skewness and kurtosis respectively, representing dominance orders 1 to 4, without directly computing four moments. Vinod(2008) sec. 4.3 explains the details. The 'wtdpapb' function creates the input for stochdom2 which in turn computes the stochastic dominance. See Vinod (2004) for details about quantitative stochastic dominance.

Usage

```
wtdpapb(xa, xb)
```

Arguments

xa Vector of (excess) returns for the first investment option A or values of any random variable being compared to another.

xb Vector of returns for the second option B

Value

wpa Weighted vector of probabilities for option A

wpb Weighted vector of probabilities for option B

dj Vector of interval widths (distances) when both sets of data are forced on a common support

Note

Function is needed before using stochastic dominance

In Vinod (2008) where the purpose of wtdpab is to map from standard ‘expected utility theory’ weights to more sophisticated ‘non-expected utility theory’ weights using Prelec’s (1998, *Econometrica*, p. 497) method. These weights are not needed here. Hence we provide the function `prelec2` which does not use Prelec weights at all, thereby simplifying and speeding up the R code provided in Vinod (2008). This function avoids sophisticated ‘non-expected’ utility theory which incorporates commonly observed human behavior favoring loss aversion and other anomalies inconsistent with precepts of the expected utility theory. Such weighting is not needed for our application.

Author(s)

Prof. H. D. Vinod, Economics Dept., Fordham University, NY

References

Vinod, H. D., ‘Hands-On Intermediate Econometrics Using R’ (2008) World Scientific Publishers: Hackensack, NJ. <https://www.worldscientific.com/worldscibooks/10.1142/6895>

Vinod, H. D. ‘Ranking Mutual Funds Using Unconventional Utility Theory and Stochastic Dominance,’ *Journal of Empirical Finance* Vol. 11(3) 2004, pp. 353-377.

See Also

See Also [stochdom2](#)

Examples

```
## Not run:  
set.seed(234);x=sample(1:30);y=sample(5:34)  
wtdpab(x,y)  
## End(Not run)
```

Index

- * **3D plot**
 - pillar3D, 105
- * **Hausman-Wu exogeneity criteria**
 - silentPairs, 117
 - siPairsBlk, 121
- * **Hausman-Wu statistic**
 - abs_stdhrserr, 15
- * **Prelec weights**
 - prelec2, 106
- * **R* asymmetric correlations**
 - gmcmtxZ, 66
 - gmcxy_np, 67
- * **R* asymmetric matrix of generalized correlation coefficients**
 - gmcmtx0, 63
 - gmcmtxBlk, 64
- * **absolute residual values**
 - allPairs, 16
- * **amorphous partial derivative apd**
 - allPairs, 16
- * **amorphous partial derivatives**
 - mag, 76
- * **apd amorphous partial derivatives**
 - mag_ctrl, 77
- * **apd amorphous partial derivative**
 - kern, 70
 - kern2, 71
 - kern2ctrl, 73
 - kern_ctrl, 74
- * **apd**
 - abs_stdapd, 9
 - abs_stdapdC, 10
- * **asymmetric p-values**
 - depMeas, 48
 - rstar, 111
- * **blocking observations**
 - gmcmtxBlk, 64
- * **bootstrap confidence intervals**
 - bootQuantile, 26
- * **bootstrap**
 - bootSign, 27
 - bootSignPcent, 29
 - bootSummary, 30
 - pcause, 104
 - probSign, 107
- * **causal criteria**
 - silentMtx, 113
 - silentMtx0, 115
 - silentPairs0, 119
 - some0Pairs, 124
 - someCPairs, 126
 - someCPairs2, 128
 - somePairs, 132
 - somePairs2, 134
- * **causal path**
 - causeAllPair, 33
 - causeSummary, 35
 - causeSummary0, 37
 - causeSummBlk, 40
 - causeSumNoP, 42
- * **cofactor of a matrix**
 - cofactor, 44
- * **da2Lagtasets**
 - da2Lag, 47
- * **datasets**
 - badCol, 17
 - diff.e0, 51
 - ibad, 69
 - ii, 69
 - j, 70
- * **financial portfolio choice**
 - comp_portfo2, 45
- * **fourth order stochastic dominance**
 - bigfp, 18
 - silentMtx, 113
- * **generalized correlations**
 - silentMtx, 113
 - silentMtx0, 115

- silentPairs, 117
- silentPairs0, 119
- siPairsBlk, 121
- some0Pairs, 124
- someCPairs2, 128
- somePairs, 132
- somePairs2, 134
- * **kernel regression gradients**
 - abs_stdapd, 9
 - abs_stdapdC, 10
 - kern, 70
 - kern2, 71
 - kern2ctrl, 73
 - kern_ctrl, 74
- * **kernel regression residuals**
 - abs_res, 8
 - abs_stdres, 11
 - abs_stdresC, 12
 - abs_stdrhserC, 14
 - absBstdres, 5
 - absBstdresC, 6
 - absBstdrhserC, 7
 - kern, 70
 - kern2, 71
 - kern2ctrl, 73
 - kern_ctrl, 74
 - stdres, 136
- * **kernel regression**
 - abs_stdrhser, 15
 - bootQuantile, 26
 - bootSign, 27
 - bootSignPcent, 29
 - bootSummary, 30
 - gmcmtx0, 63
 - gmcmtxBlk, 64
 - gmcmtxZ, 66
 - gmcxy_np, 67
 - probSign, 107
- * **maximum entropy bootstrap**
 - bootGcLC, 20
 - bootGcRsq, 21
 - bootPairs, 23
 - pcause, 104
- * **meboot**
 - bootQuantile, 26
 - bootSign, 27
 - bootSignPcent, 29
 - bootSummary, 30
 - probSign, 107
- * **minor of a matrix**
 - minor, 78
- * **non expected utility function**
 - prelec2, 106
- * **outlier detection**
 - get0outliers, 60
- * **paired t test**
 - heurist, 68
- * **pairwise comparisons**
 - bootQuantile, 26
 - bootSign, 27
 - bootSignPcent, 29
 - bootSummary, 30
 - probSign, 107
- * **partial correlations**
 - parcor_ridg, 102
 - parcorBMany, 89
 - parcorMany, 91
 - parcorMtx, 93
 - parcorSilent, 94
 - parcorVec, 96
 - parcorVecH, 98
 - sudoCoefParcor, 139
 - sudoCoefParcorH, 141
- * **partial derivatives**
 - someMagPairs, 130
- * **ridge biasing factor**
 - parcorSilent, 94
- * **stochastic dominance from local kurtosis**
 - stochdom2, 138
- * **stochastic dominance from local skewness**
 - stochdom2, 138
- * **stochastic dominance orders**
 - causeAllPair, 33
 - causeSummary, 35
 - causeSummBlk, 40
 - causeSumNoP, 42
- * **stochastic dominance**
 - allPairs, 16
 - comp_portfo2, 45
 - silentPairs, 117
 - siPairsBlk, 121
 - someCPairs2, 128
 - wtdpab, 144
- * **summary index**
 - causeAllPair, 33
 - causeSummary, 35

- causeSummary0, [37](#)
- causeSummBlk, [40](#)
- causeSumNoP, [42](#)
- * **wireframe plot**
- pillar3D, [105](#)
- abs_res, [8](#)
- abs_stdapd, [9](#), [11](#)
- abs_stdapdC, [10](#)
- abs_stdres, [7](#), [8](#), [11](#), [13](#), [14](#)
- abs_stdresC, [12](#)
- abs_stdrhserC, [14](#)
- abs_stdrhser, [15](#)
- absBstdres, [5](#)
- absBstdresC, [6](#)
- absBstdrhserC, [7](#)
- allPairs, [16](#)
- badCol, [17](#)
- bigfp, [18](#)
- bootDom12, [19](#)
- bootGcLC, [20](#)
- bootGcRsq, [21](#), [54](#)
- bootPairs, [23](#), [25](#), [34](#), [37](#), [39](#), [41](#), [44](#), [119](#), [121](#), [123](#)
- bootPairs0, [24](#)
- bootQuantile, [26](#), [28](#), [30](#)
- bootSign, [27](#), [30](#)
- bootSignPcent, [28](#), [29](#)
- bootSummary, [30](#)
- canonRho, [31](#)
- causeAllPair, [33](#), [44](#)
- causeSummary, [34](#), [35](#), [41](#), [44](#), [54](#), [55](#)
- causeSummary0, [37](#), [37](#), [44](#)
- causeSummBlk, [34](#), [40](#)
- causeSumNoP, [42](#)
- cofactor, [44](#), [101](#), [102](#)
- comp_portfolio, [45](#)
- da, [46](#)
- da2Lag, [47](#)
- decileVote, [47](#)
- depMeas, [48](#)
- dif4, [49](#)
- dif4mtx, [50](#)
- diff.e0, [51](#)
- dig, [51](#)
- e0, [51](#)
- EuroCrime, [52](#)
- exactSdMtx, [19](#), [52](#)
- GcRsqX12, [22](#), [53](#), [57](#)
- GcRsqX12c, [21](#), [54](#), [58](#)
- GcRsqYX, [54](#), [56](#)
- GcRsqYXc, [55](#), [57](#)
- generalCorrInfo, [59](#)
- get0outliers, [60](#)
- getSeq, [61](#)
- gmc0, [62](#)
- gmc1, [62](#)
- gmcmtx0, [32](#), [49](#), [63](#), [111](#)
- gmcmtxBlk, [49](#), [62](#), [64](#), [64](#), [85](#), [111](#)
- gmcmtxZ, [66](#)
- gmcxy_np, [67](#)
- goodCol, [68](#)
- heurist, [68](#)
- i, [69](#)
- ibad, [69](#)
- ii, [69](#)
- j, [70](#)
- kern, [32](#), [70](#), [74](#), [75](#), [88](#), [91](#), [100](#)
- kern2, [57](#), [71](#)
- kern2ctrl, [57](#), [73](#)
- kern_ctrl, [58](#), [71](#), [72](#), [74](#)
- mag, [76](#), [78](#)
- mag_ctrl, [76](#), [77](#), [132](#)
- min.e0, [78](#)
- minor, [78](#), [101](#), [102](#)
- momentVote, [79](#)
- mtx, [80](#)
- mtx0, [81](#)
- mtx2, [81](#)
- n, [81](#)
- nall, [82](#)
- nam.badCol, [82](#)
- nam.goodCol, [82](#)
- nam.mtx0, [82](#)
- napair, [83](#), [84](#)
- naTriplet, [83](#)
- NLhat, [84](#)
- out1, [85](#)

p1, 85
 Panel2Lag, 86
 PanelLag, 86, 87
 parcor_ijk, 88, 90–92, 94, 95, 97, 99, 99,
 102, 140, 142
 parcor_ijkOLD, 100, 103
 parcor_linear, 100, 101
 parcor_ridge, 102
 parcorBijk, 88
 parcorBMany, 89
 parcorHijk, 90
 parcorMany, 90, 91
 parcorMtx, 93
 parcorSilent, 94
 parcorVec, 96, 99
 parcorVecH, 97, 98, 140, 142
 pcause, 104
 pillar3D, 105
 prelec2, 106
 probSign, 107

 rhs.lag2, 109
 rhs1, 109
 ridgek, 109
 rij, 109
 rijMrji, 110
 rji, 110
 rrij, 110
 rrji, 110
 rstar, 111

 sales2Lag, 112
 salesLag, 112
 seed, 112
 sgn.e0, 113
 silentMtx, 113, 119, 121, 123
 silentMtx0, 115
 silentPairs, 24, 27, 28, 30, 31, 37, 39, 108,
 114, 117, 121
 silentPairs0, 25, 117, 119
 siPairsBlk, 34, 41, 44, 121
 some0Pairs, 114, 117, 119, 121, 123, 124,
 127, 130, 133, 135
 someCPairs, 34, 37, 39, 41, 114, 117, 119,
 121, 123, 126, 132
 someCPairs2, 128
 someMagPairs, 130
 somePairs, 125, 127, 130, 132
 somePairs2, 134, 135

 sort.abse0, 135
 sort.e0, 135
 sort_matrix, 136
 stdres, 136
 stdz_xy, 137
 stochdom2, 46, 138, 145
 sudoCoefParcor, 139
 sudoCoefParcorH, 141
 summaryRank, 143
 symmze, 143

 wtdpabb, 139, 144