

Package ‘lingtypology’

August 26, 2019

Type Package

Title Linguistic Typology and Mapping

Version 1.0.14

Depends R (>= 3.5.0)

Imports leaflet, leaflet.minicharts, stats, utils, stringdist,
grDevices, rowr

Author George Moroz

Maintainer George Moroz <agricolamz@gmail.com>

Description Provides R with the Glottolog database <<http://glottolog.org>> and some more abilities for purposes of linguistic mapping. The Glottolog database contains the catalogue of languages of the world. This package helps researchers to make a linguistic maps, using philosophy of the Cross-Linguistic Linked Data project <<http://clld.org/>>, which allows for while at the same time facilitating uniform access to the data across publications. A tutorial for this package is available on GitHub pages <<https://ropensci.github.io/lingtypology/>> and package vignette. Maps created by this package can be used both for the investigation and linguistic teaching. In addition, package provides an ability to download data from typological databases such as WALS, AUTOTYP and some others and to create your own database website.

License GPL (>= 2)

URL <https://CRAN.R-project.org/package=lingtypology>,
<https://docs.ropensci.org/lingtypology>,
<https://github.com/ropensci/lingtypology/>

BugReports <https://github.com/ropensci/lingtypology/issues>

LazyData TRUE

RoxygenNote 6.1.1

Encoding UTF-8

Suggests knitr, rmarkdown, testthat, covr, MASS, sp, rgeos, rgdal,
ggplot2

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2019-08-26 17:30:02 UTC

R topics documented:

abvd	3
abvd.feature	3
afbo.feature	4
aff.lang	5
amap	5
area.lang	6
atlas.database	6
autotyp	7
autotyp.feature	7
circassian	8
countries	9
country.lang	9
ejective_and_n_consonants	10
ggmap.feature	10
glottolog.modified	11
glottolog.original	12
gltc.iso	14
gltc.lang	14
imports	15
is.glottolog	15
iso.gltc	16
iso.lang	17
lang.aff	17
lang.country	18
lang.gltc	19
lang.iso	20
lat.lang	20
long.lang	21
map.feature	22
oto_mangueanIC	27
oto_mangueanIC.feature	27
phoible	28
phoible.feature	29
polygon.points_fd	30
polygon.points_kde	30
providers	31
sails.feature	31
uralex	32
uralex.feature	32
url.lang	33
valpal.feature	34
wals	34

<code>abvd</code>	3
<code>wals.feature</code>	35
Index	36

<code>abvd</code>	<i>ABVD's Language identifiers</i>
-------------------	------------------------------------

Description

Language identifiers from ABVD (<https://abvd.shh.mpg.de/austronesian/>). This dataset is created for `abvd.feature` function.

Usage

```
abvd
```

Format

A data frame with 1468 rows and 2 variables:

id language identifier
glottocode Glottocode

<code>abvd.feature</code>	<i>Download ABVD data</i>
---------------------------	---------------------------

Description

This function downloads data from ABVD (<https://abvd.shh.mpg.de/austronesian/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
abvd.feature(feature, glottolog.source = "modified")
```

Arguments

`feature` A character vector that define a language id from ABVD (e. g. "1", "292").
`glottolog.source` A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# abvd.feature(c(292, 7))
```

<code>afbo.feature</code>	<i>Download AfBo data</i>
---------------------------	---------------------------

Description

This function downloads data from AfBo (<http://afbo.info>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
afbo.feature(features = "all", na.rm = TRUE,
             glottolog.source = "modified")
```

Arguments

<code>features</code>	A character vector that define with an affix functions from AfBo (e. g. "all", "adjectivizer", "focus").
<code>na.rm</code>	Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.
<code>glottolog.source</code>	A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# afbo.feature()
# afbo.feature(c("adjectivizer", "adverbializer"))
```

aff.lang *Get affiliation by language*

Description

Takes any vector of languages and return affiliation.

Usage

```
aff.lang(x, glottolog.source = "modified")
```

Arguments

x A character vector of the languages (can be written in lower case)
glottolog.source A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[area.lang](#), [country.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
aff.lang('Korean')  
aff.lang(c('Korean', 'Polish'))
```

amap *Atlantic center template for gmap.feature() function*

Description

.

Usage

```
amap
```

Format

A list with 9 variables.

area.lang *Get macro area by language*

Description

Takes any vector of languages and return macro area.

Usage

```
area.lang(x, glottolog.source = "modified")
```

Arguments

x character vector of the languages (can be written in lower case)
glottolog.source A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [country.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
area.lang('Adyghe')  
area.lang(c('Adyghe', 'Aduge'))
```

atlas.database *Create an atlas*

Description

This function creates an rmarkdown based atlas from data provided by users. This function creates the template, after it should be rendered by rmarkdown package. The DT package is required during the rendering.

Usage

```
atlas.database(languages, latitude, longitude, features, atlas_name = "",  
author = "")
```

Arguments

languages	character vector of languages (can be written in lower case)
latitude	numeric vector of latitudes (optional)
longitude	numeric vector of longitudes (optional)
features	dataframe where each column is a feature set
atlas_name	string with an atlas name
author	string with the authors list

autotyp *AUTOTYP's Language identifiers*

Description

Language identifiers from AUTOTYP v. 0.1.0 (<https://github.com/autotyp/autotyp-data>). This dataset is created for `autotyp.feature` function.

Usage

```
autotyp
```

Format

An object of class `data.frame` with 2950 rows and 2 columns.

Details

#' @format A data frame with 2950 rows and 2 variables:

LID language identifier

Glottocode Glottocode

autotyp.feature *Download AUTOTYP data*

Description

This function downloads data from AUTOTYP (<https://github.com/autotyp/autotyp-data#the-autotyp-database>) and changes language names to the names from `lingtypology` database. You need the internet connection.

Usage

```
autotyp.feature(features, na.rm = TRUE, glottolog.source = "modified")
```

Arguments

<code>features</code>	A character vector that define with a feature names from AUTOTYP.
<code>na.rm</code>	Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.
<code>glottolog.source</code>	A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# autotyp.feature(c('Gender', 'Numeral classifiers'))
```

circassian

Circassian villages in Russia

Description

A dataset contains the list of the Circassian villages in Russia with genealogical affiliation, coordinates and district names. Most data collected during the fieldworks (2011–2018).

Usage

```
circassian
```

Format

A data frame with 158 rows and 6 variables:

longitude longitude

latitude latitude

village name of the village

district names of the subjects of the Russian Federation: kbr — Kabardino–Balkar Republic, kch — Karachay–Cherkess Republic, kk — Krasnodar Krai, ra — Republic of Adygea, stv — Stavropol Krai

dialect names of the Circassian dialects

language according standard Circassian devision there are Adyghe and Kabardian languages

countries	<i>Catalogue of countries names.</i>
-----------	--------------------------------------

Description

Catalogue of countries names.

Usage

```
countries
```

Format

A data frame with 86 rows and 3 variables:

common common name

official official name

abbreviation abbreviated name

official_languages official languages from the given country

country.lang	<i>Get country by language</i>
--------------	--------------------------------

Description

Takes any vector of languages and return affiliation.

Usage

```
country.lang(x, intersection = FALSE, glottolog.source = "modified")
```

Arguments

x character vector of the languages (can be written in lower case)

intersection logical. If TRUE, function returns vector of countries, where all languages from x argument are spoken.

glottolog.source

A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
country.lang('Udi')
country.lang(c('Udi', 'Laz'))
country.lang(c('Udi', 'Laz'), intersection = TRUE)
```

ejective_and_n_consonants

Number of consonants and presence of ejectives

Description

Number of consonants and presence of ejectives

Usage

```
ejective_and_n_consonants
```

Format

A data frame with 19 rows and 4 variables:

language language name

consonants number of consonants. Based on UPSID database.

vowels number of vowels. Based on UPSID database.

ejectives presence of ejective sounds

ggmap.feature

Create a map with ggplot2

Description

Map a set of languages and color them by feature.

Usage

```
ggmap.feature(languages, features = "", latitude = NA,
  longitude = NA, color = NULL, title = NULL, legend = TRUE,
  width = 2, opacity = 1, map.orientation = "Atlantic",
  glottolog.source = "modified")
```

Arguments

languages	character vector of languages (can be written in lower case).
features	character vector of features.
latitude	numeric vector of latitudes.
longitude	numeric vector of longitudes.
color	vector of colors or palette. The color argument can be (1) a character vector of RGM or named colors; (2) the name of an RColorBrewer palette; (3) the full name of a viridis palette; (4) a function that receives a single value between 0 and 1 and returns a color. For more examples see colorNumeric .
title	title of a legend.
legend	logical. If TRUE, function show legend. By default is TRUE.
width	a numeric vector of radius for circles or width for barcharts in minicharts.
opacity	a numeric vector of marker opacity.
map.orientation	a character vector with values "Pacific" and "Atlantic". It distinguishes Pacific-centered and Atlantic-centered maps. By default is "Atlantic".
glottolog.source	A character vector that define which glottolog database is used: "original" or "modified" (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
ggmap.feature(c("Adyghe", "Russian"))
```

glottolog.modified *Catalogue of languages of the world*

Description

A dataset contains the modified catalogue of languages of the world involving genealogical affiliation, macro-area, country, iso code, and coordinates.

Usage

```
glottolog.modified
```

Format

A data frame with 8566 rows and 7 variables:

language name of the language

iso code based on ISO 639-3 <http://www-01.sil.org/iso639-3/>

glottocode languoid code from Glottolog 2.7

longitude longitude

latitude latitude

affiliation genealogical affiliation

area have six values Africa, Australia, Eurasia, North America, Papunesia, South America

alternate names alternative language names

affiliation-HH some additional source for affiliation

country list of countries, where the language is spoken

dialects dialects of language

language status language status. In glottolog.modified comments are removed. In glottolog.original they are reserved. Have 14 categories: 1 (National); 2 (Provincial); 3 (Wider communication); 4 (Educational); 5 (Developing); 6a (Vigorous); 6b (Threatened); 7 (Shifting); 8a (Moribund); 8b (Nearly extinct); 8c (Reintroduced); 9 (Dormant); 9 (Second language only); 10 (Extinct)

language use language use

location location

population numeric pure population info

typology some information from WALS

writing information about writing system

Details

Glottolog 2.7. Hammarstrom, Harald & Forkel, Robert & Haspelmath, Martin & Bank, Sebastian. 2016. Max Planck Institute for the Science of Human History. Accessed on 2016-06-15.

glottolog.original *Catalogue of languages of the world*

Description

A dataset contains the original catalogue of languages of the world involving genealogical affiliation, macro-area, country, iso code, and coordinates.

Usage

glottolog.original

Format

A data frame with 8566 rows and 7 variables:

language name of the language

iso code based on ISO 639-3 <http://www-01.sil.org/iso639-3/>

glottocode languoid code from Glottolog 2.7

longitude longitude

latitude latitude

affiliation genealogical affiliation

area have six values Africa, Australia, Eurasia, North America, Papunesia, South America

alternate names alternative language names

affiliation-HH some additional source for affiliation

country list of countries, where the language is spoken

dialects dialects of language

language status language status. In glottolog.modified comments are removed. In glottolog.original they are reserved. Have 14 categories: 1 (Natioanl); 2 (Provincial); 3 (Wider communication); 4 (Educational); 5 (Developing); 6a (Vigorous); 6b (Threatened); 7 (Shifting); 8a (Moribund); 8b (Nearly extinct); 8b (Reintroduced); 9 (Dormant); 9 (Second language only); 10 (Extinct)

language use language use

location location

population numeric pure population info

typology some information form WALS

writing information about writing system

Details

Glottolog 2.7. Hammarstrom, Harald & Forkel, Robert & Haspelmath, Martin & Bank, Sebastian. 2016. Max Planck Institute for the Science of Human History. Accessed on 2016-06-15.

Source

<http://glottolog.org/>

gltc.iso	<i>Get Glottocode by ISO 639–3 code</i>
----------	---

Description

Takes any vector of ISO 639–3 codes and returns Glottocodes.

Usage

```
gltc.iso(x, glottolog.source = "modified")
```

Arguments

x	A character vector of the Glottocodes.
glottolog.source	A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
gltc.iso('ady')
gltc.iso(c('ady', 'rus'))
```

gltc.lang	<i>Get Glottocode by language</i>
-----------	-----------------------------------

Description

Takes any vector of languages and returns Glottocode.

Usage

```
gltc.lang(x, glottolog.source = "modified")
```

Arguments

x	A character vector of the languages (can be written in lower case)
glottolog.source	A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
gltc.lang('Adyghe')
gltc.lang(c('Adyghe', 'Udi'))
```

imports

Objects imported from other packages

Description

These objects are imported from other packages. Follow the links to their documentation.

magrittr [%>%](#)

is.glottolog

Are these languages in glottolog?

Description

Takes any vector of languages or ISO codes and return a logical vector.

Usage

```
is.glottolog(x, response = FALSE, glottolog.source = "modified")
```

Arguments

x A character vector of languages (can be written in lower case) or ISO codes

response logical. If TRUE, when language is absent, return warnings with a possible candidates.

glottolog.source A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```

is.glottolog(c('Adyghe', 'Russian'))
is.glottolog('Buyaka')

# Add warning message with suggestions
is.glottolog(c('Adygey', 'Russian'), response = TRUE)
# > FALSE TRUE
# Warning message:
# In is.glottolog(c('Adyge', 'Russian'), response = TRUE) :
# Language Adyge is absent in our version of the Glottolog database. Did you mean Aduge, Adyghe?

```

iso.gltc

Get ISO 639–3 code by Glottocode

Description

Takes any vector of Glotocodes and returns ISO code.

Usage

```
iso.gltc(x, glottolog.source = "modified")
```

Arguments

x A character vector of Glottocodes.
glottolog.source A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [lat.lang](#), [long.lang](#)

Examples

```

iso.gltc('adyg1241')
iso.gltc(c('adyg1241', 'udii1243'))

```

iso.lang *Get ISO 639–3 code by language*

Description

Takes any vector of languages and returns ISO code.

Usage

```
iso.lang(x, glottolog.source = "modified")
```

Arguments

x A character vector of the languages (can be written in lower case)
glottolog.source A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
iso.lang('Adyghe')  
iso.lang(c('Adyghe', 'Udi'))
```

lang.aff *Get languages by affiliation*

Description

Takes any vector of affiliations and return languages.

Usage

```
lang.aff(x, list = FALSE, glottolog.source = "modified")
```

Arguments

`x` A character vector of the affiliations (can be written in lower case)
`list` logical. If TRUE, returns a list of languages, if FALSE return a named vector.
`glottolog.source` A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[lang.country](#), [lang.iso](#)

Examples

```
lang.aff('Slavic')
lang.aff(c('Slavic', 'Celtic'))
lang.aff(c('Slavic', 'Celtic'), list = TRUE)
```

lang.country

Get languages by country

Description

Takes any vector of countries and return languages.

Usage

```
lang.country(x, list = FALSE, official = FALSE,
            glottolog.source = "modified")
```

Arguments

`x` character vector of the countries (can be written in lower case)
`list` logical. If TRUE, returns a list of languages, if FALSE return a vector.
`official` logical. If TRUE, returns a vector of official languages, if FALSE return a vector from Glottolog database.
`glottolog.source` A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[lang.aff](#), [lang.iso](#)

Examples

```
lang.country('North Korea')
lang.country(c('North Korea', 'Luxembourg'))
lang.country(c('North Korea', 'Luxembourg'), list = TRUE)
lang.country(c('Germany', 'Luxembourg'), official = TRUE)
```

lang.gltc

Get language by Glottocode

Description

Takes any vector of Glottocodes and return languages.

Usage

```
lang.gltc(x, glottolog.source = "modified")
```

Arguments

x A character vector of the Glottocodes.
glottolog.source A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[lang.aff](#), [lang.country](#)

Examples

```
lang.gltc('adyg1241')
lang.gltc(c('adyg1241', 'udii1243'))
```

lang.iso *Get language by ISO 639–3 code*

Description

Takes any vector of ISO codes and return languages.

Usage

```
lang.iso(x, glottolog.source = "modified")
```

Arguments

x A character vector of the ISO codes.
glottolog.source A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[lang.aff](#), [lang.country](#)

Examples

```
lang.iso('ady')  
lang.iso(c('ady', 'rus'))
```

lat.lang *Get latitude by language*

Description

Takes any vector of languages and return latitude.

Usage

```
lat.lang(x, glottolog.source = "modified")
```

Arguments

x A character vector of the languages (can be written in lower case)
glottolog.source A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [iso.lang](#), [long.lang](#)

Examples

```
lat.lang('Adyghe')
long.lang('Adyghe')
lat.lang(c('Adyghe', 'Russian'))
long.lang(c('Adyghe', 'Russian'))
```

long.lang

Get longitude by language

Description

Takes any vector of languages and return longitude.

Usage

```
long.lang(x, map.orientation = "Pacific",
          glottolog.source = "modified")
```

Arguments

x A character vector of the languages (can be written in lower case)

map.orientation A character vector with values "Pacific" and "Atlantic". It distinguishes Pacific-centered and Atlantic-centered maps. By default is "Pacific".

glottolog.source A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [iso.lang](#), [lat.lang](#)

Examples

```

lat.lang('Adyghe')
long.lang('Adyghe')
lat.lang(c('Adyghe', 'Russian'))
long.lang(c('Adyghe', 'Russian'))
long.lang(c('Adyghe', 'Aleut'), map.orientation = "Pacific")

```

map.feature

Create a map

Description

Map a set of languages and color them by feature or two sets of features.

Usage

```

map.feature(languages, features = "", label = "", popup = "",
  latitude = NA, longitude = NA, label.hide = TRUE,
  label.fsize = 15, label.font = "sans-serif",
  label.position = "right", label.emphasize = list(NULL, "black"),
  shape = NULL, shape.size = 20, pipe.data = NULL,
  shape.color = "black", stroke.features = NULL,
  density. estimation = NULL, density.method = "fixed distance",
  density. estimation.color = NULL, density. estimation.opacity = 0.6,
  density.points = TRUE, density.width = NULL, density.legend = TRUE,
  density.legend.opacity = 1, density.legend.position = "bottomleft",
  density.title = "", density.control = FALSE, isogloss = NULL,
  isogloss.color = "black", isogloss.opacity = 0.2,
  isogloss.line.width = 3, isogloss.width = NULL, color = NULL,
  stroke.color = NULL, image.url = NULL, image.width = 100,
  image.height = 100, image.X.shift = 0, image.Y.shift = 0,
  title = NULL, stroke.title = NULL, control = FALSE,
  legend = TRUE, legend.opacity = 1, legend.position = "topright",
  stroke.legend = TRUE, stroke.legend.opacity = 1,
  stroke.legend.position = "bottomleft", width = 5,
  stroke.radius = 9.5, opacity = 1, stroke.opacity = 1,
  scale.bar = TRUE, scale.bar.position = "bottomleft",
  minimap = FALSE, minimap.position = "bottomright",
  minimap.width = 150, minimap.height = 150, facet = NULL,
  tile = "OpenStreetMap.Mapnik", tile.name = NULL,
  zoom.control = FALSE, zoom.level = NULL, rectangle.lng = NULL,
  rectangle.lat = NULL, rectangle.color = "black", line.lng = NULL,
  line.lat = NULL, line.type = "standard", line.color = "black",
  line.opacity = 0.8, line.label = NULL, line.width = 3,
  graticule = NULL, minichart = NULL, minichart.data = NULL,
  minichart.time = NULL, minichart.labels = FALSE,
  map.orientation = "Pacific", glottolog.source = "modified",
  radius = NULL)

```

Arguments

languages	character vector of languages (can be written in lower case)
features	character vector of features
label	character vector of strings that will appear near points
popup	character vector of strings that will appear in pop-up window
latitude	numeric vector of latitudes
longitude	numeric vector of longitudes
label.hide	logical. If FALSE, labels are displayed allways. If TRUE, labels are displayed on mouse over. By default is TRUE.
label.fsize	numeric value of the label font size. By default is 14.
label.font	string with values of generic family: "serif", "sans-serif", "monospace", or font name e. g. "Times New Roman"
label.position	the position of labels: "left", "right", "top", "bottom"
label.emphasize	is the list. First argument is a vector of points in dataframe that should be emphasized. Second argument is a string with a color for emphasis.
shape	<ol style="list-style-type: none"> 1. if TRUE, creates icons (up to five categories) for values in the features variable; 2. it also could be a vector of any strings that represents the levels of the features variable; 3. it also could be a string vector that represents the number of observations in dataset.
shape.size	size of the shape icons
pipe.data	this variable is important, when you use map.feature with dplyr pipes. Expected usage: pipe.data = .
shape.color	color of the shape icons
stroke.features	additional independent stroke features
density.estimation	additional independent features, used for density estimation
density.method	string with one of the two methods: "kernal density estimation" or "fixed distance" (default)
density.estimation.color	vector of density polygons' colors
density.estimation.opacity	a numeric vector of density polygons opacity.
density.points	logical. If FALSE, it doesn't show points in polygones.
density.width	for density.method = "fixed distance" it is a numeric measure (1 is 1km). For density.method = "kernal density estimation" it is a vector with two meausures (first is latitude, secong is longitude). Defaults are normal reference bandwidth (see bandwidth.nrd).

density.legend logical. If TRUE, function show legend for density features. By default is FALSE.
 density.legend.opacity a numeric vector of density-legend opacity.
 density.legend.position the position of the legend: "topright", "bottomright", "bottomleft", "topleft"
 density.title title of a density-feature legend
 density.control logical. If TRUE, function show layer control buttons for density plot. By default is FALSE
 isogloss dataframe with corresponding features
 isogloss.color vector of isoglosses' colors
 isogloss.opacity a numeric vector of density polygons opacity.
 isogloss.line.width a numeric value for line width
 isogloss.width for density.method = "fixed distance" it is a numeric measure (1 is 1km). For density.method = "kernel density estimation" it is a vector with two measures (first is latitude, second is longitude). Defaults are normal reference bandwidth (see [bandwidth.nrd](#)).
 color vector of colors or palette. The color argument can be (1) a character vector of RGM or named colors; (2) the name of an RColorBrewer palette; (3) the full name of a viridis palette; (4) a function that receives a single value between 0 and 1 and returns a color. For more examples see [colorNumeric](#)
 stroke.color vector of stroke colors
 image.url character vector of URLs with an images
 image.width numeric vector of image widths
 image.height numeric vector of image heights
 image.X.shift numeric vector of image's X axis shift relative to the latitude-longitude point
 image.Y.shift numeric vector of image's Y axis shift relative to the latitude-longitude point
 title title of a legend.
 stroke.title title of a stroke-feature legend.
 control logical. If TRUE, function show layer control buttons. By default is FALSE
 legend logical. If TRUE, function show legend. By default is TRUE.
 legend.opacity a numeric vector of legend opacity.
 legend.position the position of the legend: "topright", "bottomright", "bottomleft", "topleft"
 stroke.legend logical. If TRUE, function show stroke.legend. By default is FALSE.
 stroke.legend.opacity a numeric vector of stroke.legend opacity.
 stroke.legend.position the position of the stroke.legend: "topright", "bottomright", "bottomleft", "topleft"

width	a numeric vector of radius for circles or width for barcharts in minicharts.
stroke.radius	a numeric vector of stroke radii for the circles.
opacity	a numeric vector of marker opacity.
stroke.opacity	a numeric vector of stroke opacity.
scale.bar	logical. If TRUE, function shows scale-bar. By default is TRUE.
scale.bar.position	the position of the scale-bar: "topright", "bottomright", "bottomleft", "topleft"
minimap	logical. If TRUE, function shows mini map. By default is FALSE.
minimap.position	the position of the minimap: "topright", "bottomright", "bottomleft", "topleft"
minimap.width	The width of the minimap in pixels.
minimap.height	The height of the minimap in pixels.
facet	character vector that provide a grouping variable. If it is no NULL, then as a result a list of leaflets for sync or latticeView functions from mapview package is returned.
tile	a character vector with a map tiles, popularized by Google Maps. See here for the complete set.
tile.name	a character vector with a user's map tiles' names.
zoom.control	logical. If TRUE, function shows zoom controls. By default is FALSE.
zoom.level	a numeric value of the zoom level.
rectangle.lng	vector of two longitude values for rectangle.
rectangle.lat	vector of two latitude values for rectangle.
rectangle.color	vector of rectangle border color.
line.lng	vector of two (or more) longitude values for line.
line.lat	vector of two (or more) latitude values for line.
line.type	a character string indicating which type of line is to be computed. One of "standard" (default), or "logit". The first one should be combined with the arguments line.lat and line.lng and provide simple lines. Other variant "logit" is the decision boundary of the logistic regression made using longitude and latitude coordinates (works only if feature argument have two levels).
line.color	vector of line color.
line.opacity	a numeric vector of line opacity.
line.label	character vector that will appear near the line.
line.width	a numeric vector of line width.
graticule	a numeric vector for graticule spacing in map units between horizontal and vertical lines.
minichart	citation from leaflet.minicharts package: "Possible values are "bar" for bar charts, "pie" for pie charts, "polar-area" and "polar-radius"."

`minichart.data` citation from leaflet.minicharts package: "A numeric matrix with number of rows equal to the number of elements in lng or lat and number of column equal to the number of variables to represent. If parameter time is set, the number of rows must be equal to the length of lng times the number of unique time steps in the data."

`minichart.time` citation from leaflet.minicharts package: "A vector with length equal to the number of rows in chartdata and containing either numbers representing time indices or dates or datetimes. Each unique value must appear as many times as the others. This parameter can be used when one wants to represent the evolution of some variables on a map."

`minichart.labels` citation from leaflet.minicharts package: "Should values be displayed above chart elements."

`map.orientation` a character vector with values "Pacific" and "Atlantic". It distinguishes Pacific-centered and Atlantic-centered maps. By default is "Pacific".

`glottolog.source` A character vector that define which glottolog database is used: "original" or "modified" (by default)

`radius` deprecated argument

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
map.feature(c("Adyghe", "Russian"))

## Map all Slavic languages
map.feature(lang.aff(c("Slavic")))

## Color languages by feature
df <- data.frame(lang = c("Adyghe", "Kabardian", "Polish", "Russian", "Bulgarian"),
  feature = c("polysynthetic", "polysynthetic", "fusion", "fusion", "fusion"))
map.feature(df$lang, df$feature)

## Add your own coordinates
map.feature("Adyghe", latitude = 43, longitude = 57)

## Change map tile
map.feature("Adyghe", tile = "Thunderforest.OpenCycleMap")

## Add you own colors
df <- data.frame(lang = c("Adyghe", "Kabardian", "Polish", "Russian", "Bulgarian"),
  feature = c("polysynthetic", "polysynthetic", "fusion", "fusion", "fusion"),
  popup = c("Circassian", "Circassian", "Slavic", "Slavic", "Slavic"))
map.feature(df$lang, df$feature, df$popup, color = c("green", "navy"))

## Map two sets of features
```

```
df <- data.frame(lang = c("Adyghe", "Kabardian", "Polish", "Russian", "Bulgarian"),
  feature = c("polysynthetic", "polysynthetic", "fusion", "fusion", "fusion"),
  popup = c("Circassian", "Circassian", "Slavic", "Slavic", "Slavic"))
map.feature(df$lang, df$feature, df$popup,
  stroke.features = df$popup)

## Add a minimap to plot
map.feature(c("Adyghe", "Russian"), minimap = TRUE)

## Remove scale bar
map.feature(c("Adyghe", "Russian"), scale.bar = FALSE)
```

 oto_mangueanIC

Oto-Manguean Inflectional Class Database Language identifiers

Description

Language identifiers from Oto-Manguean Inflectional Class Database (<http://wals.info/>). This dataset is created for `oto_mangueanIC.feature` function.

Usage

```
oto_mangueanIC
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 20 rows and 2 columns.

Details

#' @format A data frame with 20 rows and 2 variables:

Language.name Language names from Oto-Manguean Inflectional Class Database

language Language names from Glottolog database

 oto_mangueanIC.feature

Download Oto-Manguean Inflectional Class Database data

Description

This function downloads data from Oto-Manguean Inflectional Class Database (<http://www.oto-manguean.surrey.ac.uk/>) and creates a language column with the names from lingtypology database. You need the internet connection.

Usage

```
oto_mangueanIC.feature()
```

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# oto_mangueanIC.feature()
```

phoible

Phoible glottolog - language correspondencies

Description

Language correspondencies for Phoible (<https://phoible.org/>). This dataset is created for [phoible.feature](#) function.

Usage

```
phoible
```

Format

A data frame with 2185 rows and 2 variables:

language language

Glottocode Glottocode

phoible.feature	<i>Download PHOIBLE data</i>
-----------------	------------------------------

Description

This function downloads data from PHOIBLE (<http://phoible.org/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
phoible.feature(source = "all", na.rm = TRUE,  
               glottolog.source = "modified")
```

Arguments

source	A character vector that define with a source names from PHOIBLE (possible values: "all", "AA", "GM", "PH", "RA", "SAPHON", "SPA", "UPSID").
na.rm	Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.
glottolog.source	A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# phoible.feature()  
# phoible.feature(c('consonants', 'vowels'), source = "UPSID")
```

polygon.points_fd *Get poligons from fixed distance circles around coordinates*

Description

This function is based on this answer: <https://www.r-bloggers.com/merging-spatial-buffers-in-r/>

Usage

```
polygon.points_fd(latitude, longitude, width)
```

Arguments

latitude	numeric vector of latitudes
longitude	numeric vector of longitudes
width	radius for creating poligons around points

polygon.points_kde *Get kernel density estimation poligon from coordinates*

Description

This function is based on this answer: <https://gis.stackexchange.com/a/203623>

Usage

```
polygon.points_kde(latitude, longitude, latitude_width, longitude_width)
```

Arguments

latitude	numeric vector of latitudes
longitude	numeric vector of longitudes
latitude_width	bandwidths for latitude values. Defaults to normal reference bandwidth (see bandwidth.nrd).
longitude_width	bandwidths for longitude values. Defaults to normal reference bandwidth (see bandwidth.nrd).

 providers

Providers

Description

List of all providers with their variations taken from leaflet package

Usage

```
providers
```

Format

A list of characters

Source

<https://github.com/leaflet-extras/leaflet-providers/blob/master/leaflet-providers.js>

 sails.feature

Download SAILS data

Description

This function downloads data from SAILS (<http://sails.cld.org/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
sails.feature(features, na.rm = TRUE, glottolog.source = "modified")
```

Arguments

features	A character vector that define with a feature ids from SAILS (e. g. "and1", "argex4-1-3").
na.rm	Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.
glottolog.source	A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# sails.feature(c("and1", "and11"))
```

uralex	<i>UraLex's Language identifiers</i>
--------	--------------------------------------

Description

Language identifiers from UraLex (<https://github.com/lexibank/uralex>). This dataset is created for [uralex.feature](#) function.

Usage

```
uralex
```

Format

A data frame with 27 rows and 3 variables:

language language name from database

Glottocode Glottocodes

language2 language from lingtypology

uralex.feature	<i>Download UraLex data</i>
----------------	-----------------------------

Description

This function downloads data from UraLex (<https://github.com/lexibank/uralex>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
uralex.feature(na.rm = TRUE)
```

Arguments

na.rm Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# uralex.feature()
```

url.lang

Make a url-link to glottolog page for a language

Description

Takes any vector of languages and return links to glottolog pages.

Usage

```
url.lang(x, popup = "", glottolog.source = "modified")
```

Arguments

x	A character vector of languages (can be written in lower case)
popup	character vector of strings that will appear in pop-up window of the function map.feature
glottolog.source	A character vector that define which glottolog database is used: 'original' or 'modified' (by default)

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
url.lang('Korean')  
url.lang(c('Gangou', 'Hachijo', 'Adyghe', 'Ganai'))
```

valpal.feature	<i>Download ValPaL data</i>
----------------	-----------------------------

Description

This function downloads data from ValPal (<http://www.valpal.info/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
valpal.feature(na.rm = FALSE)
```

Arguments

na.rm Logical. If TRUE function removes all languages not available in lingtypology database. By default is FALSE.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [wals.feature](#)

Examples

```
# valpal.feature()
```

wals	<i>WALS's Language identifiers</i>
------	------------------------------------

Description

Language identifiers from WALS (<http://wals.info/>). This dataset is created for [wals.feature](#) function.

Usage

```
wals
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 2679 rows and 2 columns.

Details

```
#' @format A data frame with 2950 rows and 2 variables:
```

```
wals code  WALs language identifier
```

```
glottocode Glottocode
```

```
wals.feature
```

```
Download WALs data
```

Description

This function downloads data from WALs (<http://wals.info>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
wals.feature(features, na.rm = TRUE, glottolog.source = "modified")
```

Arguments

```
features      A character vector that define with a feature ids from WALs (e. g. "1a", "21b").
```

```
na.rm         Logical. If TRUE function removes all languages not available in lingtypology  
              database. By default is TRUE.
```

```
glottolog.source A character vector that define which glottolog database is used: 'original' or  
                 'modified' (by default)
```

Author(s)

```
George Moroz <agricolamz@gmail.com>
```

See Also

```
abvd.feature, afbo.feature, autotyp.feature, oto\_mangueanIC.feature, phoible.feature,  
sails.feature, uralex.feature, valpal.feature
```

Examples

```
# wals.feature(c("1a", "20a"))
```

Index

*Topic **datasets**

- abvd, 3
 - amap, 5
 - autotyp, 7
 - circassian, 8
 - countries, 9
 - ejective_and_n_consonants, 10
 - glottolog.modified, 11
 - glottolog.original, 12
 - oto_mangueanIC, 27
 - phoible, 28
 - providers, 31
 - uralex, 32
 - wals, 34
- %>(imports), 15
- %>, 15
- abvd, 3
- abvd.feature, 3, 3, 4, 8, 28, 29, 32–35
- afbo.feature, 4, 4, 8, 28, 29, 32–35
- aff.lang, 5, 6, 10, 14–17, 21
- amap, 5
- area.lang, 5, 6, 10, 14–17, 21
- atlas.database, 6
- autotyp, 7
- autotyp.feature, 4, 7, 7, 28, 29, 32–35
- bandwidth.nrd, 23, 24, 30
- circassian, 8
- colorNumeric, 11, 24
- countries, 9
- country.lang, 5, 6, 9, 14–17, 21
- ejective_and_n_consonants, 10
- ggmap.feature, 10
- glottolog.modified, 11
- glottolog.original, 12
- gltc.iso, 14
- gltc.lang, 14
- imports, 15
- is.glottolog, 15
- iso.gltc, 16
- iso.lang, 5, 6, 10, 17, 21
- lang.aff, 17, 19, 20
- lang.country, 18, 18, 19, 20
- lang.gltc, 19
- lang.iso, 18, 19, 20
- lat.lang, 5, 6, 10, 14–17, 20, 21
- long.lang, 5, 6, 10, 14–17, 21, 21
- map.feature, 22
- oto_mangueanIC, 27
- oto_mangueanIC.feature, 4, 8, 27, 27, 29, 32–35
- phoible, 28
- phoible.feature, 4, 8, 28, 29, 32, 34, 35
- polygon.points_fd, 30
- polygon.points_kde, 30
- providers, 31
- sails.feature, 4, 8, 28, 29, 31, 33–35
- uralex, 32
- uralex.feature, 4, 8, 28, 29, 32, 32, 33–35
- url.lang, 33
- valpal.feature, 4, 8, 28, 29, 32, 33, 34, 35
- wals, 34
- wals.feature, 4, 8, 28, 29, 32–34, 35