

Package ‘modeldatatoo’

August 26, 2023

Title More Data Sets Useful for Modeling Examples

Version 0.2.1

Description More data sets used for demonstrating or testing model-related packages are contained in this package. The data sets are downloaded and cached, allowing for more and bigger data sets.

License MIT + file LICENSE

URL <https://github.com/tidymodels/modeldatatoo>,
<https://modeldatatoo.tidymodels.org/>

BugReports <https://github.com/tidymodels/modeldatatoo/issues>

Depends R (>= 3.6)

Imports pins

Suggests covr, rstudioapi, testthat (>= 3.0.0)

Config/Needs/website tidyverse/tidytemplate

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Author Emil Hvitfeldt [aut, cre] (<<https://orcid.org/0000-0002-0679-1945>>),
Posit Software, PBC [cph, fnd]

Maintainer Emil Hvitfeldt <emil.hvitfeldt@posit.co>

Repository CRAN

Date/Publication 2023-08-25 22:50:16 UTC

R topics documented:

data_animals	2
data_chimiometrie_2019	4
data_elevators	6
data_hotel_rates	8

data_pharma_bioreactors	9
data_taxi	11
internal_board	13
small_fine_foods	14

Index	17
--------------	-----------

data_animals	<i>animals data set</i>
--------------	-------------------------

Description

Data set with characteristics of many animals, including the field text which is a long-form description of the animal.

Usage

```
data_animals(...)
```

Arguments

... Arguments passed to `pins::pin_read()`.

Details

This data set contains quite a bit of missing data and malformed fields.

Value

tibble

tibble print

```
data_animals()
#> # A tibble: 610 x 48
#>   text colour lifespan weight kingdom class phylum diet conservation_status
#>   <chr> <chr> <chr> <chr> <chr> <chr> <chr> <chr> <chr>
#> 1 "Aardv~ Brown~ 23 years 60kg ~ Animal~ Mamm~ Chord~ Omni~ Least Concern
#> 2 "Abyss~ Fawn,~ <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#> 3 "Adeli~ Black~ 10 - 20~ 3kg ~ Animal~ Aves Chord~ Carn~ Least Concern
#> 4 "Affen~ Black~ <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#> 5 "Afgha~ Black~ <NA> <NA> <NA> <NA> <NA> <NA> <NA>
#> 6 "Afric~ Grey,~ 60 - 70~ 3,600~ Animal~ Mamm~ Chord~ Herb~ Threatened
#> 7 "Afric~ Black~ 15 - 20~ 1.4kg~ Animal~ Mamm~ Chord~ Omni~ Least Concern
#> 8 "Afric~ Brown~ 8 - 15 ~ 25g ~ Animal~ Amph~ Chord~ Carn~ Least Concern
#> 9 "Afric~ Grey,~ 60 - 70~ 900kg~ Animal~ Mamm~ Chord~ Herb~ Endangered
#> 10 "Afric~ Black~ 15 - 20~ 1.4kg~ Animal~ Mamm~ Chord~ Omni~ Least Concern
#> # i 600 more rows
#> # i 39 more variables: order <chr>, scientific_name <chr>, skin_type <chr>,
```

```
#> # habitat <chr>, predators <chr>, family <chr>, lifestyle <chr>,
#> # average_litter_size <chr>, genus <chr>, top_speed <chr>,
#> # favourite_food <chr>, main_preys <chr>, type <chr>, common_name <chr>,
#> # group <chr>, size <chr>, distinctive_features <chr>, size_l <chr>,
#> # origin <chr>, special_features <chr>, location <chr>, ...
```

glimpse()

```
tibble::glimpse(data_animals())
#> Rows: 610
#> Columns: 48
#> $ text <chr> "Aardvark Classification and Evolution\nAard~
#> $ colour <chr> "Brown, grey, yellow", "Fawn, Red, Blue, Gre~
#> $ lifespan <chr> "23 years", NA, "10 - 20 years", NA, NA, "60~
#> $ weight <chr> "60kg - 80kg (130lbs - 180lbs)", NA, "3kg - ~
#> $ kingdom <chr> "Animalia", NA, "Animalia", NA, NA, "Animali~
#> $ class <chr> "Mammalia", NA, "Aves", NA, NA, "Mammalia", ~
#> $ phylum <chr> "Chordata", NA, "Chordata", NA, NA, "Chordat~
#> $ diet <chr> "Omnivore", NA, "Carnivore", NA, NA, "Herbiv~
#> $ conservation_status <chr> "Least Concern", NA, "Least Concern", NA, NA~
#> $ order <chr> "Tubulidentata", NA, "Sphenisciformes", NA, ~
#> $ scientific_name <chr> "Orycteropus afer", NA, "Pygoscelis adeliae"~
#> $ skin_type <chr> "Hair", NA, "Feathers", NA, NA, "Leather", "~
#> $ habitat <chr> "Sandy and clay soil", NA, "Antarctic land a~
#> $ predators <chr> "Lions, Leopards, Hyenas", NA, "Leopard Seal~
#> $ family <chr> "Orycteropodidae", NA, "Spheniscidae", NA, N~
#> $ lifestyle <chr> "Nocturnal", NA, "Diurnal", NA, NA, "Diurnal~
#> $ average_litter_size <chr> "1", "6", NA, "3", "7", "1", "3", NA, "1", "~
#> $ genus <chr> "Orycteropus", NA, "Pygoscelis", NA, NA, "Lo~
#> $ top_speed <chr> "40kph (25mph)", NA, "72kph (45mph)", NA, NA~
#> $ favourite_food <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
#> $ main_preys <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
#> $ type <chr> NA, "Shorthair", NA, "Terrier", "Hound", NA,~
#> $ common_name <chr> "Aardvark", "Abyssinian", "Adelie Penguin", ~
#> $ group <chr> "Mammal", "Cat", "Bird", "Dog", "Dog", "Mamm~
#> $ size <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
#> $ distinctive_features <chr> NA, "Silky fur and almond shaped eyes", NA, ~
#> $ size_l <chr> "1.05m - 2.20m (3.4ft - 7.3ft)", NA, NA, NA,~
#> $ origin <chr> NA, "Egypt", NA, "Germany", "Afghanistan", N~
#> $ special_features <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
#> $ location <chr> "Sub-Saharan Africa", NA, "Coastal Antarctic~
#> $ number_of_species <chr> "18", NA, "1", NA, NA, "1", "1", "1", "1", "~
#> $ average_clutch_size <chr> NA, NA, "2", NA, NA, NA, NA, NA, NA, "2"~
#> $ size_h <chr> NA, NA, "40cm - 75cm (16in - 30in)", NA, NA,~
#> $ group_behaviour <chr> "Solitary", NA, "Colony", NA, NA, "Herd", "S~
#> $ fun_fact <chr> "Can move up to 2ft of soil in just 15 secon~
#> $ age_of_sexual_maturity <chr> "2 years", NA, "2 - 3 years", NA, NA, "11 - ~
#> $ name_of_young <chr> "Cub", NA, "Chicks", NA, NA, "Calf", "Pup", ~
#> $ prey <chr> "Termites, Ants", NA, "Krill, Fish, Squid", ~
```

```
#> $ estimated_population_size <chr> "Unknown", NA, "5 million", NA, NA, "300,000~
#> $ biggest_threat           <chr> "Habitat loss", NA, "Rapid ice melt", NA, NA~
#> $ average_lifespan         <chr> NA, "15 years", NA, "12 years", "14 years", ~
#> $ most_distinctive_feature <chr> "Long, sticky tongue and rabbit-like ears", ~
#> $ other_name_s             <chr> "Antbear, Earth Pig", NA, NA, NA, NA, "Afric~
#> $ gestation_period         <chr> "7 months", NA, NA, NA, NA, "20 - 24 months"~
#> $ age_of_weaning           <chr> "3 months", NA, NA, NA, NA, "6 - 18 months",~
#> $ average_weight           <chr> NA, "4.5kg (10lbs)", NA, "3.6kg (8lbs)", "27~
#> $ temperament             <chr> NA, "Intelligent and curious", NA, "Alert an~
#> $ wingspan                 <chr> NA, NA, "35cm - 70cm (14in - 27.5in)", NA, N~
```

Source

<https://github.com/emilhvitefeldt/animals>

Examples

```
data_animals()
```

data_chimiometrie_2019

Chimiometrie 2019 Data Set

Description

Larsen and Clemmensen (2019) state: "This data set was published as the challenge at the Chimiometrie 2019 conference held in Montpellier and is available at the conference homepage. The data consist of 6915 training spectra and 600 test spectra measured at 550 (unknown) wavelengths. The target was the amount of soy oil (0-5.5%), ucerne (0-40%) and barley (0-52%) in a mixture."

The test set included a distribution shift due to the use of a different instrument and this competition was designed to measure how models might be made to be resistant to such a difference. However, since there are no test set outcomes, we only include the training set here.

There are 6,915 rows and 553 columns. The columns whose names start with `wvlngth_` are the spectral values with the numbers in the column names referring to the order (as opposed to the wavenumber). Fernández Pierna (2020) suggest that the wavelengths range from 1300 2nm to 2398 2nm.

The three outcome columns are "soy_oil", "lucerne", and "barley".

Usage

```
data_chimiometrie_2019(...)
```

Arguments

```
... Arguments passed to pins::pin_read().
```

Value

A tibble.

glimpse()

```
tibble::glimpse(data_chimiometrie_2019()[, 1:10])
#> Rows: 6,915
#> Columns: 10
#> $ soy_oil    <dbl> 2.1, 2.1, 2.1, 0.5, 0.5, 0.5, 0.5, 0.5, 0.5, 0.5, 0.5, 0.5, ~
#> $ lucerne   <dbl> 23.5712, 23.5712, 23.5712, 25.0000, 25.0000, 25.0000, 25.00~
#> $ barley    <dbl> 0, 0, 0, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, ~
#> $ wvlgth_001 <dbl> 0.2076995, 0.2064382, 0.2070081, 0.2057694, 0.2005429, 0.20~
#> $ wvlgth_002 <dbl> 0.2074427, 0.2062003, 0.2067785, 0.2055505, 0.2003232, 0.20~
#> $ wvlgth_003 <dbl> 0.2072212, 0.2059973, 0.2065901, 0.2053678, 0.2001469, 0.20~
#> $ wvlgth_004 <dbl> 0.2070317, 0.2058266, 0.2064396, 0.2052174, 0.2000069, 0.20~
#> $ wvlgth_005 <dbl> 0.2068830, 0.2056964, 0.2063288, 0.2051110, 0.1999092, 0.20~
#> $ wvlgth_006 <dbl> 0.2067773, 0.2056115, 0.2062618, 0.2050571, 0.1998616, 0.20~
#> $ wvlgth_007 <dbl> 0.2067083, 0.2055686, 0.2062386, 0.2050495, 0.1998592, 0.20~
```

License:

No license was given for the data.

Source

<https://chemom2019.sciencesconf.org/resource/page/id/13.html>

References

J. Larsen and L. Clemmensen (2019) "Deep learning for Chemometric and non-translational data," *arXiv.org*, <https://arxiv.org/abs/1910.00391>.

J.A. Fernández Pierna, A. Laborde, L. Lakhali, M. Lesnoff, M. Martin, Y. Roggo, and P. Dardenne (2020) "The applicability of vibrational spectroscopy and multivariate analysis for the characterization of animal feed where the reference values do not follow a normal distribution: A new chemometric challenge posed at the 'Chimiométrie 2019' congress," *Chemometrics and Intelligent Laboratory Systems*, vol 202, p. 104026. doi:10.1016/j.chemolab.2020.104026

Examples

```
data_chimiometrie_2019()
```

data_elevators *elevators data set*

Description

A data set containing information of a subset of the elevators in NYC. The data set has been filtered to contain active elevators with non-missing speed.

Usage

```
data_elevators(...)
```

Arguments

... Arguments passed to `pins::pin_read()`.

Details

device_number Unique identify number for the elevator

bin Building Identification Number

borough Regional subdivisions of NYC. One of "Manhattan", "Bronx", "Brooklyn", "Queens", or "Staten Island"

tax_block Id for tax block. Smaller than borough

tax_lot Id for tax block. Smaller than tax_block

house_number House number, very poorly parsed. Use with caution

street_name Street name, very poorly parsed. Use with caution

zip_code Zip code, formatted to 5 digits. 0 and 99999 are marked as NA

device_type Type of device. Most common type is "Passenger Elevator"

lastper_insp_date Date, refers to the last periodic inspection by the Department of Buildings. These dates will no longer be accurate, as they were collected by November 2015

approval_date Date of approval for elevator

manufacturer Name of manufacturer, poorly cleaned. Most assigned NA

travel_distance Distance travelled, not cleaned. Mixed formats

speed_fpm Speed in feet/minute

capacity_lbs Capacity in lbs

car_buffer_type Buffer type. A buffer is a device designed to stop a descending car or counter-weight beyond its normal limit and to soften the force with which the elevator runs into the pit during an emergency. Takes values "Oil", "Spring", and NA

governor_type Governor type, An overspeed governor is an elevator device which acts as a stopping mechanism in case the elevator runs beyond its rated speed

machine_type Machine type, labels unknown.

safety_type Safety type, labels unknown.

mode_operation Operation mode, labels unknown.
floor_from Lowest floor, not cleaned. Mixed formats
floor_to Highest floor, not cleaned. Mixed formats
latitude Latitude of elevator
longitude Longitude of elevator
elevators_per_building number of elevators in building ...

Value

tibble

tibble print

```
data_elevators()
#> # A tibble: 35,042 x 25
#>   device_number bin    tax_block tax_lot house_number street_name    zip_code
#>   <chr>          <chr> <chr>    <chr> <chr>      <chr>      <chr>
#> 1 1D10028      1024795 1021    26    1614      BROADWAY    10019
#> 2 1D10094      1041822 1392    25     53      E 77TH ST   10021
#> 3 1D10097      1038223 1323     1    201      E 49 ST     10017
#> 4 1D10146      1080443 1274     6     40      CENTRAL PARK S~ <NA>
#> 5 1D10200      1085777 1074    24    651      TENTH AVENUE <NA>
#> 6 1D10301      1002075 181     16    179      FRANKLIN STREET 10013
#> 7 1D10302      1010518 606     4     121      WEST 10 STREET 10011
#> 8 1D10303      1085955 1329     1    915      3 AVENUE     10022
#> 9 1D10304      1044058 1430     5    220      E. 76 ST     10021
#> 10 1D10305      1087468 1951     4    133      MORNINGSID AV~ <NA>
#> # i 35,032 more rows
#> # i 18 more variables: borough <fct>, device_type <chr>,
#> #   lastper_insp_date <date>, approval_date <date>, manufacturer <chr>,
#> #   travel_distance <chr>, speed_fpm <dbl>, capacity_lbs <dbl>,
#> #   car_buffer_type <chr>, governor_type <chr>, machine_type <chr>,
#> #   safety_type <chr>, mode_operation <chr>, floor_from <chr>, floor_to <chr>,
#> #   latitude <dbl>, longitude <dbl>, elevators_per_building <int>
```

glimpse()

```
tibble::glimpse(data_elevators())
#> Rows: 35,042
#> Columns: 25
#> $ device_number    <chr> "1D10028", "1D10094", "1D10097", "1D10146", "1D~
#> $ bin              <chr> "1024795", "1041822", "1038223", "1080443", "10~
#> $ tax_block        <chr> "1021", "1392", "1323", "1274", "1074", "181", ~
#> $ tax_lot          <chr> "26", "25", "1", "6", "24", "16", "4", "1", "5"~
#> $ house_number     <chr> "1614", "53", "201", "40", "651", "179", "121", ~
#> $ street_name      <chr> "BROADWAY", "E 77TH ST", "E 49 ST", "CENTRAL PA~
#> $ zip_code         <chr> "10019", "10021", "10017", NA, NA, "10013", "10~
#> $ borough          <fct> Manhattan, Manhattan, Manhattan, Manhattan, Man~
```

```

#> $ device_type           <chr> "Dumbwaiter", "Dumbwaiter", "Dumbwaiter", "Dumb~
#> $ lastper_insp_date     <date> 2015-09-18, 2015-08-07, 2015-04-02, 2014-10-15~
#> $ approval_date        <date> 2006-03-07, 2006-05-15, 1998-09-21, 2010-08-02~
#> $ manufacturer         <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
#> $ travel_distance       <chr> "16'4\"", NA, "23", "8'", "24 FT", "9'0", "12'0~
#> $ speed_fpm             <dbl> 50, 25, 50, 50, 50, 50, 50, 50, 50, 100, 100, 5~
#> $ capacity_lbs         <dbl> 500, 500, 500, 500, NA, 500, 300, 500, 500, 500~
#> $ car_buffer_type      <chr> "Spring", NA, NA, NA, NA, NA, "Spring", NA, NA, ~
#> $ governor_type        <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
#> $ machine_type         <chr> NA, "OD", "BD", "BD", NA, "OD", "OD", "BD", "OG~
#> $ safety_type          <chr> "I", NA, "I", NA, NA, "I", "I", NA, "I", NA, NA~
#> $ mode_operation       <chr> "A", "P", "A", "A", NA, "A", "A", "A", "A", "P"~
#> $ floor_from           <chr> "B", "SB", "B", "B", "C", "BAS", "B", "C", "BMT~
#> $ floor_to             <chr> "1", "3", "2", "1", "G", "1", "1", "2", "4", "5~
#> $ latitude             <dbl> 40.76088, 40.77502, 40.75518, 40.76500, 40.7622~
#> $ longitude            <dbl> -73.98391, -73.96256, -73.97079, -73.97573, -73~
#> $ elevators_per_building <int> 11, 2, 1, 1, 2, 2, 1, 1, 1, 5, 5, 1, 2, 1, 1, 2~

```

Source

<https://github.com/datanews/elevators>

Examples

```
data_elevators()
```

data_hotel_rates	<i>Daily Hotel Rate Data</i>
------------------	------------------------------

Description

A data set to predict the average daily rate for a hotel in Lisbon Portugal.

Usage

```
data_hotel_rates(...)
```

Arguments

... Arguments passed to `pins::pin_read()`.

Details

Data are originally described in Antonio, de Almeida, and Nunes (2019). This version of the data is filtered for one hotel (the "Resort Hotel") and is intended as regression data set for predicting the average daily rate for a room. The data are post-2016; the 2016 data were used to have a predictor for the historical daily rates. See the `hotel_rates.R` file in the `data-raw` directory of the package to understand other filters used when creating this version of the data.

The `agent` and `company` fields were changed from random characters to use a set of random names. The outcome column is `avg_price_per_room`.

License:

No license was given for the data; See the reference below for source.

Value

A tibble.

Source

<https://github.com/rfordatascience/tidytuesday/tree/master/data/2020/2020-02-11>

References

Antonio, N., de Almeida, A., and Nunes, L. (2019). Hotel booking demand datasets. *Data in Brief*, 22, 41-49.

Examples

```
data_hotel_rates()
```

data_pharma_bioreactors

Pharmaceutical manufacturing monitoring data set

Description

Samples were collected each day from all bioreactors and glucose was measured using both spectroscopy and the traditional manner. The goal is to create models on the data from the more numerous small-scale bioreactors and then evaluate if these results can accurately predict what is happening in the large-scale bioreactors (see details below).

Usage

```
data_pharma_bioreactors(...)
```

Arguments

... Arguments passed to `pins::pin_read()`.

Details**Experimental Background:**

Pharmaceutical companies use spectroscopy measurements to assess critical process parameters during the manufacturing of a biological drug. Models built on this process can be used with real-time data to recommend changes that can increase product yield. In the example that follows, Raman spectroscopy was used to generate the data. These data were generated from real data, but have been distinctly modified to preserve confidentiality and achieve illustration purposes.

To manufacture the drug being used for this example, a specific type of protein is required and that protein can be created by a particular type of cell. A batch of cells are seeded into a *bioreactor* which is a device that is designed to help grow and maintain the cells. In production, a large bioreactor would be about 2000 liters and is used to make large quantities of proteins in about two weeks.

Many factors can affect product yield. For example, because the cells are living, working organisms, they need the right temperature and sufficient food (glucose) to generate drug product. During the course of their work, the cells also produce waste (ammonia). Too much of the waste product can kill the cells and reduce the overall product yield. Typically key attributes like glucose and ammonia are monitored daily to ensure that the cells are in optimal production conditions. Samples are collected and off-line measurements are made for these key attributes. If the measurements indicate a potential problem, the manufacturing scientists overseeing the process can tweak the contents of the bioreactor to optimize the conditions for the cells.

One issue is that conventional methods for measuring glucose and ammonia are time consuming and the results may not come in time to address any issues. Spectroscopy is a potentially faster method of obtaining these results if an effective model can be used to take the results of the spectroscopy assay to make predictions on the substances of interest (i.e., glucose and ammonia). However, it is not feasible to do experiments using many large-scale bioreactors. Two parallel experimental systems were used:

- 15 small-scale (5 liters) bioreactors were seeded with cells and were monitored daily for 14 days.
- Three large-scale bioreactors were also seeded with cells from the same batch and monitored daily for 14 days

Notes on Data:

The intensity values have undergone signal processing up to smoothing. See the reference for more details.

License:

```
data_pharma_bioreactors()
#> # A tibble: 664,524 x 6
#>   reactor_id  day glucose wave_number intensity size
#>   <chr>      <int> <dbl>     <dbl>     <dbl> <chr>
#> 1 S_01         1  24.7       407  0.909 small
#> 2 S_01         1  24.7       408  0.858 small
#> 3 S_01         1  24.7       409  0.766 small
```

```

#> 4 S_01          1    24.7          410    0.627    small
#> 5 S_01          1    24.7          411    0.448    small
#> 6 S_01          1    24.7          412    0.236    small
#> 7 S_01          1    24.7          413    0.00707  small
#> 8 S_01          1    24.7          414   -0.222    small
#> 9 S_01          1    24.7          415   -0.438    small
#> 10 S_01         1    24.7          416   -0.629    small
#> # i 664,514 more rows

```

Value

tibble

glimpse()

```

tibble::glimpse(data_pharma_bioreactors())
#> Rows: 664,524
#> Columns: 6
#> $ reactor_id <chr> "S_01", "S_01", "S_01", "S_01", "S_01", "S_01", "S_01", "S_~
#> $ day         <int> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1~
#> $ glucose     <dbl> 24.74713, 24.74713, 24.74713, 24.74713, 24.74713, 24.74713~
#> $ wave_number <dbl> 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418~
#> $ intensity   <dbl> 0.909439216, 0.857607637, 0.766150467, 0.626862221, 0.4480~
#> $ size        <chr> "small", "small", "small", "small", "small", "small", "sma~

```

Source

Kuhn, Max, and Kjell Johnson. *Feature engineering and selection: A practical approach for predictive models*. Chapman and Hall/CRC, 2019.

<https://bookdown.org/max/FES/illustrative-data-pharmaceutical-manufacturing-monitoring.html>

Examples

```
data_pharma_bioreactors()
```

data_taxi	<i>Chicago taxi data set</i>
-----------	------------------------------

Description

A data set containing information on a subset of taxi trips in the city of Chicago in 2022.

Usage

```
data_taxi(...)
```

Arguments

... Arguments passed to `pins::pin_read()`.

Details

The source data are originally described on the linked City of Chicago data portal. The data exported here are a pre-processed subset motivated by the modeling problem of predicting whether a rider will tip or not.

tip Whether the rider left a tip. A factor with levels "yes" and "no".

distance The trip distance, in odometer miles.

company The taxi company, as a factor. Companies that occurred few times were binned as "other".

local Whether the trip started in the same community area as it began. See the source data for community area values.

dow The day of the week in which the trip began, as a factor.

month The month in which the trip began, as a factor.

hour The hour of the day in which the trip began, as a numeric.

Previous releases of this data (with `version = "20230630T214846Z-643d0"`) included additional columns:

id A unique identifier for the trip, as a factor.

duration The trip duration, in seconds.

fare The cost of the trip fare, in USD

tolls The cost of tolls for the trip, in USD.

extras The cost of extra charges for the trip, in USD.

total_cost The total cost of the trip, in USD. This is the sum of the previous three columns plus tip.

payment_type Type of payment for the trip. A factor with levels "Credit Card", "Dispute", "Mobile", "No Charge", "Pcard", and "Unknown".

Value

tibble

tibble print

```
data_taxi()
#> # A tibble: 10,000 x 7
#>   tip distance company local dow month hour
#>   <fct>   <dbl> <fct>   <fct> <fct> <fct> <int>
#> 1 yes     17.2 Chicago Independents no Thu Feb 16
#> 2 yes     0.88 City Service yes Thu Mar 8
#> 3 yes     18.1 other no Mon Feb 18
#> 4 yes     20.7 Chicago Independents no Mon Apr 8
```

```
#> 5 yes      12.2 Chicago Independents      no  Sun  Mar   21
#> 6 yes       0.94 Sun Taxi                    yes Sat  Apr   23
#> 7 yes      17.5 Flash Cab                    no  Fri  Mar   12
#> 8 yes      17.7 other                        no  Sun  Jan    6
#> 9 yes       1.85 Taxicab Insurance Agency Llc no  Fri  Apr   12
#> 10 yes     1.47 City Service                  no  Tue  Mar   14
#> # i 9,990 more rows
```

glimpse()

```
tibble::glimpse(data_taxi())
#> Rows: 10,000
#> Columns: 7
#> $ tip      <fct> yes, yes, yes, yes, yes, yes, yes, yes, yes, yes, yes, yes, y~
#> $ distance <dbl> 17.19, 0.88, 18.11, 20.70, 12.23, 0.94, 17.47, 17.67, 1.85, 1~
#> $ company  <fct> Chicago Independents, City Service, other, Chicago Independen~
#> $ local    <fct> no, yes, no, no, no, yes, no, no, no, no, no, no, yes, no~
#> $ dow      <fct> Thu, Thu, Mon, Mon, Sun, Sat, Fri, Sun, Fri, Tue, Tue, Sun, W~
#> $ month    <fct> Feb, Mar, Feb, Apr, Mar, Apr, Mar, Jan, Apr, Mar, Mar, Apr, A~
#> $ hour     <int> 16, 8, 18, 8, 21, 23, 12, 6, 12, 14, 18, 11, 12, 19, 17, 13, ~
```

Source

<https://data.cityofchicago.org/Transportation/Taxi-Trips/wrvz-psew>

Examples

```
data_taxi()
```

internal_board

Internal pins board

Description

Pins board used internally to manage download, reading, and caching of data sets.

Usage

```
internal_board()
```

Value

a pins board

Examples

```
internal_board()
```

small_fine_foods	<i>small_fine_foods data sets</i>
------------------	-----------------------------------

Description

Training and testing data set of fine food reviews.

Usage

```
attach_small_fine_foods(envir = parent.frame(), quiet = FALSE, ...)
```

Arguments

envir	Environment to load data sets into. Defaults to <code>parent.frame()</code> .
quiet	Logical, should function announce what data sets are loaded.
...	Arguments passed to <code>pins::pin_read()</code> .

Details

These data are from Amazon, who describe it as "This dataset consists of reviews of fine foods from amazon. The data span a period of more than 10 years, including all ~500,000 reviews up to October 2012. Reviews include product and user information, ratings, and a plaintext review."

A subset of the data are contained here and are split into a training and test set. The training set sampled 10 products and retained all of their individual reviews. Since the reviews within these products are correlated, we recommend resampling the data using a leave-one-product-out approach. The test set sampled 500 products that were not included in the training set and selected a single review at random for each.

There is a column for the product, a column for the text of the review, and a factor column for a class variable. The outcome is whether the reviewer gave the product a 5-star rating or not.

Value

tibble

tibble print

```

attach_small_fine_foods()
#> The following data sets have been loaded:
#> `training_data`, `testing_data`
#> Silence this message by setting `quiet = TRUE`.

training_data
#> # A tibble: 4,000 x 3
#>   product      review      score
#>   <chr>      <chr>      <fct>
#> 1 B000J0LSBG "this stuff is not stuffing its not good at all save yo~ other
#> 2 B000EYLDYE "I absolutely LOVE this dried fruit. LOVE IT. Whenever I ~ great
#> 3 B0026LIO9A "GREAT DEAL, CONVENIENT TOO. Much cheaper than WalMart and~ great
#> 4 B00473P8SK "Great flavor, we go through a ton of this sauce! I discove~ great
#> 5 B001SAWTNM "This is excellent salsa/hot sauce, but you can get it for ~ great
#> 6 B000FAG90U "Again, this is the best dogfood out there. One suggestion~ great
#> 7 B006BXTCEK "The box I received was filled with teas, hot chocolates, a~ other
#> 8 B002GWH50Y "This is delicious coffee which compares favorably with muc~ great
#> 9 B003R0MFYY "Don't let these little tiny cans fool you. They pack a lo~ great
#> 10 B001E05ZXI "One of the nicest, smoothest cup of chai I've made. Nice m~ great
#> # i 3,990 more rows

testing_data
#> # A tibble: 1,000 x 3
#>   product      review      score
#>   <chr>      <chr>      <fct>
#> 1 B005GXFP60 "These are the best tasting gummy fruits I have ever eaten.~ great
#> 2 B000G7V394 "I have been a consumer of Snyders hard sourdough pretzels ~ great
#> 3 B004WJAULO "This tastes so bad, I'm considering throwing it away. But~ other
#> 4 B003D4MBOS "This product is way too pricey to have so little chocolate~ other
#> 5 B0030Z95B2 "I bought this for my Mom as a gift to accompany her Dolce ~ great
#> 6 B000LRH4WE "This thing is 7 dollars in US?I know its exported from Cyp~ other
#> 7 B000Z91SZW "This tea tastes like hot cocoa. Very pleasant experience.~ other
#> 8 B00563VNEI "This product is great for a quick cup of coffee. If you us~ great
#> 9 B0085NFX20 "Grilled out brats, chicken, and burgers for the entire fam~ great
#> 10 B000LRH7XK "I ordered 4 cans of this product. The product is fine, bu~ other
#> # i 990 more rows

```

glimpse()

```

tibble::glimpse(training_data)
#> Rows: 4,000
#> Columns: 3
#> $ product <chr> "B000J0LSBG", "B000EYLDYE", "B0026LIO9A", "B00473P8SK", "B001S~
#> $ review <chr> "this stuff is not stuffing its not good at all save your ~
#> $ score <fct> other, great, great, great, great, great, other, great, great,~
tibble::glimpse(testing_data)
#> Rows: 1,000
#> Columns: 3

```

```
#> $ product <chr> "B005GXFP60", "B000G7V394", "B004WJAULO", "B003D4MBOS", "B0030~  
#> $ review <chr> "These are the best tasting gummy fruits I have ever eaten. Ca~  
#> $ score <fct> great, great, other, other, great, other, other, great, great,~
```

Source

<https://snap.stanford.edu/data/web-FineFoods.html>

Examples

```
attach_small_fine_foods()
```


Index

`attach_small_fine_foods`
 (`small_fine_foods`), [14](#)

`data_animals`, [2](#)
`data_chimiometrie_2019`, [4](#)
`data_elevators`, [6](#)
`data_hotel_rates`, [8](#)
`data_pharma_bioreactors`, [9](#)
`data_taxi`, [11](#)

`internal_board`, [13](#)

`pins::pin_read()`, [2](#), [4](#), [6](#), [8](#), [10](#), [12](#), [14](#)

`small_fine_foods`, [14](#)

`testing_data` (`small_fine_foods`), [14](#)
`training_data` (`small_fine_foods`), [14](#)