

Package ‘tidybayes’

November 2, 2020

Title Tidy Data and 'Geoms' for Bayesian Models

Version 2.3.1

Date 2020-10-30

Maintainer Matthew Kay <mjskay@northwestern.edu>

Description

Compose data for and extract, manipulate, and visualize posterior draws from Bayesian models ('JAGS', 'Stan', 'rstanarm', 'brms', 'MCMCglmm', 'coda', ...) in a tidy data format. Functions are provided to help extract tidy data frames of draws from Bayesian models and that generate point summaries and intervals in a tidy format. In addition, 'ggplot2' 'geoms' and 'stats' are provided for common visualization primitives like points with multiple uncertainty intervals, eye plots (intervals plus densities), and fit curves with multiple, arbitrary uncertainty bands.

Depends R (>= 3.5.0)

Imports ggdist (>= 2.3.0), plyr, dplyr (>= 0.8.0), tidyr (>= 1.0.0), ggplot2 (>= 3.3.0), coda, purrr (>= 0.2.3), rlang (>= 0.3.0), forcats, arrayhelpers, tidyselect, tibble, magrittr

Suggests knitr, testthat, vdiff (>= 0.3.0), svglite, rstan (>= 2.17.0), runjags, rjags, jagsUI, rstanarm (>= 2.19.2), emmeans, broom (>= 0.4.3), dotwhisker, MCMCglmm, bayesplot, modelr, brms (>= 2.13.0), cowplot, covr, gdtools, rmarkdown, ggrepel, bindrcpp, RColorBrewer, gganimate, gifski, png, pkgdown, transformr

License GPL (>= 3)

Language en-US

BugReports <https://github.com/mjskay/tidybayes/issues/new>

URL <https://mjskay.github.io/tidybayes/>,
<https://github.com/mjskay/tidybayes/>

VignetteBuilder knitr

RoxygenNote 7.1.1

LazyData true

Encoding UTF-8

Collate ``ggdist-geom_slabinterval.R" ``ggdist-geom_dotsinterval.R"
 ``ggdist-geom_interval.R" ``ggdist-geom_lineribbon.R"
 ``ggdist-geom_pointinterval.R" ``ggdist-lkycorr_marginal.R"
 ``ggdist-parse_dist.R" ``ggdist-scales.R"
 ``ggdist-stat_slabinterval.R" ``ggdist-stat_dist_slabinterval.R"
 ``ggdist-stat_sample_slabinterval.R"
 ``ggdist-stat_dotsinterval.R" ``ggdist-stat_pointinterval.R"
 ``ggdist-stat_interval.R" ``ggdist-stat_lineribbon.R"
 ``ggdist-student_t.R" ``ggdist-theme_ggdist.R"
 ``ggdist-tidy_format_translators.R" ``tidybayes-package.R"
 ``add_draws.R" ``combine_chains.R" ``compare_levels.R"
 ``compose_data.R" ``density_bins.R" ``emmeans_comparison.R"
 ``fitted_draws.R" ``flip_aes.R" ``gather_draws.R"
 ``gather_emmeans_draws.R" ``gather_pairs.R" ``gather_variables.R"
 ``get_variables.R" ``global_variables.R" ``onAttach.R"
 ``point_interval.R" ``predict_curve.R" ``predicted_draws.R"
 ``recover_types.R" ``residual_draws.R" ``sample_draws.R"
 ``spread_draws.R" ``tidy_draws.R" ``tidybayes-models.R"
 ``ungather_draws.R" ``unspread_draws.R" ``util.R" ``x_at_y.R"
 ``deprecated.R"

NeedsCompilation no**Author** Matthew Kay [aut, cre],
Timothy Mastny [ctb]**Repository** CRAN**Date/Publication** 2020-11-02 08:20:03 UTC**R topics documented:**

tidybayes-package	3
add_draws	4
add_fitted_draws	5
combine_chains	12
compare_levels	13
compose_data	16
data_list	18
density_bins	20
emmeans_comparison	21
gather_draws	23
gather_emmeans_draws	27
gather_pairs	29
gather_variables	32
get_variables	34
n_prefix	35
predict_curve	36
recover_types	38

<i>tidybayes-package</i>	3
sample_draws	40
tidybayes-deprecated	41
tidybayes-models	44
tidy_draws	46
ungather_draws	48
x_at_y	49
Index	51

tidybayes-package	<i>Tidy Data and 'Geoms' for Bayesian Models</i>
-------------------	--

Description

tidybayes is an R package that aims to make it easy to integrate popular Bayesian modeling methods into a tidy data + ggplot workflow.

Details

Tidy data frames (one observation per row) are particularly convenient for use in a variety of R data manipulation and visualization packages (Wickham 2014). However, when using Bayesian modeling functions like JAGS or Stan in R, we often have to translate this data into a form the model understands, and then after running the model, translate the resulting sample (or predictions) into a more tidy format for use with other R functions. tidybayes aims to simplify these two common (often tedious) operations. It also provides a variety of ggplot geometries aimed at making the visualization of model output easier.

For a comprehensive overview of the package, see `vignette("tidybayes")`. For overviews aimed at the `rstanarm` and `brms` packages, see `vignette("tidy-rstanarm")` and `vignette("tidy-brms")`. For an overview of the majority of geoms in the `ggdist/tidybayes` family, see `vignette("slabinterval", package = "ggdist")`.

For a list of supported models, see [tidybayes-models](#).

References

Wickham, Hadley. (2014). Tidy data. *Journal of Statistical Software*, 59(10), 1-23. doi: [10.18637/jss.v059.i10](https://doi.org/10.18637/jss.v059.i10).

 add_draws

Add draws to a data frame in tidy format

Description

Add draws from a matrix of draws (usually draws from a predictive distribution) to a data frame in tidy format. This is a generic version of `add_fitted_draws()/add_predicted_draws()` that can be used with model types that have their own prediction functions that are not yet supported by tidybayes.

Usage

```
add_draws(data, draws, value = ".value")
```

Arguments

data	Data frame to add draws to, with M rows.
draws	N by M matrix of draws, with M columns corresponding to the M rows in data, and N draws in each column.
value	The name of the output column; default ".value".

Details

Given a data frame with M rows and an N by M matrix of N draws, adds a `.row`, `.draw`, and `.value` column (or another name if `value` is set) to data, and expands data into a long-format dataframe of draws.

`add_fitted_draws(df, m)` is roughly equivalent to `add_draws(df, posterior_linpred(m, newdata = df, summary = FALSE))`, except that `add_fitted_draws` standardizes argument names and values across packages and has additional features for some model types (like handling ordinal responses and distributional parameters in brms).

`add_predicted_draws(df, m)` is roughly equivalent to `add_draws(df, posterior_predict(m, newdata = df, summary = FALSE))`, except that `add_predicted_draws` standardizes argument names and values across packages.

Value

A data frame (actually, a [tibble](#)) with a `.row` column (a factor grouping rows from the input data), a `.draw` column (a unique index corresponding to each draw from the distribution), and a column with its name specified by the `value` argument (default is `.value`) containing the values of draws from draws. The data frame is grouped by all rows in data plus the `.row` column.

Author(s)

Matthew Kay

See Also

[add_fitted_draws\(\)](#), [add_predicted_draws\(\)](#), [add_draws\(\)](#)

Examples

```
library(ggplot2)
library(dplyr)

if (
  require("brms", quietly = TRUE) &&
  require("modelr", quietly = TRUE)
) {

  theme_set(theme_light())

  m_mpg = brm(mpg ~ hp * cyl, data = mtcars,
    # 1 chain / few iterations just so example runs quickly
    # do not use in practice
    chains = 1, iter = 500)

  # plot posterior predictive intervals
  mtcars %>%
    group_by(cyl) %>%
    data_grid(hp = seq_range(hp, n = 101)) %>%
    # the line below is equivalent to add_fitted_draws(m_mpg), except that it does not
    # standardize arguments across model types. `summary = FALSE` is not strictly necessary
    # with posterior_linpred(), but because it is necessary on some functions (otherwise
    # those functions return summaries instead of a matrix of draws) it is
    # included in this example.
    add_draws(posterior_linpred(m_mpg, newdata = ., summary = FALSE)) %>%
    ggplot(aes(x = hp, y = mpg, color = ordered(cyl))) +
    stat_lineribbon(aes(y = .value), alpha = 0.25) +
    geom_point(data = mtcars) +
    scale_fill_brewer(palette = "Greys")
}
```

add_fitted_draws

Add draws from the posterior fit, predictions, or residuals of a model to a data frame

Description

Given a data frame and a model, adds draws from the (possibly transformed) posterior "fit" (aka the linear/link-level predictor), the posterior predictions of the model, or the residuals of a model to the data frame in a long format.

Usage

```
add_fitted_draws(  
  newdata,  
  model,  
  value = ".value",  
  ...,  
  n = NULL,  
  seed = NULL,  
  re_formula = NULL,  
  category = ".category",  
  dpar = FALSE,  
  scale = c("response", "linear")  
)
```

```
fitted_draws(  
  model,  
  newdata,  
  value = ".value",  
  ...,  
  n = NULL,  
  seed = NULL,  
  re_formula = NULL,  
  category = ".category",  
  dpar = FALSE,  
  scale = c("response", "linear")  
)
```

```
add_linpred_draws(  
  newdata,  
  model,  
  value = ".value",  
  ...,  
  n = NULL,  
  seed = NULL,  
  re_formula = NULL,  
  category = ".category",  
  dpar = FALSE,  
  scale = c("response", "linear")  
)
```

```
linpred_draws(  
  model,  
  newdata,  
  value = ".value",  
  ...,  
  n = NULL,  
  seed = NULL,  
  re_formula = NULL,
```

```
    category = ".category",
    dpar = FALSE,
    scale = c("response", "linear")
  )

## Default S3 method:
fitted_draws(model, newdata, ...)

## S3 method for class 'stanreg'
fitted_draws(
  model,
  newdata,
  value = ".value",
  ...,
  n = NULL,
  seed = NULL,
  re_formula = NULL,
  category = ".category",
  dpar = FALSE,
  scale = c("response", "linear")
)

## S3 method for class 'brmsfit'
fitted_draws(
  model,
  newdata,
  value = ".value",
  ...,
  n = NULL,
  seed = NULL,
  re_formula = NULL,
  category = ".category",
  dpar = FALSE,
  scale = c("response", "linear")
)

add_predicted_draws(
  newdata,
  model,
  prediction = ".prediction",
  ...,
  n = NULL,
  seed = NULL,
  re_formula = NULL,
  category = ".category"
)

predicted_draws(
```

```
    model,
    newdata,
    prediction = ".prediction",
    ...,
    n = NULL,
    seed = NULL,
    re_formula = NULL,
    category = ".category"
  )

## Default S3 method:
predicted_draws(model, newdata, ...)

## S3 method for class 'stanreg'
predicted_draws(
  model,
  newdata,
  prediction = ".prediction",
  ...,
  n = NULL,
  seed = NULL,
  re_formula = NULL,
  category = ".category"
)

## S3 method for class 'brmsfit'
predicted_draws(
  model,
  newdata,
  prediction = ".prediction",
  ...,
  n = NULL,
  seed = NULL,
  re_formula = NULL,
  category = ".category"
)

add_residual_draws(
  newdata,
  model,
  residual = ".residual",
  ...,
  n = NULL,
  seed = NULL,
  re_formula = NULL,
  category = ".category"
)
```



```

residual_draws(
  model,
  newdata,
  residual = ".residual",
  ...,
  n = NULL,
  seed = NULL,
  re_formula = NULL,
  category = ".category"
)

## Default S3 method:
residual_draws(model, newdata, ...)

## S3 method for class 'brmsfit'
residual_draws(
  model,
  newdata,
  residual = ".residual",
  ...,
  n = NULL,
  seed = NULL,
  re_formula = NULL,
  category = ".category"
)

```

Arguments

newdata	Data frame to generate predictions from. If omitted, most model types will generate predictions from the data used to fit the model.
model	A supported Bayesian model fit that can provide fits and predictions. Supported models are listed in the second section of tidybayes-models: Models Supporting Prediction . While other functions in this package (like spread_draws()) support a wider range of models, to work with <code>add_fitted_draws</code> and <code>add_predicted_draws</code> a model must provide an interface for generating predictions, thus more generic Bayesian modeling interfaces like <code>runjags</code> and <code>rstan</code> are not directly supported for these functions (only wrappers around those languages that provide predictions, like <code>rstanarm</code> and <code>brm</code> , are supported here).
value	The name of the output column for <code>fitted_draws</code> ; default <code>".value"</code> .
...	Additional arguments passed to the underlying prediction method for the type of model given.
n	The number of draws per prediction / fit to return, or <code>NULL</code> to return all draws.
seed	A seed to use when subsampling draws (i.e. when <code>n</code> is not <code>NULL</code>).
re_formula	formula containing group-level effects to be considered in the prediction. If <code>NULL</code> (default), include all group-level effects; if <code>NA</code> , include no group-level effects. Some model types (such as brms::brmsfit and rstanarm::stanreg-objects) allow marginalizing over grouping factors by specifying new levels of a factor in

	newdata. In the case of <code>brms::brm()</code> , you must also pass <code>allow_new_levels = TRUE</code> here to include new levels (see <code>brms::predict.brmsfit()</code>).
category	For <i>some</i> ordinal, multinomial, and multivariate models (notably, <code>brms::brm()</code> models but <i>not</i> <code>rstanarm::stan_polr()</code> models), multiple sets of rows will be returned per input row for <code>fitted_draws</code> or <code>predicted_draws</code> , depending on the model type. For ordinal/multinomial models, these rows correspond to different categories of the response variable. For multivariate models, these correspond to different response variables. The <code>category</code> argument specifies the name of the column to put the category names (or variable names) into in the resulting data frame. The default name of this column (<code>".category"</code>) reflects the fact that this functionality was originally used only for ordinal models and has been re-used for multivariate models. The fact that multiple rows per response are returned only for some model types reflects the fact that <code>tidybayes</code> takes the approach of tidying whatever output is given to us, and the output from different modeling functions differs on this point. See <code>vignette("tidy-brms")</code> and <code>vignette("tidy-rstanarm")</code> for examples of dealing with output from ordinal models using both approaches.
dpar	For <code>fitted_draws</code> and <code>add_fitted_draws</code> : Should distributional regression parameters be included in the output? Valid only for models that support distributional regression parameters, such as submodels for variance parameters (as in <code>brm</code>). If <code>TRUE</code> , distributional regression parameters are included in the output as additional columns named after each parameter (alternative names can be provided using a list or named vector, e.g. <code>c(sigma.hat = "sigma")</code> would output the "sigma" parameter from a model as a column named "sigma.hat"). If <code>FALSE</code> (the default), distributional regression parameters are not included.
scale	Either "response" or "linear". If "response", results are returned on the scale of the response variable. If "linear", fitted values are returned on the scale of the linear predictor.
prediction	The name of the output column for <code>predicted_draws</code> ; default <code>".prediction"</code> .
residual	The name of the output column for <code>residual_draws</code> ; default <code>".residual"</code> .

Details

`add_fitted_draws` adds draws from (possibly transformed) posterior linear predictors (or "link-level" predictors) to the data. It corresponds to `rstanarm::posterior_linpred()` in `rstanarm` or `brms::fitted.brmsfit()` in `brms`.

`add_predicted_draws` adds draws from posterior predictions to the data. It corresponds to `rstanarm::posterior_predict()` in `rstanarm` or `brms::predict.brmsfit()` in `brms`.

`add_fitted_draws` and `fitted_draws` are alternate spellings of the same function with opposite order of the first two arguments to facilitate use in data processing pipelines that start either with a data frame or a model. Similarly, `add_predicted_draws` and `predicted_draws` are alternate spellings.

Given equal choice between the two, `add_fitted_draws` and `add_predicted_draws` are the preferred spellings.

`add_linpred_draws` and `linpred_draws` are alternative spellings of `fitted_draws` and `add_fitted_draws` for consistency with `rstanarm` terminology (specifically `rstanarm::posterior_linpred()`).

Value

A data frame (actually, a [tibble](#)) with a `.row` column (a factor grouping rows from the input `newdata`), `.chain` column (the chain each draw came from, or NA if the model does not provide chain information), `.iteration` column (the iteration the draw came from, or NA if the model does not provide iteration information), and a `.draw` column (a unique index corresponding to each draw from the distribution). In addition, `fitted_draws` includes a column with its name specified by the `value` argument (default is `.value`) containing draws from the (transformed) linear predictor, and `predicted_draws` contains a `.prediction` column containing draws from the posterior predictive distribution. For convenience, the resulting data frame comes grouped by the original input rows.

Author(s)

Matthew Kay

See Also

[add_draws\(\)](#) for the variant of these functions for use with packages that do not have explicit support for these functions yet. See [spread_draws\(\)](#) for manipulating posteriors directly.

Examples

```
library(ggplot2)
library(dplyr)

if (
  require("brms", quietly = TRUE) &&
  require("modelr", quietly = TRUE)
) {

  theme_set(theme_light())

  m_mpg = brm(mpg ~ hp * cyl, data = mtcars,
    # 1 chain / few iterations just so example runs quickly
    # do not use in practice
    chains = 1, iter = 500)

  # draw 100 fit lines from the posterior and overplot them
  mtcars %>%
    group_by(cyl) %>%
    data_grid(hp = seq_range(hp, n = 101)) %>%
    add_fitted_draws(m_mpg, n = 100) %>%
    ggplot(aes(x = hp, y = mpg, color = ordered(cyl))) +
    geom_line(aes(y = .value, group = paste(cyl, .draw)), alpha = 0.25) +
    geom_point(data = mtcars)

  # plot posterior predictive intervals
  mtcars %>%
    group_by(cyl) %>%
    data_grid(hp = seq_range(hp, n = 101)) %>%
```

```

add_predicted_draws(m_mpg) %>%
  ggplot(aes(x = hp, y = mpg, color = ordered(cyl))) +
  stat_lineribbon(aes(y = .prediction), .width = c(.99, .95, .8, .5), alpha = 0.25) +
  geom_point(data = mtcars) +
  scale_fill_brewer(palette = "Greys")
}

```

combine_chains

Combine the chain and iteration columns of tidy data frames of draws

Description

Combines the chain and iteration columns of a tidy data frame of draws from a Bayesian model fit into a new column that can uniquely identify each draw. Generally speaking **not needed for pure tidybayes code**, as tidybayes functions now automatically include a `.draw` column, but can be useful when interacting with packages that do not provide such a column.

Usage

```
combine_chains(data, chain = .chain, iteration = .iteration, into = ".draw")
```

Arguments

<code>data</code>	Tidy data frame of draws with columns representing the chain and iteration of each draw.
<code>chain</code>	Bare name of column in data indicating the chain of each row. The default (<code>.chain</code>) is the same as used by other functions in tidybayes.
<code>iteration</code>	Bare name of column in data indicating the iteration of each row. The default (<code>.iteration</code>) is the same as used by other functions in tidybayes.
<code>into</code>	Name (as a character vector) of the column to combine chains into. The default, <code>NULL</code> , replaces the chain column with NAs and writes the combined chain iteration numbers into <code>iteration</code> . If provided, <code>chain</code> and <code>iteration</code> will not be modified, and the combined iteration number will be written into a new column named <code>into</code> .

Value

A data frame of tidy draws with a combined iteration column

Author(s)

Matthew Kay

See Also

[emmeans::emmeans\(\)](#)

Examples

```

library(magrittr)
library(coda)

data(line, package = "coda")

# The `line` posterior has two chains with 200 iterations each:
line %>%
  tidy_draws() %>%
  summary()

# combine_chains combines the chain and iteration column into the .draw column.
line %>%
  tidy_draws() %>%
  combine_chains() %>%
  summary()

```

compare_levels	<i>Compare the value of draws of some variable from a Bayesian model for different levels of a factor</i>
----------------	---

Description

Given posterior draws from a Bayesian model in long format (e.g. as returned by [spread_draws\(\)](#)), compare the value of a variable in those draws across different paired combinations of levels of a factor.

Usage

```

compare_levels(
  data,
  variable,
  by,
  fun = `~`,
  comparison = "default",
  draw_indices = c(".chain", ".iteration", ".draw"),
  ignore_groups = ".row"
)

```

Arguments

data	Long-format data.frame of draws such as returned by spread_draws() or gather_draws() . If data is a grouped data frame, comparisons will be made within groups (if one of the groups in the data frame is the by column, that specific group will be ignored, as it is not possible to make comparisons both within some variable and across it simultaneously).
------	--

variable	Bare (unquoted) name of a column in data representing the variable to compare across levels.
by	Bare (unquoted) name of a column in data that is a factor or ordered. The value of <code>variable</code> will be compared across pairs of levels of this factor.
fun	Binary function to use for comparison. For each pair of levels of <code>by</code> we are comparing (as determined by <code>comparison</code>), compute the result of this function.
comparison	One of (a) the comparison types <code>ordered</code> , <code>control</code> , <code>pairwise</code> , or <code>default</code> (may also be given as strings, e.g. <code>"ordered"</code>), see <i>Details</i> ; (b) a user-specified function that takes a factor and returns a list of pairs of names of levels to compare (as strings) and/or unevaluated expressions containing representing the comparisons to make; or (c) a list of pairs of names of levels to compare (as strings) and/or unevaluated expressions representing the comparisons to make, e.g.: <code>list(c("a", "b"), c("b", "c"))</code> or <code>exprs(a - b, b - c)</code> , both of which would compare level "a" against "b" and level "b" against "c". Note that the unevaluated expression syntax ignores the <code>fun</code> argument, can include any other functions desired (e.g. variable transformations), and can even include more than two levels or other columns in data. Types (b) and (c) may use named lists, in which case the provided names are used in the output <code>variable</code> column instead converting the unevaluated expression to a string. You can also use <code>emmeans_comparison()</code> to generate a comparison function based on contrast methods from the <code>emmeans</code> package.
draw_indices	Character vector of column names in data that should be treated as indices when making the comparison (i.e. values of <code>variable</code> within each level of <code>by</code> will be compared at each unique combination of levels of <code>draw_indices</code>). Columns in <code>draw_indices</code> not found in data are ignored. The default is <code>c(".chain", ".iteration", ".draw")</code> , which are the same names used for chain/iteration/draw indices returned by <code>spread_draws()</code> or <code>gather_draws()</code> ; thus if you are using <code>compare_levels</code> with <code>spread_draws()</code> or <code>gather_draws()</code> you generally should not need to change this value.
ignore_groups	character vector of names of groups to ignore by default in the input grouping. This is primarily provided to make it easier to pipe output of <code>add_fitted_draws()</code> into this function, as that function provides a <code>".row"</code> output column that is grouped, but which is virtually never desired to group by when using <code>compare_levels</code> .

Details

This function simplifies conducting comparisons across levels of some variable in a tidy data frame of draws. It applies `fun` to all values of `variable` for each pair of levels of `by` as selected by `comparison`. By default, all pairwise comparisons are generated if `by` is an unordered factor and ordered comparisons are made if `by` is ordered.

The included comparison types are:

- `ordered`: compare each level `i` with level `i - 1`; e.g. `fun(i, i - 1)`
- `pairwise`: compare each level of `by` with every other level.
- `control`: compare each level of `by` with the first level of `by`. If you wish to compare with a different level, you can first apply `relevel()` to `by` to set the control (reference) level.
- `default`: use `ordered` if `is.ordered(by)` and `pairwise` otherwise.

Value

A data.frame with the same columns as data, except that the by column contains a symbolic representation of the comparison of pairs of levels of by in data, and variable contains the result of that comparison.

Author(s)

Matthew Kay

See Also

[emmeans_comparison\(\)](#) to use emmeans-style contrast methods with [compare_levels\(\)](#).

Examples

```
library(dplyr)
library(ggplot2)

data(RankCorr, package = "ggdist")

# Let's do all pairwise comparisons of b[i,1]:
RankCorr %>%
  spread_draws(b[i,j]) %>%
  filter(j == 1) %>%
  compare_levels(b, by = i) %>%
  median_qi()

# Or let's plot all comparisons against the first level (control):
RankCorr %>%
  spread_draws(b[i,j]) %>%
  filter(j == 1) %>%
  compare_levels(b, by = i, comparison = control) %>%
  ggplot(aes(x = b, y = i)) +
  stat_halfeye()

# Or let's plot comparisons of all levels of j within
# all levels of i
RankCorr %>%
  spread_draws(b[i,j]) %>%
  group_by(i) %>%
  compare_levels(b, by = j) %>%
  ggplot(aes(x = b, y = j)) +
  stat_halfeye() +
  facet_grid(cols = vars(i))
```

 compose_data

Compose data for input into a Bayesian model

Description

Compose data into a list suitable to be passed into a Bayesian model (JAGS, BUGS, Stan, etc).

Usage

```
compose_data(..., .n_name = n_prefix("n"))
```

Arguments

...	Data to be composed into a list suitable for being passed into Stan, JAGS, etc. Named arguments will have their name used as the name argument to <code>as_data_list</code> when translated; unnamed arguments that are not lists or data frames will have their bare value (passed through <code>make.names</code>) used as the name argument to <code>as_data_list</code> . Each argument is evaluated using <code>eval_tidy</code> in an environment that includes all list items composed so far.
.n_name	A function that is used to form dimension index variables (a variable whose value is number of levels in a factor or the length of a data frame in ...). For example, if a data frame with 20 rows and a factor "foo" (having 3 levels) is passed to <code>compose_data</code> , the list returned by <code>compose_data</code> will include an element named <code>.n_name("foo")</code> , which by default would be "n_foo", containing the value 3, and a column named "n" containing the value 20. See <code>n_prefix()</code> .

Details

This function recursively translates each argument into list elements using `as_data_list()`, merging all resulting lists together. By default this means that:

- numerics are included as-is.
- logicals are translated into numeric using `as.numeric()`.
- factors are translated into numeric using `as.numeric()`, and an additional element named `.n_name(argument_name)` is added with the number of levels in the factor. The default `.n_name` function prefixes "n_" before the factor name; e.g. a factor named `foo` will have an element named `n_foo` added containing the number of levels in `foo`.
- character vectors are converted into factors then translated into numeric in the same manner as factors are.
- lists are translated by translating all elements of the list (recursively) and adding them to the result.
- data.frames are translated by translating every column of the data.frame and adding them to the result. A variable named "n" (or `.n_name(argument_name)` if the data.frame is passed as a named argument `argument_name`) is also added containing the number of rows in the data frame.

- NULL values are dropped. Setting a named argument to NULL can be used to drop that item from the resulting list (if an unwanted element was added to the list by a previous argument, such as a column from a data frame that is not needed in the model).
- all other types are dropped (and a warning given)

As in functions like `mutate()`, each expression is evaluated in an environment containing the data list built up so far.

For example, this means that if the first argument to `compose_data` is a data frame, subsequent arguments can include direct references to columns from that data frame. This allows you, for example, to easily use `x_at_y()` to generate indices for nested models.

If you wish to add support for additional types not described above, provide an implementation of `as_data_list()` for the type. See the implementations of `as_data_list.numeric`, `as_data_list.logical`, etc for examples.

Value

A list where each element is a translated variable as described above.

Author(s)

Matthew Kay

See Also

`x_at_y()`, `spread_draws()`, `gather_draws()`.

Examples

```
library(magrittr)

df = data.frame(
  plot = factor(paste0("p", rep(1:8, times = 2))),
  site = factor(paste0("s", rep(1:4, each = 2, times = 2)))
)

# without changing `n_name`, compose_data() will prefix indices
# with "n" by default
df %>%
  compose_data()

# you can use n_prefix() to define a different prefix (e.g. "N"):
df %>%
  compose_data(.n_name = n_prefix("N"))

# If you have nesting, you may want a nested index, which can be generated using x_at_y()
# Here, site[p] will give the site for plot p
df %>%
  compose_data(site = x_at_y(site, plot))
```

Description

Functions used by `compose_data()` to create lists of data suitable for input into a Bayesian modeling function. **These functions typically should not be called directly** (instead use `compose_data()`), but are exposed for the rare cases in which you may need to provide your own conversion routines for a data type not already supported (see *Details*).

Usage

```
data_list(...)

as_data_list(object, name = "", ...)

## Default S3 method:
as_data_list(object, name = "", ...)

## S3 method for class 'numeric'
as_data_list(object, name = "", scalar_as_array = FALSE, ...)

## S3 method for class 'logical'
as_data_list(object, name = "", ...)

## S3 method for class 'factor'
as_data_list(object, name = "", .n_name = n_prefix("n"), ...)

## S3 method for class 'character'
as_data_list(object, name = "", ...)

## S3 method for class 'list'
as_data_list(object, name = "", ...)

## S3 method for class 'data.frame'
as_data_list(object, name = "", .n_name = n_prefix("n"), ...)

## S3 method for class 'data_list'
as_data_list(object, name = "", ...)
```

Arguments

...	Additional arguments passed to other implementations of <code>as_data_list</code> , or for <code>data_list</code> , passed to <code>list()</code> .
object	The object to convert (see <i>Details</i>).
name	The name of the element in the returned list corresponding to this object.

scalar_as_array	If TRUE, returns single scalars as an 1-dimensional array with one element. This is used by <code>as_data_list.data.frame</code> to ensure that columns from a data frame with only one row are still returned as arrays instead of scalars.
.n_name	A function that is used to form variables storing the number of rows in data frames or the number of levels in factors in <code>...</code> . For example, if a factor with <code>name = "foo"</code> (having three levels) is passed in, the list returned will include an element named <code>.n_name("foo")</code> , which by default would be "n_foo", containing the value 3.

Details

`data_list` creates a list with class `c("data_list", "list")` instead of `c("list")`, but largely otherwise acts like the `list()` function.

`as_data_list` recursively translates its first argument into list elements, concatenating all resulting lists together. By default this means that:

- numerics are included as-is.
- logicals are translated into numeric using `as.numeric()`.
- factors are translated into numeric using `as.numeric()`, and an additional element named `.n_name(name)` is added with the number of levels in the factor.
- character vectors are converted into factors then translated into numeric in the same manner as factors are.
- lists are translated by translating all elements of the list (recursively) and adding them to the result.
- data.frames are translated by translating every column of the data.frame and adding them to the result. A variable named "n" (or `.n_name(name)` if `name` is not "") is also added containing the number of rows in the data frame.
- all other types are dropped (and a warning given)

If you wish to add support for additional types not described above, provide an implementation of `as_data_list()` for the type. See the implementations of `as_data_list.numeric`, `as_data_list.logical`, etc for examples.

Value

An object of class `c("data_list", "list")`, where each element is a translated variable as described above.

Author(s)

Matthew Kay

See Also

[compose_data\(\)](#).

Examples

```
# Typically these functions should not be used directly.
# See the compose_data function for examples of how to translate
# data in lists for input to Bayesian modeling functions.
```

density_bins	<i>Density bins and histogram bins as data frames</i>
--------------	---

Description

Generates a data frame of bins representing the kernel density (or histogram) of a vector, suitable for use in generating predictive distributions for visualization. These functions were originally designed for use with the now-deprecated `predict_curve()`, and may be deprecated in the future.

Usage

```
density_bins(x, n = 101, ...)
histogram_bins(x, n = 30, breaks = n, ...)
```

Arguments

x	A numeric vector
n	Number of bins
...	Additional arguments passed to <code>density()</code> or <code>hist()</code> .
breaks	Used to set bins for <code>histogram_bins</code> . Can be number of bins (by default it is set to the value of n) or a method for setting bins. See the breaks argument of <code>hist()</code> .

Details

These functions are simple wrappers to `density()` and `hist()` that compute density estimates and return their results in a consistent format: a data frame of bins suitable for use with the now-deprecated `predict_curve()`.

`density_bins` computes a kernel density estimate using `density()`.

`histogram_bins` computes a density histogram using `hist()`.

Value

A data frame representing bins and their densities with the following columns:

mid	Bin midpoint
lower	Lower endpoint of each bin
upper	Upper endpoint of each bin
density	Density estimate of the bin

Author(s)

Matthew Kay

See Also

See [add_predicted_draws\(\)](#) and [stat_lineribbon\(\)](#) for a better approach. These functions may be deprecated in the future.

Examples

```
library(ggplot2)
library(dplyr)
library(purrr)
library(tidyr)

if (
  require("brms", quietly = TRUE) &&
  require("modelr", quietly = TRUE)
) {

  theme_set(theme_light())

  m_mpg = brm(mpg ~ hp * cyl, data = mtcars)

  step = 1
  mtcars %>%
    group_by(cyl) %>%
    data_grid(hp = seq_range(hp, by = step)) %>%
    add_predicted_draws(m_mpg) %>%
    summarise(densities = list(density_bins(.prediction))) %>%
    unnest(densities) %>%
    ggplot() +
    geom_rect(aes(
      xmin = hp - step/2, ymin = lower, ymax = upper, xmax = hp + step/2,
      fill = ordered(cyl), alpha = density
    )) +
    geom_point(aes(x = hp, y = mpg, fill = ordered(cyl)), shape = 21, data = mtcars) +
    scale_alpha_continuous(range = c(0, 1)) +
    scale_fill_brewer(palette = "Set2")
}
```

emmeans_comparison *Use emmeans contrast methods with compare_levels*

Description

Convert [emmeans contrast methods](#) into comparison functions suitable for use with [compare_levels\(\)](#).

Usage

```
emmeans_comparison(method, ...)
```

Arguments

method	An emmeans-style contrast method. One of: (1) a string specifying the name of an emmeans contrast method , like "pairwise", "trt.vs.ctrl", "eff"; or (2) an emmeans-style contrast function itself, like emmeans::pairwise.emmc , emmeans::trt.vs.ctrl.emmc , etc, or a custom function that takes a vector of factor levels and returns a contrast matrix.
...	Arguments passed on to the contrast method.

Details

Given an [emmeans contrast method](#) name as a string (e.g., "pairwise", "trt.vs.ctrl", etc) or an emmeans-style contrast function (e.g., [emmeans::pairwise.emmc](#), [emmeans::trt.vs.ctrl.emmc](#), etc), `emmeans_comparison()` returns a new function that can be used in the comparison argument to `compare_levels()` to compute those contrasts.

Value

A function that takes a single argument, `var`, containing a variable to generate contrasts for (e.g., a factor or a character vector) and returns a function that generates a list of named unevaluated expressions representing different contrasts of that variable. This function is suitable to be used as the comparison argument in `compare_levels()`.

Author(s)

Matthew Kay

See Also

[compare_levels\(\)](#), [emmeans::contrast-methods](#). See [gather_emmeans_draws\(\)](#) for a different approach to using emmeans with tidybayes.

Examples

```
if (requireNamespace("emmeans", quietly = TRUE)) {
  library(dplyr)
  library(ggplot2)

  data(RankCorr, package = "ggdist")

  # emmeans contrast methods return matrices. E.g. the "eff" comparison
  # compares each level to the average of all levels:
  print(emmeans:::eff.emmc(c("a", "b", "c", "d")))

  # tidybayes::compare_levels() can't use a contrast matrix like this
```

```

# directly; it takes arbitrary expressions of factor levels. But
# we can use `emmeans_comparison` to generate the equivalent expressions:
print(emmeans_comparison("eff")(c("a", "b", "c", "d")))

# We can use the "eff" comparison type with `compare_levels()` as follows:
RankCorr %>%
  spread_draws(b[i,j]) %>%
  filter(j == 1) %>%
  compare_levels(b, by = i, comparison = emmeans_comparison("eff")) %>%
  median_qi()
}

```

gather_draws	<i>Extract draws of variables in a Bayesian model fit into a tidy data format</i>
--------------	---

Description

Extract draws from a Bayesian model for one or more variables (possibly with named dimensions) into one of two types of long-format data frames.

Usage

```
gather_draws(model, ..., regex = FALSE, sep = "[, ]", n = NULL, seed = NULL)
```

```
spread_draws(model, ..., regex = FALSE, sep = "[, ]", n = NULL, seed = NULL)
```

Arguments

model	A supported Bayesian model fit. Tidybayes supports a variety of model objects; for a full list of supported models, see tidybayes-models .
...	Expressions in the form of <code>variable_name[dimension_1,dimension_2,...]</code> <code>wide_dimension</code> . See <i>Details</i> .
regex	If TRUE, variable names are treated as regular expressions and all column matching the regular expression and number of dimensions are included in the output. Default FALSE.
sep	Separator used to separate dimensions in variable names, as a regular expression.
n	The number of draws to return, or NULL to return all draws.
seed	A seed to use when subsampling draws (i.e. when n is not NULL).

Details

Imagine a JAGS or Stan fit named `fit`. The model may contain a variable named `b[i,v]` (in the JAGS or Stan language) with dimension `i` in `1:100` and dimension `v` in `1:3`. However, the default format for draws returned from JAGS or Stan in R will not reflect this indexing structure, instead they will have multiple columns with names like `"b[1,1]"`, `"b[2,1]"`, etc.

`spread_draws` and `gather_draws` provide a straightforward syntax to translate these columns back into properly-indexed variables in two different tidy data frame formats, optionally recovering dimension types (e.g. factor levels) as it does so.

`spread_draws` and `gather_draws` return data frames already grouped by all dimensions used on the variables you specify.

The difference between `spread_draws` is that names of variables in the model will be spread across the data frame as column names, whereas `gather_draws` will gather variables into a single column named `".variable"` and place values of variables into a column named `".value"`. To use naming schemes from other packages (such as `broom`), consider passing results through functions like `to_broom_names()` or `to_ggmcmc_names()`.

For example, `spread_draws(fit, a[i], b[i, v])` might return a grouped data frame (grouped by `i` and `v`), with:

- column `".chain"`: the chain number. NA if not applicable to the model type; this is typically only applicable to MCMC algorithms.
- column `".iteration"`: the iteration number. Guaranteed to be unique within-chain only. NA if not applicable to the model type; this is typically only applicable to MCMC algorithms.
- column `".draw"`: a unique number for each draw from the posterior. Order is not guaranteed to be meaningful.
- column `"i"`: value in 1:5
- column `"v"`: value in 1:10
- column `"a"`: value of `"a[i]"` for draw `".draw"`
- column `"b"`: value of `"b[i, v]"` for draw `".draw"`

`gather_draws(fit, a[i], b[i, v])` on the same fit would return a grouped data frame (grouped by `i` and `v`), with:

- column `".chain"`: the chain number
- column `".iteration"`: the iteration number
- column `".draw"`: the draw number
- column `"i"`: value in 1:5
- column `"v"`: value in 1:10, or NA if `".variable"` is `"a"`.
- column `".variable"`: value in `c("a", "b")`.
- column `".value"`: value of `"a[i]"` (when `".variable"` is `"a"`) or `"b[i, v]"` (when `".variable"` is `"b"`) for draw `".draw"`

`spread_draws` and `gather_draws` can use type information applied to the `fit` object by `recover_types()` to convert columns back into their original types. This is particularly helpful if some of the dimensions in your model were originally factors. For example, if the `v` dimension in the original data frame data was a factor with levels `c("a", "b", "c")`, then we could use `recover_types` before `spread_draws`:

```
fit %>%
  recover_types(data)
  spread_draws(fit, b[i, v])
```


Which would return the same data frame as above, except the "v" column would be a value in `c("a", "b", "c")` instead of `1:3`.

For variables that do not share the same subscripts (or share some but not all subscripts), we can supply their specifications separately. For example, if we have a variable `d[i]` with the same `i` subscript as `b[i,v]`, and a variable `x` with no subscripts, we could do this:

```
spread_draws(fit, x, d[i], b[i,v])
```

Which is roughly equivalent to this:

```
spread_draws(fit, x) %>%
  inner_join(spread_draws(fit, d[i])) %>%
  inner_join(spread_draws(fit, b[i,v])) %>%
  group_by(i,v)
```

Similarly, this:

```
gather_draws(fit, x, d[i], b[i,v])
```

Is roughly equivalent to this:

```
bind_rows(
  gather_draws(fit, x),
  gather_draws(fit, d[i]),
  gather_draws(fit, b[i,v])
)
```

The `c` and `cbind` functions can be used to combine multiple variable names that have the same dimensions. For example, if we have several variables with the same subscripts `i` and `v`, we could do either of these:

```
spread_draws(fit, c(w, x, y, z)[i,v])
```

```
spread_draws(fit, cbind(w, x, y, z)[i,v]) # equivalent
```

Each of which is roughly equivalent to this:

```
spread_draws(fit, w[i,v], x[i,v], y[i,v], z[i,v])
```

Besides being more compact, the `c()`-style syntax is currently also faster (though that may change).

Dimensions can be omitted from the resulting data frame by leaving their names blank; e.g. `spread_draws(fit, b[,v])` will omit the first dimension of `b` from the output. This is useful if a dimension is known to contain all the same value in a given model.

The shorthand `..` can be used to specify one column that should be put into a wide format and whose names will be the base variable name, plus a dot ("`.`"), plus the value of the dimension at `...`. For example:

```
spread_draws(fit, b[i, ..])
```

would return a grouped data frame (grouped by `i`), with:

- column ".chain": the chain number
- column ".iteration": the iteration number
- column ".draw": the draw number
- column "i": value in 1:20
- column "b.1": value of "b[i,1]" for draw ".draw"
- column "b.2": value of "b[i,2]" for draw ".draw"
- column "b.3": value of "b[i,3]" for draw ".draw"

An optional clause in the form `| wide_dimension` can also be used to put the data frame into a wide format based on `wide_dimension`. For example, this:

```
spread_draws(fit, b[i,v] | v)
```

is roughly equivalent to this:

```
spread_draws(fit, b[i,v]) %>% spread(v,b)
```

The main difference between using the `|` syntax instead of the `..` syntax is that the `|` syntax respects prototypes applied to dimensions with `recover_types()`, and thus can be used to get columns with nicer names. For example:

```
fit %>% recover_types(data) %>% spread_draws(b[i,v] | v)
```

would return a grouped data frame (grouped by `i`), with:

- column ".chain": the chain number
- column ".iteration": the iteration number
- column ".draw": the draw number
- column "i": value in 1:20
- column "a": value of "b[i,1]" for draw ".draw"
- column "b": value of "b[i,2]" for draw ".draw"
- column "c": value of "b[i,3]" for draw ".draw"

The shorthand `.` can be used to specify columns that should be nested into vectors, matrices, or n-dimensional arrays (depending on how many dimensions are specified with `.`).

For example, `spread_draws(fit, a[.], b[.])` might return a data frame, with:

- column ".chain": the chain number.
- column ".iteration": the iteration number.
- column ".draw": a unique number for each draw from the posterior.
- column "a": a list column of vectors.
- column "b": a list column of matrices.

Ragged arrays are turned into non-ragged arrays with missing entries given the value NA.

Finally, variable names can be regular expressions by setting `regex = TRUE`; e.g.:

```
spread_draws(fit, `b_.*`[i], regex = TRUE)
```

Would return a tidy data frame with variables starting with `b_` and having one dimension.

Value

A data frame.

Author(s)

Matthew Kay

See Also

[recover_types\(\)](#), [compose_data\(\)](#).

Examples

```
library(dplyr)
library(ggplot2)

data(RankCorr, package = "ggdist")

RankCorr %>%
  spread_draws(b[i, j])

RankCorr %>%
  spread_draws(b[i, j], tau[i], u_tau[i])

RankCorr %>%
  gather_draws(b[i, j], tau[i], u_tau[i])

RankCorr %>%
  gather_draws(tau[i], typical_r) %>%
  median_qi()
```

`gather_emmeans_draws` *Extract a tidy data frame of draws of posterior distributions of "estimated marginal means" (emmeans/lmeans) from a Bayesian model fit.*

Description

Extract draws from the result of a call to `emmeans::emmeans()` (formerly `lsmeans`) or `emmeans::ref_grid()` applied to a Bayesian model.

Usage

```
gather_emmeans_draws(object, value = ".value", ...)

## Default S3 method:
gather_emmeans_draws(object, value = ".value", ...)

## S3 method for class 'emm_list'
gather_emmeans_draws(object, value = ".value", grid = ".grid", ...)
```

Arguments

object	An emmGrid object such as returned by <code>emmeans::ref_grid()</code> or <code>emmeans::emmeans()</code> .
value	The name of the output column to use to contain the values of draws. Defaults to <code>".value"</code> .
...	Additional arguments passed to the underlying method for the type of object given.
grid	If object is an <code>emmeans::emm_list()</code> , the name of the output column to use to contain the name of the reference grid that a given row corresponds to. Defaults to <code>".grid"</code> .

Details

`emmeans::emmeans()` provides a convenient syntax for generating draws from "estimated marginal means" from a model, and can be applied to various Bayesian models, like `rstanarm::stanreg-objects` and `MCMCglmm::MCMCglmm()`. Given a `emmeans::ref_grid()` object as returned by functions like `emmeans::ref_grid()` or `emmeans::emmeans()` applied to a Bayesian model, `gather_emmeans_draws` returns a tidy format data frame of draws from the marginal posterior distributions generated by `emmeans::emmeans()`.

Value

A tidy data frame of draws. The columns of the reference grid are returned as-is, with an additional column called `.value` (by default) containing marginal draws. The resulting data frame is grouped by the columns from the reference grid to make use of summary functions like `point_interval()` straightforward.

If object is an `emmeans::emm_list()`, which contains estimates from different reference grids, an additional column with the default name of `".grid"` is added to indicate the reference grid for each row in the output. The name of this column is controlled by the `grid` argument.

Author(s)

Matthew Kay

See Also

`emmeans::emmeans()`

Examples

```

library(dplyr)
library(magrittr)

if (
  require("brms", quietly = TRUE) &&
  require("emmeans", quietly = TRUE)
) {

  # Here's an example dataset with a categorical predictor (`condition`) with several levels:
  set.seed(5)
  n = 10
  n_condition = 5
  ABC =
    tibble(
      condition = rep(c("A", "B", "C", "D", "E"), n),
      response = rnorm(n * 5, c(0,1,2,1,-1), 0.5)
    )

  m = brm(response ~ condition, data = ABC,
    # 1 chain / few iterations just so example runs quickly
    # do not use in practice
    chains = 1, iter = 500)

  # Once we've fit the model, we can use emmeans() (and functions
  # from that package) to get whatever marginal distributions we want.
  # For example, we can get marginal means by condition:
  m %>%
    emmeans(~ condition) %>%
    gather_emmeans_draws() %>%
    median_qi()

  # or we could get pairwise differences:
  m %>%
    emmeans(~ condition) %>%
    contrast(method = "pairwise") %>%
    gather_emmeans_draws() %>%
    median_qi()

  # see the documentation of emmeans() for more examples of types of
  # contrasts supported by that package.
}

```

Description

Fast method for producing combinations of values in a value column for different levels of a key column, assuming long-format (tidy) data with an equal number of values per key. Among other things, this is useful for producing scatter-plot matrices.

Usage

```
gather_pairs(
  data,
  key,
  value,
  row = ".row",
  col = ".col",
  x = ".x",
  y = ".y",
  triangle = c("lower only", "upper only", "lower", "upper", "both only", "both")
)
```

Arguments

data	Tidy data frame.
key	Bare name of column in data containing the key .
value	Bare name of column in data containing the value.
row	Character vector giving the name of the output column identifying rows in the matrix of pairs (takes values of key).
col	Character vector giving the name of the output column identifying columns in the matrix of pairs (takes values of key).
x	Character vector giving the name of the output column with x values in the matrix of pairs (takes values of value).
y	Character vector giving the name of the output column with y values in the matrix of pairs (takes values of value).
triangle	Should the upper or lower triangle of the matrix of all possible combinations be returned? The default, "lower only", returns the lower triangle without the diagonal; "lower" returns the lower triangle with the diagonal ("upper" and "upper only" operate analogously), "both" returns the full set of possible combinations, and "both only" returns all combinations except the diagonal. This method is particularly useful for constructing scatterplot matrices. See examples below.

Value

A tidy data frame of combinations of values in key and value, with columns row and col (default names ".row" and ".col") containing values from key, and columns y and x (default names ".y" and ".x") containing values from value.

Author(s)

Matthew Kay

See Also[emmeans::emmeans\(\)](#)**Examples**

```
library(ggplot2)
library(dplyr)

t_a = rnorm(100)
t_b = rnorm(100, t_a * 2)
t_c = rnorm(100)

df = rbind(
  data.frame(g = "a", t = t_a),
  data.frame(g = "b", t = t_b),
  data.frame(g = "c", t = t_c)
)

df %>%
  gather_pairs(g, t, row = "g_row", col = "g_col", x = "t_x", y = "t_y") %>%
  ggplot(aes(t_x, t_y)) +
  geom_point() +
  facet_grid(vars(g_row), vars(g_col))

df %>%
  gather_pairs(g, t, triangle = "upper") %>%
  ggplot(aes(.x, .y)) +
  geom_point() +
  facet_grid(vars(.row), vars(.col))

df %>%
  gather_pairs(g, t, triangle = "both") %>%
  ggplot(aes(.x, .y)) +
  geom_point() +
  facet_grid(vars(.row), vars(.col))

data(line, package = "coda")

line %>%
  tidy_draws() %>%
  gather_variables() %>%
  gather_pairs(.variable, .value) %>%
  ggplot(aes(.x, .y)) +
  geom_point(alpha = .25) +
  facet_grid(vars(.row), vars(.col))
```

```
line %>%
  tidy_draws() %>%
  gather_variables() %>%
  gather_pairs(.variable, .value) %>%
  ggplot(aes(.x, .y, color = factor(.chain))) +
  geom_density_2d(alpha = .5) +
  facet_grid(vars(.row), vars(.col))
```

gather_variables	<i>Gather variables from a tidy data frame of draws from variables into a single column</i>
------------------	---

Description

Given a data frame such as might be returned by `tidy_draws()` or `spread_draws()`, gather variables and their values from that data frame into a `".variable"` and `".value"` column.

Usage

```
gather_variables(data, exclude = c(".chain", ".iteration", ".draw", ".row"))
```

Arguments

data	A data frame with variable names spread across columns, such as one returned by <code>tidy_draws()</code> or <code>spread_draws()</code> .
exclude	A character vector of names of columns to be excluded from the gather. Default ignores several meta-data column names used in tidybayes.

Details

This function gathers every column except grouping columns and those matching the expression `exclude` into key/value columns `".variable"` and `".value"`.

Imagine a data frame `data` as returned by `spread_draws(fit, a[i], b[i, v])`, like this:

- column `".chain"`: the chain number
- column `".iteration"`: the iteration number
- column `".draw"`: the draw number
- column `"i"`: value in 1:5
- column `"v"`: value in 1:10
- column `"a"`: value of `"a[i]"` for draw number `".draw"`
- column `"b"`: value of `"b[i, v]"` for draw number `".draw"`

`gather_variables(data)` on that data frame would return a grouped data frame (grouped by `i` and `v`), with:

- column ".chain": the chain number
- column ".iteration": the iteration number
- column ".draw": the draw number
- column "i": value in 1:5
- column "v": value in 1:10
- column ".variable": value in c("a", "b").
- column ".value": value of "a[i]" (when ".variable" is "a"; repeated for every value of "v") or "b[i,v]" (when ".variable" is "b") for draw number ".draw"

In this example, this call:

```
gather_variables(data)
```

Is roughly equivalent to:

```
data %>%
  gather(.variable, .value, -c(.chain, .iteration, .draw, i, v)) %>%
  group_by(.variable, .add = TRUE)
```

Value

A data frame.

Author(s)

Matthew Kay

See Also

[spread_draws\(\)](#), [tidy_draws\(\)](#).

Examples

```
library(dplyr)

data(RankCorr, package = "ggdist")

RankCorr %>%
  spread_draws(b[i,v], tau[i]) %>%
  gather_variables() %>%
  median_qi()

# the first three lines below are roughly equivalent to ggmcmc::ggs(RankCorr)
RankCorr %>%
  tidy_draws() %>%
  gather_variables() %>%
  median_qi()
```

get_variables	<i>Get the names of the variables in a fitted Bayesian model</i>
---------------	--

Description

Get a character vector of the names of the variables in a variety of fitted Bayesian model types. All models supported by [tidy_draws\(\)](#) are supported.

Usage

```
get_variables(model)

## Default S3 method:
get_variables(model)

## S3 method for class 'mcmc'
get_variables(model)

## S3 method for class 'mcmc.list'
get_variables(model)
```

Arguments

model	A supported Bayesian model fit. Tidybayes supports a variety of model objects; for a full list of supported models, see tidybayes-models .
-------	--

Details

This function is often useful for inspecting a model interactively in order to construct calls to [spread_draws\(\)](#) or [gather_draws\(\)](#) in order to extract draws from models in a tidy format.

Value

A character vector of variable names in the fitted model.

Author(s)

Matthew Kay

See Also

[spread_draws\(\)](#), [gather_draws\(\)](#).

Examples

```
data(line, package = "coda")
get_variables(line)

data(RankCorr, package = "ggdist")
get_variables(RankCorr)
```

n_prefix

*Prefix function generator for composing dimension index columns***Description**

Generates a function for generating names of index columns for factors in `compose_data()` by prefixing a character vector to the original column name.

Usage

```
n_prefix(prefix)
```

Arguments

`prefix` Character vector to be prepended to column names by `compose_data()` to create index columns. Typically something like "n" (that is the default used in the `.n_name` argument of `compose_data()`).

Returns a function. The function returned takes a character vector, `name` and returns `paste0(prefix, "_", name)`, unless `name` is empty, in which case it will return `prefix`.

`n_prefix("n")` is the default method that `compose_data()` uses to generate column names for variables storing the number of levels in a factor. Under this method, given a data frame `df` with a factor column "foo" containing 5 levels, the results of `compose_data(df)` will include an element named "n" (the result of `n_prefix("n")("")`) equal to the number of rows in `df` and an element named "n_foo" (the result of `n_prefix("n")("foo")`) equal to the number of levels in `df$foo`.

See Also

The `.n_name` argument of `compose_data()`.

Examples

```
library(magrittr)

df = data.frame(
  plot = factor(paste0("p", rep(1:8, times = 2))),
```

```

  site = factor(paste0("s", rep(1:4, each = 2, times = 2)))
)

# without changing `.n_name`, compose_data() will prefix indices
# with "n" by default
df %>%
  compose_data()

# you can use n_prefix() to define a different prefix (e.g. "N"):
df %>%
  compose_data(.n_name = n_prefix("N"))

```

predict_curve

Deprecated: Prediction curves for arbitrary functions of posteriors

Description

Deprecated function for generating prediction curves (or a density for a prediction curve).

Usage

```

predict_curve(data, formula, summary = median, ...)

predict_curve_density(
  data,
  formula,
  summary = function(...) density_bins(..., n = n),
  n = 50,
  ...
)

```

Arguments

data	A data.frame , tbl_df or grouped_df representing posteriors from a Bayesian model as might be obtained through spread_draws() . Grouped data frames as returned by group_by() are supported.
formula	A formula specifying the prediction curve. The left-hand side of the formula should be a name representing the name of the column that will hold the predicted response in the returned data frame. The right-hand side is an expression that may include numeric columns from data and variables passed into this function in
summary	The function to apply to summarize each predicted response. Useful functions (if you just want a curve) might be median() , mean() , or Mode() . If you want predictive distribution at each point on the curve, try density_bins() or histogram_bins() .
...	Variables defining the curve. The right-hand side of formula is evaluated for every combination of values of variables in

`n` For `predict_curve_density`, the number of bins to use to represent the distribution at each point on the curve.

Details

This function is deprecated. Use `modelr::data_grid()` combined with `point_interval()` or `dplyr::do()` and `density_bins()` instead.

The function generates a predictive curve given posterior draws (`data`), an expression (`formula`), and a set of variables defining the curve (`...`). For every group in `data` (if it is a grouped data frame—see `group_by()`; otherwise the entire data frame is taken at once), and for each combination of values in `...`, the right-hand side of `formula` is evaluated and its results passed to the summary function. This allows a predictive curve to be generated, given (e.g.) some samples of coefficients in `data` and a set of predictors defining the space of the curve in `...`

Given a summary function like `median()` or `mean()`, this function will produce the median (resp. mean) prediction at each point on the curve.

Given a summary function like `density_bins()`, this function will produce a predictive distribution for each point on the curve. `predict_curve_density` is a shorthand for such a call, with a convenient argument for adjusting the number of bins per point on the curve.

Value

If `formula` is in the form `lhs ~ rhs` and `summary` is a function that returns a single value, such as `median` or `mode`, then `predict_curve` returns a `data.frame` with a column for each group in `data` (if it was grouped), a column for each variable in `...`, and a column named `lhs` with the value of `summary(rhs)` evaluated for every group in `data` and combination of variables in `...`

If `summary` is a function that returns a `data.frame`, such as `density_bins()`, `predict_curve` has the same set of columns as above, except that in place of the `lhs` column is a set of columns named `lhs.x` for every column named `x` returned by `summary`. For example, `density_bins()` returns a data frame with the columns `mid`, `lower`, `upper`, and `density`, so the data frame returned by `predict_curve` with `summary = density_bins` will have columns `lhs.mid`, `lhs.lower`, `lhs.upper`, and `lhs.density` in place of `lhs`.

Author(s)

Matthew Kay

See Also

See `density_bins()`.

Examples

```
# Deprecated; see examples for density_bins
```

recover_types	<i>Decorate a model fit or sample with data types recovered from the input data</i>
---------------	---

Description

Decorate a Bayesian model fit or a sample from it with types for variable and dimension data types. Meant to be used before calling `spread_draws()` or `gather_draws()` so that the values returned by those functions are translated back into useful data types.

Usage

```
recover_types(model, ...)
```

Arguments

model	A supported Bayesian model fit. Tidybayes supports a variety of model objects; for a full list of supported models, see tidybayes-models .
...	Lists (or data frames) providing data prototypes used to convert columns returned by <code>spread_draws()</code> and <code>gather_draws()</code> back into useful data types. See <i>Details</i> .

Details

Each argument in `...` specifies a list or data.frame. The `model` is decorated with a list of constructors that can convert a numeric column into the data types in the lists in `...`.

Then, when `spread_draws()` or `gather_draws()` is called on the decorated `model`, each list entry with the same name as the variable or a dimension in `variable_spec` is used as a prototype for that variable or dimension — i.e., its type is taken to be the expected type of that variable or dimension. Those types are used to translate numeric values of variables back into useful values (for example, levels of a factor).

The most common use of `recover_types` is to automatically translate dimensions of a variable that correspond to levels of a factor in the original data back into levels of that factor. The simplest way to do this is to pass in the data frame from which the original data came.

Supported types of prototypes are factor, ordered, and logical. For example:

- if `prototypes$v` is a factor, the `v` column in the returned draws is translated into a factor using `factor(v, labels=levels(prototypes$v), ordered=is.ordered(prototypes$v))`.
- if `prototypes$v` is a logical, the `v` column is translated into a logical using `as.logical(v)`.

Additional data types can be supported by providing a custom implementation of the generic function `as_constructor`.

Value

A decorated version of `model`.

Author(s)

Matthew Kay

See Also[spread_draws\(\)](#), [gather_draws\(\)](#), [compose_data\(\)](#).**Examples**

```

library(dplyr)
library(magrittr)

if(require("rstan", quietly = TRUE)) {

  # Here's an example dataset with a categorical predictor (`condition`) with several levels:
  set.seed(5)
  n = 10
  n_condition = 5
  ABC =
    tibble(
      condition = rep(c("A", "B", "C", "D", "E"), n),
      response = rnorm(n * 5, c(0,1,2,1,-1), 0.5)
    )

  # We'll fit the following model to it:
  stan_code = "
  data {
    int<lower=1> n;
    int<lower=1> n_condition;
    int<lower=1, upper=n_condition> condition[n];
    real response[n];
  }
  parameters {
    real overall_mean;
    vector[n_condition] condition_zoffset;
    real<lower=0> response_sd;
    real<lower=0> condition_mean_sd;
  }
  transformed parameters {
    vector[n_condition] condition_mean;
    condition_mean = overall_mean + condition_zoffset * condition_mean_sd;
  }
  model {
    response_sd ~ cauchy(0, 1); // => half-cauchy(0, 1)
    condition_mean_sd ~ cauchy(0, 1); // => half-cauchy(0, 1)
    overall_mean ~ normal(0, 5);

    //=> condition_mean ~ normal(overall_mean, condition_mean_sd)
    condition_zoffset ~ normal(0, 1);

```

```

    for (i in 1:n) {
      response[i] ~ normal(condition_mean[condition[i]], response_sd);
    }
  }
}
"

m = stan(model_code = stan_code, data = compose_data(ABC), control = list(adapt_delta=0.99),
  # 1 chain / few iterations just so example runs quickly
  # do not use in practice
  chains = 1, iter = 500)

# without using recover_types(), the `condition` column returned by spread_draws()
# will be an integer:
m %>%
  spread_draws(condition_mean[condition]) %>%
  median_qi()

# If we apply recover_types() first, subsequent calls to other tidybayes functions will
# automatically back-convert factors so that they are labeled with their original levels
# (assuming the same name is used)
m %<>% recover_types(ABC)

# now the `condition` column will be a factor with levels "A", "B", "C", ...
m %>%
  spread_draws(condition_mean[condition]) %>%
  median_qi()
}

```

sample_draws

Sample draws from a tidy-format data frame of draws

Description

Given a tidy-format data frame of draws with a column indexing each draw, subsample the data frame to a given size based on a column indexing draws, ensuring that rows in sub-groups of a grouped data frame are sampled from the same draws.

Usage

```
sample_draws(data, n, draw = ".draw")
```

Arguments

data	Data frame to sample from
n	The number of draws to select
draw	The name of the column indexing the draws

Details

`sample_draws()` makes it easier to sub-sample a grouped, tidy-format data frame of draws. On a grouped data frame, the naive approach of using `filter` with the `.draw` column will give incorrect results as it will select a different sample within each group. `sample_draws()` ensures the same sample is selected within each group.

Author(s)

Matthew Kay

Examples

```
library(ggplot2)
library(dplyr)

if (
  require("brms", quietly = TRUE) &&
  require("modelr", quietly = TRUE)
) {

  theme_set(theme_light())

  m_mpg = brm(mpg ~ hp * cyl, data = mtcars,
    # 1 chain / few iterations just so example runs quickly
    # do not use in practice
    chains = 1, iter = 500)

  # draw 100 fit lines from the posterior and overplot them
  mtcars %>%
    group_by(cyl) %>%
    data_grid(hp = seq_range(hp, n = 101)) %>%
    add_fitted_draws(m_mpg) %>%
    sample_draws(100) %>%
    ggplot(aes(x = hp, y = mpg, color = ordered(cyl))) +
    geom_line(aes(y = .value, group = paste(cyl, .draw)), alpha = 0.25) +
    geom_point(data = mtcars)
}
```

tidybayes-deprecated *Deprecated functions, arguments, and column names in tidybayes*

Description

Deprecated functions, arguments, and column names and their alternatives are listed below. Many of the deprecations are due to a naming scheme overhaul in tidybayes version 1.0 (see *Deprecated*

Functions and Deprecated Arguments and Column Names below) or due to the deprecation of horizontal shortcut geoms and stats in tidybayes 2.1 (see *Deprecated Horizontal Shortcut Geoms and Stats*).

Deprecated Functions

Several deprecated versions of functions use slightly different output formats (e.g., they use names like `term` and `estimate` where new functions use `.variable` and `.value`; or they set `.iteration` even when iteration information is not available — new functions always set `.draw` but may not set `.iteration`), so be careful when upgrading to new function names. See *Deprecated Arguments and Column Names*, below, for more information.

Deprecated functions include:

- `spread_samples`, `extract_samples`, and `tidy_samples` are deprecated names for `spread_draws()`. The `spread/gather` terminology better distinguishes the resulting data frame format, and `draws` is more correct terminology than `samples` for describing multiple realizations from a posterior distribution.
- `gather_samples` is a deprecated name for `gather_draws()`, reflecting a package-wide move to using `draws` instead of `samples` for describing multiple realizations from a distribution.
- `unspread_samples` is a deprecated name for `unspread_draws()`, reflecting a package-wide move to using `draws` instead of `samples` for describing multiple realizations from a distribution.
- `ungather_samples` is a deprecated name for `ungather_draws()`, reflecting a package-wide move to using `draws` instead of `samples` for describing multiple realizations from a distribution.
- `fitted_samples` / `add_fitted_samples` are deprecated names for `fitted_draws()` / `add_fitted_draws()`, reflecting a package-wide move to using `draws` instead of `samples` for describing multiple realizations from a distribution.
- `predicted_samples` / `add_predicted_samples` are deprecated names for `predicted_draws()` / `add_predicted_draws()`, reflecting a package-wide move to using `draws` instead of `samples` for describing multiple realizations from a distribution.
- `gather_lsmeans_samples` and `gather_emmeans_samples` are deprecated aliases for `gather_emmeans_draws()`. The new name (estimated marginal means) is more appropriate for Bayesian models than the old name (least-squares means), and reflects the naming of the newer `emmeans` package. It also reflects a package-wide move to using `draws` instead of `samples` for describing multiple realizations from a distribution.
- `as_sample_tibble` and `as_sample_data_frame` are deprecated aliases for `tidy_draws()`. The original intent of `as_sample_tibble` was to be used primarily internally (hence its less user-friendly name); however, increasingly I have come across use cases of `tidy_draws` that warrant a more user-friendly name. It also reflects a package-wide move to using `draws` instead of `samples` for describing multiple realizations from a distribution.
- `ggeye` is deprecated: for a package whose goal is flexible and customizable visualization, monolithic functions are inflexible and do not sufficiently capitalize on users' existing knowledge of `ggplot`; instead, I think it is more flexible to design geoms and stats that can be used within a complete `ggplot` workflow. `stat_eye()` offers a horizontal eye plot geom that can be used instead of `ggeye`.

- See the sections below for additional deprecated functions, including horizontal geoms, stats, and point_intervals

Deprecated Eye Geom Spellings

`geom_eye`, `geom_eyeh`, and `geom_halfeyeh` are deprecated spellings of `stat_eye()` and `stat_halfeye()` from before name standardization of stats and geoms. Use those functions instead.

Deprecated Horizontal Shortcut Geoms and Stats

Due to the introduction of automatic orientation detection in tidybayes 2.1, shortcut geoms and stats (which end in h) are no longer necessary, and are deprecated. In most cases, these can simply be replaced with the same geom without the h suffix and they will remain horizontal; e.g. `stat_halfeyeh(...)` can simply be replaced with `stat_halfeye(...)`. If automatic orientation detection fails, override it with the orientation parameter; e.g. `stat_halfeye(orientation = "horizontal")`.

These deprecated stats and geoms include:

- `stat_eyeh` / `stat_dist_eyeh`
- `stat_halfeyeh` / `stat_dist_halfeyeh`
- `geom_slabh` / `stat_slabh` / `stat_dist_slabh`
- `geom_intervalh` / `stat_intervalh` / `stat_dist_intervalh`
- `geom_pointintervalh` / `stat_pointintervalh` / `stat_dist_pointintervalh`
- `stat_gradientintervalh` / `stat_dist_gradientintervalh`
- `stat_cdfintervalh` / `stat_dist_cdfintervalh`
- `stat_ccdfintervalh` / `stat_dist_ccdfintervalh`
- `geom_dotsh` / `stat_dotsh` / `stat_dist_dotsh`
- `geom_dotsintervalh` / `stat_intervalh` / `stat_dist_intervalh`
- `stat_histintervalh`

Deprecated Horizontal Point/Interval Functions

These functions ending in h (e.g., `point_intervalh`, `median_qih`) used to be needed for use with `ggstance::stat_summaryh`, but are no longer necessary because `ggplot2::stat_summary()` supports automatic orientation detection, so they have been deprecated. They behave identically to the corresponding function without the h, except that when passed a vector, they return a data frame with `x/xmin/xmax` instead of `y/ymin/ymax`.

- `point_intervalh`
- `mean_qih` / `median_qih` / `mode_qih`
- `mean_hdih` / `median_hdih` / `mode_hdih`
- `mean_hdcih` / `median_hdcih` / `mode_hdcih`

Deprecated Arguments and Column Names

Versions of tidybayes before version 1.0 used a different naming scheme for several arguments and output columns.

Deprecated arguments and column names are:

- `term` is now `.variable`
- `estimate` is now `.value`
- `pred` is now `.prediction`
- `conf.low` is now `.lower`
- `conf.high` is now `.upper`
- `.prob` is now `.width`
- The `.draw` column was added, and should be used instead of `.chain` and `.iteration` to uniquely identify draws when you do not care about chains. (`.chain` and `.iteration` are still provided for identifying draws *within* chains, if desired).

To translate to/from the old naming scheme in output, use `to_broom_names()` and `from_broom_names()`.

Many of these names were updated in version 1.0 in order to make terminology more consistent and in order to satisfy these criteria:

- Ignore compatibility with broom names on the assumption an adapter function can be created.
- Use names that could be compatible with frequentist approaches (hence `.width` instead of `.prob`).
- Always precede with "." to avoid collisions with variable names in models.
- No abbreviations (remembering if something is abbreviated or not can be a pain).
- No two-word names (multi-word names can always be standardized on and used in documentation, but I think data frame output should be succinct).
- Names should be nouns (I made an exception for lower/upper because they are common).

Author(s)

Matthew Kay

tidybayes-models

Models supported by tidybayes

Description

Tidybayes supports two classes of models and sample formats: Models/formats that provide prediction functions, and those that do not.

All Supported Models/Sample Formats

All supported models/formats support the base tidybayes sample extraction functions, such as `tidy_draws()`, `spread_draws()`, and `gather_draws()`. These models/formats include:

- `rstan` models
- `brms::brm()` models
- `rstanarm` models
- `runjags::runjags()` models
- `rjags::jags.model()` models, if sampled using `rjags::coda.samples()`
- `jagsUI::jags()` models
- `MCMCglmm::MCMCglmm()` models
- `coda::mcmc()` and `coda::mcmc.list()` objects, which are output by several model types.
- Any object with an implementation of `coda::as.mcmc.list()`. For a list of those available in your environment, run `methods(as.mcmc.list)`

If you install the `tidybayes.rethinking` package, models from the `rethinking` package are also supported.

Models Supporting Prediction

In addition, the following models support fit and prediction extraction functions, such as `add_fitted_draws()` and `add_predicted_draws()`:

- `brms::brm()` models
- `rstanarm` models

If your model type is not in the above list, you may still be able to use the `add_draws()` function to turn matrices of predictive draws (or fit draws) into tidy data frames.

If you install the `tidybayes.rethinking` package, models from the `rethinking` package are also supported.

Extending tidybayes

To include basic support for new models, one need only implement the `tidy_draws()` generic function for that model.

To include support for estimation and prediction, one must implement the `fitted_draws()` and `predicted_draws()` generic functions.

`tidy_draws`*Get a sample of posterior draws from a model as a tibble*

Description

Extract draws from a Bayesian fit into a wide-format data frame with a `.chain`, `.iteration`, and `.draw` column, as well as all variables as columns. While this function can be useful for quick glances at models (especially combined with `gather_variables()` and `median_qi()`), it is generally speaking not as useful as `spread_draws()` or `gather_draws()` for most applications, and is mainly used internally (see *Details*).

Usage

```
tidy_draws(model, ...)

## Default S3 method:
tidy_draws(model, ...)

## S3 method for class 'data.frame'
tidy_draws(model, ...)

## S3 method for class 'mcmc.list'
tidy_draws(model, ...)

## S3 method for class 'stanfit'
tidy_draws(model, ...)

## S3 method for class 'stanreg'
tidy_draws(model, ...)

## S3 method for class 'runjags'
tidy_draws(model, ...)

## S3 method for class 'jagsUI'
tidy_draws(model, ...)

## S3 method for class 'brmsfit'
tidy_draws(model, ...)

## S3 method for class 'matrix'
tidy_draws(model, ...)

## S3 method for class 'MCMCglmm'
tidy_draws(model, ...)
```

Arguments

model	A supported Bayesian model fit object. See tidybayes-models() for a list of supported models.
...	Further arguments passed to other methods (mostly unused).

Details

In practice, apart from quick looks at a model you will probably not call this directly; [spread_draws\(\)](#) or [gather_draws\(\)](#), which are build on top of this function, provide support for extracting variable dimensions are so are often more useful.

To provide support for new models in tidybayes, you must provide an implementation of this function *or* an implementation of `coda::as.mcmc.list()` (tidy_draws should work on any model with an implementation of `coda::as.mcmc.list()`)

tidy_draws can be applied to a data frame that is already a tidy-format data frame of draws, provided it has one row per draw. In other words, it can be applied to data frames that have the same format it returns, and it will return the same data frame back, while checking to ensure the `.chain`, `.iteration`, and `.draw` columns are all integers (converting if possible) and that the `.draw` column is unique. This allows you to pass already-tidy-format data frames into other tidybayes functions, like [spread_draws\(\)](#) or [gather_draws\(\)](#).

Value

A data frame (actually, a [tibble](#)) with a `.chain` column, `.iteration` column, `.draw` column, and one column for every variable in model.

Author(s)

Matthew Kay

See Also

[spread_draws\(\)](#) or [gather_draws\(\)](#), which use this function internally and provides a friendly interface for extracting tidy data frames from model fits.

Examples

```
library(magrittr)

data(line, package = "coda")

line %>%
  tidy_draws()
```

ungather_draws	<i>Turn tidy data frames of variables from a Bayesian model back into untidy data</i>
----------------	---

Description

Inverse operations of [spread_draws\(\)](#) and [gather_draws\(\)](#), giving results that look like [tidy_draws\(\)](#).

Usage

```
ungather_draws(
  data,
  ...,
  variable = ".variable",
  value = ".value",
  draw_indices = c(".chain", ".iteration", ".draw"),
  drop_indices = FALSE
)

unspread_draws(
  data,
  ...,
  draw_indices = c(".chain", ".iteration", ".draw"),
  drop_indices = FALSE
)
```

Arguments

data	A tidy data frame of draws, such as one output by spread_draws or gather_draws .
...	Expressions in the form of <code>variable_name[dimension_1,dimension_2,...]</code> . See spread_draws() .
variable	The name of the column in data that contains the names of variables from the model.
value	The name of the column in data that contains draws from the variables.
draw_indices	Character vector of column names in data that should be treated as indices of draws. The default is <code>c(".chain", ".iteration", ".draw")</code> , which are the same names used for chain, iteration, and draw indices returned by spread_draws() or gather_draws() .
drop_indices	Drop the columns specified by <code>draw_indices</code> from the resulting data frame. Default FALSE.

Details

These functions take symbolic specifications of variable names and dimensions in the same format as [spread_draws\(\)](#) and [gather_draws\(\)](#) and invert the tidy data frame back into a data frame whose column names are variables with dimensions in them.

Value

A data frame.

Author(s)

Matthew Kay

See Also

[spread_draws\(\)](#), [gather_draws\(\)](#), [tidy_draws\(\)](#).

Examples

```
library(dplyr)

data(RankCorr, package = "ggdist")

# We can use unspread_draws to allow us to manipulate draws with tidybayes
# and then transform the draws into a form we can use with packages like bayesplot.
# Here we subset b[i,j] to just values of i in 1:2 and j == 1, then plot with bayesplot
RankCorr %>%
  spread_draws(b[i,j]) %>%
  filter(i %in% 1:2, j == 1) %>%
  unspread_draws(b[i,j], drop_indices = TRUE) %>%
  bayesplot::mcmc_areas()

# As another example, we could use compare_levels to plot all pairwise comparisons
# of b[1,j] for j in 1:3
RankCorr %>%
  spread_draws(b[i,j]) %>%
  filter(i == 1, j %in% 1:3) %>%
  compare_levels(b, by = j) %>%
  unspread_draws(b[j], drop_indices = TRUE) %>%
  bayesplot::mcmc_areas()
```

x_at_y

Generate lookup vectors for composing nested indices

Description

Generates a lookup vector such that `x_at_y(x,y)[y] == x`. Particularly useful for generating lookup tables for nested indices in conjunction with [compose_data\(\)](#).

Usage

```
x_at_y(x, y, missing = NA)
```

Arguments

x	Values in the resulting lookup vector. There should be only one unique value of x for every corresponding value of y.
y	Keys in the resulting lookup vector. Should be factors or integers.
missing	Missing levels from y will be filled in with this value in the resulting lookup vector. Default NA.

Details

`x_at_y(x,y)` returns a vector `k` such that `k[y] == x`. It also fills in missing values in `y`: if `y` is an integer, `k` will contain entries for all values from 1 to `max(y)`; if `y` is a factor, `k` will contain entries for all values from 1 to `nlevels(y)`. Missing values are replaced with `missing` (default NA).

Author(s)

Matthew Kay

See Also

[compose_data\(\)](#).

Examples

```
library(magrittr)

df = data.frame(
  plot = factor(paste0("p", rep(1:8, times = 2))),
  site = factor(paste0("s", rep(1:4, each = 2, times = 2)))
)

# turns site into a nested index: site[p] gives the site for plot p
df %>%
  compose_data(site = x_at_y(site, plot))
```

Index

- * **datasets**
 - tidybayes-deprecated, 41
- * **manip**
 - add_draws, 4
 - add_fitted_draws, 5
 - combine_chains, 12
 - compare_levels, 13
 - compose_data, 16
 - data_list, 18
 - density_bins, 20
 - gather_draws, 23
 - gather_emmeans_draws, 27
 - gather_pairs, 29
 - gather_variables, 32
 - get_variables, 34
 - predict_curve, 36
 - recover_types, 38
 - sample_draws, 40
 - tidy_draws, 46
 - ungather_draws, 48
- add_draws, 4
- add_draws(), 5, 11, 45
- add_fitted_draws, 5
- add_fitted_draws(), 4, 5, 14, 42, 45
- add_fitted_samples
 - (tidybayes-deprecated), 41
- add_linpred_draws (add_fitted_draws), 5
- add_predicted_draws (add_fitted_draws), 5
- add_predicted_draws(), 4, 5, 21, 42, 45
- add_predicted_samples
 - (tidybayes-deprecated), 41
- add_residual_draws (add_fitted_draws), 5
- apply_prototypes (recover_types), 38
- as.numeric(), 16, 19
- as_data_list (data_list), 18
- as_data_list(), 16, 17, 19
- as_sample_data_frame
 - (tidybayes-deprecated), 41
- as_sample_tibble
 - (tidybayes-deprecated), 41
- brms::brm(), 10, 45
- brms::brmsfit, 9
- brms::fitted.brmsfit(), 10
- brms::predict.brmsfit(), 10
- coda::as.mcmc.list(), 45, 47
- coda::mcmc(), 45
- coda::mcmc.list(), 45
- combine_chains, 12
- compare_levels, 13
- compare_levels(), 15, 21, 22
- compose_data, 16
- compose_data(), 18, 19, 27, 35, 39, 49, 50
- data.frame, 36
- data_list, 18
- density(), 20
- density_bins, 20
- density_bins(), 36, 37
- dplyr::do(), 37
- emmeans contrast method, 22
- emmeans contrast methods, 21
- emmeans::contrast-methods, 22
- emmeans::emm_list(), 28
- emmeans::emmeans(), 12, 27, 28, 31
- emmeans::pairwise.emmc, 22
- emmeans::ref_grid(), 27, 28
- emmeans::trt.vs.ctrl.emmc, 22
- emmeans_comparison, 21
- emmeans_comparison(), 14, 15
- extract_samples (tidybayes-deprecated), 41
- fitted_draws (add_fitted_draws), 5
- fitted_draws(), 42, 45
- fitted_samples (tidybayes-deprecated), 41

- from_broom_names(), 44
- gather_draws, 23
- gather_draws(), 13, 14, 17, 34, 38, 39, 42, 45–49
- gather_emmeans_draws, 27
- gather_emmeans_draws(), 22, 42
- gather_emmeans_samples (tidybayes-deprecated), 41
- gather_lsmeans_samples (tidybayes-deprecated), 41
- gather_pairs, 29
- gather_samples (tidybayes-deprecated), 41
- gather_terms (tidybayes-deprecated), 41
- gather_variables, 32
- gather_variables(), 46
- geom_dotsh (tidybayes-deprecated), 41
- geom_dotsintervalh (tidybayes-deprecated), 41
- geom_eye (tidybayes-deprecated), 41
- geom_eyeh (tidybayes-deprecated), 41
- geom_halfeyeh (tidybayes-deprecated), 41
- geom_intervalh (tidybayes-deprecated), 41
- geom_pointintervalh (tidybayes-deprecated), 41
- geom_slabh (tidybayes-deprecated), 41
- GeomIntervalh (tidybayes-deprecated), 41
- GeomPointintervalh (tidybayes-deprecated), 41
- get_variables, 34
- ggeye (tidybayes-deprecated), 41
- group_by(), 36, 37
- grouped_df, 36
- hist(), 20
- histogram_bins (density_bins), 20
- histogram_bins(), 36
- jagsUI::jags(), 45
- linpred_draws (add_fitted_draws), 5
- list(), 18, 19
- MCMCglimm::MCMCglimm(), 28, 45
- mean(), 36, 37
- mean_hdcih (tidybayes-deprecated), 41
- mean_hdih (tidybayes-deprecated), 41
- mean_qih (tidybayes-deprecated), 41
- median(), 36, 37
- median_hdcih (tidybayes-deprecated), 41
- median_hdih (tidybayes-deprecated), 41
- median_qi(), 46
- median_qih (tidybayes-deprecated), 41
- Mode(), 36
- mode_hdcih (tidybayes-deprecated), 41
- mode_hdih (tidybayes-deprecated), 41
- mode_qih (tidybayes-deprecated), 41
- modelr::data_grid(), 37
- mutate(), 17
- n_prefix, 35
- n_prefix(), 16
- parameters (tidybayes-deprecated), 41
- point_interval(), 28, 37
- point_intervalh (tidybayes-deprecated), 41
- predict_curve, 36
- predict_curve(), 20
- predict_curve_density (predict_curve), 36
- predicted_draws (add_fitted_draws), 5
- predicted_draws(), 42, 45
- predicted_samples (tidybayes-deprecated), 41
- recover_types, 38
- recover_types(), 24, 26, 27
- relevel(), 14
- residual_draws (add_fitted_draws), 5
- rjags::coda.samples(), 45
- rjags::jags.model(), 45
- rstan, 45
- rstanarm, 45
- rstanarm::posterior_linpred(), 10
- rstanarm::posterior_predict(), 10
- rstanarm::stan_polr(), 10
- rstanarm::stanreg-objects, 9, 28
- runjags::runjags(), 45
- sample_draws, 40
- spread_draws (gather_draws), 23
- spread_draws(), 9, 11, 13, 14, 17, 32–34, 36, 38, 39, 42, 45–49
- spread_samples (tidybayes-deprecated), 41

stat_ccdfintervalh
(tidybayes-deprecated), 41

stat_cdfintervalh
(tidybayes-deprecated), 41

stat_dist_ccdfintervalh
(tidybayes-deprecated), 41

stat_dist_cdfintervalh
(tidybayes-deprecated), 41

stat_dist_dotsh (tidybayes-deprecated),
41

stat_dist_dotsintervalh
(tidybayes-deprecated), 41

stat_dist_eyeh (tidybayes-deprecated),
41

stat_dist_gradientintervalh
(tidybayes-deprecated), 41

stat_dist_halfeyeh
(tidybayes-deprecated), 41

stat_dist_intervalh
(tidybayes-deprecated), 41

stat_dist_pointintervalh
(tidybayes-deprecated), 41

stat_dist_slabh (tidybayes-deprecated),
41

stat_dotsh (tidybayes-deprecated), 41

stat_dotsintervalh
(tidybayes-deprecated), 41

stat_eye(), 42, 43

stat_eyeh (tidybayes-deprecated), 41

stat_gradientintervalh
(tidybayes-deprecated), 41

stat_halfeye(), 43

stat_halfeyeh (tidybayes-deprecated), 41

stat_histintervalh
(tidybayes-deprecated), 41

stat_intervalh (tidybayes-deprecated),
41

stat_lineribbon(), 21

stat_pointintervalh
(tidybayes-deprecated), 41

stat_slabh (tidybayes-deprecated), 41

tbl_df, 36

tibble, 4, 11, 47

tidy_draws, 46

tidy_draws(), 32–34, 42, 45, 48, 49

tidy_samples (tidybayes-deprecated), 41

tidybayes (tidybayes-package), 3

tidybayes-deprecated, 41

tidybayes-models, 3, 9, 23, 34, 38, 44

tidybayes-package, 3

to_broom_names(), 24, 44

to_ggmcmc_names(), 24

ungather_draws, 48

ungather_draws(), 42

ungather_samples
(tidybayes-deprecated), 41

unspread_draws (ungather_draws), 48

unspread_draws(), 42

unspread_samples
(tidybayes-deprecated), 41

x_at_y, 49

x_at_y(), 17