

Package ‘tstools’

September 11, 2018

Type Package

Version 0.3.8

Title A Time Series Toolbox for Official Statistics

Description Plot official statistics' time series conveniently: automatic legends, highlight windows, stacked bar charts with positive and negative contributions, sum-as-line option, two y-axes with automatic horizontal grids that fit both axes and other popular chart types. 'tstools' comes with a plethora of defaults to let you plot without setting an abundance of parameters first, but gives you the flexibility to tweak the defaults. In addition to charts, 'tstools' provides a super fast, 'data.table' backed time series I/O that allows the user to export / import long format, wide format and transposed wide format data to various file types.

Depends R (>= 3.0.0), zoo (>= 1.7-12),

Imports xts, stats, graphics, jsonlite, data.table,

Suggests knitr, rmarkdown, testthat, reshape2, openxlsx

VignetteBuilder knitr

Date 2018-09-11

License GPL-2

LazyData true

Maintainer Matthias Bannert <bannert@kof.ethz.ch>

NeedsCompilation no

Author Matthias Bannert [aut, cre],
Severin Thoenig [aut]

RoxygenNote 6.0.1

Repository CRAN

Date/Publication 2018-09-11 12:20:02 UTC

R topics documented:

CHGDP	2
color_blind	3

compute_decimal_time	3
concat_ts	4
create_dummy_ts	4
df_to_reg_ts	5
fill_year_with_nas	6
generate_random_ts	6
getCiLegendColors	7
get_date_vector	8
init_tsplot_theme	8
KOF	14
long_to_ts	15
m_to_q	15
overlap_sorted_ts_lists	16
overlap_ts_lists_by_name	16
read_swissdata	17
read_ts	17
regularize	18
resolve_ts_overlap	19
set_month_to_NA	20
start_ts_after_internal_nas	20
strip_ts_of_leading_nas	21
tsplot	21
tsqm	23
tstools-deprecated	23
wide_to_ts	24
write_ts	24

Index 26

CHGDP	<i>CH GDP Growth Contributions</i>
-------	------------------------------------

Description

A list of time series containing sector contributions to Swiss GDP over time.

Usage

CHGDP

Format

List list of six time series of class ts, containing contributions to Swiss GDP growth

manufacturing Growth contribution of manufacturing.

energy Growth contribution of energy, water sector

construction Growth contribution construction sector.

hotels Growth contribution of hotels.

fin_insur Growth contribution of financial services and insurances.

other Growth contribution of other sectors.

Source

<https://www.seco.admin.ch/seco/en/home/wirtschaftslage---wirtschaftspolitik/Wirtschaftslage/bip-quartalsschaetzungen-/daten.html>

color_blind

Provide Colorblind Compliant Colors

Description

8 Hex RGB color defintions suitable for charts for colorblind people.

Usage

color_blind()

compute_decimal_time

Compute Decimal Time from a ts Period Vector

Description

Standard ts object use a vector of length two to store a period. E.g. 2010,1 means first quarter of 2010, if the series was quarterly and first month if the series was monthly etc.

Usage

compute_decimal_time(v, f)

Arguments

v integer vector denoting a point in time

f frequency

concat_ts	<i>Concatenate to Non-Overlapping Time Series</i>
-----------	---

Description

Append one time series to another. This only works for non-overlapping time series of the same frequency. For overlapping time series please see [resolveOverlap](#).

Usage

```
concat_ts(ts1, ts2)
```

Arguments

ts1	object of class ts1, typically the older of two time series.
ts2	object of class ts1, typically the younger of two time series.

create_dummy_ts	<i>Flexible Function to Create Time Series Dummy Variables</i>
-----------------	--

Description

Generate time series with a default value that is changed within a certain subperiod. The function allows for additional convenience when specifying single period dummies and dummies that go from a certain point in time to the end of the series.

Usage

```
create_dummy_ts(end_basic, dummy_start, dummy_end = NULL, sp = T,
  start_basic = c(1980, 1), basic_value = 0, dummy_value = 1,
  frequency = 4)
```

Arguments

end_basic	numeric vector of form c(yyyy,p) defining the end of the time series.
dummy_start	numeric vector of form c(yyyy,p) defining the beginning of the period with different value.
dummy_end	numeric vector of form c(yyyy,p) defining the end of the period with different value. Defaults to NULL, using the end_date of the series.
sp	logical should NULL value for dummy_end lead to a single period dummy (TRUE) or to alternative values until the end.
start_basic	numeric vector of form c(yyyy,p) defining the start of the time series. Defaults to c(1980,1)
basic_value	default value of the time series, defaults to 0.
dummy_value	the alternative value, defaults to 1.
frequency	integer frequency of the regular time series, defaults to 4 (quarterly).

Author(s)

Matthias Bannert

df_to_reg_ts

*Turn data.frame to Regular Monthly or Quarterly Time Series***Description**

Turn a data.frame with date columns to a regular time series object if possible. Design to work with quarterly and monthly data.

Usage

```
df_to_reg_ts(dframe, var_cols, year_col = "year", period_col = "month",
  freq = 12, return_ts = T, by = NULL)
```

Arguments

dframe	data.frame input
var_cols	columns that contain variables as opposed to date index.
year_col	integer, logical or character vector indicating the year position within the data.frame.
period_col	integer, logical or character vector indicating the period position within the data.frame.
freq	integer indicating the frequency of new time series.
return_ts	logical should a (list of) time series be returned? Defaults to TRUE. FALSE returns data.frame.
by	character overwrite automatically detected (from freq) by parameter. e.g. '1 day'. Defaults to NULL.

Examples

```
start_m <- as.Date("2017-01-01")
df_missing <- data.frame(
  date = seq(start_m, by='2 months', length=6),
  value = 1:6,
  another_value = letters[1:6],
  yet_another_col = letters[6:1]
)
df_to_reg_ts(df_missing, c("value", "another_value"))
df_to_reg_ts(df_missing, c("value", "another_value"), return_ts = FALSE)
```

fill_year_with_nas *Fill Up a Time Series with NAs*

Description

When plotting a time series you might want set the range of the plot a little wider than just the start and end date of the original series. This function add fills up the current period (typically year) with NA.

Usage

```
fill_year_with_nas(x, add_periods = 1, fill_up_start = FALSE)
```

Arguments

x object of class ts
 add_periods integer periods to add.
 fill_up_start logical should start year be filled up? Defaults to FALSE.

generate_random_ts *Generate a list of random time series*

Description

Useful for development or generating easily reproducible examples

Usage

```
generate_random_ts(n = 1, lengths = 36, starts = 1988, frequencies = 12,
  ranges_min = -1, ranges_max = 1, shifts = 0,
  ts_names = sprintf("ts%d", 1:n), seed = 30042018, random_NAs = FALSE,
  random_NA_proportions = 0.1, normally_distributed = FALSE,
  normal_means = 0, normal_sds = 1, frequency_shifts = FALSE,
  frequency_shift_after = 0.5)
```

Arguments

n The number of ts objects to generate
 lengths The lengths of the time series
 starts The start points of the time series in single number notation (e.g. 1990.5)
 frequencies The frequencies of the time series
 ranges_min The minimum values of the time series (if normally_distributed == FALSE)
 ranges_max The maximum values of the time series (if normally_distributed == FALSE)

shifts	The shifts of time series values per series
ts_names	The names of the ts objects in the resulting list
seed	The random seed to be used
random_NAs	Whether or not to introduce NA values at random positions in the ts
random_NA_proportions	The fraction of values to be replaced with NAs if random_NAs is TRUE for the series
normally_distributed	Use normal distribution instead of uniform
normal_means	The means to use for normal distribution. Ignored unless normally_distributed is set to TRUE.
normal_sds	The sds to use for normal distribution. Ignored unless normally_distributed is set to TRUE.
frequency_shifts	Introduce frequency shifts (from 4 to 12) in the ts
frequency_shift_after	After what fraction of the ts to shift frequencies

Details

Except for `n` and `ts_names`, all parameters accept either a single value or a vector of values. If a single value is supplied, that value is used for all time series being generated. If a vector is supplied, its values will be used for the corresponding series (e.g. `starts[1]` is used for the first series, `starts[2]` for the second and so on). Vectors are recycled if `n` is larger than their length.

If a `ts_names` vector is supplied, it must have length `n` and must not contain duplicates.

Value

A list of ts objects

Examples

```
generate_random_ts()
```

```
generate_random_ts(n = 3, ranges_min = c(-10, 0, 10), ranges_max = 20, starts = 2011)
```

getCilLegendColors *Helper to calculate ci colors for legends*

Description

Helper to calculate ci colors for legends

Usage

```
getCilLegendColors(color, n = 1, alpha = NULL)
```

Arguments

color	The color of the ci band
n	The number if ci bands
alpha	The alpha/transparency of the ci band

Details

Color may be specified as either a named color or a hex value Transparency may be specified as a hex value, number 0-255 or number 0-1

Value

A vector of non-transparent colors that result from overlaying color over pure white 1:n times

get_date_vector	<i>Compute the Period Vector representation of a Decimal Time value</i>
-----------------	---

Description

The period value will be rounded down to the nearest integer. This function is not vectorized so only a single value can be converted at a time.

Usage

```
get_date_vector(dtime, frq)
```

Arguments

dtime	numeric decimal time value denoting a point in time
frq	integer frequency

init_tsplot_theme	<i>Initiate Default Theme</i>
-------------------	-------------------------------

Description

The `tsplot` methods provide a theme argument which is used to pass on a plethora of useful defaults. These defaults are essentially stored in a list. Sometimes the user may want to tweak some of these defaults while keeping most of them. Hence the `init_tsplot_theme` function create a fresh list object containing default values for lot of different layout parameters etc. By replacing single elements of the list and passing the entire list to the plot function, single aspects can be tweaked while keeping most defaults. `Init defaultTheme` does not need any parameters.

This function provides sensible defaults for margins, font size, line width etc. scaled to the dimensions of the output file.

Usage

```

init_tsplot_theme(auto_bottom_margin = FALSE, band_fill_color = c(ETH8 =
"#007A92", ETH8_60 = "#66b0c2", ETH8_30 = "#b3d7e0", ETH8_20 = "#cce5eb", ETH5
= "#91056a", ETH5_60 = "#cc67a7", ETH5_30 = "#e6b3d3"),
bar_border = "#000000", bar_border_lwd = 1, bar_fill_color = c(ETH8 =
"#007A92", ETH8_60 = "#66b0c2", ETH8_30 = "#b3d7e0", ETH8_20 = "#cce5eb", ETH5
= "#91056a", ETH5_60 = "#cc67a7", ETH5_30 = "#e6b3d3"), bar_gap = 15,
bar_group_gap = 30, ci_alpha = "44", ci_colors = line_colors,
ci_legend_label = "%ci_value%% ci for %series%",
default_bottom_margin = 15, fill_up_start = FALSE,
fill_year_with_nas = TRUE, highlight_color = "#e9e9e9",
highlight_window = FALSE, highlight_window_end = NA,
highlight_window_freq = 4, highlight_window_start = NA,
label_pos = "mid", legend_all_left = FALSE, legend_box_size = 2,
legend_col = 1, legend_font_size = 1, legend_intersp_x = 1,
legend_intersp_y = 1, legend_margin_bottom = 5, legend_margin_top = 12,
legend_seg.len = 2, line_colors = c(ETH_8_100 = "#a9af66", ETH_4_100 =
"#72791c", ETH_8_20 = "#cce5eb", ETH_5_60 = "#cc67a7", ETH_8_60 = "#66b0c2",
ETH_5_100 = "#91056a", ETH_4_60 = "#007a92"), line_to_middle = TRUE,
lty = 1, lwd = c(2, 3, 1, 4, 2, 4), lwd_box = 1.5,
lwd_quarterly_ticks = 1, lwd_x_axis = 1.5, lwd_y_axis = 1.5,
lwd_y_ticks = 1.5, lwd_yearly_ticks = 1.5, margins = c(NA, 7, 12, 7),
NA_continue_line = FALSE, output_wide = FALSE, point_symbol = 1:18,
pointsize = 12, preferred_y_gap_sizes = c(25, 20, 15, 10, 5, 2.5, 1, 0.5),
quarterly_ticks = TRUE, range_must_not_cross_zero = TRUE,
show_left_y_axis = TRUE, show_points = FALSE, show_right_y_axis = TRUE,
show_x_axis = TRUE, show_y_grids = TRUE, subtitle_adj = 0,
subtitle_adj_r = 0.9, subtitle_cex = 1, subtitle_margin = 2,
subtitle_outer = FALSE, subtitle_transform = "toupper",
sum_as_line = FALSE, sum_legend = "sum", sum_line_color = c(ETH_8_100 =
"#007a92"), sum_line_lty = 1, sum_line_lwd = 3,
tcl_quarterly_ticks = -0.4, tcl_y_ticks = -0.75,
tcl_yearly_ticks = -0.75, title_adj = 0, title_cex.main = 1,
title_margin = 5, title_outer = FALSE, title_transform = NA,
total_bar_margin_pct = 0.2, use_bar_gap_in_groups = FALSE,
use_box = FALSE, x_tick_dt = 1, xaxis = "i", y_grid_color = "#CCCCCC",
y_grid_count = c(5, 6, 8, 10), y_grid_count_strict = FALSE, y_las = 2,
y_range_min_size = NULL, y_tick_force_integers = FALSE,
y_tick_margin = 0.15, yaxs = "i", yearly_ticks = TRUE)

```

```

init_tsplot_print_theme(output_wide = FALSE, margins = c(NA, 10/if
(output_wide) 1 + 1/3 else 1, 10, 7/if (output_wide) 1 + 1/3 else 1),
lwd = scale_theme_param_for_print(c(2, 3, 1, 4, 2, 4), if (output_wide) c(10
+ 2/3, 6) else c(8, 6)), sum_line_lwd = scale_theme_param_for_print(3, if
(output_wide) c(10 + 2/3, 6) else c(8, 6)),
lwd_box = scale_theme_param_for_print(1.5, if (output_wide) c(10 + 2/3, 6)
else c(8, 6)), lwd_x_axis = scale_theme_param_for_print(1.5, if
(output_wide) c(10 + 2/3, 6) else c(8, 6)),

```

```

lwd_yearly_ticks = scale_theme_param_for_print(1.5, if (output_wide) c(10 +
2/3, 6) else c(8, 6)), lwd_quarterly_ticks = scale_theme_param_for_print(1,
if (output_wide) c(10 + 2/3, 6) else c(8, 6)),
lwd_y_axis = scale_theme_param_for_print(1.5, if (output_wide) c(10 + 2/3,
6) else c(8, 6)), lwd_y_ticks = scale_theme_param_for_print(1.5, if
(output_wide) c(10 + 2/3, 6) else c(8, 6)),
legend_intersp_y = scale_theme_param_for_print(1, if (output_wide) c(10 +
2/3, 6) else c(8, 6)), legend_box_size = scale_theme_param_for_print(2, if
(output_wide) c(10 + 2/3, 6) else c(8, 6)), legend_margin_top = 8,
legend_margin_bottom = 3, legend_seg.len = scale_theme_param_for_print(2,
if (output_wide) c(10 + 2/3, 6) else c(8, 6)),
pointsize = scale_theme_param_for_print(12, if (output_wide) c(10 + 2/3, 6)
else c(8, 6)), ...)

```

Arguments

auto_bottom_margin	logical Should the bottom margin be automatically calculated? This will be overridden if margins[1] is not NA. Default FALSE
band_fill_color	character vector of hex colors for the bands if left_as_band == TRUE.
bar_border	character hex colors for the border around bars in bar charts.
bar_border_lwd	numeric The line width of the borders of bars in barplots. Default 1
bar_fill_color	character vector of hex colors for the bars if left_as_bar == TRUE
bar_gap	numeric The width of the gap between bars, in % of space allotted to the bar.
bar_group_gap	numeric The width of the gap between groups of bars if group_bar_chart is TRUE.
ci_alpha	Numeric 0-255, numeric 0-1 or hex 00-FF, transparency of the confidence interval bands
ci_colors	Named colors or hex values Colors of the confidence interval bands
ci_legend_label	character A formatting template for how the ci bands should be labelled. May contain the placeholders. '%ci_value%' will be replaced with the ci label. '%series%' (will be replaced with the series name) exactly once. Defaults to '%ci_value% ci for %series%'
default_bottom_margin	numeric The bottom margin to use when margins[1] is NA but neither auto_legend nor auto_bottom_margin are true. Default 3
fill_up_start	logical should the start of the year also be filled? Has no effect if fill_year_with_nas == FALSE. Default FALSE
fill_year_with_nas	logical should year be filled up with missing in order to plot the entire year on the axis. Defaults to TRUE,
highlight_color	character hex color code of highlight background, defaults to "#e9e9e9".

highlight_window	logical should a particular time span be highlighted by different background color. Defaults to FALSE.
highlight_window_end	integer vector highlight window start position, defaults to NA.,
highlight_window_freq	integer frequency of the highlight window definition, defaults to 4.
highlight_window_start	integer vector highlight window start position, defaults to NA.
label_pos	character, denotes where the x-axis label is at. defaults to "mid", alternative value: "start".
legend_all_left	logical Should all legend entries be drawn on the left side of the plot? Default FALSE
legend_box_size	numeric The size of the squares denoting bar colors in the legend. Default 2
legend_col	integer number of columns for the legend, defaults to 3.
legend_font_size	numeric passed on to the cex parameter of <code>legend</code> , defaults to 1
legend_intersp_x	numeric same as base <code>legend</code> parameter, defaults to 1
legend_intersp_y	numeric same as base <code>legend</code> parameter, defaults to 1
legend_margin_bottom	numeric Distance between bottom of legend and bottom of graphic in % of device height, default 5
legend_margin_top	numeric Distance between bottom of plot and top of legends % of device height, defaults to 12
legend_seg.len	numeric Length of the line segments in the legend. Default 2
line_colors	character vector of hex colors for 6 lines.
line_to_middle	logical try to put a line into the middle of the plot. defaults to TRUE.
lty	integer vector line type defaults to 1.
lwd	integer vector line width, defaults to c(2,3,1,4,2,4).
lwd_box	numeric Line width of the box around the plot. Default 1.5
lwd_quarterly_ticks	numeric, width of yearly ticks, defaults to 1.
lwd_x_axis	numeric The line width of the x axis. Default 1.5
lwd_y_axis	numeric The line width of the y axis. Default 1.5
lwd_y_ticks	numeric Line width of the y ticks. Default 1.5
lwd_yearly_ticks	numeric, width of yearly ticks, defaults to 1.5.

<code>margins</code>	integer vector defaults to <code>c(NA, 4, 3, 3) + 0.1</code> . Set <code>margins[1]</code> to <code>NA</code> to automatically determine the bottom margin such that the legend fits (if either <code>auto_legend</code> or <code>auto_bottom_margin</code> are <code>TRUE</code>)
<code>NA_continue_line</code>	boolean If true, <code>NA</code> values in time series are ignored and a continuous line is drawn. Multiple values to turn this behavior on/off for individual series are supported. Default <code>FALSE</code>
<code>output_wide</code>	logical Should the output file be in a wide format (16:9) or (4:3)? Only if <code>output_format</code> is not "plot". Default <code>FALSE</code>
<code>point_symbol</code>	integer or character The symbol to use for marking data points. Multiple values can be supplied to set the symbol for each individual series See <code>pch</code> in <code>?par</code> . Default <code>1:18</code>
<code>pointsize</code>	Numeric Point size of text, in 1/72 of an inch
<code>preferred_y_gap_sizes</code>	numeric <code>c(25, 20, 15, 10, 5, 2.5, 1, 0.5)</code> ,
<code>quarterly_ticks</code>	logical, should quarterly ticks be shown. Defaults to <code>TRUE</code> .
<code>range_must_not_cross_zero</code>	logical automatic range finders are forced to do not find ranges below zero. Defaults to <code>TRUE</code> .
<code>show_left_y_axis</code>	logical: should left y axis be shown, defaults to <code>TRUE</code> .
<code>show_points</code>	boolean Whether to draw the symbol specified by <code>point_symbol</code> at the data points. Multiple values can be supplied to enable/disable showing points for each individual series Default <code>FALSE</code>
<code>show_right_y_axis</code>	logical: should left y axis be shown, defaults to <code>TRUE</code> .
<code>show_x_axis</code>	logical: should x axis be shown, defaults to <code>TRUE</code>
<code>show_y_grids</code>	logical should y_grids by shown at all, defaults to <code>TRUE</code> .
<code>subtitle_adj</code>	numeric same as base <code>plot</code> parameter, defaults to 0.
<code>subtitle_adj_r</code>	numeric same as base <code>plot</code> parameter, defaults to .9
<code>subtitle_cex</code>	numeric same as base <code>plot</code> parameter, defaults to 1.
<code>subtitle_margin</code>	numeric How far above the plot the title is placed in % of the device height. Defaults to 2.
<code>subtitle_outer</code>	logical same as base <code>plot</code> parameter, defaults to <code>TRUE</code>
<code>subtitle_transform</code>	function to transform the subtitle, defaults to "toupper",
<code>sum_as_line</code>	logical should the sum of stacked time series be displayed as a line on top of stacked bar charts. Defaults to <code>FALSE</code> ,
<code>sum_legend</code>	character Label for the sum line, defaults to "sum". Set to <code>NULL</code> to not label the line at all.
<code>sum_line_color</code>	character hex color of of <code>sum_as_line</code> , defaults "#91056a".

sum_line_lty	integer line type of sum_as_line, defaults to 1.
sum_line_lwd	integer line width of sum_as_line, defaults to 3.
tcl_quarterly_ticks	numeric, length of quarterly ticks. See tcl_yearly_ticks, defaults to -0.4
tcl_y_ticks	numeric Length of y ticks, see tcl_yearly_ticks. Default -0.75
tcl_yearly_ticks	numeric, length of yearly ticks. Analogous to cex for axis . defaults to -0.75.
title_adj	numeric, same as base plot parameter, defaults to 0.
title_cex.main	numeric, same as base plot parameter defaults to 1
title_margin	numeric How far above the plot the title is placed in % of the device height. Default 8
title_outer	logical, currently undocumented. Defaults to TRUE.
title_transform	function to transform the title, defaults to NA.
total_bar_margin_pct	numeric definition as in base plot, defaults to "i", defaults to .2,
use_bar_gap_in_groups	logical Should there be gaps of size bar_gap between the bars in a group if group_bar_chart = TRUE? Default FALSE
use_box	logical use a box around the plot.
x_tick_dt	numeric The distance between ticks on the x axis in years. The first tick will always be at the start of the plotted time series. Defaults to 1.
xaxs	character axis definition as in base plot, defaults to "i".
y_grid_color	character hex color of grids. Defaults to gray "#CCCCCC".
y_grid_count	integer vector preferred y grid counts c(5,6,8,10).
y_grid_count_strict	logical should we strictly stick to preferred y grid count? Defaults to FALSE.
y_las	integer, same as base plot parameter defaults to 2.
y_range_min_size	= NULL ,
y_tick_force_integers	logical Should y ticks be forced (rounded down) to whole numbers? Default FALSE
y_tick_margin	numeric, minimal percentage of horizontal grid that needs to be clean, i.e., without lines or bars. Defaults to 0.15 (15 percent).
yaxs	character axis definition as in base plot, defaults to "i".
yearly_ticks	logical, should yearly ticks be shown. Defaults to TRUE.
...	All the other arguments to init_tsplot_thene

Details

Themes are essentially list that contain `par` parameters. Below all items are listed, some of them with comments. The per-line parameters (`line_colors`, `lwd`, `lty`, `show_points`, `point_symbol`) are recycled if more time series than elements on the corresponding theme vectors are supplied. e.g. if four time series are plotted but only two `line_colors` are supplied, the first and third series have the first color, while the second and fourth series have the second color. The list contains the following elements:

Author(s)

Matthias Bannert

Examples

```
# create a list
data(KOF)
tt <- init_tsplot_theme()
# adjust a single element
tt$highlight_window <- TRUE
# pass the list to tsplot
tsplot(KOF$kofbarometer, theme = tt)
# for more theme examples check the vignette
vignette("tstools")
```

KOF

KOF Barometer - Swiss Business Cycle Indicator

Description

A list of time series containing two time series the KOF Barometer and the growth of Swiss GDP over time. KOF Barometer is a monthly business cycle indicator computed by the KOF Swiss Economic Institute. The GDP growth rate is used as a reference series to the Barometer.

Usage

KOF

Format

A list of two time series of class `ts`

kofbarometer KOF Barometer Indicator'

reference Reference series to KOF Barometer, change in Swiss GDP compared to previous month

baro_point_fc Auto Arima point forecast of the KOF Barometer

baro_lo_80 Auto Arima 80 percent CI lower bound of the KOF Barometer forecast

baro_hi_80 Auto Arima 80 percent CI upper bound of the KOF Barometer forecast

baro_lo_95 Auto Arima 95 percent CI lower bound of the KOF Barometer forecast

baro_hi_95 Auto Arima 95 percent CI upper bound of the KOF Barometer forecast ...

Source

<https://www.kof.ethz.ch/en/forecasts-and-indicators/indicators/kof-economic-barometer.html>

long_to_ts	<i>Transform a long format data.frame of time series to a tsvlist</i>
------------	---

Description

The data.frame must have three columns "date", "value" and "series" (identifying the time series)

Usage

```
long_to_ts(data)
```

Arguments

data	data.frame The data.frame to be transformed
------	---

m_to_q	<i>Turn monthly series with regular NAs to quarter</i>
--------	--

Description

Monthly series with NAs in non-quarter months are turned to quarterly series. Series without NAs are just returned.

Usage

```
m_to_q(series)
```

Arguments

series	an object of class ts with monthly frequency
--------	--

`overlap_sorted_ts_lists`*Concat Time Series list wise*

Description

Concat overlapping time series list wise. List needs to be of same length. Takes names of list B.

Usage

```
overlap_sorted_ts_lists(listA, listB)
```

Arguments

<code>listA</code>	list of time series
<code>listB</code>	list of time series

`overlap_ts_lists_by_name`*Resolve Overlap Listwise, helpful with SA*

Description

Resolve Overlap Listwise, helpful with SA

Usage

```
overlap_ts_lists_by_name(listA, listB, chunkA = "_f4", chunkB = "_f12")
```

Arguments

<code>listA</code>	list of time series often of lower frequency
<code>listB</code>	list of time series often of higher frequency
<code>chunkA</code>	character chunk representing frequencies, defaults to <code>_f4</code> .
<code>chunkB</code>	character chunk representing frequencies, defaults to <code>_f12</code> .

read_swissdata	<i>Read data generated by the Swissdata project</i>
----------------	---

Description

Read data from swissdata compliant .csv files and turn them into a list of time series.

Usage

```
read_swissdata(path, key_columns, filter = NULL)
```

Arguments

path	character full path to dataset.
key_columns	character vector specifying all columns that should be part of the key.
filter	function A function that is applied to the raw data.data table after it is read. Useful for filtering out undesired data.

Details

The order of dimensions in key_columns determines their order in the key The resulting ts_key will be of the form <swissdata-set-name>.<instance of key_columns[1]>...

Examples

```
ds_location <- system.file("example_data/ch.seco.css.csv",package = "tstools")
tslist <- read_swissdata(ds_location,"idx_type")
tsplot(tslist[1])
```

read_ts	<i>Import time series data from a file.</i>
---------	---

Description

If importing from a zip file, the archive should contain a single file with the extension .csv, .xlsx or .json.

Usage

```
read_ts(file, format = c("csv", "xlsx", "json", "zip"), sep = ",",
        skip = 0)
```

Arguments

file	Path to the file to be read
format	Which file format is the data stored in? If no format is supplied, read_ts will attempt to guess from the file extension.
sep	character separator for csv files. defaults to ','.
skip	numeric See data.table's fread.

Value

A named list of ts objects

regularize	<i>Turn an Irregular Time Series to a Regular, ts-Based Series</i>
------------	--

Description

Adds missing values to turn an irregular time series into a regular one. This function is currently experimental. Only works on target frequencies 1,2,4,12.

Usage

```
regularize(x)
```

Arguments

x an irregular time series object of class zoo or xts.

Examples

```
ts1 <- rnorm(5)
dv <- c(seq(as.Date("2010-01-01"), length = 3, by="3 years"),
seq(as.Date("2018-01-01"), length = 2, by="2 years"))
library(zoo)
xx <- zoo(ts1,dv)
regularize(xx)

dv2 <- c(seq(as.Date("2010-01-01"), length = 20, by = "1 months"))
dv2 <- dv2[c(1:10, 14:20)]
xx2 <- zoo(rnorm(length(dv2)), dv2)
regularize(xx2)
```

 resolve_ts_overlap *Concatenate Time Series and Resolve Overlap Automatically*

Description

Append time series to each other. Resolve overlap determines which of two ts class time series is reaching further and arranges the two series into first and second series accordingly. Both time series are concatenated to one if both series had the same frequency. Typically this function is used concatenate two series that have a certain overlap, but one series clearly starts earlier while the other lasts longer. If one series starts earlier and stops later, all elements of the shorter series will be inserted into the larger series, i.e. elements of the smaller series will replace the elements of the longer series. Usually ts2 is kept.

Usage

```
resolve_ts_overlap(ts1, ts2, keep_ts2 = T, tolerance = 0.001)
```

Arguments

ts1	ts time series, typically the older series
ts2	ts time series, typically the younger series
keep_ts2	logical should ts2 be kept? Defaults to TRUE.
tolerance	numeric when comparing min and max values with a index vector of a time series R runs in to trouble with precision handling, thus a tolerance needs to be set. Typically this does not need to be adjusted. E.g. 2010 != 2010.000. With the help of the tolerance parameter these two are equal.

Examples

```
ts1 <- ts(rnorm(100),start = c(1990,1),frequency = 4)
ts2 <- ts(1:18,start = c(2000,1),frequency = 4)
resolve_ts_overlap(ts1,ts2)

# automatical detection of correction sequence!
ts1 <- ts(rnorm(90),start = c(1990,1),frequency = 4)
ts2 <- ts(1:60,start = c(2000,1),frequency = 4)
resolve_ts_overlap(ts1,ts2)

# both series are of the same length use sequence of arguments.
ts1 <- ts(rnorm(100),start = c(1990,1),frequency = 4)
ts2 <- ts(1:48,start = c(2003,1),frequency = 4)
resolve_ts_overlap(ts1,ts2)
ts1 <- ts(rnorm(101),start = c(1990,1),frequency = 4)
ts2 <- ts(1:61,start = c(2000,1),frequency = 4)
resolve_ts_overlap(ts1,ts2)
#' clearly dominatn ts2 series
ts1 <- ts(rnorm(50),start = c(1990,1),frequency = 4)
ts2 <- ts(1:100,start = c(1990,1),frequency = 4)
resolve_ts_overlap(ts1,ts2)
```

set_month_to_NA	<i>Set Periods to NA</i>
-----------------	--------------------------

Description

This function is typically used to discard information in non-quarter month. I.e., data is only kept in January, April, July and December and otherwise set to NA. In combination with `m_to_q` this function is useful to turn monthly series into quarterly series by letting the quarter month values represent the entire quarter. This can be useful when data was interpolated because of mixing data of different frequencies and needs to be converted back to a regular, quarterly time series.

Usage

```
set_month_to_NA(series, keep_month = c(1, 4, 7, 10))
```

Arguments

series	ts object
keep_month	integer vector denoting the months that not be set to NA. Defaults to c(1,4,7,10)

Examples

```
tsq <- ts(1:20, start=c(1990,1), frequency = 4)
aa <- tsqm(tsq)
m_to_q(set_month_to_NA(aa))
```

start_ts_after_internal_nas	<i>Start a Time Series after the Last Internal NA</i>
-----------------------------	---

Description

Internal NAs can cause trouble for time series operations such as X-13-ARIMA SEATS seasonal adjustment. Often, internal NAs only occur at at the beginning of a time series. Thus an easy solution to the problem is to discard the initial part of the data which contains the NA values. This way only a small part of the information is lost as opposed to not being able to seasonally adjust an entire series.

Usage

```
start_ts_after_internal_nas(series)
```

Arguments

series	on object of class ts
--------	-----------------------

See Also

[stripLeadingNAsFromTs](#), [stripTrailingNAsFromTs](#)

Examples

```
ts1 <- 1:30
ts1[c(3,6)] <- NA
ts1 <- ts(ts1,start=c(2000,1),frequency = 4)
start_ts_after_internal_nas(ts1)
```

strip_ts_of_leading_nas

Strip Leading / Trailing NAs from a Time Series Object

Description

Removes NAs to begin with and starts time series index at the first non-NA value.

Usage

```
strip_ts_of_leading_nas(s)
strip_ts_of_trailing_nas(s)
```

Arguments

`s` an object of class `ts`.

tsplot

Plot Time Series

Description

Conveniently plot time series.

Usage

```
tsplot(..., tsr = NULL, ci = NULL, left_as_bar = FALSE,
  group_bar_chart = FALSE, relative_bar_chart = FALSE,
  left_as_band = FALSE, plot_title = NULL, plot_subtitle = NULL,
  plot_subtitle_r = NULL, find_ticks_function = "findTicks",
  overall_xlim = NULL, overall_ylim = NULL, manual_date_ticks = NULL,
  manual_value_ticks_l = NULL, manual_value_ticks_r = NULL,
  manual_ticks_x = NULL, theme = NULL, quiet = TRUE, auto_legend = TRUE,
  output_format = "plot", filename = "tsplot",
  close_graphics_device = TRUE)
```

Arguments

...	multiple objects of class ts or a list of time series. All objects passed through the ... parameter relate to the standard left y-axis.
tsr	list of time series objects of class ts.
ci	list of confidence intervals for time series
left_as_bar	logical should the series that relate to the left bar be drawn as (stacked) bar charts?
group_bar_chart	logical should a bar chart be grouped instead of stacked?
relative_bar_chart	logical Should time series be normalized such that bars range from 0 to 1? Defaults to FALSE. That way every sub bar (time series) is related to the global max. Hence do not expect every single bar to reach 1. This works for stacked and grouped charts and does not change anything but the scale of the chart.
left_as_band	logical Should the time series assigned to the left axis be displayed as stacked area charts?
plot_title	character title to be added to the plot
plot_subtitle	character subtitle to be added to the plot
plot_subtitle_r	character second subtitle to be added at the top right
find_ticks_function	function to compute ticks.
overall_xlim	integer overall x-axis limits, defaults to NULL.
overall_ylim	integer overall y-axis limits, defaults to NULL.
manual_date_ticks	character vector of manual date ticks.
manual_value_ticks_l	numeric vector, forcing ticks to the left y-axis
manual_value_ticks_r	numeric vector, forcing ticks to the right y-axis
manual_ticks_x	numeric vector, forcing ticks on the x axis
theme	list of default plot output parameters. Defaults to NULL, which leads to init_tsplo_theme being called. Please see the vignette for details about tweaking themes.
quiet	logical suppress output, defaults to TRUE.
auto_legend	logical should legends be printed automatically, defaults to TRUE.
output_format	character Should the plot be drawn on screen or written to a file? Possible values are "plot" for screen output and "pdf". Default "plot"
filename	character Path to the file to be written if output_format is "pdf". Default "tsplo.pdf"
close_graphics_device	logical Should the graphics device of the output file be closed after tsplo? Set this to FALSE to be able to make modifications to the plot after tsplo finishes. Default TRUE

Details

The ci parameter is a 3-level list of the form `list(ts1 = list(ci_value_1 = list(ub = upper_bound_ts_object, lb = lower_bound_ts_object), ...), ...)`

See `vignette("tstools")` for details.

tsqm	<i>Interpolate quarterly time series into monthly</i>
------	---

Description

Repeat quarterly variables two times to generate a monthly variable.

Usage

```
tsqm(qts)
```

Arguments

qts quarterly time series

Examples

```
tsq <- ts(1:20, start=c(1990,1), frequency = 4)
tsqm(tsq)
```

tstools-deprecated	<i>Deprecated function(s) in tstools</i>
--------------------	--

Description

These functions are provided for compatibility with older version of the `tstools` package. They may eventually be completely removed.

Arguments

... Parameters to be passed to the modern version of the function

Details

computeDecimalTime	now a synonym for compute_decimal_time
concatTs	now a synonym for concat_ts
fillupYearWithNAs	now a synonym for fill_year_with_nas
importTimeSeries	now a synonym for read_ts
init_tsplot_theme	now a synonym for init_tsplot_theme
overlapSortedLists	now a synonym for overlap_sorted_ts_lists
overlapTslByName	now a synonym for overlap_ts_lists_by_name
resolveOverlap	now a synonym for resolve_ts_overlap
stripLeadingNAsFromTs	now a synonym for strip_ts_of_leading_nas
stripTrailingNAsFromTs	now a synonym for strip_ts_of_trailing_nas
writeTimeSeries	now a synonym for write_ts

`wide_to_ts`*Transform a wide format data.frame into a tslist*

Description

The time series in the data.frame may be stored either rowwise or columnwise. The identifying column must be called date (for columnwise) or series (for rowwise)

Usage

```
wide_to_ts(data)
```

Arguments

data	data.frame	The data.frame to be transformed
------	------------	----------------------------------

`write_ts`*Export a list of time series to a file.*

Description

Export a list of time series to a file.

Usage

```
write_ts(tl, fname = NULL, format = "csv", date_format = NULL,
  timestamp_to_fn = FALSE, round_digits = NULL, rdata_varname = "tslist",
  ...)
```


Arguments

t1	list of time series
fname	character file name. Defaults to NULL, displaying output on console. Set a file name without file extension in order to store a file. Default file names / location are not CRAN compliant which is why the file name defaults to NULL.
format	character denotes export formats. Defaults to .csv. "csv", "xlsx", "json", "rdata" are available. Spreadsheet formats like csv allow for further optional parameters.
date_format	character denotes the date format. Defaults to NULL. If set to null the default is used: Jan 2010.
timestamp_to_fn	If TRUE, the current date will be appended to the file name. Defaults to FALSE.
round_digits	integer, precision in digits.
rdata_varname	character name of the list of time series within the store RData. Defaults to "tslist".
...	additional arguments used by specific formats.

Details

Additional arguments covered by ...

Name	Effect	Format(s)
wide	Export data in a wide format (one column per series)	CSV, XLSX
transpose	Transpose exported data (one row per series)	CSV, XLSX, only if wide = TRUE
zip	If set to TRUE, the file is compressed into a zip archive after export	any

Index

*Topic **datasets**

- CHGDP, [2](#)
- KOF, [14](#)

- axis, [13](#)

- CHGDP, [2](#)
- color_blind, [3](#)
- compute_decimal_time, [3](#), [24](#)
- computeDecimalTime
(tstools-deprecated), [23](#)
- concat_ts, [4](#), [24](#)
- concatTs (tstools-deprecated), [23](#)
- create_dummy_ts, [4](#)

- df_to_reg_ts, [5](#)

- fill_year_with_nas, [6](#), [24](#)
- fillupYearWithNAs (tstools-deprecated),
[23](#)

- generate_random_ts, [6](#)
- get_date_vector, [8](#)
- getCiLegendColors, [7](#)

- importTimeSeries (tstools-deprecated),
[23](#)
- init_tsplot_print_theme
(init_tsplot_theme), [8](#)
- init_tsplot_theme, [8](#), [22](#), [24](#)
- initDefaultTheme (tstools-deprecated),
[23](#)

- KOF, [14](#)

- legend, [11](#)
- long_to_ts, [15](#)

- m_to_q, [15](#), [20](#)

- overlap_sorted_ts_lists, [16](#), [24](#)

- overlap_ts_lists_by_name, [16](#), [24](#)
- overlapSortedLists
(tstools-deprecated), [23](#)
- overlapTslByName (tstools-deprecated),
[23](#)

- par, [14](#)
- plot, [12](#), [13](#)

- read_swissdata, [17](#)
- read_ts, [17](#), [24](#)
- regularize, [18](#)
- resolve_ts_overlap, [19](#), [24](#)
- resolveOverlap, [4](#)
- resolveOverlap (tstools-deprecated), [23](#)

- set_month_to_NA, [20](#)
- start_ts_after_internal_nas, [20](#)
- strip_ts_of_leading_nas, [21](#), [24](#)
- strip_ts_of_trailing_nas, [24](#)
- strip_ts_of_trailing_nas
(strip_ts_of_leading_nas), [21](#)
- stripLeadingNAsFromTs, [21](#)
- stripLeadingNAsFromTs
(tstools-deprecated), [23](#)
- stripTrailingNAsFromTs, [21](#)
- stripTrailingNAsFromTs
(tstools-deprecated), [23](#)

- tsplot, [8](#), [21](#)
- tsqm, [23](#)
- tstools-deprecated, [23](#)
- tstools-deprecated-package
(tstools-deprecated), [23](#)

- wide_to_ts, [24](#)
- write_ts, [24](#), [24](#)
- writeTimeSeries (tstools-deprecated), [23](#)