

# Package ‘usmap’

June 13, 2023

**Version** 0.6.2

**Title** US Maps Including Alaska and Hawaii

**Description** Obtain United States map data frames of varying region types (e.g. county, state). The map data frames include Alaska and Hawaii conveniently placed to the bottom left, as they appear in most maps of the US. Convenience functions for plotting choropleths and working with FIPS codes are also provided.

**Depends** R (>= 3.5.0)

**License** GPL (>= 3)

**Encoding** UTF-8

**Language** en-US

**LazyData** true

**URL** <https://usmap.dev>

**BugReports** <https://github.com/pdil/usmap/issues>

**Imports** rlang, usmapdata, utils

**Suggests** covr, ggplot2, ggrepel, knitr, proto, rmarkdown, scales, sp, sf, stringr, testthat

**RoxygenNote** 7.2.3

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Paolo Di Lorenzo [aut, cre]

**Maintainer** Paolo Di Lorenzo <paolo@dilorenzo.pl>

**Repository** CRAN

**Date/Publication** 2023-06-13 08:50:02 UTC

## R topics documented:

.east_north_central . . . . .	2
.east_south_central . . . . .	3
.midwest_region . . . . .	3

.mid_atlantic . . . . .	4
.mountain . . . . .	4
.new_england . . . . .	5
.northeast_region . . . . .	5
.north_central_region . . . . .	6
.pacific . . . . .	6
.south_atlantic . . . . .	7
.south_region . . . . .	7
.west_north_central . . . . .	8
.west_region . . . . .	8
.west_south_central . . . . .	9
citypop . . . . .	9
countypop . . . . .	10
countypov . . . . .	10
earthquakes . . . . .	11
fips . . . . .	12
fips_info . . . . .	13
map_with_data . . . . .	14
plot_usmap . . . . .	15
statepop . . . . .	17
statepov . . . . .	17
usmap . . . . .	18
usmap_crs . . . . .	19
usmap_transform . . . . .	20
us_map . . . . .	21
<b>Index</b>	<b>23</b>

---

`.east_north_central` *East North Central census division*

---

### Description

US Census Bureau regional division containing Illinois, Indiana, Michigan, Ohio, and Wisconsin.

### Usage

```
.east_north_central
```

### Format

An object of class character of length 5.

### Details

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .east_north_central, labels = TRUE)
```

---

```
.east_south_central    East South Central census division
```

---

**Description**

US Census Bureau regional division containing Alabama, Kentucky, Mississippi, and Tennessee.

**Usage**

```
.east_south_central
```

**Format**

An object of class character of length 4.

**Details**

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .east_south_central, labels = TRUE)
```

---

```
.midwest_region    Midwest census region
```

---

**Description**

US Census Bureau region containing the East North Central and West North Central divisions. This region was designated as "North Central Region" prior to June 1984.

**Usage**

```
.midwest_region
```

**Format**

An object of class character of length 12.

**Details**

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .midwest_region, labels = TRUE)
```

---

.mid_atlantic	<i>Mid-Atlantic census division</i>
---------------	-------------------------------------

---

**Description**

US Census Bureau regional division containing New Jersey, New York, and Pennsylvania.

**Usage**

```
.mid_atlantic
```

**Format**

An object of class character of length 3.

**Details**

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .mid_atlantic, labels = TRUE)
```

---

.mountain	<i>Mountain census division</i>
-----------	---------------------------------

---

**Description**

US Census Bureau regional division containing Arizona, Colorado, Idaho, Montana, Nevada, New Mexico, Utah, and Wyoming.

**Usage**

```
.mountain
```

**Format**

An object of class character of length 8.

**Details**

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .mountain, labels = TRUE)
```

---

.new\_england                      *New England census division*

---

**Description**

US Census Bureau regional division containing Connecticut, Maine, Massachusetts, New Hampshire, Rhode Island, and Vermont.

**Usage**

.new\_england

**Format**

An object of class character of length 6.

**Details**

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .new_england, labels = TRUE)
```

---

.northeast\_region                      *Northeast census region*

---

**Description**

US Census Bureau region containing the New England and Mid-Atlantic divisions.

**Usage**

.northeast\_region

**Format**

An object of class character of length 9.

**Details**

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .northeast_region, labels = TRUE)
```

---

`.north_central_region` *North-Central census region*

---

**Description**

Former US Census Bureau region containing the East North Central and West North Central divisions. This region has been designated as "Midwest" since June 1984.

**Usage**

```
.north_central_region
```

**Format**

An object of class character of length 12.

**Details**

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .north_central_region, labels = TRUE)
```

---

`.pacific` *Pacific census division*

---

**Description**

US Census Bureau regional division containing Alaska, California, Hawaii, Oregon, and Washington.

**Usage**

```
.pacific
```

**Format**

An object of class character of length 5.

**Details**

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .pacific, labels = TRUE)
```

---

.south\_atlantic      *South Atlantic census division*

---

### Description

US Census Bureau regional division containing Delaware, Florida, Georgia, Maryland, North Carolina, South Carolina, Virginia, District of Columbia, and West Virginia.

### Usage

```
.south_atlantic
```

### Format

An object of class character of length 9.

### Details

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

### Examples

```
plot_usmap(include = .south_atlantic, labels = TRUE)
```

---

.south\_region      *South census region*

---

### Description

US Census Bureau region containing the South Atlantic, East South Central, and West South Central divisions.

### Usage

```
.south_region
```

### Format

An object of class character of length 17.

### Details

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

### Examples

```
plot_usmap(include = .midwest_region, labels = TRUE)
```

---

.west\_north\_central     *West North Central census division*

---

**Description**

US Census Bureau regional division containing Iowa, Kansas, Minnesota, Missouri, Nebraska, North Dakota, and South Dakota.

**Usage**

```
.west_north_central
```

**Format**

An object of class character of length 7.

**Details**

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .west_north_central, labels = TRUE)
```

---

.west\_region     *West census region*

---

**Description**

US Census Bureau region containing the Mountain and Pacific divisions.

**Usage**

```
.west_region
```

**Format**

An object of class character of length 13.

**Details**

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

**Examples**

```
plot_usmap(include = .midwest_region, labels = TRUE)
```



---

.west\_south\_central     *West South Central census division*

---

### Description

US Census Bureau regional division containing Arkansas, Louisiana, Oklahoma, and Texas.

### Usage

```
.west_south_central
```

### Format

An object of class character of length 4.

### Details

See [https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us\\_regdiv.pdf](https://www2.census.gov/geo/pdfs/maps-data/maps/reference/us_regdiv.pdf)

### Examples

```
plot_usmap(include = .west_south_central, labels = TRUE)
```

---

citypop     *Most populous city in each state (2010)*

---

### Description

The most populous city in each US state, as of the 2010 US Census.

The data is formatted for transforming with `usmap_transform`. Once the longitude and latitude is transformed, it can be added to `plot_usmap` using ggplot2 layers.

### Usage

```
data(citypop)
```

### Format

A data frame with 51 rows and 5 variables.

### Details

- lon The longitude of the most populous city.
- lat The latitude of the most populous city.
- state The name of the state containing the city.
- most\_populous\_city The name of the city.
- city\_pop The population of the city.

**References**

- <https://www.census.gov/programs-surveys/decennial-census/decade.2010.html>

---

countypop	<i>Population estimates (2015), county level</i>
-----------	--

---

**Description**

US census population estimates by county for 2015.

The data is formatted for easy merging with output from [us\\_map](#).

**Usage**

```
data(countypop)
```

**Format**

A data frame with 3142 rows and 4 variables.

**Details**

- fips The 5-digit FIPS code corresponding to the county.
- abbr The 2-letter state abbreviation.
- county The full county name.
- pop\_2015 The 2015 population estimate (in number of people) for the corresponding county.

**References**

- <https://www.census.gov/programs-surveys/popest.html>
- <https://www.ers.usda.gov/data-products/county-level-data-sets/>

---

countypov	<i>Poverty percentage estimates (2014), county level</i>
-----------	--

---

**Description**

US census poverty percentage estimates by county for 2014.

The data is formatted for easy merging with output from [us\\_map](#).

**Usage**

```
data(countypov)
```

**Format**

A data frame with 3142 rows and 4 variables.

**Details**

- `fips` The 5-digit FIPS code corresponding to the county.
- `abbr` The 2-letter state abbreviation.
- `county` The full county name.
- `pct_pov_2014` The 2014 poverty estimate (in percent of county population) for the corresponding county.

**References**

- <https://www.census.gov/topics/income-poverty/poverty.html>
- <https://www.ers.usda.gov/data-products/county-level-data-sets/>

---

earthquakes

*Earthquakes (2019)*

---

**Description**

US earthquakes with a magnitude of 2.5 or greater, occurring in the first half of 2019, from January 1st to June 30th, from USGS.

The data is formatted for transforming with `usmap_transform`. Once the longitude and latitude is transformed, it can be added to `plot_usmap` using `ggplot2` layers.

**Usage**

```
data(earthquakes)
```

**Format**

A data frame with 2254 rows and 3 variables.

**Details**

- `lon` The longitude of the earthquake's location.
- `lat` The latitude of the earthquake's location.
- `mag` The magnitude of the earthquake.

**References**

- <https://www.usgs.gov/programs/earthquake-hazards/earthquakes>
- <https://earthquake.usgs.gov/earthquakes/search/>

---

`fips`*Retrieve FIPS code for either a US state or county*

---

### Description

Each US state and county has a unique FIPS (Federal Information Processing Standards) code. Use this function to obtain the FIPS code for a state or county.

### Usage

```
fips(state, county = c())
```

### Arguments

<code>state</code>	The state(s) for which to obtain a FIPS code(s). Can be entered as either a state abbreviation or full name (case-insensitive). state can be entered as either a single state or a vector of states. If state is a vector, county must be omitted.
<code>county</code>	The county for which to obtain a FIPS code. Can be entered with or without "county" (case-insensitive).

### Details

State and county FIPS (Federal Information Processing Standards) are two and five digit codes, respectively. They uniquely identify all states and counties within the United States. The first two digits of the five digit county codes correspond to the state that the county belongs to. FIPS codes also exist for US territories and minor outlying islands, though this package only provides information for the 50 US states (and their associated counties and census designated areas).

### Value

The FIPS code(s) of given state or county.

If only states are entered, a vector of length equal to the number of states is returned. If any states are not found or are invalid, NA is returned in their place.

If a state and county are entered, a single value with the FIPS code for the given county is returned. If the county is invalid for the given state, an error is thrown.

If both state and county are omitted, the entire list of available FIPS codes is returned, sorted by the state's abbreviation (e.g. Alaska (AK) comes before Alabama (AL)).

### Note

A state must be included when searching for county, otherwise multiple results may be returned for duplicate county names.

## Examples

```
fips()

fips("NJ")
fips("California")

fips(c("AK", "CA", "UT"))

fips("CA", county = "orange")
fips(state = "AL", county = "autauga")
fips(state = "Alabama", county = "Autauga County")
```

---

fips\_info

*Retrieve states or counties using FIPS codes*

---

## Description

Retrieve states or counties using FIPS codes

## Usage

```
fips_info(fips, sortAndRemoveDuplicates = FALSE)

## S3 method for class 'numeric'
fips_info(fips, sortAndRemoveDuplicates = FALSE)

## S3 method for class 'character'
fips_info(fips, sortAndRemoveDuplicates = FALSE)
```

## Arguments

**fips** A one to five digit, either numeric or character, vector of FIPS codes for which to look up states or counties. States have a two digit FIPS code and counties have a five digit FIPS code (where the first 2 numbers pertain to the state).

**sortAndRemoveDuplicates** Whether or not to sort the output and remove duplicates. By default, the output will be returned in the order of the values provided to the `fips` parameter. Set this parameter to `TRUE` to return the output sorted by FIPS with a single instance of each FIPS.

## Value

A data frame with the states or counties and the associated FIPS codes.

If `fips` is omitted, the data frame containing all available states is returned.

**Examples**

```
fips_info(2)
fips_info("2")
fips_info(c("02", "03", "04"))

fips_info(2016)
fips_info(c("02016", "02017"), sortAndRemoveDuplicates = TRUE)
```

---

map_with_data	<i>Join county or state level data to US map data</i>
---------------	---

---

**Description**

Join county or state level data to US map data

**Usage**

```
map_with_data(data, values = "values", include = c(), exclude = c(), na = NA)
```

**Arguments**

data	The data that should be joined to a US map. This parameter should be a data frame consisting of two columns, a fips code (2 characters for state, 5 characters for county) and the value that should be associated with that region. The columns of data <i>must</i> be fips or state and the value of the values parameter. If both fips and state are provided, this function uses the fips.
values	The name of the column that contains the values to be associated with a given region. The default is "values".
include	The regions to include in the resulting map. If regions is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. If states are provided in the county map, only counties in the included states will be returned.
exclude	The regions to exclude in the resulting map. If regions is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. The regions listed in the include parameter are applied first and the exclude regions are then removed from the resulting map. Any excluded regions not present in the included regions will be ignored.
na	The value to be inserted for states or counties that don't have a value in data. This value must be of the same type as the value column of data.

**Value**

A data frame composed of the map data frame (from [us\\_map](#)) except an extra column containing the values in data is included.

The result can be plotted using `ggplot2`. See [us\\_map](#) or [plot\\_usmap](#) for more details.

## Examples

```
state_data <- data.frame(fips = c("01", "02", "04"), values = c(1, 5, 8))
df <- map_with_data(state_data, na = 0)

state_data <- data.frame(state = c("AK", "CA", "Utah"), values = c(6, 9, 3))
df <- map_with_data(state_data, na = 0)
```

---

plot\_usmap

*Conveniently plot basic US map*

---

## Description

Conveniently plot basic US map

## Usage

```
plot_usmap(
  regions = c("states", "state", "counties", "county"),
  include = c(),
  exclude = c(),
  data = data.frame(),
  values = "values",
  theme = theme_map(),
  labels = FALSE,
  label_color = "black",
  ...
)
```

## Arguments

- |         |  |
|---------|--|
| regions | The region breakdown for the map, can be one of ("states", "state", "counties", "county"). The default is "states".  |
| include | The regions to include in the resulting map. If regions is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. If states are provided in the county map, only counties in the included states will be returned.   |
| exclude | The regions to exclude in the resulting map. If regions is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. The regions listed in the include parameter are applied first and the exclude regions are then removed from the resulting map. Any excluded regions not present in the included regions will be ignored. |

data	A data frame containing values to plot on the map. This parameter should be a data frame consisting of two columns, a fips code (2 characters for state, 5 characters for county) and the value that should be associated with that region. The columns of data <i>must</i> be fips or state and the value of the values parameter.
values	The name of the column that contains the values to be associated with a given region. The default is "value".
theme	The theme that should be used for plotting the map. The default is theme_map from <a href="#">ggthemes</a> .
labels	Whether or not to display labels on the map. Labels are not displayed by default. For now, labels only work for state maps. County labels may be added in the future.
label_color	The color of the labels to display. Corresponds to the color option in the <a href="#">aes</a> mapping. The default is "black". <a href="#">Click here</a> for more color options.
...	Other arguments to pass to <code>ggplot2::aes()</code> . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>color = "red"</code> or <code>size = 3</code> . They affect the appearance of the polygons used to render the map (for example fill color, line color, line thickness, etc.). If any of <code>color/colour</code> , <code>fill</code> , or <code>size</code> are not specified they are set to their default values of <code>color="black"</code> , <code>fill="white"</code> , and <code>size=0.4</code> .

### Value

A [ggplot](#) object that contains a basic US map with the described parameters. Since the result is a [ggplot](#) object, it can be extended with more geom layers, scales, labels, themes, etc.

### See Also

[usmap](#), [theme](#)

### Examples

```
plot_usmap()
plot_usmap(regions = "states")
plot_usmap(regions = "counties")
plot_usmap(regions = "state")
plot_usmap(regions = "county")

# Output is ggplot object so it can be extended
# with any number of ggplot layers
library(ggplot2)
plot_usmap(include = c("CA", "NV", "ID", "OR", "WA")) +
  labs(title = "Western States")

# Color maps with data
plot_usmap(data = statepop, values = "pop_2015")

# Include labels on map (e.g. state abbreviations)
plot_usmap(data = statepop, values = "pop_2015", labels = TRUE)
# Choose color for labels
```



```
plot_usmap(data = statepop, values = "pop_2015", labels = TRUE, label_color = "white")
```

---

statepop	<i>Population estimates (2015), state level</i>
----------	---

---

**Description**

US census population estimates by state for 2015.

The data is formatted for easy merging with output from [us\\_map](#).

**Usage**

```
data(statepop)
```

**Format**

A data frame with 51 rows and 4 variables.

**Details**

- `fips` The 2-digit FIPS code corresponding to the state.
- `abbr` The 2-letter state abbreviation.
- `full` The full state name.
- `pop_2015` The 2015 population estimate (in number of people) for the corresponding state.

**References**

- <https://www.census.gov/programs-surveys/popest.html>
- <https://www.ers.usda.gov/data-products/county-level-data-sets/>

---

statepov	<i>Poverty percentage estimates (2014), state level</i>
----------	---

---

**Description**

US census poverty percentage estimates by state for 2014.

The data is formatted for easy merging with output from [us\\_map](#).

**Usage**

```
data(statepov)
```

## Format

A data frame with 51 rows and 4 variables.

## Details

- `fips` The 2-digit FIPS code corresponding to the state.
- `abbr` The 2-letter state abbreviation.
- `full` The full state name.
- `pct_pov_2014` The 2014 poverty estimate (in percent of state population) for the corresponding state

## References

- <https://www.census.gov/topics/income-poverty/poverty.html>
- <https://www.ers.usda.gov/data-products/county-level-data-sets/>

---

usmap

*usmap: US maps including Alaska and Hawaii*

---

## Description

It is usually difficult or inconvenient to create US maps that include both Alaska and Hawaii in a convenient spot. All map data frames produced by this package use the Albers Equal Area projection.

## Map data frames

Alaska and Hawaii have been manually moved to a new location so that their new coordinates place them to the bottom-left corner of the map. These maps can be accessed by using the `us_map` function.

The function provides the ability to retrieve maps with either state borders or county borders using the `regions` parameter for convenience.

States (or counties) can be included and excluded using the provided `include` and `exclude` parameters. These parameters can be used together with any combination of names, abbreviations, or FIPS code to create more complex maps.

## FIPS lookup tools

Several functions have been included to lookup the US state or county pertaining to a FIPS code.

Likewise a reverse lookup can be done where a FIPS code can be used to retrieve the associated state(s) or county(ies). This can be useful when preparing data to be merged with the map data frame.

## Plot US map data

A convenience function `plot_usmap` has been included which takes similar parameters to `us_map` and returns a `ggplot2::ggplot2` object. Since the output is a `ggplot` object, other layers can be added such as scales, themes, and labels. Including data in the function call will color the map according to the values in the data, creating a choropleth.

## Author(s)

Paolo Di Lorenzo

- Email: [paolo@dilorenzo.pl](mailto:paolo@dilorenzo.pl)
- Website: <https://dilorenzo.pl>
- GitHub: <https://github.com/pdil/>

## References

Rudis, Bob. "Moving The Earth (well, Alaska & Hawaii) With R." Blog post. Rud.is., 16 Nov. 2014. Web. 10 Aug. 2015. <https://rud.is/b/2014/11/16/moving-the-earth-well-alaska-hawaii-with-r/>.

## See Also

Helpful links:

- FIPS code information  
[https://en.wikipedia.org/wiki/FIPS\\_county\\_code](https://en.wikipedia.org/wiki/FIPS_county_code) [https://en.wikipedia.org/wiki/FIPS\\_state\\_code](https://en.wikipedia.org/wiki/FIPS_state_code)
- US Census Shapefiles  
<https://www.census.gov/geographies/mapping-files/time-series/geo/cartographic-boundary.html>
- Map Features  
[https://en.wikipedia.org/wiki/Map\\_projection](https://en.wikipedia.org/wiki/Map_projection) [https://en.wikipedia.org/wiki/Albers\\_projection](https://en.wikipedia.org/wiki/Albers_projection) <https://en.wikipedia.org/wiki/Choropleth>

---

usmap\_crs

*usmap coordinate reference system*

---

## Description

This coordinate reference system (CRS) represents the canonical projection used by the `usmap` package. It can be used to transform shape files, spatial points, spatial data frames, etc. to the same coordinate representation that is used by the `plot_usmap` function.

## Usage

`usmap_crs()`

---

usmap_transform	<i>Convert coordinate data frame to usmap projection</i>
-----------------	--

---

### Description

Converting an external data frame of map coordinates will allow those points to line up with the regular usmap plot by applying the same Albers Equal Area projection to those points as well.

### Usage

```
usmap_transform(
  data,
  input_names = c("lon", "lat"),
  output_names = c("x", "y")
)

## S3 method for class 'data.frame'
usmap_transform(
  data,
  input_names = c("lon", "lat"),
  output_names = c("x", "y")
)
```

### Arguments

data	A data frame containing coordinates in a two column format where the first column represents longitude and the second data frame represents latitude. The names of the data frame column do not matter, just that the order of the columns is kept intact.
input_names	A character vector of length two which specifies the longitude and latitude columns of the input data (the ones that should be transformed), respectively. Defaults to c("lon", "lat").
output_names	A character vector of length two which specifies the longitude and latitude columns of the output data (after transformation), respectively. Defaults to c("x", "y").

### Value

A data frame containing the transformed coordinates from the input data frame with the Albers Equal Area projection applied. The transformed columns will be appended to the data frame so that all original columns should remain intact.

### Examples

```
data <- data.frame(
  lon = c(-74.01, -95.36, -118.24, -87.65, -134.42, -157.86),
  lat = c(40.71, 29.76, 34.05, 41.85, 58.30, 21.31),
```

```
  pop = c(8398748, 2325502, 3990456, 2705994, 32113, 347397)
)

# Transform data
transformed_data <- usmap_transform(data)

# Plot transformed data on map
library(ggplot2)

plot_usmap() + geom_point(
  data = transformed_data,
  aes(x = x, y = y, size = pop),
  color = "red", alpha = 0.5
)
```

---

us\_map

*Retrieve US map data*

---

## Description

Retrieve US map data

## Usage

```
us_map(
  regions = c("states", "state", "counties", "county"),
  include = c(),
  exclude = c()
)
```

## Arguments

regions	The region breakdown for the map, can be one of ("states", "state", "counties", "county"). The default is "states".
include	The regions to include in the resulting map. If regions is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. If states are provided in the county map, only counties in the included states will be returned.
exclude	The regions to exclude in the resulting map. If regions is "states"/"state", the value can be either a state name, abbreviation or FIPS code. For counties, the FIPS must be provided as there can be multiple counties with the same name. The regions listed in the include parameter are applied first and the exclude regions are then removed from the resulting map. Any excluded regions not present in the included regions will be ignored.

**Value**

A data frame of US map coordinates divided by the desired regions.

**See Also**

[usmapdata::us\\_map\(\)](#) of which this function is a wrapper for.

**Examples**

```
str(us_map())
```

```
df <- us_map(regions = "counties")  
west_coast <- us_map(include = c("CA", "OR", "WA"))
```

```
south_atl_excl_FL <- us_map(include = .south_atlantic, exclude = "FL")
```

# Index

## \* datasets

- .east\_north\_central, 2
- .east\_south\_central, 3
- .mid\_atlantic, 4
- .midwest\_region, 3
- .mountain, 4
- .new\_england, 5
- .north\_central\_region, 6
- .northeast\_region, 5
- .pacific, 6
- .south\_atlantic, 7
- .south\_region, 7
- .west\_north\_central, 8
- .west\_region, 8
- .west\_south\_central, 9

## \* data

- citypop, 9
- countypop, 10
- countypov, 10
- earthquakes, 11
- statepop, 17
- statepov, 17
- .east\_north\_central, 2
- .east\_south\_central, 3
- .mid\_atlantic, 4
- .midwest\_region, 3
- .mountain, 4
- .new\_england, 5
- .north\_central\_region, 6
- .northeast\_region, 5
- .pacific, 6
- .south\_atlantic, 7
- .south\_region, 7
- .west\_north\_central, 8
- .west\_region, 8
- .west\_south\_central, 9

aes, 16

citypop, 9

countypop, 10

countypov, 10

earthquakes, 11

fips, 12

fips\_info, 13

ggplot, 16

ggplot2::ggplot2, 19

map\_with\_data, 14

plot\_usmap, 9, 11, 14, 15, 19

statepop, 17

statepov, 17

theme, 16

us\_map, 10, 14, 17–19, 21

usmap, 16, 18

usmap-package (usmap), 18

usmap\_crs, 19

usmap\_transform, 9, 11, 20

usmapdata::us\_map(), 22